TCT 通测检测
TESTING CENTRE TECHNOLOGY

TEST REPORT

FCC ID. ..... :	2BAHU2023006
Test Report No..... :	TCT230922E025
Date of issue..... :	Nov. 30, 2023
Testing laboratory ..... :	SHENZHEN TONGCE TESTING LAB
Testing location/ address:	2101 & 2201, Zhenchang Factory Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
Applicant's name..... :	DIALN PRODUCTS INC.
Address..... :	8312 Page Ave, Saint Louis, Missouri 63130, United States
Manufacturer's name ... :	DIALN PRODUCTS INC.
Address..... :	8312 Page Ave, Saint Louis, Missouri 63130, United States
Standard(s) ..... :	FCC CFR Title 47 Part 15 Subpart E Section 15.407 KDB 662911 D01 Multiple Transmitter Output v02r01 KDB 789033 D02 General U-NII Test Procedures New Rules v02r01
Product Name..... :	LTE Tablet
Trade Mark ..... :	DIALN
Model/Type reference..... :	X10 Pulse
Rating(s)..... :	Adapter Information: MODEL: BOS050250-02AU INPUT: AC 100-240V, 50/60Hz, 0.50A OUTPUT: DC 5V, 2500mA Rechargeable Li-ion Battery DC 3.8V
Date of receipt of test item ..... :	Sep. 22, 2023
Date (s) of performance of test..... :	Sep. 22, 2023 - Nov. 30, 2023
Tested by (+signature) ... :	Brews XU
Check by (+signature).... :	Beryl ZHAO
Approved by (+signature):	Tomsin

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information 3
1.1. EUT description 3
1.2. Model(s) list 3
1.3. Test Frequency 4
2. Test Result Summary 5
3. General Information 6
3.1. Test environment and mode 6
3.2. Description of Support Units 7
4. Facilities and Accreditations 8
4.1. Facilities 8
4.2. Location 8
4.3. Measurement Uncertainty 8
5. Test Results and Measurement Data 9
5.1. Antenna requirement 9
5.2. Conducted Emission 10
5.3. Maximum Conducted Output Power 14
5.4. 6dB Emission Bandwidth 16
5.5. 26dB Bandwidth and 99% Occupied Bandwidth 17
5.6. Power Spectral Density 18
5.7. Band edge 19
5.8. Unwanted Emissions 34
5.9. Frequency Stability Measurement 47
Appendix A: Test Result of Conducted Test
Appendix B: Photographs of Test Setup
Appendix C: Photographs of EUT

1. General Product Information

1.1. EUT description

Product Name.....:	LTE Tablet
Model/Type reference.....:	X10 Pulse
Sample Number.....:	TCT230922E014-0101
Operation Frequency.....:	Band 1: 5180 MHz ~ 5240 MHz Band 3: 5745 MHz ~ 5825 MHz
Channel Bandwidth.....:	802.11a: 20MHz 802.11n: 20MHz, 40MHz 802.11ac: 20MHz, 40MHz, 80MHz
Modulation Technology.....:	Orthogonal Frequency Division Multiplexing(OFDM)
Modulation Type.....:	256QAM, 64QAM, 16QAM, BPSK, QPSK
Antenna Type.....:	PIFA Antenna
Antenna Gain.....:	Band 1: -3.24dBi Band 3: -0.21dBi
Rating(s).....:	Adapter Information: MODEL: BOS050250-02AU INPUT: AC 100-240V, 50/60Hz, 0.50A OUTPUT: DC 5V, 2500mA Rechargeable Li-ion Battery DC 3.8V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

1.3. Test Frequency

Band 1

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180	38	5190	42	5210
40	5200	46	5230		
48	5240				

Band 3

20MHz		40MHz		80MHz	
Channel	Frequency	Channel	Frequency	Channel	Frequency
149	5745	151	5755	155	5775
157	5785	159	5795		
165	5825				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Maximum Conducted Output Power	§15.407(a)	PASS
6dB Emission Bandwidth	§15.407(a)	PASS
26dB Emission Bandwidth& 99% Occupied Bandwidth	§15.407(a)	PASS
Power Spectral Density	§15.407(a)	PASS
Restricted Bands around fundamental frequency	§15.407(b)	PASS
Radiated Emission	§15.407(b)	PASS
Frequency Stability	§15.407(g)	PASS

Note:

1. PASS: Test item meets the requirement.

2. Fail: Test item does not meet the requirement.

3. N/A: Test case does not apply to the test object.

4. The test result judgment is decided by the limit of test standard.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

3. General Information

3.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Software:	
Software Information:	Engineer mode
Power Level:	12
Test Mode:	
Engineer mode:	Keep the EUT in continuous transmitting by select channel and modulations with max. duty cycle.

The sample was placed 0.8m/1.5m for blow/above 1GHz above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	6.5 Mbps
802.11n(HT40)	13.5 Mbps
802.11ac(VHT20)	6.5 Mbps
802.11ac(VHT40)	13.5 Mbps
802.11ac(VHT80)	29.3 Mbps

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3. For conducted measurements (Output Power, Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098
  SHENZHEN TONGCE TESTING LAB
  Designation Number: CN1205
  The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.
- IC - Registration No.: 10668A-1
  SHENZHEN TONGCE TESTING LAB
  CAB identifier: CN0031
  The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB
Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
TEL: +86-755-27673339

4.3. Measurement Uncertainty

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
E.U.T Antenna:	
The EUT antenna is PIFA antenna which permanently attached, and the maximum gain of the antenna is -0.21dBi at UNII-B3.	



5.2. Conducted Emission

5.2.1. Test Specification

<table>
<tr><td>Test Requirement:</td><td>FCC Part15 C Section 15.207</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10:2013</td></tr>
<tr><td>Frequency Range:</td><td>150 kHz to 30 MHz</td></tr>
<tr><td>Receiver setup:</td><td>RBW=9 kHz, VBW=30 kHz, Sweep time=auto</td></tr>
<tr><td>Limits:</td><td><table>
<tr><td rowspan="2">Frequency range (MHz)</td><td colspan="2">Limit (dBuV)</td></tr>
<tr><td>Quasi-peak</td><td>Average</td></tr>
<tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr>
<tr><td>0.5-5</td><td>56</td><td>46</td></tr>
<tr><td>5-30</td><td>60</td><td>50</td></tr>
</table></td></tr>
<tr><td>Test Setup:</td><td> 

Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m</td></tr>
<tr><td>Test Mode:</td><td>Charging + Transmitting Mode</td></tr>
<tr><td>Test Procedure:</td><td>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</td></tr>
<tr><td>Test Result:</td><td>PASS</td></tr>
</table>

5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMI Test Receiver	R&S	ESCI3	100898	Jun. 29, 2024
Line Impedance Stabilisation Newtork(LISN)	Schwarzbeck	NSLK 8126	8126453	Feb. 20, 2024
Line-5	TCT	CE-05	/	Jul. 03, 2024
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room | Phase: *L1* | Temperature: 23.5 (℃) | Humidity: 52 %

Limit: FCC Part 15C Conduction(QP) | Power: AC 120 V/60 Hz

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1900	32.69	10.14	42.83	64.04	-21.21	QP	
2		0.1900	16.29	10.14	26.43	54.04	-27.61	AVG	
3		0.2779	25.76	9.95	35.71	60.88	-25.17	QP	
4		0.2779	12.76	9.95	22.71	50.88	-28.17	AVG	
5		0.3659	33.07	9.57	42.64	58.59	-15.95	QP	
6		0.3659	16.94	9.57	26.51	48.59	-22.08	AVG	
7		0.5658	28.32	9.39	37.71	56.00	-18.29	QP	
8		0.5658	16.14	9.39	25.53	46.00	-20.47	AVG	
9		1.4539	30.04	10.00	40.04	56.00	-15.96	QP	
10		1.4539	15.96	10.00	25.96	46.00	-20.04	AVG	
11	*	12.5540	34.46	10.16	44.62	60.00	-15.38	QP	
12		12.5540	20.27	10.16	30.43	50.00	-19.57	AVG	

Note:

Freq. = Emission frequency in MHz
Reading level (dBµV) = Receiver reading
Corr. Factor (dB) = LISN factor + Cable loss
Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)
Limit (dBµV) = Limit stated in standard
Margin (dB) = Measurement (dBµV) – Limits (dBµV)
Q.P. =Quasi-Peak
AVG =average
** is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.*

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room | Phase: *N* | Temperature: 23.5 (℃) | Humidity: 52 %

Limit: FCC Part 15C Conduction(QP) | Power: AC 120 V/60 Hz

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1833	27.70	10.13	37.83	64.33	-26.50	QP	
2		0.1833	13.38	10.13	23.51	54.33	-30.82	AVG	
3		0.2644	30.63	9.94	40.57	61.29	-20.72	QP	
4		0.2644	15.73	9.94	25.67	51.29	-25.62	AVG	
5		0.3579	31.51	9.58	41.09	58.78	-17.69	QP	
6		0.3579	17.57	9.58	27.15	48.78	-21.63	AVG	
7		0.5299	31.53	9.43	40.96	56.00	-15.04	QP	
8		0.5299	17.93	9.43	27.36	46.00	-18.64	AVG	
9	*	0.8459	32.34	9.13	41.47	56.00	-14.53	QP	
10		0.8459	18.96	9.13	28.09	46.00	-17.91	AVG	
11		13.4459	34.53	10.23	44.76	60.00	-15.24	QP	
12		13.4459	22.23	10.23	32.46	50.00	-17.54	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBµV) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dBµV) = Reading level (dBµV) + Corr. Factor (dB)

Limit (dBµV) = Limit stated in standard

Margin (dB) = Measurement (dBµV) – Limits (dBµV)

Q.P. =Quasi-Peak

AVG =average

** is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.*

Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80) and the worst case Mode (Middle channel and 802.11a) was submitted only.

5.3. Maximum Conducted Output Power

5.3.1. Test Specification

<table>
<tr><td>Test Requirement:</td><td>FCC Part15 E Section 15.407(a)& Part 2 J Section 2.1046</td></tr>
<tr><td>Test Method:</td><td>KDB662911 D01 Multiple Transmitter Output v02r01
KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E</td></tr>
<tr><td>Limit:</td><td><table>
<tr><td>Frequency Band (MHz)</td><td>Limit</td></tr>
<tr><td>5180 - 5240</td><td>24dBm(250mW) for client device</td></tr>
<tr><td>5260 - 5320</td><td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td></tr>
<tr><td>5470 - 5725</td><td>24dBm(250mW) or 11 dBm + 10 log B, B is the 26 dB emission bandwidth in megahertz</td></tr>
<tr><td>5745 - 5825</td><td>30dBm(1W)</td></tr>
</table></td></tr>
<tr><td>Test Setup:</td><td> 
</td></tr>
<tr><td>Test Mode:</td><td>Transmitting mode with modulation</td></tr>
<tr><td>Test Procedure:</td><td>1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.</td></tr>
<tr><td>Test Result:</td><td>PASS</td></tr>
<tr><td>Remark:</td><td>Conducted output power= measurement power +10log(1/x), X is duty cycle.</td></tr>
</table>

5.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Power Meter	Agilent	E4418B	MY45100357	Jun. 27, 2024
Power Sensor	Agilent	8481A	MY41091497	Jun. 27, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.4. 6dB Emission Bandwidth

5.4.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407(e)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Limit:	>500kHz
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

5.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.5. 26dB Bandwidth and 99% Occupied Bandwidth

5.5.1. Test Specification

Test Requirement:	47 CFR Part 15C Section 15.407 (a)& Part 2 J Section 2.1049
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Limit:	No restriction limits
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW. Set the Video bandwidth (VBW) = 3 *RBW. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Test Result:	PASS

5.5.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.6. Power Spectral Density

5.6.1. Test Specification

Test Requirement:	FCC Part15 E Section 15.407 (a)
Test Method:	KDB662911 D01 Multiple Transmitter Output v02r01 KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F
Limit:	≤11.00dBm/MHz for Band 1 5150MHz-5250MHz(client device) ≤11.00dBm/MHz for Band 2A&2C 5250-5350&5470-5725 ≤30.00dBm/500KHz for Band 3 5725MHz-5850MHz
Test Setup:	
Test Mode:	Transmitting mode with modulation
Test Procedure:	1. Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. 2. Allow the sweeps to continue until the trace stabilizes. 3. Use the peak marker function to determine the maximum amplitude level. 4. The E.I.R.P spectral density used radiated test method. At a test site that has been validated using the procedures of ANSI C63.4 or the latest CISPR 16-1-4 for measurements above 1 GHz, so as to simulate a near free-space environment.
Test Result:	PASS

5.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.7. Band edge

5.7.1. Test Specification

<table>
<tr><td>Test Requirement:</td><td>FCC CFR47 Part 15E Section 15.407</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10 2013</td></tr>
<tr><td>Limit:</td><td>In un-restricted band:
For Band 1&2A&2C: -27dBm/MHz
For Band 3:
<table>
<tr><td>Frequency (MHz)</td><td>Limit (dBm/MHz)</td><td>Frequency (MHz)</td><td>Limit (dBm/MHz)</td></tr>
<tr><td>< 5650</td><td>-27</td><td>5850~5855</td><td>27~15.6</td></tr>
<tr><td>5650~5700</td><td>-27~10</td><td>5855~5875</td><td>15.6~10</td></tr>
<tr><td>5700~5720</td><td>10~15.6</td><td>5875~5925</td><td>10~-27</td></tr>
<tr><td>5720~5725</td><td>15.6~27</td><td>> 5925</td><td>-27</td></tr>
</table>
E[dBμV/m] = EIRP[dBm] + 95.2 @3m
In restricted band:
<table>
<tr><td>Detector</td><td>Limit@3m</td></tr>
<tr><td>Peak</td><td>74dBμV/m</td></tr>
<tr><td>AVG</td><td>54dBμV/m</td></tr>
</table></td></tr>
<tr><td>Test Setup:</td><td> 
</td></tr>
<tr><td>Test Mode:</td><td>Transmitting mode with modulation</td></tr>
<tr><td>Test Procedure:</td><td>1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</td></tr>
</table>

	6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data sheet.
Test Result:	PASS

5.7.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMI Test Receiver	R&S	ESIB7	100197	Jun. 29, 2024
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 29, 2024
Spectrum Analyzer	Agilent	N9020A	MY49100619	Jun. 28, 2024
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Feb. 20, 2024
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Feb. 20, 2024
Pre-amplifier	HP	8447D	2727A05017	Jun. 27, 2024
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jul. 02, 2024
Broadband Antenna	Schwarzbeck	VULB9163	340	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Feb. 24, 2024
Coaxial cable	SKET	RC-18G-N-M	/	Feb. 24, 2024
Coaxial cable	SKET	RC_40G-K-M	/	Feb. 24, 2024
Antenna Mast	Keleto	CC-A-4M	/	/
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.7.3. Test Data

AC20-5180



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5150.000	73.53	-8.63	64.90	74.00	-9.10	peak	P	
2	5150.075	53.80	-8.63	45.17	122.20	-77.03	AVG	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	64.67	-8.63	56.04	74.00	-17.96	peak	P	
2 *	5150.000	47.88	-8.63	39.25	54.00	-14.75	AVG	P	

AC20-5240



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	50.48	-8.22	42.26	74.00	-31.74	peak	P	
2 *	5350.000	40.41	-8.22	32.19	54.00	-21.81	AVG	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	49.51	-8.22	41.29	74.00	-32.71	peak	P	
2 *	5350.000	39.34	-8.22	31.12	54.00	-22.88	AVG	P	

AC40-5190



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	76.57	-8.63	67.94	74.00	-6.06	peak	P	
2 *	5150.000	64.31	-8.63	55.68	54.00	1.68	AVG	F	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	71.94	-8.63	63.31	74.00	-10.69	peak	P	
2 *	5150.000	53.43	-8.63	44.80	54.00	-9.20	AVG	P	

AC40-5230



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	56.26	-8.22	48.04	74.00	-25.96	peak	P	
2 *	5350.000	43.23	-8.22	35.01	54.00	-18.99	AVG	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	50.41	-8.22	42.19	74.00	-31.81	peak	P	
2 *	5350.000	40.94	-8.22	32.72	54.00	-21.28	AVG	P	

AC80-5210



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	76.92	-8.63	68.29	74.00	-5.71	peak	P	
2 *	5150.000	60.11	-8.63	51.48	54.00	-2.52	AVG	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5150.000	63.56	-8.63	54.93	74.00	-19.07	peak	P	
2 *	5150.000	50.44	-8.63	41.81	54.00	-12.19	AVG	P	

AC80-5210



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	60.14	-8.22	51.92	74.00	-22.08	peak	P	
2 *	5350.000	48.98	-8.22	40.76	54.00	-13.24	AVG	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	5350.000	57.83	-8.22	49.61	74.00	-24.39	peak	P	
2 *	5350.000	45.47	-8.22	37.25	54.00	-16.75	AVG	P	

AC20-5745



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5639.275	53.39	-7.58	45.81	68.20	-22.39	peak	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5637.900	51.06	-7.58	43.48	68.20	-24.72	peak	P	

AC20-5825



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5913.125	50.55	-6.91	43.64	68.20	-24.56	peak	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5930.625	50.29	-6.87	43.42	68.20	-24.78	peak	P	

AC40-5755



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5643.025	53.61	-7.57	46.04	68.20	-22.16	peak	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5647.525	50.32	-7.56	42.76	68.20	-25.44	peak	P	

AC40-5795



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5913.094	50.14	-6.91	43.23	68.20	-24.97	peak	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5926.719	50.24	-6.88	43.36	68.20	-24.84	peak	P	

AC80-5775



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5645.870	59.33	-7.57	51.76	68.20	-16.44	peak	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 25.3(℃) Humidity: 45 %

Limit: FCC part 15.407 band edge B3 (PK) Power:DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5644.605	56.27	-7.57	48.70	68.20	-19.50	peak	P	



Site: #3 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5924.962	50.95	-6.89	44.06	68.20	-24.14	peak	P	



Site: #3 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 24.2(℃) Humidity: 52 %

Limit: FCC part 15.407 band edge (PK) Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	5915.663	50.57	-6.91	43.66	68.20	-24.54	peak	P	

Note: *All modulation (802.11a, 802.11n, 802.11ac) have been tested, only the worst case in 802.11ac be reported.*

5.8. Unwanted Emissions

5.8.1. Test Specification

Test Requirement:	FCC CFR47 Part 15 Section 15.407 & 15.209 & 15.205
Test Method:	KDB 789033 D02 v02r01
Frequency Range:	9kHz to 40GHz
Measurement Distance:	3 m
Antenna Polarization:	Horizontal & Vertical
Operation mode:	Transmitting mode with modulation
Receiver Setup:	

Frequency	Detector	RBW	VBW	Remark
9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	Peak	1MHz	10Hz	Average Value

Limit:

Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

In restricted bands:

Frequency	Detector	Limit@3m
Above 1G	Peak	74dBμV/m
	AVG	54dBμV/m

Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(KHz	300
0.490-1.705	24000/F(KHz)	3
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

In un-restricted bands: 68.2dBuV/m

Test setup:

For radiated emissions below 30MHz



30MHz to 1GHz

	 Above 1GHz 
Test Procedure:	1. The EUT was placed at a height of 0.8 m or 1.5m above the floor on a support in a 3 meter camber. The table was rotated 360 degrees todetermine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, whichwas mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and thenthe antenna was tuned to heights from 1 meter to 4 meters and the rotatablewas turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and SpecifiedBandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limitspecified, then testing could be stopped and the peak values of the EUT wouldbe reported. Otherwise the emissions that did not have 10dB margin would bere-tested one by one using peak, quasi-peak or average method as specified andthen reported in a data sheet.
Test results:	PASS

5.8.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
EMI Test Receiver	R&S	ESIB7	100197	Jun. 29, 2024
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 29, 2024
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012102	Feb. 20, 2024
Pre-amplifier	SKET	LNPA_1840G-50	SK202109203500	Feb. 20, 2024
Pre-amplifier	HP	8447D	2727A05017	Jun. 27, 2024
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jul. 02, 2024
Broadband Antenna	Schwarzbeck	VULB9163	340	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Feb. 24, 2024
Antenna Mast	Keleto	RE-AM	/	/
Coaxial cable	SKET	RC-18G-N-M	/	Feb. 24, 2024
Coaxial cable	SKET	RC_40G-K-M	/	Feb. 24, 2024
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.8.3. Test Data

Please refer to following diagram for individual

Below 1GHz

Horizontal:



Site: #1 3m Anechoic Chamber Polarization: ***Horizontal*** Temperature: 24.3(C) Humidity: 52 %

Limit: FCC Part 15C RE_3m Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	56.3947	6.94	13.13	20.07	40.00	-19.93	QP	P	
2	112.1303	6.38	11.62	18.00	43.50	-25.50	QP	P	
3	148.4410	5.83	14.40	20.23	43.50	-23.27	QP	P	
4	299.3158	6.35	13.98	20.33	46.00	-25.67	QP	P	
5	449.5557	6.81	17.53	24.34	46.00	-21.66	QP	P	
6 *	625.0779	6.96	21.04	28.00	46.00	-18.00	QP	P	

Vertical:



Site: #1 3m Anechoic Chamber Polarization: ***Vertical*** Temperature: 24.3(C) Humidity: 52 %

Limit: FCC Part 15C RE_3m Power: DC 3.8 V

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	38.8878	5.97	14.11	20.08	40.00	-19.92	QP	P	
2	52.9453	6.69	13.37	20.06	40.00	-19.94	QP	P	
3	128.1129	5.92	13.12	19.04	43.50	-24.46	QP	P	
4	170.7926	6.02	13.60	19.62	43.50	-23.88	QP	P	
5	332.5187	5.68	14.80	20.48	46.00	-25.52	QP	P	
6 *	776.8778	7.38	23.10	30.48	46.00	-15.52	QP	P	

Note: *1.The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported*

2. Measurements were conducted in all three channels (high, middle, low) and all modulation (802.11a, 802.11n(HT20), 802.11n(HT40), 802.11ac(VHT20), 802.11ac(VHT40), 802.11ac(VHT80) and the worst case Mode (Middle channel and 802.11a) was submitted only.

3.Measurement (dBμV) = Reading level + Correction Factor , correction Factor= Antenna Factor + Cable loss – Pre-amplifier.

Modulation Type: Band 1									
11a CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	38.74	---	8.02	46.76	---	68.2	---	-21.44
15540	H	38.03	---	9.87	47.9	---	74	54	-6.1
---	H	---	---	---	---	---	---	---	---
10360	V	38.25	---	8.02	46.27	---	68.2	---	-21.93
15540	V	38.61	---	9.87	48.48	---	74	54	-5.52
---	V	---	---	---	---	----	---	---	---
11a CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.27	---	7.97	47.24	---	68.2	---	-20.96
15600	H	38.03	---	9.83	47.86	---	74	54	-6.14
---	H	---	---	---	---	---	---	---	---
10400	V	40.58	---	7.97	48.55	---	68.2	---	-19.65
15600	V	38.64	---	9.83	48.47	---	74	54	-5.53
---	V	---	---	---	---	----	---	---	---
11a CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	38.78	---	7.97	46.75	---	68.2	---	-21.45
15720	H	37.19	---	9.83	47.02	---	74	54	-6.98
---	H	---	---	---	---	---	---	---	---
10480	V	38.50	---	7.97	46.47	---	68.2	---	-21.73
15720	V	36.84	---	9.83	46.67	---	74	54	-7.33
---	V	---	---	---	---	----	---	---	---
11n(HT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	41.43	---	8.02	49.45	---	68.2	---	-18.75
15540	H	37.91	---	9.87	47.78	---	74	54	-6.22
---	H	---	---	---	---	---	---	---	---
10360	V	42.26	---	8.02	50.28	---	68.2	---	-17.92
15540	V	37.89	---	9.87	47.76	---	74	54	-6.24
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	40.9	---	7.97	48.87	---	68.2	---	-19.33
15600	H	38.16	---	9.83	47.99	---	74	54	-6.01
---	H	---	---	---	---	---	---	---	---
10400	V	40.37	---	7.97	48.34	---	68.2	---	-19.86
15600	V	37.11	---	9.83	46.94	---	74	54	-7.06
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH48: 5240MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	41.85	---	7.97	49.82	---	68.2	---	-18.38
15720	H	39.49	---	9.83	49.32	---	74	54	-4.68
---	H	---	---	---	---	---	---	---	---
10480	V	40.63	---	7.97	48.6	---	68.2	---	-19.6
15720	V	39.15	---	9.83	48.98	---	74	54	-5.02
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH38: 5190MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	39.83	---	7.75	47.58	---	68.2	---	-20.62
15570	H	37.51	---	9.87	47.38	---	74	54	-6.62
---	H	---	---	---	---	---	---	---	---
10380	V	40.27	---	7.75	48.02	---	68.2	---	-20.18
15570	V	37.64	---	9.87	47.51	---	74	54	-6.49
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH46: 5230MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	41.33	---	7.97	49.3	---	68.2	---	-18.9
15690	H	38.01	---	9.83	47.84	---	74	54	-6.16
---	H	---	---	---	---	---	---	---	---
10460	V	41.62	---	7.97	49.59	---	68.2	---	-18.61
15690	V	38.97	---	9.83	48.8	---	74	54	-5.2
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH36: 5180MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10360	H	40.38	---	8.02	48.4	---	68.2	---	-19.8
15540	H	37.27	---	9.87	47.14	---	74	54	-6.86
---	H	---	---	---	---	---	---	---	---
10360	V	38.11	---	8.02	46.13	---	68.2	---	-22.07
15540	V	39.63	---	9.87	49.5	---	74	54	-4.5
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH40: 5200MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10400	H	39.14	---	7.97	47.11	---	68.2	---	-21.09
15600	H	38.03	---	9.83	47.86	---	74	54	-6.14
---	H	---	---	---	---	---	---	---	---
10400	V	39.77	---	7.97	47.74	---	68.2	---	-20.46
15600	V	38.19	---	9.83	48.02	---	74	54	-5.98
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH48:5240									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10480	H	37.61	---	7.97	45.58	---	68.2	---	-22.62
15720	H	37.84	---	9.83	47.67	---	74	54	-6.33
---	H	---	---	---	---	---	---	---	---
10480	V	38.04	---	7.97	46.01	---	68.2	---	-22.19
15720	V	38.56	---	9.83	48.39	---	74	54	-5.61
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH38:5190									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10380	H	40.27	---	7.75	48.02	---	68.2	---	-20.18
15570	H	39.75	---	9.87	49.62	---	74	54	-4.38
---	H	---	---	---	---	---	---	---	---
10380	V	38.53	---	7.75	46.28	---	68.2	---	-21.92
15570	V	38.24	---	9.87	48.11	---	74	54	-5.89
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH46:5230									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10460	H	38.17	---	7.97	46.14	---	68.2	---	-22.06
15690	H	38.63	---	9.83	48.46	---	74	54	-5.54
---	H	---	---	---	---	---	---	---	---
10460	V	39.59	---	7.97	47.56	---	68.2	---	-20.64
15690	V	37.18	---	9.83	47.01	---	74	54	-6.99
---	V	---	---	---	---	----	---	---	---

11ac(VHT80) CH42:5210									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
10420	H	41.53	---	7.96	49.49	---	68.2	---	-18.71
15630	H	39.07	---	9.84	48.91	---	74	54	-5.09
---	H	---	---	---	---	---	---	---	---
10420	V	41.29	---	7.96	49.25	---	68.2	---	-18.95
15630	V	39.71	---	9.84	49.55	---	74	54	-4.45
---	V	---	---	---	---	----	---	---	---

Note:

1. *Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier*
2. *Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.*
5. *Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.*

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

Modulation Type: Band 3									
11a CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	37.24	---	8.09	45.33	---	74	54	-8.67
17235	H	37.59	---	9.67	47.26	---	68.2	---	-20.94
---	H	---	---	---	---	---	---	---	---
11490	V	40.81	---	8.09	48.9	---	74	54	-5.1
17235	V	38.26	---	9.67	47.93	---	68.2	---	-20.27
---	V	---	---	---	---	----	---	---	---
11a CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	39.48	---	8.10	47.58	---	74	54	-6.42
17355	H	38.13	---	9.65	47.78	---	68.2	---	-20.42
---	H	---	---	---	---	---	---	---	---
11570	V	38.96	---	8.10	47.06	---	74	54	-6.94
17355	V	39.72	---	9.65	49.37	---	68.2	---	-18.83
---	V	---	---	---	---	----	---	---	---
11a CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	37.18	---	8.12	45.3	---	74	54	-8.7
17475	H	36.02	---	9.62	45.64	---	68.2	---	-22.56
---	H	---	---	---	---	---	---	---	---
11650	V	38.55	---	8.12	46.67	---	74	54	-7.33
17475	V	38.61	---	9.62	48.23	---	68.2	---	-19.97
---	V	---	---	---	---	----	---	---	---
11n(HT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	38.48	---	8.09	46.57	---	74	54	-7.43
17235	H	38.73	---	9.67	48.4	---	68.2	---	-19.8
---	H	---	---	---	---	---	---	---	---
11490	V	39.89	---	8.09	47.98	---	74	54	-6.02
17235	V	37.02	---	9.67	46.69	---	68.2	---	-21.51
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.57	---	8.10	46.67	---	74	54	-7.33
17355	H	39.94	---	9.65	49.59	---	68.2	---	-18.61
---	H	---	---	---	---	---	---	---	---
11570	V	38.4	---	8.10	46.5	---	74	54	-7.5
17355	V	39.56	---	9.65	49.21	---	68.2	---	-18.99
---	V	---	---	---	---	----	---	---	---

11n(HT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	38.65	---	8.12	46.77	---	74	54	-7.23
17475	H	37.19	---	9.62	46.81	---	68.2	---	-21.39
---	H	---	---	---	---	---	---	---	---
11650	V	38.83	---	8.12	46.95	---	74	54	-7.05
17475	V	39.16	---	9.62	48.78	---	68.2	---	-19.42
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	40.22	---	8.09	48.31	---	74	54	-5.69
17265	H	37.69	---	9.67	47.36	---	68.2	---	-20.84
---	H	---	---	---	---	---	---	---	---
11510	V	41.08	---	8.09	49.17	---	74	54	-4.83
17265	V	38.43	---	9.67	48.1	---	68.2	---	-20.1
---	V	---	---	---	---	----	---	---	---

11n(HT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	38.71	---	8.10	46.81	---	74	54	-7.19
17385	H	38.53	---	9.65	48.18	---	68.2	---	-20.02
---	H	---	---	---	---	---	---	---	---
11590	V	38.06	---	8.10	46.16	---	74	54	-7.84
17385	V	37.84	---	9.65	47.49	---	68.2	---	-20.71
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH149: 5745MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11490	H	40.11	---	8.09	48.2	---	74	54	-5.8
17235	H	37.58	---	9.67	47.25	---	68.2	---	-20.95
---	H	---	---	---	---	---	---	---	---
11490	V	40.27	---	8.09	48.36	---	74	54	-5.64
17235	V	38.49	---	9.67	48.16	---	68.2	---	-20.04
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH157: 5785MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11570	H	38.57	---	8.10	46.67	---	74	54	-7.33
17355	H	36.93	---	9.65	46.58	---	68.2	---	-21.62
---	H	---	---	---	---	---	---	---	---
11570	V	37.68	---	8.10	45.78	---	74	54	-8.22
17355	V	38.14	---	9.65	47.79	---	68.2	---	-20.41
---	V	---	---	---	---	----	---	---	---

11ac(VHT20) CH165: 5825MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11650	H	40.05	---	8.12	48.17	---	74	54	-5.83
17475	H	38.17	---	9.62	47.79	---	68.2	---	-20.41
---	H	---	---	---	---	---	---	---	---
11650	V	38.53	---	8.12	46.65	---	74	54	-7.35
17475	V	40.46	---	9.62	50.08	---	68.2	---	-18.12
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH151: 5755MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11510	H	39.67	---	8.09	47.76	---	74	54	-6.24
17265	H	37.11	---	9.67	46.78	---	68.2	---	-21.42
---	H	---	---	---	---	---	---	---	---
11510	V	40.59	---	8.09	48.68	---	74	54	-5.32
17265	V	36.28	---	9.67	45.95	---	68.2	---	-22.25
---	V	---	---	---	---	----	---	---	---

11ac(VHT40) CH159: 5795MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11590	H	40.34	---	8.10	48.44	---	74	54	-5.56
17385	H	37.82	---	9.65	47.47	---	68.2	---	-20.73
---	H	---	---	---	---	---	---	---	---
11590	V	39.61	---	8.10	47.71	---	74	54	-6.29
17385	V	38.24	---	9.65	47.89	---	68.2	---	-20.31
---	V	---	---	---	---	----	---	---	---

11ac(VHT80) CH155: 5775MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
11550	H	40.19	---	8.09	48.28	---	74	54	-5.72
17325	H	38.62	---	9.66	48.28	---	68.2	---	-19.92
---	H	---	---	---	---	---	---	---	---
11550	V	41.34	---	8.09	49.43	---	74	54	-4.57
17325	V	38.67	---	9.66	48.33	---	68.2	---	-19.87
---	V	---	---	---	---	----	---	---	---

Note:

1. *Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier*
2. *Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)*
3. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
4. *Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency. The highest test frequency is 40GHz.*
5. *Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.*

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

5.9. Frequency Stability Measurement

5.9.1. Test Specification

Test Requirement:	FCC Part15 Section 15.407(g) &Part2 J Section 2.1055
Test Method:	ANSI C63.10: 2013
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Setup:	
Test Procedure:	The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage. b. Turn the EUT on and couple its output to a spectrum analyzer. c. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Test Result:	PASS
Remark:	Pre-scan was performed at all models(11a,11n,11ac), the worst case (11ac) was found and test data was shown in this report.

Test plots as follows:

Test mode:	802.11ac(HT20)	Frequency(MHz):	5180
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5179.98	-20000	PASS
35		5179.98	-20000	PASS
25		5180	0	PASS
15		5179.98	-20000	PASS
5		5179.98	-20000	PASS
0		5179.98	-20000	PASS
25	2.75V	5180	0	PASS
	3.8V	5179.98	-20000	PASS
	4.35V	5179.98	-20000	PASS

Test mode:	802.11ac(HT20)	Frequency(MHz):	5200
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5199.98	-20000	PASS
35		5199.98	-20000	PASS
25		5199.98	-20000	PASS
15		5199.98	-20000	PASS
5		5199.98	-20000	PASS
0		5199.98	-20000	PASS
25	2.75V	5199.98	-20000	PASS
	3.8V	5199.98	-20000	PASS
	4.35V	5199.98	-20000	PASS

Test mode:	802.11ac(HT20)	Frequency(MHz):	5240
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5239.96	-40000	PASS
35		5239.98	-20000	PASS
25		5239.98	-20000	PASS
15		5239.96	-40000	PASS
5		5239.98	-20000	PASS
0		5239.98	-20000	PASS
25	2.75V	5239.96	-40000	PASS
	3.8V	5239.98	-20000	PASS
	4.35V	5240	0	PASS

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

Test mode:	802.11ac(HT20)	Frequency(MHz):	5745	
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5745	0	PASS
35		5744.98	-20000	PASS
25		5745	0	PASS
15		5745	0	PASS
5		5744.98	-20000	PASS
0		5744.98	-20000	PASS
25	2.75V	5745	0	PASS
	3.8V	5744.98	-20000	PASS
	4.35V	5745	0	PASS

Test mode:	802.11ac(HT20)	Frequency(MHz):	5785	
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5785	0	PASS
35		5785	0	PASS
25		5785	0	PASS
15		5784.98	-20000	PASS
5		5785	0	PASS
0		5785	0	PASS
25	2.75V	5785	0	PASS
	3.8V	5784.98	-20000	PASS
	4.35V	5784.98	-20000	PASS

Test mode:	802.11ac(HT20)	Frequency(MHz):	5825	
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5824.98	-20000	PASS
35		5824.98	-20000	PASS
25		5824.98	-20000	PASS
15		5824.98	-20000	PASS
5		5825	0	PASS
0		5824.98	-20000	PASS
25	2.75V	5824.98	-20000	PASS
	3.8V	5825	0	PASS
	4.35V	5825	0	PASS

Test mode:	802.11ac(HT40)	Frequency(MHz):	5190
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5189.96	-40000	PASS
35		5189.96	-40000	PASS
25		5190	0	PASS
15		5190	0	PASS
5		5190	0	PASS
0		5189.96	-40000	PASS
25	2.75V	5189.96	-40000	PASS
	3.8V	5189.96	-40000	PASS
	4.35V	5190	0	PASS

Test mode:	802.11ac(HT40)	Frequency(MHz):	5230
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5229.96	-40000	PASS
35		5229.96	-40000	PASS
25		5229.96	-40000	PASS
15		5229.96	-40000	PASS
5		5230	0	PASS
0		5229.96	-40000	PASS
25	2.75V	5229.96	-40000	PASS
	3.8V	5229.96	-40000	PASS
	4.35V	5230	0	PASS

Test mode:	802.11ac(HT40)	Frequency(MHz):	5755
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5754.96	-40000	PASS
35		5755	0	PASS
25		5755	0	PASS
15		5755	0	PASS
5		5754.96	-40000	PASS
0		5755	0	PASS
25	2.75V	5754.96	-40000	PASS
	3.8V	5754.96	-40000	PASS
	4.35V	5754.96	-40000	PASS

Test mode:	802.11ac(HT40)	Frequency(MHz):	5795	
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5794.96	-40000	PASS
35		5795	0	PASS
25		5794.96	-40000	PASS
15		5794.96	-40000	PASS
5		5795	0	PASS
0		5795	0	PASS
25	2.75V	5794.96	-40000	PASS
	3.8V	5794.96	-40000	PASS
	4.35V	5794.96	-40000	PASS

Test mode:	802.11ac(VHT80)	Frequency(MHz):	5210	
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5210	0	PASS
35		5210	0	PASS
25		5210	0	PASS
15		5210	0	PASS
5		5210	0	PASS
0		5210	0	PASS
25	2.75V	5210	0	PASS
	3.8V	5210	0	PASS
	4.35V	5210	0	PASS

Test mode:	802.11ac(VHT80)	Frequency(MHz):	5775	
Temperature (°C)	Voltage(VDC)	Measurement Frequency(MHz)	Delta Frequency(Hz)	Result
45	3.8V	5775	0	PASS
35		5775	0	PASS
25		5775	0	PASS
15		5775	0	PASS
5		5775	0	PASS
0		5775	0	PASS
25	2.75V	5775	0	PASS
	3.8V	5775	0	PASS
	4.35V	5775	0	PASS

Appendix A: Test Result of Conducted Test

Duty Cycle

Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)
NVNT	a	5180	92.72	0.33
NVNT	a	5200	92.87	0.32
NVNT	a	5240	92.91	0.32
NVNT	n20	5180	91.97	0.36
NVNT	n20	5200	91.88	0.37
NVNT	n20	5240	91.82	0.37
NVNT	n40	5190	83.72	0.77
NVNT	n40	5230	84.60	0.73
NVNT	ac20	5180	91.20	0.40
NVNT	ac20	5200	91.90	0.37
NVNT	ac20	5240	91.88	0.37
NVNT	ac40	5190	84.41	0.74
NVNT	ac40	5230	84.81	0.72
NVNT	ac80	5210	69.38	1.59
NVNT	a	5745	92.89	0.32
NVNT	a	5785	92.85	0.32
NVNT	a	5825	92.85	0.32
NVNT	n20	5745	91.93	0.37
NVNT	n20	5785	92.04	0.36
NVNT	n20	5825	91.87	0.37
NVNT	n40	5755	84.61	0.73
NVNT	n40	5795	84.67	0.72
NVNT	ac20	5745	91.84	0.37
NVNT	ac20	5785	91.95	0.36
NVNT	ac20	5825	91.86	0.37
NVNT	ac40	5755	84.88	0.71
NVNT	ac40	5795	84.74	0.72
NVNT	ac80	5775	72.82	1.38

Test Graphs

Duty Cycle NVNT a 5180MHz



Duty Cycle NVNT a 5200MHz



Duty Cycle NVNT a 5240MHz



Duty Cycle NVNT n20 5180MHz



Duty Cycle NVNT n20 5200MHz



Duty Cycle NVNT n20 5240MHz



Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com

Duty Cycle NVNT n40 5190MHz



Duty Cycle NVNT n40 5230MHz



Duty Cycle NVNT ac20 5180MHz



Duty Cycle NVNT ac20 5200MHz



Duty Cycle NVNT ac20 5240MHz



Duty Cycle NVNT ac40 5190MHz



Duty Cycle NVNT ac40 5230MHz



Duty Cycle NVNT ac80 5210MHz



Test Graphs

Duty Cycle NVNT a 5745MHz



Duty Cycle NVNT a 5785MHz



Duty Cycle NVNT a 5825MHz



Duty Cycle NVNT n20 5745MHz



Duty Cycle NVNT n20 5785MHz



Duty Cycle NVNT n20 5825MHz



Duty Cycle NVNT n40 5755MHz



Duty Cycle NVNT n40 5795MHz



Duty Cycle NVNT ac20 5745MHz



Duty Cycle NVNT ac20 5785MHz



Duty Cycle NVNT ac20 5825MHz



Duty Cycle NVNT ac40 5755MHz



Duty Cycle NVNT ac40 5795MHz



Duty Cycle NVNT ac80 5775MHz



Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	11.89	0.33	12.22	24	Pass
NVNT	a	5200	12.07	0.32	12.39	24	Pass
NVNT	a	5240	11.76	0.32	12.08	24	Pass
NVNT	n20	5180	11.77	0.36	12.13	24	Pass
NVNT	n20	5200	11.99	0.37	12.36	24	Pass
NVNT	n20	5240	11.71	0.37	12.08	24	Pass
NVNT	n40	5190	11.02	0.77	11.79	24	Pass
NVNT	n40	5230	11.09	0.73	11.82	24	Pass
NVNT	ac20	5180	11.69	0.40	12.09	24	Pass
NVNT	ac20	5200	11.96	0.37	12.33	24	Pass
NVNT	ac20	5240	11.70	0.37	12.07	24	Pass
NVNT	ac40	5190	11.03	0.74	11.77	24	Pass
NVNT	ac40	5230	11.10	0.72	11.82	24	Pass
NVNT	ac80	5210	10.13	1.59	11.72	24	Pass
NVNT	a	5745	10.30	0.32	10.62	30	Pass
NVNT	a	5785	11.39	0.32	11.71	30	Pass
NVNT	a	5825	11.28	0.32	11.60	30	Pass
NVNT	n20	5745	10.33	0.37	10.70	30	Pass
NVNT	n20	5785	11.49	0.3	11.84	30	Pass
NVNT	n20	5825	11.24	0.37	11.61	30	Pass
NVNT	n40	5755	10.46	0.73	11.19	30	Pass
NVNT	n40	5795	11.48	0.72	12.20	30	Pass
NVNT	ac20	5745	10.30	0.37	10.67	30	Pass
NVNT	ac20	5785	11.33	0.36	11.69	30	Pass
NVNT	ac20	5825	11.34	0.37	11.71	30	Pass
NVNT	ac40	5755	10.48	0.71	11.19	30	Pass
NVNT	ac40	5795	11.49	0.72	12.21	30	Pass
NVNT	ac80	5775	10.02	1.38	11.40	30	Pass

Test Graphs

Power NVNT a 5180MHz



Power NVNT a 5200MHz



Power NVNT a 5240MHz



Power NVNT n20 5180MHz



Power NVNT n20 5200MHz



Power NVNT n20 5240MHz