RF TEST REPORT

For

SensoScientific, Inc.
Product Name: WiFi Node
Test Model(s).: B80-500-OTA

Report Reference No.	:	**DACE240415001RL001**
FCC ID	:	**2BAJL-BXX500OTA**
Applicant's Name	:	SensoScientific, Inc.
Address	:	685 COCHRAN ST STE 200 SIMI VALLEY CA 93065
Testing Laboratory	:	Shenzhen DACE Testing Technology Co., Ltd.
Address	:	101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Test Specification Standard	:	**47 CFR Part 15.247** **ANSI C63.10-2013 & KDB 558074 D01 15.247 Meas Guidance v05r02**
Date of Receipt	:	April 15, 2024
Date of Test	:	April 15, 2024 to May 16, 2024
Data of Issue	:	May 16, 2024
Result	:	**Pass**

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	DACE240415001RL001	May 16, 2024

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:	Supervised by:	Approved by:
Keren Huang	Stone Yin	Tom Chen
Keren Huang / Test Engineer	Stone Yin / Project Engineer	Tom Chen / Manager

CONTENTS

1 TEST SUMMARY 5
1.1 TEST STANDARDS 5
1.2 SUMMARY OF TEST RESULT 5
2 GENERAL INFORMATION 6
2.1 CLIENT INFORMATION 6
2.2 DESCRIPTION OF DEVICE (EUT) 6
2.3 DESCRIPTION OF TEST MODES 7
2.4 DESCRIPTION OF SUPPORT UNITS 7
2.5 EQUIPMENTS USED DURING THE TEST 8
2.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY 8
2.7 IDENTIFICATION OF TESTING LABORATORY 9
2.8 ANNOUNCEMENT 9
3 EVALUATION RESULTS (EVALUATION) 10
3.1 ANTENNA REQUIREMENT 10
3.1.1 Conclusion: 10
4 RADIO SPECTRUM MATTER TEST RESULTS (RF) 11
4.1 CONDUCTED EMISSION AT AC POWER LINE 11
4.1.1 E.U.T. Operation: 11
4.1.2 Test Setup Diagram: 11
4.1.3 Test Data: 11
4.2 OCCUPIED BANDWIDTH 12
4.2.1 E.U.T. Operation: 12
4.2.2 Test Setup Diagram: 12
4.2.3 Test Data: 12
4.3 MAXIMUM CONDUCTED OUTPUT POWER 13
4.3.1 E.U.T. Operation: 13
4.3.2 Test Setup Diagram: 13
4.3.3 Test Data: 14
4.4 POWER SPECTRAL DENSITY 15
4.4.1 E.U.T. Operation: 15
4.4.2 Test Setup Diagram: 15
4.4.3 Test Data: 15
4.5 EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS 16
4.5.1 E.U.T. Operation: 16
4.5.2 Test Setup Diagram: 16
4.5.3 Test Data: 16
4.6 BAND EDGE EMISSIONS (RADIATED) 17
4.6.1 E.U.T. Operation: 17
4.6.2 Test Setup Diagram: 17
4.6.3 Test Data: 18
4.7 EMISSIONS IN FREQUENCY BANDS (BELOW 1GHZ) 24
4.7.1 E.U.T. Operation: 25
4.7.2 Test Setup Diagram: 25
4.7.3 Test Data: 26
4.8 EMISSIONS IN FREQUENCY BANDS (ABOVE 1GHZ) 28
4.8.1 E.U.T. Operation: 29

4.8.2 Test Setup Diagram: 29
4.8.3 Test Data: 30

5 TEST SETUP PHOTOS 33
6 PHOTOS OF THE EUT 33
APPENDIX 34

1. -6dB BANDWIDTH 34
2. 99% OCCUPIED BANDWIDTH 39
3. MAX. OUTPUT POWER 44
4. POWER SPECTRAL DENSITY 49
5. BANDEDGE 54
6. SPURIOUS EMISSION 60

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

1.2 Summary of Test Result

Item	Standard	Method	Requirement	Result
Antenna requirement	47 CFR Part 15.247	/	47 CFR 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15.247	ANSI C63.10-2013 section 6.2	47 CFR 15.207(a)	N/A
Occupied Bandwidth	47 CFR Part 15.247	ANSI C63.10-2013, section 11.8	47 CFR 15.247(a)(2)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	ANSI C63.10-2013, section 11.9.1	47 CFR 15.247(b)(3)	Pass
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10-2013, section 11.10	47 CFR 15.247(e)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	ANSI C63.10-2013 section 11.11	47 CFR 15.247(d), 15.209, 15.205	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	ANSI C63.10-2013 section 6.10	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	ANSI C63.10-2013 section 6.6.4	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	ANSI C63.10-2013 section 6.6.4	47 CFR 15.247(d), 15.209, 15.205	Pass

Note:1. N/A-- Not applicable to the this test clause.
2. The results of all conduction method tests include cable loss.

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : SensoScientific, Inc.
Address : 685 COCHRAN ST STE 200 SIMI VALLEY CA 93065

Manufacturer : Vietnam IBE Laser Co.,ltd
Address : Lot CN-34 and CN-39, Thuan Thanh II Industrial Park, An Binh Ward and, Mao Dien Commune, Thuan Thanh Town, Bac Ninh Province, Vietnam

2.2 Description of Device (EUT)

Product Name:	WiFi Node
Model/Type reference:	B80-500-OTA
Series Model:	B26-500-OTA,B23-500-OTA,B22-500-OTA, B21-500-OTA,B20-500-OTA,B19-500-OTA,B18-500-OTA,B17-500-OTA,B16-500-OTA, B15-500-OTA,B14-500-OTA,B13-500-OTA,B11-500-OTA,B10-500-OTA
Model Difference:	The internal motherboard circuits, WiFi modules, antennas, and PCB layout of all models are the same, but customers may burn different software according to their needs, resulting in inconsistent versions, which is why there are so many models. But these differences will not affect the EMC and WiFi performance of the product.
Trade Mark:	SENSOSCIENTIFIC
Product Description:	WiFi Node
Power Supply:	DC3.0V from AA*2battery
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz;
Number of Channels:	802.11b/g/n(HT20): 11 Channels;
Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n(HT20): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type:	External Panel-Mount WiFi/WLAN Antenna
Antenna Gain:	3.2dBi
Hardware Version:	94V-0
Software Version:	CC3xxxRadioTool-1.0.3.19

Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	5	2432MHz	9	2452MHz
2	2417MHz	6	2437MHz	10	2457MHz
3	2422MHz	7	2442MHz	11	2462MHz
4	2427MHz	8	2447MHz		

Note: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	**Frequency (MHz)**	
	20MHz-BW	40MHz-BW

Lowest channel	2412MHz	/
Middle channel	2437MHz	/
Highest channel	2462MHz	/

2.3 Description of Test Modes

No	Title	Description
TM1	802.11b mode	Keep the EUT in continuously transmitting mode with 802.11b modulation type. All bandwidth and data rates has been tested and found the data rate @ 11Mbps is the worst case. Only the data of worst case is recorded in the report.
TM2	802.11g mode	Keep the EUT in continuously transmitting mode with 802.11g modulation type. All bandwidth and data rates has been tested and found the data rate @ 54Mbps is the worst case. Only the data of worst case is recorded in the report.
TM3	802.11n(HT20) mode	Keep the EUT in continuously transmitting mode with 802.11 n(HT20) modulation type. All bandwidth and data rates has been tested and found the data rate @ MCS7 is the worst case. Only the data of worst case is recorded in the report.

Description

Eut uses the maximum duty cycle (>98%) for continuous emission

☒Special software is used.
☐Through engineering command into the engineering mode.
engineering command: *#*#3646633#*#*
☐Other method:

Special software:



Duty cycle	Use the maximum possible duty cycle (100%) during testing.

2.4 Description of Support Units

Title	Manufacturer	Model No.	Serial No.
/	/	/	/

2.5 Equipments Used During The Test

Maximum Conducted Output Power
Power Spectral Density
Emissions in non-restricted frequency bands
Occupied Bandwidth

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	Tachoy Information	RTS-01	V2.0.0.0	/	/
RF Sensor Unit	Tachoy Information	TR1029-2	000001	2023-11-09	2024-11-08
Vector signal generator	Keysight	N5181A	MY48180415	2023-11-09	2024-11-08
Signal generator	Keysight	N5182A	MY50143455	2023-11-09	2024-11-08
Spectrum Analyzer	Keysight	N9020A	MY53420323	2023-12-12	2024-12-11

Band edge emissions (Radiated)
Emissions in frequency bands (below 1GHz)
Emissions in frequency bands (above 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	/	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2022-04-05	2025-04-04
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2023-04-05	2025-04-04
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2021-07-05	2024-07-04
Cable(LF)#2	Schwarzbeck	/	/	2024-02-19	2025-02-18
Cable(LF)#1	Schwarzbeck	/	/	2024-02-19	2025-02-18
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2024-03-20	2025-03-19
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2024-03-20	2025-03-19
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2023-06-13	2024-06-12
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2023-06-13	2024-06-12
Spectrum Analyzer	R&S	FSP30	1321.3008K40 -101729-jR	2023-06-14	2024-06-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2023-05-13	2025-05-12
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2023-05-21	2025-05-20
Test Receiver	R&S	ESCI	102109	2023-06-13	2024-06-12

2.6 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Disturbance (0.15~30MHz)	±3.41dB
Occupied Bandwidth	±3.63%
RF conducted power	±0.733dB

RF power density	±0.234%
Conducted Spurious emissions	±1.98dB
Radiated Emission (Above 1GHz)	±5.46dB
Radiated Emission (Below 1GHz)	±5.79dB
Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

2.7 Identification of Testing Laboratory

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252

Identification of the Responsible Testing Location

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	101-102 Building H5 & 1/F., Building H, Hongfa Science & Technology Park, Tangtou, Shiyan, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252
FCC Registration Number:	0032847402
Designation Number:	CN1342
Test Firm Registration No.:	778666
A2LA Certificate Number:	6270.01

2.8 Announcement

(1) The test report reference to the report template version v0.

(2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.

(3) The test report is invalid if there is any evidence and/or falsification.

(4) This document may not be altered or revised in any way unless done so by DACE and all revisions are duly noted in the revisions section.

(5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

(6) We hereby declare that the laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant. the laboratory is not responsible for the accuracy of the information provided by the client. When the information provided by the customer may affect the effectiveness of the results, the responsibility lies with the customer, and the laboratory does not assume any responsibility.

3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.1 Conclusion:

4 Radio Spectrum Matter Test Results (RF)

4.1 Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b)and (c)of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN).
Test Limit:	

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Test Method:	ANSI C63.10-2013 section 6.2
Procedure:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices

4.1.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.3 °C	Humidity:	51.4 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.1.2 Test Setup Diagram:



4.1.3 Test Data:

N/A

(The device is powered by AA batteries, and the USB port is only used for data transmission without charging)

4.2 Occupied Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2013, section 11.8
Procedure:	a) Set RBW = 100 kHz. b) Set the VBW >= [3 × RBW]. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.3 °C	Humidity:	51.4 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.2.2 Test Setup Diagram:



4.2.3 Test Data:

Please Refer to Appendix for Details.

4.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2013, section 11.9.1
Procedure:	ANSI C63.10-2013, section 11.9.1 Maximum peak conducted output power Note: Per ANSI C63.10-2013, if there are two or more antnnas, the conducted powers at Core 0, Core 1,…, Core i were first measured separately, as shown in the section above(this product olny have one antenna). The measured values were then summed in linear power units then converted back to dBm. Per ANSI C63.10-2013 Section 14.4.3.2.3, the directional gain is calculated using the following formula, where GN is the gain of the nth antenna and NANT, the total number of antennas used. For correlated unequal antenna gain Directional gain = 10*log[(10G1/20 + 10G2/20 + … + 10GN/20)2 / NANT] dBi For completely uncorrelated unequal antenna gain Directional gain = 10*log[(10G1/10 + 10G2/10 + … + 10GN/10)/ NANT] dBi Sample Multiple antennas Calculation: Core 0 + Core 1 +…Core i. = MIMO/CDD (i is the number of antennas) (#VALUE! mW + mW) = #VALUE! mW = dBm Sample e.i.r.p. Calculation: e.i.r.p. (dBm) = Conducted Power (dBm) + Ant gain (dBi)

4.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.3 °C	Humidity:	51.4 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.3.2 Test Setup Diagram:



4.3.3 Test Data:

Please Refer to Appendix for Details.

4.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2013, section 11.10
Procedure:	ANSI C63.10-2013, section 11.10, Maximum power spectral density level in the fundamental emission

4.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.3 °C	Humidity:	51.4 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.4.2 Test Setup Diagram:



4.4.3 Test Data:

Please Refer to Appendix for Details.

4.5 Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d), 15.209, 15.205
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2013 section 11.11
Procedure:	ANSI C63.10-2013 Section 11.11.1, Section 11.11.2, Section 11.11.3

4.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.3 °C	Humidity:	51.4 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1, TM2, TM3				

4.5.2 Test Setup Diagram:



4.5.3 Test Data:

Please Refer to Appendix for Details.

4.6 Band edge emissions (Radiated)

<table>
<tr><td>Test Requirement:</td><td>Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`</td></tr>
<tr><td>Test Limit:</td><td>
<table>
<tr><td>Frequency (MHz)</td><td>Field strength (microvolts/meter)</td><td>Measurement distance (meters)</td></tr>
<tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr>
<tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr>
<tr><td>1.705-30.0</td><td>30</td><td>30</td></tr>
<tr><td>30-88</td><td>100 **</td><td>3</td></tr>
<tr><td>88-216</td><td>150 **</td><td>3</td></tr>
<tr><td>216-960</td><td>200 **</td><td>3</td></tr>
<tr><td>Above 960</td><td>500</td><td>3</td></tr>
</table>
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10-2013 section 6.10</td></tr>
<tr><td>Procedure:</td><td>ANSI C63.10-2013 section 6.10.5.2
Mesurement Level = Reading level + Correct Factor,
Margin= Mesurement Level - Limit</td></tr>
</table>

4.6.1 E.U.T. Operation:

<table>
<tr><td colspan="6">Operating Environment:</td></tr>
<tr><td>Temperature:</td><td>23.3 °C</td><td>Humidity:</td><td>51.4 %</td><td>Atmospheric Pressure:</td><td>102 kPa</td></tr>
<tr><td colspan="2">Pretest mode:</td><td colspan="4">TM1, TM2, TM3</td></tr>
<tr><td colspan="2">Final test mode:</td><td colspan="4">TM1, TM2, TM3</td></tr>
</table>

4.6.2 Test Setup Diagram:



4.6.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	47.69	-6.93	40.76	74.00	-33.24	peak	150		P	
2	2310.000	38.35	-6.93	31.42	54.00	-22.58	AVG	150		P	
3	2390.000	51.35	-6.72	44.63	74.00	-29.37	peak	150		P	
4 *	2390.000	39.27	-6.72	32.55	54.00	-21.45	AVG	150		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	46.31	-8.23	38.08	74.00	-35.92	peak	150		P	
2	2310.000	35.65	-8.23	27.42	54.00	-26.58	AVG	150		P	
3	2390.000	47.99	-7.91	40.08	74.00	-33.92	peak	150		P	
4 *	2390.000	35.94	-7.91	28.03	54.00	-25.97	AVG	150		P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	52.50	-6.47	46.03	74.00	-27.97	peak	149		P	
2 *	2483.500	39.87	-6.47	33.40	54.00	-20.60	AVG	149		P	
3	2500.000	51.95	-6.43	45.52	74.00	-28.48	peak	149		P	
4	2500.000	39.69	-6.43	33.26	54.00	-20.74	AVG	149		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	47.58	-7.54	40.04	74.00	-33.96	peak	149		P	
2	2483.500	36.29	-7.54	28.75	54.00	-25.25	AVG	149		P	
3	2500.000	48.92	-7.48	41.44	74.00	-32.56	peak	149		P	
4 *	2500.000	36.62	-7.48	29.14	54.00	-24.86	AVG	149		P	

TM2 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	44.05	-6.93	37.12	74.00	-36.88	peak	149		P	
2	2310.000	33.26	-6.93	26.33	54.00	-27.67	AVG	149		P	
3 *	2390.000	54.70	-6.72	47.98	74.00	-26.02	peak	149		P	
4	2390.000	34.68	-6.72	27.96	54.00	-26.04	AVG	149		P	

TM2 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	45.35	-8.23	37.12	74.00	-36.88	peak	149		P	
2	2310.000	34.53	-8.23	26.30	54.00	-27.70	AVG	149		P	
3	2390.000	46.85	-7.91	38.94	74.00	-35.06	peak	149		P	
4 *	2390.000	34.66	-7.91	26.75	54.00	-27.25	AVG	149		P	

TM2 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	54.02	-6.47	47.55	74.00	-26.45	peak	149		P	
2 *	2483.500	34.77	-6.47	28.30	54.00	-25.70	AVG	149		P	
3	2500.000	49.40	-6.43	42.97	74.00	-31.03	peak	149		P	
4	2500.000	33.32	-6.43	26.89	54.00	-27.11	AVG	149		P	

TM2 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	50.94	-7.54	43.40	74.00	-30.60	peak	149		P	
2 *	2483.500	34.65	-7.54	27.11	54.00	-26.89	AVG	149		P	
3	2500.000	45.36	-7.48	37.88	74.00	-36.12	peak	149		P	
4	2500.000	33.97	-7.48	26.49	54.00	-27.51	AVG	149		P	

TM3 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	44.14	-6.93	37.21	74.00	-36.79	peak	149		P	
2	2310.000	33.29	-6.93	26.36	54.00	-27.64	AVG	149		P	
3	2390.000	52.94	-6.72	46.22	74.00	-27.78	peak	149		P	
4 *	2390.000	34.60	-6.72	27.88	54.00	-26.12	AVG	149		P	

TM3 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	45.87	-8.23	37.64	74.00	-36.36	peak	149		P	
2	2310.000	34.35	-8.23	26.12	54.00	-27.88	AVG	149		P	
3	2390.000	45.76	-7.91	37.85	74.00	-36.15	peak	149		P	
4 *	2390.000	34.48	-7.91	26.57	54.00	-27.43	AVG	149		P	

TM3 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	2483.500	56.09	-6.47	49.62	74.00	-24.38	peak	149		P	
2	2483.500	35.87	-6.47	29.40	54.00	-24.60	AVG	149		P	
3	2500.000	47.40	-6.43	40.97	74.00	-33.03	peak	149		P	
4	2500.000	33.77	-6.43	27.34	54.00	-26.66	AVG	149		P	

TM3 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	46.11	-7.54	38.57	74.00	-35.43	peak	149		P	
2 *	2483.500	34.18	-7.54	26.64	54.00	-27.36	AVG	149		P	
3	2500.000	45.29	-7.48	37.81	74.00	-36.19	peak	149		P	
4	2500.000	34.02	-7.48	26.54	54.00	-27.46	AVG	149		P	

1. Margin = Measurement Level - Limit ; Measurement Level=Test receiver reading + correction factor

2.The test software will only record the worst test angle and height, and only the worst case will be recorded in the test report.

4.7 Emissions in frequency bands (below 1GHz)

<table>
<tr><td>Test Requirement:</td><td>Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`</td></tr>
<tr><td>Test Limit:</td><td>
<table>
<tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr>
<tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr>
<tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr>
<tr><td>1.705-30.0</td><td>30</td><td>30</td></tr>
<tr><td>30-88</td><td>100 **</td><td>3</td></tr>
<tr><td>88-216</td><td>150 **</td><td>3</td></tr>
<tr><td>216-960</td><td>200 **</td><td>3</td></tr>
<tr><td>Above 960</td><td>500</td><td>3</td></tr>
</table>
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10-2013 section 6.6.4</td></tr>
<tr><td>Procedure:</td><td>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.
Remark:
1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.</td></tr>
</table>

	2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level =Receiver Reading + Antenna Factor + Cable Factor ¨C Preamplifier Factor 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown. Margin= Mesurement Level- Limit Measurement Level=Test receiver reading + correction factor Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

4.7.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.3 °C	Humidity:	51.4 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1(worse case)				

4.7.2 Test Setup Diagram:





4.7.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	31.6202	22.43	-3.30	19.13	40.00	-20.87	QP	100		P	
2	114.9169	23.13	-5.03	18.10	43.50	-25.40	QP	100		P	
3	177.5092	23.08	-3.17	19.91	43.50	-23.59	QP	100		P	
4	387.9920	23.03	1.47	24.50	46.00	-21.50	QP	100		P	
5 *	704.2261	23.34	5.66	29.00	46.00	-17.00	QP	100		P	
6	993.0114	22.73	10.27	33.00	54.00	-21.00	QP	100		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.7455	21.97	-3.06	18.91	40.00	-21.09	QP	100		P	
2	129.4677	22.83	-4.51	18.32	43.50	-25.18	QP	100		P	
3	188.4125	23.03	-3.05	19.98	43.50	-23.52	QP	100		P	
4	422.0577	23.53	1.27	24.80	46.00	-21.20	QP	100		P	
5 *	785.0935	24.73	5.91	30.64	46.00	-15.36	QP	100		P	
6	996.4996	22.88	10.36	33.24	54.00	-20.76	QP	100		P	

Remark:

1.Margin= Mesurement Level- Limit; Measurement Level=Test receiver reading + correction factor

2.The EMC test software will only record the worst test angle and height, and only the worst case will be record edin the test report.

4.8 Emissions in frequency bands (above 1GHz)

<table>
<tr><td>Test Requirement:</td><td>In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`</td></tr>
<tr><td>Test Limit:</td><td>
<table>
<tr><th>Frequency (MHz)</th><th>Field strength (microvolts/meter)</th><th>Measurement distance (meters)</th></tr>
<tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr>
<tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr>
<tr><td>1.705-30.0</td><td>30</td><td>30</td></tr>
<tr><td>30-88</td><td>100 **</td><td>3</td></tr>
<tr><td>88-216</td><td>150 **</td><td>3</td></tr>
<tr><td>216-960</td><td>200 **</td><td>3</td></tr>
<tr><td>Above 960</td><td>500</td><td>3</td></tr>
</table>
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10-2013 section 6.6.4</td></tr>
<tr><td>Procedure:</td><td>a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.
Remark:
1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.</td></tr>
</table>

	2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level =Receiver Reading + Antenna Factor + Cable Factor ¨C Preamplifier Factor 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown. Margin= Mesurement Level- Limit Measurement Level=Test receiver reading + correction factor Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

4.8.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.3 °C	Humidity:	51.4 %	Atmospheric Pressure:	102 kPa
Pretest mode:	TM1, TM2, TM3				
Final test mode:	TM1(worse case)				

4.8.2 Test Setup Diagram:



4.8.3 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4818.750	64.18	-0.85	63.33	74.00	-10.67	peak	149		P	
2 *	4818.750	48.72	-0.85	47.87	54.00	-6.13	AVG	149		P	
3	7239.250	42.51	4.17	46.68	74.00	-27.32	peak	149		P	
4	7239.250	31.01	4.17	35.18	54.00	-18.82	AVG	149		P	
5	9648.000	34.67	8.10	42.77	74.00	-31.23	peak	149		P	
6	9648.000	23.98	8.10	32.08	54.00	-21.92	AVG	149		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4818.750	49.31	-0.23	49.08	74.00	-24.92	peak	149		P	
2 *	4818.750	34.81	-0.23	34.58	54.00	-19.42	AVG	149		P	
3	7239.250	37.16	4.16	41.32	74.00	-32.68	peak	149		P	
4	7239.250	26.05	4.16	30.21	54.00	-23.79	AVG	149		P	
5	9648.000	34.82	8.05	42.87	74.00	-31.13	peak	149		P	
6	9648.000	24.04	8.05	32.09	54.00	-21.91	AVG	149		P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4877.500	63.30	-0.65	62.65	74.00	-11.35	peak	149		P	
2 *	4877.500	47.47	-0.65	46.82	54.00	-7.18	AVG	149		P	
3	7309.750	44.01	4.29	48.30	74.00	-25.70	peak	149		P	
4	7309.750	32.66	4.29	36.95	54.00	-17.05	AVG	149		P	
5	9748.000	35.03	8.10	43.13	74.00	-30.87	peak	149		P	
6	9748.000	24.48	8.10	32.58	54.00	-21.42	AVG	149		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: M



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4877.500	47.77	-0.04	47.73	74.00	-26.27	peak	149		P	
2 *	4877.500	33.32	-0.04	33.28	54.00	-20.72	AVG	149		P	
3	7309.750	37.63	4.34	41.97	74.00	-32.03	peak	149		P	
4	7309.750	26.37	4.34	30.71	54.00	-23.29	AVG	149		P	
5	9748.000	35.58	8.12	43.70	74.00	-30.30	peak	149		P	
6	9748.000	24.47	8.12	32.59	54.00	-21.41	AVG	149		P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4924.500	62.30	-0.50	61.80	74.00	-12.20	peak	149		P	
2 *	4924.500	44.73	-0.50	44.23	54.00	-9.77	AVG	149		P	
3	7392.000	41.87	4.42	46.29	74.00	-27.71	peak	149		P	
4	7392.000	30.21	4.42	34.63	54.00	-19.37	AVG	149		P	
5	9848.000	35.76	8.10	43.86	74.00	-30.14	peak	149		P	
6	9848.000	24.57	8.10	32.67	54.00	-21.33	AVG	149		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4924.500	47.61	0.11	47.72	74.00	-26.28	peak	149		P	
2 *	4924.500	32.90	0.11	33.01	54.00	-20.99	AVG	149		P	
3	7356.750	36.09	4.44	40.53	74.00	-33.47	peak	149		P	
4	7427.250	24.86	4.62	29.48	54.00	-24.52	AVG	149		P	
5	9848.000	35.16	8.19	43.35	74.00	-30.65	peak	149		P	
6	9848.000	24.29	8.19	32.48	54.00	-21.52	AVG	149		P	

Remark: 1.Margin= Level – Limit; Level=Test receiver reading + correction factor

2.The test software will only record the worst test angle and height, and only the worst case will be recorded in the test report.

5 TEST SETUP PHOTOS

Please Refer to test setup file for Details.

6 PHOTOS OF THE EUT

Please Refer to external photos file and internal photos for Details.

Appendix

1. -6dB Bandwidth

Condition	Antenna	Modulation	Frequency (MHz)	-6dB BW(MHz)	limit(kHz)	Result
NVNT	ANT1	802.11b	2412.00	9.19	500	Pass
NVNT	ANT1	802.11b	2437.00	9.19	500	Pass
NVNT	ANT1	802.11b	2462.00	9.20	500	Pass
NVNT	ANT1	802.11g	2412.00	16.45	500	Pass
NVNT	ANT1	802.11g	2437.00	16.44	500	Pass
NVNT	ANT1	802.11g	2462.00	16.43	500	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	17.66	500	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	17.70	500	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	17.69	500	Pass

-6dB_Bandwidth_NVNT_ANT1_802_11b_2412



-6dB_Bandwidth_NVNT_ANT1_802_11b_2437



-6dB_Bandwidth_NVNT_ANT1_802_11b_2462



-6dB_Bandwidth_NVNT_ANT1_802_11g_2412



-6dB_Bandwidth_NVNT_ANT1_802_11g_2437



-6dB_Bandwidth_NVNT_ANT1_802_11g_2462



-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2412



-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2437



-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2462



2. 99% Occupied Bandwidth

Condition	Antenna	Modulation	Frequency (MHz)	99%%BW(MHz)
NVNT	ANT1	802.11b	2412.00	14.460
NVNT	ANT1	802.11b	2437.00	14.333
NVNT	ANT1	802.11b	2462.00	14.309
NVNT	ANT1	802.11g	2412.00	17.698
NVNT	ANT1	802.11g	2437.00	17.481
NVNT	ANT1	802.11g	2462.00	17.430
NVNT	ANT1	802.11n(HT20)	2412.00	18.552
NVNT	ANT1	802.11n(HT20)	2437.00	18.358
NVNT	ANT1	802.11n(HT20)	2462.00	18.313

99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2412



99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2437



99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2462



99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2412



99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2437



99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2462



99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2412



99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2437

99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2462



3. MAX. Output Power

Condition	Antenna	Modulation	Frequency (MHz)	Detector	Conducted Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	Peak	12.26	30	Pass
NVNT	ANT1	802.11b	2437.00	Peak	13.22	30	Pass
NVNT	ANT1	802.11b	2462.00	Peak	14.56	30	Pass
NVNT	ANT1	802.11g	2412.00	Peak	7.86	30	Pass
NVNT	ANT1	802.11g	2437.00	Peak	9.05	30	Pass
NVNT	ANT1	802.11g	2462.00	Peak	9.82	30	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	Peak	8.25	30	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	Peak	8.71	30	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	Peak	9.97	30	Pass

MAX__Output_Power_NVNT_ANT1_802_11b_2412



MAX__Output_Power_NVNT_ANT1_802_11b_2437



MAX__Output_Power_NVNT_ANT1_802_11b_2462



MAX__Output_Power_NVNT_ANT1_802_11g_2412



MAX__Output_Power_NVNT_ANT1_802_11g_2437



MAX__Output_Power_NVNT_ANT1_802_11g_2462



MAX__Output_Power_NVNT_ANT1_802_11n(HT20)_2412



MAX__Output_Power_NVNT_ANT1_802_11n(HT20)_2437



MAX__Output_Power_NVNT_ANT1_802_11n(HT20)_2462



4. Power Spectral Density

Condition	Antenna	Modulation	Frequency (MHz)	PSD (dBm/30kHz)	RB factor (dB)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
NVNT	ANT1	802.11b	2412.00	-7.29	-10.00	-17.29	8	Pass
NVNT	ANT1	802.11b	2437.00	-6.21	-10.00	-16.21	8	Pass
NVNT	ANT1	802.11b	2462.00	-4.82	-10.00	-14.82	8	Pass
NVNT	ANT1	802.11g	2412.00	-14.54	-10.00	-24.54	8	Pass
NVNT	ANT1	802.11g	2437.00	-13.22	-10.00	-23.22	8	Pass
NVNT	ANT1	802.11g	2462.00	-12.45	-10.00	-22.45	8	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	-14.45	-10.00	-24.45	8	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	-14.11	-10.00	-24.11	8	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	-12.71	-10.00	-22.71	8	Pass

PSD(dBm/3kHz) = PSD(dBm/30kHz) + RB factor (dB); RB factor (dB) = 10*log(3/30)=-10dB

Power_Spectral_Density_NVNT_ANT1_802_11b_2412



Power_Spectral_Density_NVNT_ANT1_802_11b_2437



Power_Spectral_Density_NVNT_ANT1_802_11b_2462



Power_Spectral_Density_NVNT_ANT1_802_11g_2412



Power_Spectral_Density_NVNT_ANT1_802_11g_2437



Power_Spectral_Density_NVNT_ANT1_802_11g_2462



Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_2412



Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_2437



Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_2462



5. Bandedge

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_frequency(MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	2398.480	-36.506	-22.785	Pass
NVNT	ANT1	802.11b	2462.00	2490.400	-52.337	-21.126	Pass
NVNT	ANT1	802.11g	2412.00	2398.592	-37.885	-30.018	Pass
NVNT	ANT1	802.11g	2462.00	2484.208	-54.762	-27.935	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	2398.816	-40.244	-29.868	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	2483.536	-51.208	-27.898	Pass

1_Reference_Level_NVNT_ANT1_802_11b_2412



2_Bandedge_NVNT_ANT1_802_11b_2412



1_Reference_Level_NVNT_ANT1_802_11b_2462



2_Bandedge_NVNT_ANT1_802_11b_2462

1_Reference_Level_NVNT_ANT1_802_11g_2412



2_Bandedge_NVNT_ANT1_802_11g_2412



1_Reference_Level_NVNT_ANT1_802_11g_2462



2_Bandedge_NVNT_ANT1_802_11g_2462

1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412

2_Bandedge_NVNT_ANT1_802_11n(HT20)_2412



1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462



2_Bandedge_NVNT_ANT1_802_11n(HT20)_2462

6. Spurious Emission

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_frequency(MHz)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	2561.958	-57.321	-22.785	Pass
NVNT	ANT1	802.11b	2437.00	24398.223	-56.071	-21.779	Pass
NVNT	ANT1	802.11b	2462.00	24540.552	-49.048	-21.126	Pass
NVNT	ANT1	802.11g	2412.00	2569.449	-62.611	-30.018	Pass
NVNT	ANT1	802.11g	2437.00	24530.564	-57.689	-28.638	Pass
NVNT	ANT1	802.11g	2462.00	24912.605	-61.663	-27.935	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	2559.461	-62.854	-29.868	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	24523.073	-58.264	-29.362	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	2601.910	-62.200	-27.898	Pass

1_Reference_Level_NVNT_ANT1_802_11b_2412



2_Spurious_Emission_NVNT_ANT1_802_11b_2412



1_Reference_Level_NVNT_ANT1_802_11b_2437



2_Spurious_Emission_NVNT_ANT1_802_11b_2437



1_Reference_Level_NVNT_ANT1_802_11b_2462



2_Spurious_Emission_NVNT_ANT1_802_11b_2462



1_Reference_Level_NVNT_ANT1_802_11g_2412



2_Spurious_Emission_NVNT_ANT1_802_11g_2412



1_Reference_Level_NVNT_ANT1_802_11g_2437



2_Spurious_Emission_NVNT_ANT1_802_11g_2437



1_Reference_Level_NVNT_ANT1_802_11g_2462



2_Spurious_Emission_NVNT_ANT1_802_11g_2462



1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412



2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2412



1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2437



2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2437



1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462



2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2462



********** End of Report **********