

TEST REPORT

Product Name: Wireless Auto Shut-off Valve
FCC ID: 2BAJX-F104
Trademark: N/A
Model Number: F104H, F104C, F104E, F104F, F104G, F104I, F104K, F104L, F104M, F104N, F104P, F104Q, F104R
Prepared For: ZHEJIANG RUNLUCKY PURIFICATION TECHNOLOGY CO., LTD.
Address: No.12, Bailian Road, Nanmingshan Street, Liandu District, Lishui, Zhejiang, China
Manufacturer: WENZHOU RUNXIN MANUFACTURING MACHINE CO., LTD.
Address: No.169, Runxin Road, Shanfu Town, Wenzhou, Zhejiang, China
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: Feb. 24, 2023
Sample tested Date: Feb. 24, 2023 to Mar. 09, 2023
Issue Date: Mar. 09, 2023
Report No.: CTB230309044RFX
Test Standards: FCC Part15.231
ANSI C63.10:2013
Test Results: PASS
Remark: This is 433MHz radio test report.

Compiled by:

ChenZheng

Chen Zheng

Reviewed by:

Arron Liu

Arron Liu

Approved by:

Bin Mei / Director

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report r
Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

TABLE OF CONTENT

Test Report Declaration	Page
1. VERSION.....	3
2. TEST SUMMARY	4
3. MEASUREMENT UNCERTAINTY	5
4. PRODUCT INFORMATION AND TEST SETUP	6
4.1 Product Information	6
4.2 Test Setup Configuration.....	6
4.3 Support Equipment.....	6
4.4 Test Mode	7
4.5 Test Environment	7
5. TEST FACILITY AND TEST INSTRUMENT USED	8
5.1 Test Facility	8
5.2 Test Instrument Used	8
6. AC POWER LINE CONDUCTED EMISSION	11
6.1 Block Diagram Of Test Setup.....	11
6.2 Limit.....	11
6.3 Test procedure	11
6.4 Test Result	12
7. RADIATED EMISSION.....	14
7.1 Block Diagram Of Test Setup.....	14
7.2 Limit.....	14
7.3 Test procedure	15
7.4 Test Result	16
8. DWELL TIME.....	22
8.1 Block Diagram Of Test Setup.....	22
8.2 Limit.....	22
8.3 Test procedure	22
8.4 Test Result	23
9. OCCUPIED BANDWIDTH	24
9.1 Block Diagram Of Test Setup.....	24
9.2 Limit.....	24
9.3 Test procedure	24
9.4 Test Result	25
10. ANTENNA REQUIREMENT	26
11. EUT PHOTOGRAPHS.....	27
12. EUT TEST SETUP PHOTOGRAPHS.....	28

(Note: N/A means not applicable)

1. VERSION

Report No.	Issue Date	Description	Approved
CTB230309044RFX	Mar. 09, 2023	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	N/A
Radiated Emission	47 CFR Part 15 Subpart C Section 15.209; 15.231(b)	ANSI C63.10-2013	PASS
Dwell Time	47 CFR Part 15 Subpart C Section 15.231 (a)	ANSI C63.10-2013	PASS
Occupied Bandwidth	47 CFR Part 15 Subpart C Section 15.231(c)	ANSI C63.10-2013	PASS
Antenna requirement	47 CFR Part 15 Subpart C Section 15.203	ANSI C63.10-2013	PASS

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Item	Uncertainty
Occupancy bandwidth	$U=\pm 54.3\text{Hz}$
Conducted output power Above 1G	$U=\pm 1.0\text{dB}$
Conducted output power below 1G	$U=\pm 0.9\text{dB}$
Power Spectral Density , Conduction	$U=\pm 1.0\text{dB}$
Conduction spurious emissions	$U=\pm 2.8\text{dB}$
Out of band emission	$U=\pm 54\text{Hz}$
3m camber Radiated spurious emission(30MHz-1GHz)	$U=\pm 4.3\text{dB}$
3m chamber Radiated spurious emission(1GHz-18GHz)	$U=\pm 4.5\text{dB}$
humidity uncertainty	$U=\pm 5.3\%$
Temperature uncertainty	$U=\pm 0.59^{\circ}\text{C}$
Supply voltages	$U=\pm 3\%$
Time	$U=\pm 5\%$

4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Model(s):	F104H, F104C, F104E, F104F, F104G, F104I, F104K, F104L, F104M, F104N, F104P, F104Q, F104R
Model Description:	All model's the function, software and electric circuit are the same, only with the product size and model named different. Test sample model: F104H
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	433.82MHz
Type of Modulation:	ASK
Antenna installation:	FPC antenna
Antenna Gain:	2.5dBi
Ratings:	Input:100-240V~ 50/60Hz 0.6A Max Output:12V === 1500mA

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Data Cable	Power Cord
1.	---	---	---	---	---	--

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test mode
Keep the EUT in transmitting mode with modulation.

4.5 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(AC):	120V
Normal Temperature(°C)	23

5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at 1&2F., Building A, No. 26, Xinghe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

5.2 Test Instrument Used

No.	Equipment	Manufacturer	Model No.	Serial No.	Calibrated date	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	2022.07.20	2023.07.19
2	Power Sensor	Agilent	U2021XA	MY56120032	2022.07.20	2023.07.19
3	Power Sensor	Agilent	U2021XA	MY56120034	2022.07.20	2023.07.19
4	Communication test set	R&S	CMW500	108058	2022.07.20	2023.07.19
5	Spectrum Analyzer	R&S	N9020A	MY51289897	2022.07.20	2023.07.19
6	Signal Generator	Agilent	N5181A	MY50140365	2022.07.20	2023.07.19
7	Vector signal generator	Agilent	N5182A	MY47420195	2022.07.20	2023.07.19
8	Communication test set	Agilent	E5515C	MY50102567	2022.07.20	2023.07.19
9	2.4 GHz Filter	Shenxiang	MSF2400-2483.5MS-1154	20181015001	2022.07.20	2023.07.19
10	5 GHz Filter	Shenxiang	MSF5150-5850MS-1155	20181015001	2022.07.20	2023.07.19
11	Filter	Xingbo	XBLBQ-DZA120	190821-1-1	2022.07.20	2023.07.19
12	BT&WI-FI Automatic test software	Microwave	MTS8000	Ver. 2.0.0.0	/	/
13	Rohde & Schwarz SFU Broadcast Test	R&S	SFU	101017	2021.10.31	2023.10.30

	System					
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	2022.07.20	2023.07.19
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/	/
16	966 chamber	C.R.T.	966	/	2021.08.12	2024.08.11
17	Receiver	R&S	ESPI	100362	2022.07.20	2023.07.19
18	Amplifier	HP	8447E	2945A02747	2022.07.20	2023.07.19
19	Amplifier	Agilent	8449B	3008A01838	2022.07.20	2023.07.19
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	00869	2022.07.20	2023.07.1
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	2022.07.20	2023.07.19
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/
23	3-Loop Antenna	Daze	FMZB 1519B	1519B-224	2022.07.20	2023.07.19
24	loop antenna	ZHINAN	ZN30900A	GTS534	2022.07.20	2023.07.19
25	40G Horn antenna	A/H/System	SAS-574	588	2021.10.31	2024.10.30
26	Amplifier	AEROFLEX	Aeroflex	097	2022.07.20	2024.10.30


Continuous disturbance						
No.	Equipment	Manufacturer	Model No.	Serial No.	Calibrated date	Calibrated until
1	LISN	ROHDE&SCHWARZ	ESH3-Z5	100318	2022.07.20	2023.07.19
2	Pulse limiter	ROHDE&SCHWARZ	ESH3Z2	357881052	2022.07.20	2023.07.19
3	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428/003	2022.07.20	2023.07.19
4	Coaxial cable	ZDECL	Z302S-NJ-SMAJ-12M	18091905	2022.07.20	2023.07.19
5	ISN	Schwarzbeck	NTFM8158	183	2022.07.20	2023.07.19
6	Communication test set	Agilent	E5515C	MY50102567	2022.07.20	2023.07.19
7	Communication test set	R&S	CMW500	108058	2022.07.20	2023.07.19

8	EZ-EMC	Frad	EMC-con3A1.1	/	/	/
---	--------	------	--------------	---	---	---

Radiated emission						
No.	Equipment	Manufacturer	Model No.	Serial No.	Calibrated date	Calibrated until
1	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120D	1911	2022.07.23	2023.07.22
2	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	869	2022.07.23	2023.07.22
3	Amplifier	Agilent	8449B	3008A01838	2022.07.20	2023.07.19
4	Amplifier	HP	8447E	2945A02747	2022.07.20	2023.07.19
5	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESPI7	100362	2022.07.20	2023.07.19
6	Coaxial cable	ETS	RFC-SNS-100-NMS-80 NI	/	2022.07.20	2023.07.19
7	Coaxial cable	ETS	RFC-SNS-100-NMS-20 NI	/	2022.07.20	2023.07.19
8	Coaxial cable	ETS	RFC-SNS-100-SMS-20 NI	/	2022.07.20	2023.07.19
9	Coaxial cable	ETS	RFC-NNS-100-NMS-300 NI	/	2022.07.20	2023.07.19
10	Communication test set	Agilent	E5515C	MY50102567	2022.07.20	2023.07.19
11	Communication test set	R&S	CMW500	108058	2022.07.20	2023.07.19
12	EZ-EMC	Frad	EMC-con3A1.1	/	/	/

6. AC POWER LINE CONDUCTED EMISSION

6.1 Block Diagram Of Test Setup



6.2 Limit

Frequency (MHz)	Maximum RF Line Voltage (dB μ V)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50


* Decreasing linearly with the logarithm of the frequency

6.3 Test procedure

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50 Ω /50 μ H + 5 Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

6.4 Test Result


Temperature:	23℃	Relative Humidity:	54%
Pressure:	101.6kPa	Phase :	L
Test Mode	1(the worst data)	Remark:	N/A



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1986	41.57	10.00	51.57	63.67	-12.10	QP
2		0.1986	25.58	10.00	35.58	53.67	-18.09	AVG
3		0.4380	33.06	9.98	43.04	57.10	-14.06	QP
4		0.4380	21.18	9.98	31.16	47.10	-15.94	AVG
5		0.6820	27.15	9.97	37.12	56.00	-18.88	QP
6		0.6820	14.62	9.97	24.59	46.00	-21.41	AVG
7		1.2100	24.94	9.99	34.93	56.00	-21.07	QP
8		1.2100	11.58	9.99	21.57	46.00	-24.43	AVG
9		2.1660	21.56	10.04	31.60	56.00	-24.40	QP
10		2.1660	7.82	10.04	17.86	46.00	-28.14	AVG
11		13.5220	22.62	10.43	33.05	60.00	-26.95	QP
12		13.5220	16.57	10.43	27.00	50.00	-23.00	AVG

Remark: Result=Reading +Factor
Over Limit=Result -Limit

Temperature:	23℃	Relative Humidity:	54%
Pressure:	101.6kPa	Phase :	N
Test Mode	1(the worst data)	Remark:	N/A



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	*	0.1500	45.21	10.01	55.22	66.00	-10.78	QP
2		0.1500	25.69	10.01	35.70	56.00	-20.30	AVG
3		0.4460	28.87	9.98	38.85	56.95	-18.10	QP
4		0.4460	16.40	9.98	26.38	46.95	-20.57	AVG
5		1.2860	20.21	9.99	30.20	56.00	-25.80	QP
6		1.2860	6.85	9.99	16.84	46.00	-29.16	AVG
7		3.5380	16.71	10.10	26.81	56.00	-29.19	QP
8		3.5380	4.23	10.10	14.33	46.00	-31.67	AVG
9		13.5219	23.03	10.43	33.46	60.00	-26.54	QP
10		13.5219	16.38	10.43	26.81	50.00	-23.19	AVG
11		27.0460	12.04	10.63	22.67	60.00	-37.33	QP
12		27.0460	2.97	10.63	13.60	50.00	-36.40	AVG

Remark: Result=Reading +Factor
Over Limit=Result -Limit

7. RADIATED EMISSION

7.1 Block Diagram Of Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1GHz

7.2 Limit

Spurious Emissions:

Frequency	Field strength (dBμV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	$20\log 2400/F \text{ (kHz)} + 80$	-	3
0.490MHz-1.705MHz	$20\log 24000/F \text{ (kHz)} + 40$	-	3
1.705MHz-30MHz	$20\log 30 + 40$	-	3
30MHz-88MHz	40.0	Quasi-peak	3
88MHz-216MHz	43.5	Quasi-peak	3
216MHz-960MHz	46.0	Quasi-peak	3
960MHz-1GHz	54.0	Quasi-peak	3
Above 1GHz	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Field Strength of Fundamental Limit:

Fundamental and harmonics emission limits Frequency(MHz)	Field strength of Fundamental((microvolts/meter) of	Field strength of spurious emissions(microvolts/meter)
40.66-40.70	2280	225
70-130	1250	125
130-174	1250 to 3750**	125 to 375**
174-260	3750	375
260-470	3750 to 12500**	375 to 1250**
Above 470	12500	1250

** linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, $\mu\text{V/m}$ at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

Frequency	Limit (dB $\mu\text{V/m}$ @3m)	Remark
433MHz	80.8	Average Value
	100.8	Peak Value

7.3 Test procedure

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
- Test the EUT in the lowest channel ,the middle channel ,the Highest channel
- Repeat above procedures until all frequencies measured was complete.

Receiver set:


Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100 kHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average


7.4 Test Result

7.4.1 Calculation of average factor

The output field strengths of specification in accordance with the FCC rules specify measurements with an average detector. During the test, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The duty cycle is measured in 100 ms or the repetition cycle period, whichever is a shorter time frame. The duty cycle is measured by placing the spectrum analyzer to set zero span at 100kHz resolution bandwidth.





Average factor:

Calculate Formula:	Average value=Peak value + PDCF
	PDCF=20 log(Duty cycle)
	Duty cycle = T on time / T period
Calculated average factor:	Ton time = 1.02×13+0.32×12=17.10(ms); T period =44.4(ms)
	PDCF = 20 log(17.10/44.4)= -8.29dB

7.4.2 Radiated Spurious Emission

Frequency Range (9 kHz-30MHz)


Frequency (MHz)	Level@3m (dBμV/m)	Limit@3m (dBμV/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note: 1. Emission Level=Reading+ Cable loss-Antenna factor-Amp factor

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement


About 30MHz-1GHz Test Results:

Antenna polarity: H



Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
45.6946	26.88	-6.56	20.32	40.00	-19.68	
160.0646	37.79	-5.48	32.31	43.50	-11.19	QP
219.4596	36.43	-8.99	27.44	46.00	-18.56	QP
434.8267	72.55	-1.71	70.84	100.8	-29.96	QP
585.8156	27.85	2.11	29.96	46.00	-16.04	QP
869.1301	40.75	6.66	47.41	80.8	-33.39	QP

Antenna polarity: V



Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
44.9004	29.79	-6.54	23.25	40.00	-16.75	
130.8369	42.29	-6.23	36.06	43.50	-7.44	QP
161.4740	42.34	-5.65	36.69	43.5	-6.81	QP
434.8267	69.85	-1.71	68.14	100.8	-32.66	QP
762.0384	30.92	5.05	35.97	46.00	-10.03	QP
869.1301	40.50	6.66	47.16	80.8	-33.64	QP

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Limit – Level

For average Emission

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit AV	Margin	Polarization
434.83	70.84	-8.29	62.55	80.80	-18.25	Horizontal
869.13	47.41	-8.29	39.12	60.80	-21.68	Horizontal
434.83	68.14	-8.29	59.85	80.80	-20.95	Vertical
869.13	47.16	-8.29	38.87	60.80	-21.93	Vertical

Notes: Average emission Level = Peak Level + Duty cycle factor


Above 1GHz Test Results

Frequency MHz	Peak Level dBuV/m	Duty cycle factor	Average Level dBuV/m	Limit		Margin dB		Polarization
				PK	AV	PK	AV	
1304.58	50.34	-9.02	41.32	80.8	60.8	-30.46	-19.48	Vertical
1739.44	48.76	-9.02	39.74	80.8	60.8	-32.04	-21.06	Vertical
2174.3	44.84	-9.02	35.82	80.8	60.8	-35.96	-24.98	Vertical
2609.16	42.02	-9.02	33.00	80.8	60.8	-38.78	-27.80	Vertical
3044.02	41.91	-9.02	32.89	80.8	60.8	-38.89	-27.91	Vertical
3478.88	40.70	-9.02	31.68	80.8	60.8	-40.10	-29.12	Vertical
2607.39	49.21	-9.02	40.19	80.8	60.8	-31.59	-20.61	Horizontal
3476.52	46.84	-9.02	37.82	80.8	60.8	-33.96	-22.98	Horizontal
4345.65	42.82	-9.02	33.80	80.8	60.8	-37.98	-27.00	Horizontal
5214.78	40.69	-9.02	31.67	80.8	60.8	-40.11	-29.13	Horizontal
6083.91	41.57	-9.02	32.55	80.8	60.8	-39.23	-28.25	Horizontal
6953.04	40.51	-9.02	31.49	80.8	60.8	-40.29	-29.31	Horizontal

Notes: Average emission Level = Peak Level + Duty cycle factor

8. DWELL TIME

8.1 Block Diagram Of Test Setup



8.2 Limit

According to FCC 15.231(a) requirement:


A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

8.3 Test procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.


8.4 Test Result

Transmitting time(S)	Limit (S)	Results
2.48	≤5	Pass



9. OCCUPIED BANDWIDTH

9.1 Block Diagram Of Test Setup



9.2 Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.


B.W (20dBc) Limit = 0.25% * f(MHz) = 0.25% * 433.92MHz = 1.0848MHz

9.3 Test procedure

1. Set RBW = 10 kHz.
2. Set the video bandwidth (VBW) ≥ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

9.4 Test Result

20dB bandwidth (kHz)	Limit (MHz)	Results
18.98	1.0848	Pass



10. ANTENNA REQUIREMENT

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is FPC antenna and no consideration of replacement. The best case gain of the antenna is 2.5dBi.

11. EUT PHOTOGRAPHS

External Photos EUT Photo 1

EUT Photo 2

12. EUT TEST SETUP PHOTOGRAPHS

Radiated Emission


Below 1GHz



Above 1GHz



Conducted emission



***** END OF REPORT *****