FCC TEST REPORT
FCC ID:2BAJY-RY-LC-MB

Report Number.....:	ZKT-230223L0972E-2
Date of Test.....	Dec. 20, 2022 to Apr. 04, 2023
Date of issue.....:	Apr. 04, 2023
Total number of pages.....	59
Test Result .....:	PASS
Testing Laboratory.....:	**Shenzhen ZKT Technology Co., Ltd.**
Address .....:	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Applicant's name .....:	**Zhejiang Rain Intelligent Technology Co.,Ltd.**
Address .....:	No. 77, Jing 10 Road, Yueqing Economic Development Zone, Yueqing City, Wenzhou City, Zhejiang Province China
Manufacturer's name .....:	**Zhejiang Rain Intelligent Technology Co.,Ltd.**
Address .....:	No. 77, Jing 10 Road, Yueqing Economic Development Zone, Yueqing City, Wenzhou City, Zhejiang Province China
Test specification:	
Standard.....:	FCC CFR Title 47 Part 15 Subpart E Section 15.407 ANSI C63.10:2013 KDB 789033 D02 v01r02
Test procedure.....:	/
Non-standard test method .....:	N/A
Test Report Form No.....:	TRF-EL-113_V0
Test Report Form(s) Originator.....:	ZKT Testing
Master TRF .....:	Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name.....:	**E-bayfan Laptop**
Trademark .....:	N/A
Model/Type reference.....:	RY-LC-MB(R3000)CPU(5400U)MC(8G)HD(512G)SP(156)MT(AL6063T6)SL(358)SW(228)SH(18)
Ratings.....:	Adapter: Input：AC100-240V 50/60Hz 1.5A Output: DC 19V 3.42A DC 11.4V from the battery

Testing procedure and testing location:

Testing Laboratory..... :	Shenzhen ZKT Technology Co., Ltd.
Address..... :	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Tested by (name + signature)..... :	Alen He
Reviewer (name + signature)..... :	Joe Liu
Approved (name + signature)..... :	Lake Xie

Table of Contents **Page**

1. VERSION 5
2.SUMMARY OF TEST RESULTS 6
2.1 TEST FACILITY 7
2.2 MEASUREMENT UNCERTAINTY 7
3. GENERAL INFORMATION 8
3.1 GENERAL DESCRIPTION OF EUT 8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 10
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS 11
4.EMC EMISSION TEST 13
4.1 CONDUCTED EMISSION MEASUREMENT 13
4.1.1 POWER LINE CONDUCTED EMISSION Limits 13
4.1.2 TEST PROCEDURE 13
4.1.3 DEVIATION FROM TEST STANDARD 13
4.1.4 TEST SETUP 14
4.1.5 EUT OPERATING CONDITIONS 14
4.1.6 TEST RESULT 15
4.2 RADIATED EMISSION MEASUREMENT 17
4.2.1 APPLICABLE STANDARD 17
4.2.2 CONFORMANCE LIMIT 17
4.2.3 MEASURING INSTRUMENTS 17
4.2.4 TEST CONFIGURATION 18
4.2.5 TEST PROCEDURE 19
4.2.6 TEST RESULT 20
5.POWER SPECTRAL DENSITY TEST 29
5.1 APPLIED PROCEDURES / LIMIT 29
5.2 TEST PROCEDURE 30
5.3 DEVIATION FROM STANDARD 30
5.4 TEST SETUP 30
5.5 EUT OPERATION CONDITIONS 30
5.6 TEST RESULTS 31
6. 26DB & 99% EMISSION BANDWIDTH 38
6.1 APPLIED PROCEDURES / LIMIT 38
6.2 TEST PROCEDURE 38
6.3 EUT OPERATION CONDITIONS 39
6.4 TEST RESULTS 39
7.MAXIMUM CONDUCTED OUTPUT POWER 46

Table of Contents **Page**

7.1 PPLIED PROCEDURES / LIMIT 46
7.2 TEST PROCEDURE 46
7.3 DEVIATION FROM STANDARD 47
7.4 TEST SETUP 47
7.5 EUT OPERATION CONDITIONS 47
7.6 TEST RESULTS 48

8.OUT OF BAND EMISSIONS 49
8.1 APPLICABLE STANDARD 49
8.2 TEST PROCEDURE 49
8.3 DEVIATION FROM STANDARD 49
8.4 TEST SETUP 50
8.5 EUT OPERATION CONDITIONS 51
8.6 TEST RESULTS 51

10.Frequency Stability Measurement 52
10.1 LIMIT 52
10.2 TEST PROCEDURES 52
10.3 TEST SETUP LAYOUT 52
10.4 EUT OPERATION DURING TEST 52
10.5 TEST RESULTS 52

11.ANTENNA REQUIREMENT 58

12.DUTY CYCLE 59
12.1 TEST RESULTS 59

13. TEST SETUP PHOTO 67

14. EUT CONSTRUCTIONAL DETAILS 67

1. VERSION

Report No.	Version	Description	Approved
ZKT-230223L0972E-2	Rev.01	Initial issue of report	Apr. 04, 2023

2.SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E KDB 558074 D01, KDB 789033 D02			
Standard Section	Test Item	Judgment	Remark
15.209(a) 15.407 (b)	Spurious Radiated Emissions	PASS	
15.207	Conducted Emission	PASS	
15.407 (a)(12) 2.1049	26 dB and 99% Emission Bandwidth	PASS	
15.407(e)	6 dB bandwidth	N/A	
15.407 (a)(1) 15.407 (a)(3)	Maximum Conducted Output Power	PASS	
2.1051, 15.407(b)	Band Edge	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.203	Antenna Requirement	PASS	
KDB 789033	Duty cycle	--	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033
CAB identifier: CN0110

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	3m camber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m camber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF Band Edge	U=1.68dB
7	RF power conducted	U=1.86dB
8	RF conducted Spurious Emission	U=2.2dB
9	RF Occupied Bandwidth	U=1.8dB
10	RF Power Spectral Density	U=1.75dB
11	humidity uncertainty	U=5.3%
12	Temperature uncertainty	U=0.59℃

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	E-bayfan Laptop	
Model No.:	RY-LC-MB(R3000)CPU(5400U)MC(8G)HD(512G)SP(156)MT(AL6063T6)SL(358)SW(228)SH(18)	
Model Different.:	N/A	
Sample ID	ZKT-2205062964-1	
Sample(s) Status:	Engineer sample	
Product Description	IEEE 802.11 WLAN Mode Supported	☒ 802.11a/ac/n (20MHz channel bandwidth) ☒ 802.11ac/n (40MHz channel bandwidth) ☒ 802.11ac(80MHz channel bandwidth)
	Data Rate	802.11a/ac/n(HT20/HT40):MCS0-MCS15; 802.11ac(VHT80):NSS1, MCS0-MCS9
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n/ac;
	Operating Frequency Range	☒ 5180-5240MHz for 802.11a/ac/n(HT20); 5190-5230MHz for 802.11ac/n(HT40); 5210MHz for 802.11 ac80;
	Number of Channels	☒ 4 channels for 802.11a/ac/n20 in the 5180-5240MHz band ; 2 channels for 802.11 ac/n40 in the 5190-5230 MHz band ; 1 channels for 802.11 ac80 in the 5210MHz band ;
Channel List	Please refer to the Note 2.	
Antenna Type:	PCB Antenna	
Antenna gain:	Antenna 1: 5dBi Antenna 2: 5dBi	
Directional Gain	8dBi(For MIMO 802.11n/ac Mode)	
Power supply:	Adapter: Input：AC100-240V 50/60Hz 1.5A Output: DC 19V 3.42A DC 11.4V from the battery	
Devices Type :	Client devices	
Note：Directional Gain =5dBi +10*log(2)=8 dBi		

802.11a/ac/n(20MHz) Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	-	-	-	-
40	5200	48	5240	-	-	-	-

802.11ac/n(40MHz) Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	-	-	-	-
46	5230	-	-	-	-	-	-

802.11ac (80MHz) Frequency Channel	
Channel	Frequency (MHz)
42	5210

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Pretest Mode	Description
Mode 1	802.11a/ac / n 20 CH36/ CH40/ CH 48
Mode 2	802.11ac / n 40 CH38/ CH 46
Mode 3	802.11 ac80 CH 42
Mode 4	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11a/ac / n 20 CH36/ CH40/ CH 48
Mode 2	802.11ac / n 40 CH38/ CH 46
Mode 3	802.11 ac80 CH 42

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

Test Software	Realtek Test Tool
Power level setup	<20dBm

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission

AC Line — EUT

Radiated Emission

AC Line — EUT

Conducted Spurious

AC Line — EUT

3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	E-bayfan Laptop	N/A	RY-LC-MB(R3000)CPU(5400U)MC(8G)HD(512G)SP(156)MT(AL6063T6)SL(358)SW(228)SH(18)	N/A	EUT
E-2	Power Adapter	N/A	JHD-AP065C-190342BA-A	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:
(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	Oct. 18, 2022	Oct. 17, 2023
2	Spectrum Analyzer (1GHz-40GHz)	R&S	FSQ	100363	Oct. 17, 2022	Oct. 16, 2023
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Oct. 18, 2022	Oct. 17, 2023
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	Oct. 17, 2022	Oct. 16, 2023
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	Oct. 17, 2022	Oct. 16, 2023
6	Loop Antenna	TESEQ	HLA6121	58357	Oct. 17, 2022	Oct. 16, 2023
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	Oct. 18, 2022	Oct. 17, 2023
8	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	Oct. 18, 2022	Oct. 17, 2023
9	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Oct. 18, 2022	Oct. 17, 2023
10	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Oct. 18, 2022	Oct. 17, 2023
11	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Oct. 18, 2022	Oct. 17, 2023
12	ESG Signal Generator	Agilent	E4421B	N/A	Oct. 22, 2022	Oct. 21, 2023
13	Signal Generator	Agilent	N5182A	N/A	Oct. 22, 2022	Oct. 21, 2023
14	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	Oct. 17, 2022	Oct. 16, 2023
15	MWRF Power Meter Test system	MW	MW100-RPCB	N/A	Oct. 22, 2022	Oct. 21, 2023
16	D.C. Power Supply	LongWei	TPR-6405D	N/A	\	\
17	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\
18	RF Software	MW	MTS8310	V2.0.0.0	\	\
19	Turntable	MF	MF-7802BS	N/A	\	\
20	Antenna tower	MF	MF-7802BS	N/A	\	\
21	Signal Generator	Agilent	N5182A	N/A	Oct. 22, 2022	Oct. 21, 2023

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Oct. 22, 2022	Oct. 21, 2023
2	LISN	CYBERTEK	EM5040A	E1850400149	Oct. 22, 2022	Oct. 21, 2023
3	Test Cable	N/A	C01	N/A	Oct. 18, 2022	Oct. 17, 2023
4	Test Cable	N/A	C02	N/A	Oct. 18, 2022	Oct. 17, 2023
5	EMI Test Receiver	R&S	ESCI3	101393	Oct. 17, 2022	Oct. 16, 2023
6	Absorbing Clamp	DZ	ZN23201	15034	Oct. 17, 2022	Oct. 16, 2023
7	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\

RF Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	Oct. 18, 2022	Oct. 17, 2023
2	MWRF Power Meter Test system	MW	MW100-RPCB	N/A	Oct. 22, 2022	Oct. 21, 2023
3	D.C. Power Supply	LongWei	TPR-6405D	N/A	\	\
4	RF Software	MW	MTS8310	V2.0.0.0	\	\

4.EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

d. LISN at least 80 cm from nearest part of EUT chassis.

e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULT

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.2830	26.75	9.68	36.43	60.73	-24.30	QP	P	
2	0.2830	16.57	9.68	26.25	50.73	-24.48	AVG	P	
3 *	0.4189	35.05	9.64	44.69	57.47	-12.78	QP	P	
4	0.4189	24.96	9.64	34.60	47.47	-12.87	AVG	P	
5	0.9627	26.83	9.54	36.37	56.00	-19.63	QP	P	
6	0.9627	15.73	9.54	25.27	46.00	-20.73	AVG	P	
7	1.5315	24.51	9.63	34.14	56.00	-21.86	QP	P	
8	1.5315	14.46	9.63	24.09	46.00	-21.91	AVG	P	
9	2.2237	25.57	9.70	35.27	56.00	-20.73	QP	P	
10	2.2237	16.55	9.70	26.25	46.00	-19.75	AVG	P	
11	3.4091	19.84	9.59	29.43	56.00	-26.57	QP	P	
12	3.4091	12.49	9.59	22.08	46.00	-23.92	AVG	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1 *	0.4213	38.76	9.64	48.40	57.42	-9.02	QP	P	
2	0.4213	25.22	9.64	34.86	47.42	-12.56	AVG	P	
3	0.4909	30.64	9.61	40.25	56.15	-15.90	QP	P	
4	0.4909	16.23	9.61	25.84	46.15	-20.31	AVG	P	
5	0.9887	30.67	9.53	40.20	56.00	-15.80	QP	P	
6	0.9887	16.62	9.53	26.15	46.00	-19.85	AVG	P	
7	1.7292	29.23	9.67	38.90	56.00	-17.10	QP	P	
8	1.7292	15.29	9.67	24.96	46.00	-21.04	AVG	P	
9	2.2652	27.75	9.69	37.44	56.00	-18.56	QP	P	
10	2.2652	15.73	9.69	25.42	46.00	-20.58	AVG	P	
11	2.8494	20.53	9.64	30.17	56.00	-25.83	QP	P	
12	2.8494	7.59	9.64	17.23	46.00	-28.77	AVG	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(b) and 15.209

4.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b)(10): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part15.205, Restricted bands
According to FCC Part 15.407b(1),b(9), For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

4.2.3 MEASURING INSTRUMENTS

The Measuring equipment is listed in the section 6.3 of this test report.

4.2.4 TEST CONFIGURATION

1.For radiated emissions below 30MHz



2.For radiated emissions from 30MHz to 1000MHz



3. Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.
This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.
Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

4.2.6 TEST RESULT

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	35.7490	35.04	-16.33	18.71	40.00	-21.29	QP
2	48.1625	32.52	-16.37	16.15	40.00	-23.85	QP
3	119.8556	36.82	-18.17	18.65	43.50	-24.85	QP
4	140.3420	37.35	-16.78	20.57	43.50	-22.93	QP
5	195.1363	38.22	-18.90	19.32	43.50	-24.18	QP
6	390.7225	35.73	-13.55	22.18	46.00	-23.82	QP

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	35.7490	49.33	-16.33	33.00	40.00	-7.00	QP
2	48.3318	43.02	-16.40	26.62	40.00	-13.38	QP
3	51.8430	42.83	-16.76	26.07	40.00	-13.93	QP
4	64.6594	40.46	-17.69	22.77	40.00	-17.23	QP
5	140.8351	46.05	-16.72	29.33	43.50	-14.17	QP
6	189.0743	38.84	-18.66	20.18	43.50	-23.32	QP

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case 802.11n Low channel(MIMO mode)

Between 1GHz – 40GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	5.2G TX- 802.11a/n20/ac20(Worst case)		

802.11a ant1(Worst case)

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5180MHz									
V	10360.00	53.12	30.55	5.77	24.66	53.00	74.00	-21.00	PK
V	10360.00	43.62	30.55	5.77	24.66	43.50	54.00	-10.50	AV
V	15540.00	50.24	30.33	6.32	24.55	50.78	74.00	-23.22	PK
V	15540.00	43.94	30.33	6.32	24.55	44.48	54.00	-9.52	AV
V	20720.00	51.31	30.85	7.45	24.69	52.60	74.00	-21.40	PK
V	20720.00	43.27	30.85	7.45	24.69	44.56	54.00	-9.44	AV
V	25900.00	52.08	31.02	8.99	25.57	55.62	74.00	-18.38	PK
V	25900.00	43.53	31.02	8.99	25.57	47.07	54.00	-6.93	AV
H	10360.00	54.00	30.55	5.77	24.66	53.88	74.00	-20.12	PK
H	10360.00	43.44	30.55	5.77	24.66	43.32	54.00	-10.68	AV
H	15540.00	52.30	30.33	6.32	24.55	52.84	74.00	-21.16	PK
H	15540.00	43.07	30.33	6.32	24.55	43.61	54.00	-10.39	AV
H	20720.00	50.11	30.85	7.45	24.69	51.40	74.00	-22.60	PK
H	20720.00	43.01	30.85	7.45	24.69	44.30	54.00	-9.70	AV
H	25900.00	53.48	31.02	8.99	25.57	57.02	74.00	-16.98	PK
H	25900.00	43.28	31.02	8.99	25.57	46.82	54.00	-7.18	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5200MHz									
V	10400.00	51.38	30.55	5.77	24.66	51.26	74.00	-22.74	PK
V	10400.00	43.98	30.55	5.77	24.66	43.86	54.00	-10.14	AV
V	15600.00	50.06	30.33	6.32	24.55	50.60	74.00	-23.40	PK
V	15600.00	43.11	30.33	6.32	24.55	43.65	54.00	-10.35	AV
V	20800.00	52.05	30.85	7.45	24.69	53.34	74.00	-20.66	PK
V	20800.00	43.13	30.85	7.45	24.69	44.42	54.00	-9.58	AV
V	26000.00	53.07	31.02	8.99	25.57	56.61	74.00	-17.39	PK
V	26000.00	43.31	31.02	8.99	25.57	46.85	54.00	-7.15	AV
H	10400.00	52.18	30.55	5.77	24.66	52.06	74.00	-21.94	PK
H	10400.00	43.57	30.55	5.77	24.66	43.45	54.00	-10.55	AV
H	15600.00	54.34	30.33	6.32	24.55	54.88	74.00	-19.12	PK
H	15600.00	43.72	30.33	6.32	24.55	44.26	54.00	-9.74	AV
H	20800.00	53.18	30.85	7.45	24.69	54.47	74.00	-19.53	PK
H	20800.00	43.20	30.85	7.45	24.69	44.49	54.00	-9.51	AV
H	26000.00	53.36	31.02	8.99	25.57	56.90	74.00	-17.10	PK
H	26000.00	43.31	31.02	8.99	25.57	46.85	54.00	-7.15	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5240MHz									
V	10480.00	54.60	30.55	5.77	24.66	54.48	74.00	-19.52	PK
V	10480.00	43.57	30.55	5.77	24.66	43.45	54.00	-10.55	AV
V	15720.00	53.98	30.33	6.32	24.55	54.52	74.00	-19.48	PK
V	15720.00	43.32	30.33	6.32	24.55	43.86	54.00	-10.14	AV
V	20960.00	52.42	30.85	7.45	24.69	53.71	74.00	-20.29	PK
V	20960.00	43.62	30.85	7.45	24.69	44.91	54.00	-9.09	AV
V	26200.00	54.06	31.02	8.99	25.57	57.60	74.00	-16.40	PK
V	26200.00	43.12	31.02	8.99	25.57	46.66	54.00	-7.34	AV
H	10480.00	53.40	30.55	5.77	24.66	53.28	74.00	-20.72	PK
H	10480.00	43.50	30.55	5.77	24.66	43.38	54.00	-10.62	AV
H	15720.00	53.27	30.33	6.32	24.55	53.81	74.00	-20.19	PK
H	15720.00	43.17	30.33	6.32	24.55	43.71	54.00	-10.29	AV
H	20960.00	53.89	30.85	7.45	24.69	55.18	74.00	-18.82	PK
H	20960.00	43.52	30.85	7.45	24.69	44.81	54.00	-9.19	AV
H	26200.00	50.10	31.02	8.99	25.57	53.64	74.00	-20.36	PK
H	26200.00	43.60	31.02	8.99	25.57	47.14	54.00	-6.86	AV

802.11n20 MIMO(Worst case)

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5180MHz									
V	10360.00	53.95	30.55	5.77	24.66	53.83	74.00	-20.17	PK
V	10360.00	43.59	30.55	5.77	24.66	43.47	54.00	-10.53	AV
V	15540.00	52.81	30.33	6.32	24.55	53.35	74.00	-20.65	PK
V	15540.00	43.45	30.33	6.32	24.55	43.99	54.00	-10.01	AV
V	20720.00	50.73	30.85	7.45	24.69	52.02	74.00	-21.98	PK
V	20720.00	43.28	30.85	7.45	24.69	44.57	54.00	-9.43	AV
V	25900.00	52.56	31.02	8.99	25.57	56.10	74.00	-17.90	PK
V	25900.00	43.85	31.02	8.99	25.57	47.39	54.00	-6.61	AV
H	10360.00	53.35	30.55	5.77	24.66	53.23	74.00	-20.77	PK
H	10360.00	43.83	30.55	5.77	24.66	43.71	54.00	-10.29	AV
H	15540.00	53.67	30.33	6.32	24.55	54.21	74.00	-19.79	PK
H	15540.00	43.27	30.33	6.32	24.55	43.81	54.00	-10.19	AV
H	20720.00	51.18	30.85	7.45	24.69	52.47	74.00	-21.53	PK
H	20720.00	43.83	30.85	7.45	24.69	45.12	54.00	-8.88	AV
H	25900.00	51.31	31.02	8.99	25.57	54.85	74.00	-19.15	PK
H	25900.00	43.12	31.02	8.99	25.57	46.66	54.00	-7.34	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5200MHz									
V	10400.00	51.66	30.55	5.77	24.66	51.54	74.00	-22.46	PK
V	10400.00	43.07	30.55	5.77	24.66	42.95	54.00	-11.05	AV
V	15600.00	50.43	30.33	6.32	24.55	50.97	74.00	-23.03	PK
V	15600.00	43.89	30.33	6.32	24.55	44.43	54.00	-9.57	AV
V	20800.00	53.81	30.85	7.45	24.69	55.10	74.00	-18.90	PK
V	20800.00	43.60	30.85	7.45	24.69	44.89	54.00	-9.11	AV
V	26000.00	50.12	31.02	8.99	25.57	53.66	74.00	-20.34	PK
V	26000.00	43.96	31.02	8.99	25.57	47.50	54.00	-6.50	AV
H	10400.00	54.79	30.55	5.77	24.66	54.67	74.00	-19.33	PK
H	10400.00	43.98	30.55	5.77	24.66	43.86	54.00	-10.14	AV
H	15600.00	54.57	30.33	6.32	24.55	55.11	74.00	-18.89	PK
H	15600.00	43.87	30.33	6.32	24.55	44.41	54.00	-9.59	AV
H	20800.00	50.87	30.85	7.45	24.69	52.16	74.00	-21.84	PK
H	20800.00	43.52	30.85	7.45	24.69	44.81	54.00	-9.19	AV
H	26000.00	50.31	31.02	8.99	25.57	53.85	74.00	-20.15	PK
H	26000.00	43.97	31.02	8.99	25.57	47.51	54.00	-6.49	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5240MHz									
V	10480.00	54.68	30.55	5.77	24.66	54.56	74.00	-19.44	PK
V	10480.00	43.91	30.55	5.77	24.66	43.79	54.00	-10.21	AV
V	15720.00	53.40	30.33	6.32	24.55	53.94	74.00	-20.06	PK
V	15720.00	43.43	30.33	6.32	24.55	43.97	54.00	-10.03	AV
V	20960.00	53.27	30.85	7.45	24.69	54.56	74.00	-19.44	PK
V	20960.00	43.61	30.85	7.45	24.69	44.90	54.00	-9.10	AV
V	26200.00	53.89	31.02	8.99	25.57	57.43	74.00	-16.57	PK
V	26200.00	43.99	31.02	8.99	25.57	47.53	54.00	-6.47	AV
H	10480.00	52.28	30.55	5.77	24.66	52.16	74.00	-21.84	PK
H	10480.00	43.96	30.55	5.77	24.66	43.84	54.00	-10.16	AV
H	15720.00	50.81	30.33	6.32	24.55	51.35	74.00	-22.65	PK
H	15720.00	43.80	30.33	6.32	24.55	44.34	54.00	-9.66	AV
H	20960.00	50.29	30.85	7.45	24.69	51.58	74.00	-22.42	PK
H	20960.00	43.07	30.85	7.45	24.69	44.36	54.00	-9.64	AV
H	26200.00	54.52	31.02	8.99	25.57	58.06	74.00	-15.94	PK
H	26200.00	43.94	31.02	8.99	25.57	47.48	54.00	-6.52	AV

802.11ac20 MIMO(Worst case)

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5180MHz									
V	10360.00	54.77	30.55	5.77	24.66	53.68	74.00	-20.32	PK
V	10360.00	43.27	30.55	5.77	24.66	43.15	54.00	-10.85	AV
V	15540.00	50.97	30.33	6.32	24.55	51.51	74.00	-22.49	PK
V	15540.00	43.84	30.33	6.32	24.55	44.38	54.00	-9.62	AV
V	20720.00	54.09	30.85	7.45	24.69	55.38	74.00	-18.62	PK
V	20720.00	43.04	30.85	7.45	24.69	44.33	54.00	-9.67	AV
V	25900.00	50.98	31.02	8.99	25.57	54.52	74.00	-19.48	PK
V	25900.00	43.82	31.02	8.99	25.57	47.36	54.00	-6.64	AV
H	10360.00	52.63	30.55	5.77	24.66	52.51	74.00	-21.49	PK
H	10360.00	43.81	30.55	5.77	24.66	43.69	54.00	-10.31	AV
H	15540.00	52.03	30.33	6.32	24.55	52.57	74.00	-21.43	PK
H	15540.00	43.48	30.33	6.32	24.55	44.02	54.00	-9.98	AV
H	20720.00	52.05	30.85	7.45	24.69	53.34	74.00	-20.66	PK
H	20720.00	43.45	30.85	7.45	24.69	44.74	54.00	-9.26	AV
H	25900.00	51.16	31.02	8.99	25.57	54.70	74.00	-19.30	PK
H	25900.00	43.21	31.02	8.99	25.57	46.75	54.00	-7.25	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5200MHz									
V	10400.00	54.74	30.55	5.77	24.66	54.62	74.00	-19.38	PK
V	10400.00	43.48	30.55	5.77	24.66	43.36	54.00	-10.64	AV
V	15600.00	50.25	30.33	6.32	24.55	50.79	74.00	-23.21	PK
V	15600.00	43.85	30.33	6.32	24.55	44.39	54.00	-9.61	AV
V	20800.00	54.96	30.85	7.45	24.69	56.25	74.00	-17.75	PK
V	20800.00	43.24	30.85	7.45	24.69	44.53	54.00	-9.47	AV
V	26000.00	54.36	31.02	8.99	25.57	57.90	74.00	-16.10	PK
V	26000.00	43.69	31.02	8.99	25.57	47.23	54.00	-6.77	AV
H	10400.00	52.25	30.55	5.77	24.66	52.13	74.00	-21.87	PK
H	10400.00	43.94	30.55	5.77	24.66	43.82	54.00	-10.18	AV
H	15600.00	52.82	30.33	6.32	24.55	53.36	74.00	-20.64	PK
H	15600.00	43.21	30.33	6.32	24.55	43.75	54.00	-10.25	AV
H	20800.00	53.79	30.85	7.45	24.69	55.08	74.00	-18.92	PK
H	20800.00	43.15	30.85	7.45	24.69	44.44	54.00	-9.56	AV
H	26000.00	53.33	31.02	8.99	25.57	56.87	74.00	-17.13	PK
H	26000.00	43.73	31.02	8.99	25.57	47.27	54.00	-6.73	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5240MHz									
V	10480.00	54.99	30.55	5.77	24.66	54.87	74.00	-19.13	PK
V	10480.00	43.15	30.55	5.77	24.66	43.03	54.00	-10.97	AV
V	15720.00	53.49	30.33	6.32	24.55	54.03	74.00	-19.97	PK
V	15720.00	43.43	30.33	6.32	24.55	43.97	54.00	-10.03	AV
V	20960.00	50.12	30.85	7.45	24.69	51.41	74.00	-22.59	PK
V	20960.00	43.50	30.85	7.45	24.69	44.79	54.00	-9.21	AV
V	26200.00	51.23	31.02	8.99	25.57	54.77	74.00	-19.23	PK
V	26200.00	43.18	31.02	8.99	25.57	46.72	54.00	-7.28	AV
H	10480.00	53.43	30.55	5.77	24.66	53.31	74.00	-20.69	PK
H	10480.00	43.45	30.55	5.77	24.66	43.33	54.00	-10.67	AV
H	15720.00	51.07	30.33	6.32	24.55	51.61	74.00	-22.39	PK
H	15720.00	43.52	30.33	6.32	24.55	44.06	54.00	-9.94	AV
H	20960.00	50.99	30.85	7.45	24.69	52.28	74.00	-21.72	PK
H	20960.00	43.57	30.85	7.45	24.69	44.86	54.00	-9.14	AV
H	26200.00	53.27	31.02	8.99	25.57	56.81	74.00	-17.19	PK
H	26200.00	43.05	31.02	8.99	25.57	46.59	54.00	-7.41	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4.-27dBm(EIRP)=68.3dBuV/m(Field strength at 3m), According to the test results of the above table, while fulfill the requirements of out-of-band spurious

5.POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(a)

Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11(if directional gain＞6dbi,PSD is 9) dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

a) Set RBW ≥ 1/T, where T is defined in section II.B.I.a).

b) Set VBW ≥ 3 RBW.

c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add 10log(500kHz/RBW) to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.

d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add 10log(1MHz/RBW) to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.

e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since RBW=100 KHZ is available on nearly all spectrum analyzers.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP

5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1015 hPa	Test Voltage:	DC 11.4V
Test Mode :	TX		

Test mode	Test Channel (MHz)	PSD [dBm/MHz]			Limit (dBm/MHz)	Result
		ANT0	ANT1	Total		
802.11a20	5180	-0.13	0.75	/	11	Pass
	5200	0.34	1.42	/	11	Pass
	5240	-0.23	0	/	11	Pass
802.11n(HT20)	5180	0.38	0.83	3.62	9	Pass
	5200	0.28	0.86	3.59	9	Pass
	5240	-0.36	0.18	2.93	9	Pass
802.11n(HT40)	5190	-2.8	-2.5	0.36	9	Pass
	5230	-3.93	-3.32	-0.60	9	Pass
802.11ac(VH20)	5180	0.45	-0.03	3.23	9	Pass
	5200	0.21	0.96	3.61	9	Pass
	5240	-0.63	0.05	2.73	9	Pass
802.11ac(VH40)	5190	-2.61	-2.28	8.83	9	Pass
	5230	-4.05	-3.39	-0.70	9	Pass
802.11ac(VH80)	5210	-4.57	-4.1	-1.32	9	Pass

ANT 0

(802.11a20) PSD plot on channel 36



(802.11n20) PSD plot on channel 36



(802.11a20) PSD plot on channel 40



(802.11n20) PSD plot on channel 40



(802.11a20) PSD plot on channel 48



(802.11n20) PSD plot on channel 48



ANT 0

(802.11n40) PSD plot on channel 38



(802.11ac20) PSD plot on channel 36



(802.11n40) PSD plot on channel 46



(802.11ac20) PSD plot on channel 40



(802.11ac20) PSD plot on channel 48



ANT 0

(802.11ac40) PSD plot on channel 38



(802.11ac40) PSD plot on channel 46



(802.11ac80) PSD plot on channel 42



ANT 1

(802.11a20) PSD plot on channel 36



(802.11n20) PSD plot on channel 36



(802.11a20) PSD plot on channel 40



(802.11n20) PSD plot on channel 40



(802.11a20) PSD plot on channel 48



(802.11n20) PSD plot on channel 48



ANT 1

(802.11n40) PSD plot on channel 38



(802.11ac20) PSD plot on channel 36



(802.11n40) PSD plot on channel 46



(802.11ac20) PSD plot on channel 40



(802.11ac20) PSD plot on channel 48



ANT 1

(802.11ac40) PSD plot on channel 38



(802.11ac40) PSD plot on channel 46



(802.11ac80) PSD plot on channel 42



6. 26DB & 99% EMISSION BANDWIDTH

6.1 APPLIED PROCEDURES / LIMIT

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band, the minimum bandwidth 6 dB bandwidth of U-NII devices shall be at least 500KHz. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

6.2 TEST PROCEDURE

a) Set RBW = 100KHz.

b) Set the VBW > RBW.

c) Detector = Peak.

d) Trace mode = max hold.

e) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW ≥ 3 · RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.4 TEST RESULTS

Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	101kPa	Test Voltage :	DC 11.4V
Test Mode :	TX		

ANT 0

Test CH	-26dB Channel Bandwidth (MHz)						Limit(KHz)	Result
	802.11a20	802.11n(HT20)	802.11n (HT40)	802.11ac (HT20)	802.11ac (HT40)	802.11ac (HT80)		
Lowest	23.62	23.75	41.97	22.93	42.31		N/A	Pass
Middle	23.48	23.23		23.05		80.94		
Highest	23.74	23.58	42.07	23.82	41.32			
Test CH	99% Channel Bandwidth (MHz)						Limit(KHz)	Result
	802.11a20	802.11n(HT20)	802.11n (HT40)	802.11ac (HT20)	802.11ac (HT40)	802.11ac (HT80)		
Lowest	16.746	18.936	37.409	18.899	37.332		N/A	Pass
Middle	16.728	18.898		18.909		76.424		
Highest	16.757	18.947	37.411	18.877	37.486			

ANT 1

Test CH	-26dB Channel Bandwidth (MHz)						Limit(KHz)	Result
	802.11a20	802.11n(HT20)	802.11n (HT40)	802.11ac (HT20)	802.11ac (HT40)	802.11ac (HT80)		
Lowest	24.31	23.55	41.25	23.06	41.3		N/A	Pass
Middle	23.68	23.53		23.01		81.22		
Highest	23.68	23.3	41.62	23.41	41.11			
Test CH	99% Channel Bandwidth (MHz)						Limit(KHz)	Result
	802.11a20	802.11n(HT20)	802.11n (HT40)	802.11ac (HT20)	802.11ac (HT40)	802.11ac (HT80)		
Lowest	16.793	18.941	37.507	18.97	35.572		N/A	Pass
Middle	16.773	18.88		18.884		76.528		
Highest	16.703	18.927	37.563	18.955	37.503			

Note: OBW for the ant0 and ant1 fully located in the 5150-5250MHz

Test plot Antenna 0

(802.11 a20) 26dB Bandwidth plot on channel 36



(802.11 n20) 26dB Bandwidth plot on channel 36



(802.11 a20) 26dB Bandwidth plot on channel 40



(802.11 n20) 26dB Bandwidth plot on channel 40



(802.11 a20) 26dB Bandwidth plot on channel 48



(802.11 n20) 26dB Bandwidth plot on channel 48



Test plot Antenna 0

(802.11 n40) 26dB Bandwidth plot on channel 38



(802.11ac20) 26dB Bandwidth plot on channel 36



(802.11 n40) 26dB Bandwidth plot on channel 46



(802.11ac20) 26dB Bandwidth plot on channel 40



(802.11ac20) 26dB Bandwidth plot on channel 48



Test plot Antenna 0

(802.11 ac40) 26dB Bandwidth plot on channel 42



(802.11 ac40) 26dB Bandwidth plot on channel 42



(802.11 ac80) 26dB Bandwidth plot on channel 42