TEST REPORT

Report No.:	BCTC2307757199-5E
Applicant:	Shenzhen Qichang Intelligent Technology Co., Ltd
Product Name:	Smart phone
Model/Type reference:	F101 PRO
Tested Date:	2023-07-03 to 2023-07-14
Issued Date:	2023-07-17

Shenzhen BCTC Testing Co., Ltd.

FCC ID: 2BAK2-F101PRO

Product Name:	Smart phone
Trademark:	Fossibot
Model/Type reference:	F101 PRO F101 +, F101 PLUS, F101 S
Prepared For:	Shenzhen Qichang Intelligent Technology Co., Ltd
Address:	Room 510, Building 7, Yunli Intelligent Park, No. 7, Bantian Street, Longgang, Shenzhen
Manufacturer:	Shenzhen Qichang Intelligent Technology Co., Ltd
Address:	Room 510, Building 7, Yunli Intelligent Park, No. 7, Bantian Street, Longgang, Shenzhen
Prepared By:	Shenzhen BCTC Testing Co., Ltd.
Address:	1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date:	2023-07-03
Sample tested Date:	2023-07-03 to 2023-07-14
Issue Date:	2023-07-17
Report No.:	BCTC2307757199-5E
Test Standards:	FCC CFR Title 47 Part 2 FCC CFR Title 47 Part22 Subpart H FCC CFR Title 47 Part24 Subpart E FCC CFR Title 47 Part27 Subpart L ANSI/ TIA/ EIA-603-D-2010 FCC KDB 971168 D01 Power Meas. License Digital Systems v02v02
Test Results:	PASS
Remark:	This is GSM & WCDMAradio test report.

Tested by:

Brave Zeng/ Project Handler

Approved by:

Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table Of Content

Test Report Declaration Page
1. Version 4
2. Test Summary 5
3. Measurement Uncertainty 6
4. Product Information And Test Setup 7
4.1 Product Information 7
4.2 Test Setup Configuration 8
4.3 Support Equipment 8
4.5 Test Mode 9
5. Test Facility And Test Instrument Used 10
5.1 Test Facility 10
5.2 Test Instrument Used 10
6. RF Output Power 11
6.1 Block Diagram Of Test Setup 11
6.2 Limit 12
6.3 Test procedure 13
6.4 Test Result 13
7. Peak-to-average Ratio(PAR) of Transmitter 21
7.1 Block Diagram Of Test Setup 21
7.2 Limit 21
7.3 Test procedure 21
7.4 Test Result 21
8. Emission Bandwidth 37
8.1 Block Diagram Of Test Setup 37
8.2 Limit 37
8.3 Test procedure 37
8.4 Test Result 37
9. Out of Band Emissions at Antenna Terminal 53
9.1 Block Diagram Of Test Setup 53
9.2 Limit 53
9.3 Test procedure 53
9.4 Test Result 53
10. Spurious Radiated Emissions 77
10.1 Block Diagram Of Test Setup 77
10.2 Limit 78
10.3 Test procedure 78
10.4 Test Result 79
11. Frequency Stability 82
11.1 Block Diagram Of Test Setup 82
11.2 Limit 82
11.3 Test procedure 82
11.4 Test Result 83
12. EUT Photographs 86
13. EUT Test Setup Photographs 87

(Note: N/A Means Not Applicable)

1. Version

Report No.	Issue Date	Description	Approved
BCTC2307757199-5E	2023-07-17	Original	Valid

2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	RF Exposure	§1.1307,§2.1093	PASS
2	RF Output Power	§22.913 (a), §24.232 (c), §27.50 (d),	PASS
3	Peak-to-average Ratio(PAR) of Transmitter	§24.232(d),§22.913, §27.50(d),	PASS
4	Emission Bandwidth	§22.917 (b), §24.238(b), §27.53(g)	PASS
5	Spurious Emissions at Antenna Terminal	§22.917 (a), §24.238 (a), §27.53(g),§27.53(h)	PASS
6	Spurious Radiation Emissions	§22.917 (a), §24.238 (a), §27.53(g),§27.53(h)	PASS
7	Out of Band Emissions	§22.917 (a), §24.238 (a), §27.53(g),§27.53(h)	PASS
8	Frequency Stability	§22.355, §24.235, §27.54	PASS

3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
2	3m chamber Radiated spurious emission(9KHz-30MHz)	U=3.7dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission (150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	humidity uncertainty	U=5.3%
10	Temperature uncertainty	U=0.59℃

4. Product Information And Test Setup

4.1 Product Information

Model/Type reference:	F101 PRO F101 +, F101 PLUS, F101 S
Model differences:	All the model are the same circuit and RF module, except model names.
Hardware Version:	TE197_MAIN_PCB_V1.0
Software Version:	FOSSiBOT_F101 Pro_E
Operation Frequency:	GSM/GPRS/EGPRS 850: TX: 824~849MHz; RX: 869~894MHz; GSM/GPRS/EGPRS 1900: TX:1850~1910MHz; RX:1930~1990MHz; WCDMA Band II: TX: 1852.40~1907.60MHz; Rx: 1932.60~1987.40MHz; WCDMA Band IV: TX: 1712.40~1752.60MHz; RX: 2112.60 – 2452.40MHz WCDMA Band V: TX: 826.40~846.60MHz; RX: 871.40~ 891.60MHz;
GPRS Class:	Class 12
Max RF Output Power:	GSM/GPRS/EGPRS 850: 33.21 dBm, GSM/GPRS/EGPRS 1900: 30.31 dBm WCDMA Band II: 23.47 dBm WCDMA Band IV: 23.00 dBm WCDMA Band V: 22.85 dBm
Type of Modulation:	GSM with GMSK,8PSK Modulation WCDMA Mode with BPSK Modulation HSDPA Mode with QPSK Modulation HSUPA Mode with QPSK Modulation
Type of Emission:	GSM/GPRS 850: 254KGXW EGPRS 850:248KG7W GSM/GPRS 1900: 248KGXW EGPRS 1900:252KG7W WCDMA Band II: 4M20F9W WCDMA Band IV: 4M17F9W WCDMA Band V: 4M20F9W
Antenna installation:	Internal antenna
Antenna Gain:	GSM850: 0.2 dBi GSM1900: 1.5 dBi WCDMA Band II: 1.3 dBi WCDMA Band IV: 1.1 dBi WCDMA Band V: 0.1 dBi
Connecting I/O Port(s)	Please refer to the User's Manual
Ratings:	DC 5V from adapter/DC 3.85V from battery
Adapter Information:	Model: HJ-FC017K7-US Input: 100-240V- 50/60Hz 0.6A Output: 5.0V ⎓ 2.0A OR 7.0V ⎓ 2.0A OR 9.0V ⎓ 2.0A OR 12.0V ⎓ 1.5A 18.0W

4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.
Conducted Emission:



Radiated Spurious Emission



4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Smart phone	Fossibot	F101 PRO	N/A	EUT
E-2	Adapter	N/A	HJ-FC017K7-US	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	N/A	N/A	1M	DC cable unshielded

Notes:
1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.5 Test Mode

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EGPRS	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EGPRS	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band II	WCDMA/HSDPA/HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538
WCDMA Band IV	WCDMA/HSDPA/HSUPA	1712.4 MHz	1312
		1740 MHz	1450
		1752.6 MHz	1513
WCDMA Band V	WCDMA/HSDPA/HSUPA	826.4 MHz	4132
		836.4 MHz	4182
		846.6 MHz	4233
Note 1: the transmitter has been tested on the communications mode of WCDMA, HSDPA, HSUPA compliance test and record the worst case. Note 2: Both the SIM 1 and SIM 2 were tested, the worst mode is the SIM 1, the data recording in the report.			

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/
/	/	/	/

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
/	/	/	/

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address:1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.
FCC Test Firm Registration Number: 712850
A2LA certificate registration number is: CN1212
ISED Registered No.: 23583
ISED CAB identifier: CN0017

5.2 Test Instrument Used

Radiated Emissions Test (966 Chamber01)					
Equipment	**Manufacturer**	**Model#**	**Serial#**	**Last Cal.**	**Next Cal.**
966 chamber	ChengYu	966 Room	966	May 15, 2023	May 14, 2026
Receiver	R&S	ESR3	102075	May 15, 2023	May 14, 2024
Receiver	R&S	ESRP	101154	May 15, 2023	May 14, 2024
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 15, 2023	May 14, 2024
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	May 29, 2023	May 28, 2024
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	May 31, 2023	May 30, 2024
Amplifier	SKET	LAPA_01G18 G-45dB	\	May 15, 2023	May 14, 2024
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 31, 2023	May 30, 2024
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35-HG	2034381	May 15, 2023	May 14, 2024
Horn Antenn(18GHz -40GHz)	Schwarzbeck	BBHA9170	00822	May 31, 2023	May 30, 2024
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 15, 2023	May 14, 2024
Communication test set	R&S	CMW500	126173	Nov. 08, 2022	Nov. 07, 2023
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

6. RF Output Power

6.1 Block Diagram Of Test Setup

Conducted output power test method:



Radiated power test method:
（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



6.2 Limit

According to §22.913(a)(2),The ERP of mobileand portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d)(4), Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

6.3 Test procedure

Radiated power test method:

1.The setup of EUT is according with per ANSI/TIA Standard 603D and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

6.4 Test Result

ERP For GSM Mode GSM850

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel								
824.2	H	1.5	0	28.26	-7.98	20.28	38.45	PASS
824.2	V	1.5	0	27.79	-7.98	19.81	38.45	PASS
Middle Channel								
836.6	H	1.5	0	27.23	-7.56	19.67	38.45	PASS
836.6	V	1.5	0	27.48	-7.56	19.92	38.45	PASS
High Channel								
848.8	H	1.5	0	28.21	-7.14	21.07	38.45	PASS
848.8	V	1.5	0	27.36	-7.14	20.22	38.45	PASS

EIRP For GSM Mode PCS1900

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel								
1850.2	H	1.5	0	50.03	-21.78	28.25	33.00	PASS
1850.2	V	1.5	0	49.73	-21.78	27.95	33.00	PASS
Middle Channel								
1880	H	1.5	0	49.18	-21.67	27.51	33.00	PASS
1880	V	1.5	0	49.51	-21.67	27.84	33.00	PASS
High Channel								
1909.8	H	1.5	0	50.13	-21.55	28.58	33.00	PASS
1909.8	V	1.5	0	49.44	-21.55	27.89	33.00	PASS

ERP For GPRS Mode GSM850

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel								
824.2	H	1.5	0	27.72	-7.98	19.74	38.45	PASS
824.2	V	1.5	0	27.41	-7.98	19.43	38.45	PASS
Middle Channel								
836.6	H	1.5	0	27.30	-7.56	19.74	38.45	PASS
836.6	V	1.5	0	27.60	-7.56	20.04	38.45	PASS
High Channel								
848.8	H	1.5	0	28.51	-7.14	21.37	38.45	PASS
848.8	V	1.5	0	27.29	-7.14	20.15	38.45	PASS

EIRP For GPRS Mode PCS1900

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel								
1850.2	H	1.5	0	49.62	-21.78	27.84	33.00	PASS
1850.2	V	1.5	0	49.69	-21.78	27.91	33.00	PASS
Middle Channel								
1880	H	1.5	0	50.06	-21.67	28.39	33.00	PASS
1880	V	1.5	0	49.59	-21.67	27.92	33.00	PASS
High Channel								
1909.8	H	1.5	0	49.24	-21.55	27.69	33.00	PASS
1909.8	V	1.5	0	49.88	-21.55	28.33	33.00	PASS

ERP For EGPRS Mode GSM850

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel								
824.2	H	1.5	0	28.77	-7.98	20.79	38.45	PASS
824.2	V	1.5	0	27.46	-7.98	19.48	38.45	PASS
Middle Channel								
836.6	H	1.5	0	28.29	-7.56	20.73	38.45	PASS
836.6	V	1.5	0	27.95	-7.56	20.39	38.45	PASS
High Channel								
848.8	H	1.5	0	29.26	-7.14	22.12	38.45	PASS
848.8	V	1.5	0	27.89	-7.14	20.75	38.45	PASS

EIRP For EGPRS Mode PCS1900

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel								
1850.2	H	1.5	0	50.44	-21.78	28.66	33.00	PASS
1850.2	V	1.5	0	50.16	-21.78	28.38	33.00	PASS
Middle Channel								
1880	H	1.5	0	49.70	-21.67	28.03	33.00	PASS
1880	V	1.5	0	50.20	-21.67	28.53	33.00	PASS
High Channel								
1909.8	H	1.5	0	51.16	-21.55	29.61	33.00	PASS
1909.8	V	1.5	0	49.33	-21.55	27.78	33.00	PASS

EIRP For WCDMA Mode Band II

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel								
1852.4	H	1.5	0	41.28	-21.77	19.51	33.00	PASS
1852.4	V	1.5	0	41.03	-21.77	19.26	33.00	PASS
Middle Channel								
1880	H	1.5	0	41.53	-21.67	19.86	33.00	PASS
1880	V	1.5	0	40.50	-21.67	18.83	33.00	PASS
High Channel								
1907.6	H	1.5	0	40.31	-21.56	18.75	33.00	PASS
1907.6	V	1.5	0	40.36	-21.56	18.80	33.00	PASS

EIRP For HSDPA Mode Band II

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel								
1852.4	H	1.5	0	40.98	-21.77	19.21	33.00	PASS
1852.4	V	1.5	0	40.99	-21.77	19.22	33.00	PASS
Middle Channel								
1880	H	1.5	0	41.41	-21.67	19.74	33.00	PASS
1880	V	1.5	0	40.77	-21.67	19.10	33.00	PASS
High Channel								
1907.6	H	1.5	0	42.01	-21.56	20.45	33.00	PASS
1907.6	V	1.5	0	41.05	-21.56	19.49	33.00	PASS

EIRP For HSUPA Mode Band II

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 24E Limits (dBm)	Result
Low Channel								
1852.4	H	1.5	0	40.86	-21.77	19.09	33.00	PASS
1852.4	V	1.5	0	41.01	-21.77	19.24	33.00	PASS
Middle Channel								
1880	H	1.5	0	40.47	-21.67	18.80	33.00	PASS
1880	V	1.5	0	40.18	-21.67	18.51	33.00	PASS
High Channel								
1907.6	H	1.5	0	41.09	-21.56	19.53	33.00	PASS
1907.6	V	1.5	0	41.04	-21.56	19.48	33.00	PASS

EIRP For WCDMA Mode Band IV

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 27L Limits (dBm)	Result
Low Channel								
1712.4	H	1.5	0	41.74	-22.32	19.42	33.00	PASS
1712.4	V	1.5	0	40.97	-22.32	18.65	33.00	PASS
Middle Channel								
1740	H	1.5	0	40.80	-22.24	18.56	33.00	PASS
1740	V	1.5	0	40.39	-22.24	18.15	33.00	PASS
High Channel								
1752.6	H	1.5	0	40.94	-22.16	18.78	33.00	PASS
1752.6	V	1.5	0	40.75	-22.16	18.59	33.00	PASS

EIRP For HSDPA Mode Band IV

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 27L Limits (dBm)	Result
Low Channel								
1712.4	H	1.5	0	41.11	-22.32	18.79	33.00	PASS
1712.4	V	1.5	0	40.94	-22.32	18.62	33.00	PASS
Middle Channel								
1740	H	1.5	0	41.48	-22.24	19.24	33.00	PASS
1740	V	1.5	0	41.13	-22.24	18.89	33.00	PASS
High Channel								
1752.6	H	1.5	0	40.71	-22.16	18.55	33.00	PASS
1752.6	V	1.5	0	40.25	-22.16	18.09	33.00	PASS

EIRP For HSUPA Mode Band IV

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 27L Limits (dBm)	Result
Low Channel								
1712.4	H	1.5	0	41.15	-22.32	18.83	33.00	PASS
1712.4	V	1.5	0	40.29	-22.32	17.97	33.00	PASS
Middle Channel								
1740	H	1.5	0	42.06	-22.24	19.82	33.00	PASS
1740	V	1.5	0	41.10	-22.24	18.86	33.00	PASS
High Channel								
1752.6	H	1.5	0	41.51	-22.16	19.35	33.00	PASS
1752.6	V	1.5	0	40.83	-22.16	18.67	33.00	PASS

ERP For WCDMA Mode Band V

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel								
826.4	H	1.5	0	19.11	-7.90	11.21	30	PASS
826.4	V	1.5	0	19.15	-7.90	11.25	30	PASS
Middle Channel								
836.4	H	1.5	0	19.08	-7.56	11.52	30	PASS
836.4	V	1.5	0	18.49	-7.56	10.93	30	PASS
High Channel								
846.6	H	1.5	0	20.07	-7.22	12.85	30	PASS
846.6	V	1.5	0	18.78	-7.22	11.56	30	PASS

ERP For HSDPA Mode Band V

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel								
826.4	H	1.5	0	19.00	-7.90	11.10	30	PASS
826.4	V	1.5	0	18.24	-7.90	10.34	30	PASS
Middle Channel								
836.4	H	1.5	0	19.77	-7.56	12.21	30	PASS
836.4	V	1.5	0	18.29	-7.56	10.73	30	PASS
High Channel								
846.6	H	1.5	0	20.11	-7.22	12.89	30	PASS
846.6	V	1.5	0	18.28	-7.22	11.06	30	PASS

ERP For HSUPA Mode Band V

Frequency (MHz)	Polar (H/V)	Height (Meter)	Table (Degree)	Reading Level (dBm)	Correct Factor (dB)	Measure-ment (dBm)	FCC Part 22H Limits (dBm)	Result
Low Channel								
826.4	H	1.5	0	19.20	-7.90	11.30	30	PASS
826.4	V	1.5	0	18.77	-7.90	10.87	30	PASS
Middle Channel								
836.4	H	1.5	0	18.71	-7.56	11.15	30	PASS
836.4	V	1.5	0	18.21	-7.56	10.65	30	PASS
High Channel								
846.6	H	1.5	0	20.02	-7.22	12.80	30	PASS
846.6	V	1.5	0	18.17	-7.22	10.95	30	PASS

Correction Factor= S.G. Power - Cable loss + Antenna Gain- SPA. Reading

Max. Conducted Output Power

For Cellular Band (GSM850)

Band	GSM850			Limit (dBm)
Channel	**128**	**190**	**251**	
Frequency(MHz)	**824.2**	**836.6**	**848.8**	
GSM	32.79	32.92	32.65	33.0
GPRS Slot -1	33.09	**33.21**	32.95	33.0
GPRS Slot -2	32.16	32.27	32.01	33.0
GPRS Slot -3	30.20	30.29	30.05	33.0
GPRS Slot -4	29.18	29.24	29.01	33.0
EGPRS Slot -1	33.08	33.18	32.93	33.0
EGPRS Slot -2	32.13	32.25	31.98	33.0
EGPRS Slot -3	30.17	30.27	30.04	33.0
EGPRS Slot -4	29.15	29.22	28.98	33.0

For PCS Band (GSM1900)

Band	GSM1900			Limit (dBm)
Channel	**512**	**661**	**810**	
Frequency(MHz)	**1850.2**	**1880**	**1909.8**	
GSM	29.90	29.98	29.85	33.0
GPRS Slot -1	30.20	**30.31**	30.14	33.0
GPRS Slot -2	29.21	29.35	29.22	33.0
GPRS Slot -3	27.45	27.23	27.20	33.0
GPRS Slot -4	25.90	26.16	26.16	33.0
EGPRS Slot -1	24.46	25.27	25.52	33.0
EGPRS Slot -2	23.79	24.00	23.70	33.0
EGPRS Slot -3	21.43	21.44	21.46	33.0
EGPRS Slot -4	20.42	20.11	19.78	33.0

Band	WCDMA Band II		
Channel	**9262**	**9400**	**9538**
Frequency(MHz)	**1852.4**	**1880.0**	**1907.6**
WCDMA RMC 12.2K	23.32	23.39	**23.47**
HSDPA Subtest-1	22.44	22.48	22.54
HSDPA Subtest-2	21.76	22.01	22.01
HSDPA Subtest-3	20.66	20.94	20.78
HSDPA Subtest-4	20.87	20.98	21.13
HSUPA Subtest-1	21.27	22.31	22.34
HSUPA Subtest-2	22.27	22.43	22.53
HSUPA Subtest-3	20.81	21.22	21.27
HSUPA Subtest-4	22.43	22.48	22.54
HSUPA Subtest-5	21.23	21.38	21.57

Band	WCDMA Band IV		
Channel	**1312**	**1450**	**1513**
Frequency(MHz)	**1712.4**	**1740**	**1752.6**
WCDMA RMC 12.2K	22.56	**23.00**	22.71
HSDPA Subtest-1	21.65	22.11	21.78
HSDPA Subtest-2	21.31	21.75	21.41
HSDPA Subtest-3	20.32	20.61	20.18
HSDPA Subtest-4	20.01	20.50	19.90
HSUPA Subtest-1	19.78	21.82	21.45
HSUPA Subtest-2	21.48	22.00	21.63
HSUPA Subtest-3	19.87	20.80	20.42
HSUPA Subtest-4	21.66	22.10	21.71
HSUPA Subtest-5	20.41	21.41	21.15

Band	WCDMA Band V		
Channel	**4132**	**4182**	**4233**
Frequency(MHz)	**826.4**	**836.4**	**846.6**
WCDMA RMC 12.2K	22.76	**22.85**	22.78
HSDPA Subtest-1	21.79	21.83	21.79
HSDPA Subtest-2	21.26	21.47	21.42
HSDPA Subtest-3	20.13	20.03	20.28
HSDPA Subtest-4	20.02	20.69	20.09
HSUPA Subtest-1	20.24	21.69	21.70
HSUPA Subtest-2	21.69	21.82	21.58
HSUPA Subtest-3	19.98	20.76	20.42
HSUPA Subtest-4	21.82	21.88	21.79
HSUPA Subtest-5	20.14	21.22	21.23

7. Peak-to-average Ratio(PAR) of Transmitter

7.1 Block Diagram Of Test Setup



7.2 Limit

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

According to §27.50(B), the peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

7.3 Test procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded.Record the maximum PAPR level associated with a probability of 0.1%.

7.4 Test Result

Band	Channel	Frequency (MHz)	Result (dB)	high Limit (dB)	Verdict
GSM850	128	824.2	2.64	13.00	PASS
GSM850	190	836.6	2.60	13.00	PASS
GSM850	251	848.8	2.63	13.00	PASS
GPRS850	128	824.2	2.53	13.00	PASS
GPRS850	190	836.6	2.74	13.00	PASS
GPRS850	251	848.8	2.94	13.00	PASS
EGPRS850	128	824.2	2.67	13.00	PASS
EGPRS850	190	836.6	2.64	13.00	PASS
EGPRS850	251	848.8	2.67	13.00	PASS

GSM850 Channel=128



GSM850 Channel=190



GSM850 Channel=251



GPRS850 Channel=128



GPRS850 Channel=190



GPRS850 Channel=251



EGPRS850 Channel=128



EGPRS850 Channel=190



EGPRS850 Channel=251



Band	Channel	Frequency (MHz)	Result (dB)	high Limit (dB)	Verdict
GSM1900	512	1850.2	2.65	13.00	PASS
GSM1900	661	1880	2.65	13.00	PASS
GSM1900	810	1909.8	2.65	13.00	PASS
GPRS1900	512	1850.2	2.69	13.00	PASS
GPRS1900	661	1880	2.70	13.00	PASS
GPRS1900	810	1909.8	2.69	13.00	PASS
EGPRS1900	512	1850.2	7.43	13.00	PASS
EGPRS1900	661	1880	7.53	13.00	PASS
EGPRS1900	810	1909.8	7.29	13.00	PASS

GSM1900 Channel=512



GSM1900 Channel=661



GSM1900 Channel=810



GPRS1900 Channel=512



GPRS1900 Channel=661



GPRS1900 Channel=810



EGPRS1900 Channel=512



EGPRS1900 Channel=661



EGPRS1900 Channel=810



Band	Channel	Frequency (MHz)	Result (dB)	high Limit (dB)	Verdict
WCDMA Band2	9262	1852.4	2.51	13	PASS
WCDMA Band2	9400	1880	2.63	13	PASS
WCDMA Band2	9538	1907.6	2.66	13	PASS
WCDMA Band4	1312	1712.4	2.96	13	PASS
WCDMA Band4	1450	1740	2.64	13	PASS
WCDMA Band4	1513	1752.6	2.76	13	PASS
WCDMA Band5	4132	826.4	2.53	13	PASS
WCDMA Band5	4182	836.4	2.74	13	PASS
WCDMA Band5	4233	846.6	2.94	13	PASS

Note:In WCDMA, RMC, HSDPA and HSUPA all three tests only reflect the worst mode RMC.

WCDMA Band2 Channel=9262



WCDMA Band2 Channel=9400



WCDMA Band2 Channel=9538



WCDMA Band4 Channel=1312



WCDMA Band4 Channel=1450



WCDMA Band4 Channel=1513



WCDMA Band5 Channel=4132



WCDMA Band5 Channel=4182



WCDMA Band5 Channel=4233



8. Emission Bandwidth

8.1 Block Diagram Of Test Setup



8.2 Limit

According to §22.917(b),The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §27.53, The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

8.3 Test procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 10kHz for GSM mode and 100kHz for WCDMA mode, VBW shall be at least 3 times the RBW, and the 26dB bandwidth was recorded.

8.4 Test Result

Band	Channel	Frequency (MHz)	99% OBW (kHz)	-26dB EBW (kHz)	Verdict
GSM850	128	824.2	250.724	313.601	PASS
GSM850	190	836.6	250.586	317.956	PASS
GSM850	251	848.8	251.074	313.848	PASS
GPRS850	128	824.2	248.033	325.130	PASS
GPRS850	190	836.6	243.954	313.257	PASS
GPRS850	251	848.8	246.643	313.465	PASS
EGPRS850	128	824.2	250.573	315.421	PASS
EGPRS850	190	836.6	254.283	327.300	PASS
EGPRS850	251	848.8	243.729	318.338	PASS

GSM850 Channel=128



GSM850 Channel=190



GSM850 Channel=251



GPRS850 Channel=128



GPRS850 Channel=190



GPRS850 Channel=251



EGPRS850 Channel=128



EGPRS850 Channel=190



EGPRS850 Channel=251



Band	Channel	Frequency (MHz)	99% OBW (kHz)	-26dB EBW (kHz)	Verdict
GSM1900	512	1850.2	241.098	306.756	PASS
GSM1900	661	1880	248.237	318.124	PASS
GSM1900	810	1909.8	245.400	318.710	PASS
GPRS1900	512	1850.2	245.960	322.024	PASS
GPRS1900	661	1880	244.987	319.399	PASS
GPRS1900	810	1909.8	244.532	312.130	PASS
EGPRS1900	512	1850.2	252.012	320.026	PASS
EGPRS1900	661	1880	250.918	306.069	PASS
EGPRS1900	810	1909.8	250.560	309.656	PASS

GSM1900 Channel=512



GSM1900 Channel=661



GSM1900 Channel=810



GPRS1900 Channel=512



GPRS1900 Channel=661



GPRS1900 Channel=810



EGPRS1900 Channel=512



EGPRS1900 Channel=661



EGPRS1900 Channel=810



Band	Channel	Frequency (MHz)	99% OBW (kHz)	-26dB EBW (kHz)	Verdict
WCDMA Band2	9262	1852.4	4180.504	4757.870	PASS
WCDMA Band2	9400	1880	4178.254	4713.863	PASS
WCDMA Band2	9538	1907.6	4197.484	4745.974	PASS
WCDMA Band4	1312	1712.4	4160.892	4667.641	PASS
WCDMA Band4	1450	1740	4161.771	4711.611	PASS
WCDMA Band4	1513	1752.6	4166.930	4703.030	PASS
WCDMA Band5	4132	826.4	4177.960	4708.363	PASS
WCDMA Band5	4182	836.4	4197.209	4735.097	PASS
WCDMA Band5	4233	846.6	4196.750	4721.356	PASS

Note：In WCDMA, RMC, HSDPA and HSUPA all three tests only reflect the worst mode RMC.

WCDMA Band2 Channel=9262



WCDMA Band2 Channel=9400



WCDMA Band2 Channel=9538



WCDMA Band4 Channel=1312



WCDMA Band4 Channel=1450



WCDMA Band4 Channel=1513



WCDMA Band5 Channel=4132



WCDMA Band5 Channel=4182



WCDMA Band5 Channel=4233



9. Out of Band Emissions at Antenna Terminal

9.1 Block Diagram Of Test Setup



9.2 Limit

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least 43 + 10 log10 (P) dB.

9.3 Test procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10th harmonic

9.4 Test Result

GSM1900 Channel=512



GSM1900 Channel=810



GSM850 Channel=128



GSM850 Channel=251



GSM1900 Channel=512



GSM1900 Channel=661



GSM1900 Channel=810



GSM850 Channel=128



GSM850 Channel=190



GSM850 Channel=251



GPRS1900 Channel=512



GPRS1900 Channel=810



GPRS850 Channel=128



GPRS850 Channel=251



GPRS1900 Channel=512



GPRS1900 Channel=661



GPRS1900 Channel=810



GPRS850 Channel=128



GPRS850 Channel=190



GPRS850 Channel=251



EGPRS1900 Channel=512



EGPRS1900 Channel=810



EGPRS850 Channel=128



EGPRS850 Channel=251



EGPRS1900 Channel=512



EGPRS1900 Channel=661



EGPRS1900 Channel=810



EGPRS850 Channel=128



EGPRS850 Channel=190



EGPRS850 Channel=251



Note：In WCDMA, RMC, HSDPA and HSUPA all three tests only reflect the worst mode RMC.

WCDMA Band2 Channel=9262



WCDMA Band2 Channel=9538



WCDMA Band4 Channel=1312



WCDMA Band4 Channel=1513



WCDMA Band5 Channel=4132



WCDMA Band5 Channel=4233

WCDMA Band2 Channel=9262



WCDMA Band2 Channel=9400



WCDMA Band2 Channel=9538



WCDMA Band4 Channel=1312



WCDMA Band4 Channel=1450



WCDMA Band4 Channel=1513



WCDMA Band5 Channel=4132



WCDMA Band5 Channel=4182



WCDMA Band5 Channel=4233



10. Spurious Radiated Emissions

10.1 Block Diagram Of Test Setup

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



10.2 Limit

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least 43 + 10 log10 (P) dB.

10.3 Test procedure

1. The setup of EUT is according with per ANSI/TIA Standard 603D and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB =43+10 Log_{10} (power out in Watts)

10.4 Test Result

For Cellular Band_GSM850 Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (824.2MHz)						
79.52	-42.28	-15.82	-58.10	-13.00	-45.10	H
1648.40	-18.87	-22.56	-41.43	-13.00	-28.43	H
2472.60	-26.33	-19.10	-45.43	-13.00	-32.43	H
79.52	-41.07	-15.82	-56.89	-13.00	-43.89	V
1648.40	-18.35	-22.56	-40.91	-13.00	-27.91	V
2472.60	-26.56	-19.10	-45.66	-13.00	-32.66	V
Middle Channel (836.6MHz)						
79.52	-43.72	-15.82	-59.54	-13.00	-46.54	H
1673.20	-20.21	-22.47	-42.68	-13.00	-29.68	H
2509.80	-26.03	-18.93	-44.96	-13.00	-31.96	H
79.52	-42.21	-15.82	-58.03	-13.00	-45.03	V
1673.20	-20.92	-22.47	-43.39	-13.00	-30.39	V
2509.80	-23.71	-18.93	-42.64	-13.00	-29.64	V
High Channel (848.8MHz)						
79.52	-42.88	-15.82	-58.70	-13.00	-45.70	H
1697.60	-21.57	-22.37	-43.94	-13.00	-30.94	H
2546.40	-24.44	-18.77	-43.21	-13.00	-30.21	H
79.52	-44.86	-15.82	-60.68	-13.00	-47.68	V
1697.60	-21.69	-22.37	-44.06	-13.00	-31.06	V
2546.40	-24.42	-18.77	-43.19	-13.00	-30.19	V

For PCS Band_GSM1900 Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1850.2MHz)						
79.52	-44.29	-15.82	-60.11	-13.00	-47.11	H
3700.40	-24.27	-14.33	-38.60	-13.00	-25.60	H
5550.60	-31.53	-9.60	-41.13	-13.00	-28.13	H
79.52	-44.42	-15.82	-60.24	-13.00	-47.24	V
3700.40	-26.76	-14.33	-41.09	-13.00	-28.09	V
5550.60	-29.84	-9.60	-39.44	-13.00	-26.44	V
Middle Channel (1880MHz)						
79.52	-41.92	-15.82	-57.74	-13.00	-44.74	H
3760.00	-27.85	-14.12	-41.97	-13.00	-28.97	H
5640.00	-31.92	-9.50	-41.42	-13.00	-28.42	H
79.52	-44.58	-15.82	-60.40	-13.00	-47.40	V
3760.00	-27.81	-14.12	-41.93	-13.00	-28.93	V
5640.00	-31.41	-9.50	-40.91	-13.00	-27.91	V
High Channel (1909.8MHz)						
79.52	-44.42	-15.82	-60.24	-13.00	-47.24	H
3819.60	-25.09	-13.91	-39.00	-13.00	-26.00	H
5729.40	-30.39	-9.39	-39.78	-13.00	-26.78	H
79.52	-43.73	-15.82	-59.55	-13.00	-46.55	V
3819.60	-29.61	-13.91	-43.52	-13.00	-30.52	V
5729.40	-29.30	-9.39	-38.69	-13.00	-25.69	V

For Band WCDMA Band II Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1852.4MHz)						
79.52	-42.90	-15.82	-58.72	-13.00	-45.72	H
3704.80	-24.57	-14.31	-38.88	-13.00	-25.88	H
5557.20	-29.59	-9.60	-39.19	-13.00	-26.19	H
79.52	-42.39	-15.82	-58.21	-13.00	-45.21	V
3704.80	-29.25	-14.31	-43.56	-13.00	-30.56	V
5557.20	-28.46	-9.60	-38.06	-13.00	-25.06	V
Middle Channel (1880MHz)						
79.52	-43.21	-15.82	-59.03	-13.00	-46.03	H
3760.00	-26.72	-14.12	-40.84	-13.00	-27.84	H
5640.00	-30.24	-9.50	-39.74	-13.00	-26.74	H
79.52	-43.51	-15.82	-59.33	-13.00	-46.33	V
3760.00	-26.19	-14.12	-40.31	-13.00	-27.31	V
5640.00	-30.01	-9.50	-39.51	-13.00	-26.51	V
High Channel (1907.6MHz)						
79.52	-43.82	-15.82	-59.64	-13.00	-46.64	H
3815.20	-24.41	-13.93	-38.34	-13.00	-25.34	H
5722.80	-31.41	-9.40	-40.81	-13.00	-27.81	H
79.52	-44.04	-15.82	-59.86	-13.00	-46.86	V
3815.20	-28.36	-13.93	-42.29	-13.00	-29.29	V
5722.80	-29.88	-9.40	-39.28	-13.00	-26.28	V

Note: Result=Reading+ Correct, Margin= Result- Limit

For Band WCDMA Band IV Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1712.4MHz)						
79.52	-43.53	-15.82	-59.35	-13.00	-46.35	H
3424.80	-27.31	-15.28	-42.59	-13.00	-29.59	H
5137.20	-29.32	-10.10	-39.42	-13.00	-26.42	H
79.52	-41.88	-15.82	-57.70	-13.00	-44.70	V
3424.80	-27.94	-15.28	-43.22	-13.00	-30.22	V
5137.20	-30.90	-10.10	-41.00	-13.00	-28.00	V
Middle Channel (1740MHz)						
79.52	-42.54	-15.82	-58.36	-13.00	-45.36	H
3464.80	-27.22	-15.14	-42.36	-13.00	-29.36	H
5197.20	-31.80	-10.03	-41.83	-13.00	-28.83	H
79.52	-43.58	-15.82	-59.40	-13.00	-46.40	V
3464.80	-27.90	-15.14	-43.04	-13.00	-30.04	V
5197.20	-30.36	-10.03	-40.39	-13.00	-27.39	V
High Channel (1752.6MHz)						
79.52	-44.43	-15.82	-60.25	-13.00	-47.25	H
3505.20	-25.48	-15.00	-40.48	-13.00	-27.48	H
5257.80	-32.40	-9.95	-42.35	-13.00	-29.35	H
79.52	-42.81	-15.82	-58.63	-13.00	-45.63	V
3505.20	-28.89	-15.00	-43.89	-13.00	-30.89	V
5257.80	-31.12	-9.95	-41.07	-13.00	-28.07	V

Note: Result=Reading+ Correct, Margin= Result- Limit

For Band WCDMA Band V Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (826.4MHz)						
79.52	-42.99	-15.82	-58.81	-13.00	-45.81	H
1652.80	-18.87	-22.55	-41.42	-13.00	-28.42	H
2479.20	-25.11	-19.07	-44.18	-13.00	-31.18	H
79.52	-42.86	-15.82	-58.68	-13.00	-45.68	V
1652.80	-18.02	-22.55	-40.57	-13.00	-27.57	V
2479.20	-26.53	-19.07	-45.60	-13.00	-32.60	V
Middle Channel (836.4MHz)						
79.52	-42.93	-15.82	-58.75	-13.00	-45.75	H
1673.20	-20.33	-22.47	-42.80	-13.00	-29.80	H
2509.80	-23.38	-18.93	-42.31	-13.00	-29.31	H
79.52	-41.15	-15.82	-56.97	-13.00	-43.97	V
1673.20	-18.94	-22.47	-41.41	-13.00	-28.41	V
2509.80	-23.64	-18.93	-42.57	-13.00	-29.57	V
High Channel (846.6MHz)						
79.52	-41.68	-15.82	-57.50	-13.00	-44.50	H
1693.20	-19.96	-22.39	-42.35	-13.00	-29.35	H
2539.80	-23.85	-18.80	-42.65	-13.00	-29.65	H
79.52	-41.21	-15.82	-57.03	-13.00	-44.03	V
1693.20	-21.65	-22.39	-44.04	-13.00	-31.04	V
2539.80	-25.83	-18.80	-44.63	-13.00	-31.63	V

Note: Result=Reading+ Correct, Margin= Result- Limit

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listedin the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

11. Frequency Stability

11.1 Block Diagram Of Test Setup



11.2 Limit

FCC Part 22.355 : ±2.5 ppm
FCC Part 24.235 :
The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

11.3 Test procedure

1. The testing follows FCC KDB 971168 D01v03r01 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01v03r01 Section 9.0.
2. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.

4. The variation in frequency was measured for the worst case.

11.4 Test Result

Operation Mode	Channel Number	Test Condition		Channel Frequency (MHz)	Freq.Dev. (Hz)	Deviation (ppm)	Limit (ppm)
		Voltage (V)	Temp (℃)				
GSM850	190	VN	-20	836.60	-2.96	-0.0035	2.5
			-10	836.60	0.48	0.0006	2.5
			0	836.60	-1.70	-0.0020	2.5
			10	836.60	-5.04	-0.0060	2.5
			20	836.60	6.51	0.0078	2.5
			30	836.60	5.93	0.0071	2.5
			40	836.60	7.13	0.0085	2.5
			50	836.60	3.23	0.0039	2.5
		VL	20	836.60	5.09	0.0061	2.5
		VH	20	836.60	7.45	0.0089	2.5
VERDICT				PASS			

Operation Mode	Channel Number	Test Condition		Channel Frequency (MHz)	Freq.Dev. (Hz)	Deviation (ppm)	Limit (ppm)
		Voltage (V)	Temp (℃)				
GSM1900	512	VN	-20	1850.20	14.46	0.0078	2.5
			-10	1850.20	18.67	0.0101	2.5
			0	1850.20	15.30	0.0083	2.5
			10	1850.20	17.25	0.0093	2.5
			20	1850.20	17.41	0.0094	2.5
			30	1850.20	16.09	0.0087	2.5
			40	1850.20	17.15	0.0093	2.5
			50	1850.20	13.88	0.0075	2.5
		VL	20	1850.20	15.37	0.0083	2.5
		VH	20	1850.20	17.15	0.0093	2.5
VERDICT				PASS			

Note：All modes have been tested with GSM

All modes have been tested, and the worst result recorded was report as below

Operation Mode	Channel Number	Test Condition		Channel Frequency (MHz)	Freq.Dev. (Hz)	Deviation (ppm)	Limit (ppm)
		Voltage (V)	Temp (℃)				
WCDMA850	4132	VN	-20	836.40	14.42	0.0172	2.5
			-10	836.40	18.69	0.0223	2.5
			0	836.40	15.13	0.0181	2.5
			10	836.40	17.30	0.0207	2.5
			20	836.40	17.34	0.0207	2.5
			30	836.40	16.08	0.0192	2.5
			40	836.40	17.20	0.0206	2.5
			50	836.40	13.92	0.0166	2.5
		VL	20	836.40	15.40	0.0184	2.5
		VH	20	836.40	17.12	0.0205	2.5
VERDICT				PASS			

Operation Mode	Channel Number	Test Condition		Channel Frequency (MHz)	Freq.Dev. (Hz)	Deviation (ppm)	Limit (ppm)
		Voltage (V)	Temp (℃)				
WCDMA1700	1312	VN	-20	1712.40	14.37	0.0084	2.5
			-10	1712.40	18.76	0.0110	2.5
			0	1712.40	15.19	0.0089	2.5
			10	1712.40	17.29	0.0101	2.5
			20	1712.40	17.22	0.0101	2.5
			30	1712.40	16.13	0.0094	2.5
			40	1712.40	17.10	0.0100	2.5
			50	1712.40	13.83	0.0081	2.5
		VL	20	1712.40	15.45	0.0090	2.5
		VH	20	1712.40	17.13	0.0100	2.5
VERDICT				PASS			

Operation Mode	Channel Number	Test Condition		Channel Frequency (MHz)	Freq.Dev. (Hz)	Deviation (ppm)	Limit (ppm)
		Voltage (V)	Temp (℃)				
WCDMA1900	9262	VN	-20	1852.40	14.44	0.0078	2.5
			-10	1852.40	18.77	0.0101	2.5
			0	1852.40	15.35	0.0083	2.5
			10	1852.40	17.19	0.0093	2.5
			20	1852.40	17.29	0.0093	2.5
			30	1852.40	16.09	0.0087	2.5
			40	1852.40	17.14	0.0093	2.5
			50	1852.40	13.83	0.0075	2.5
		VL	20	1852.40	15.43	0.0083	2.5
		VH	20	1852.40	17.09	0.0092	2.5
VERDICT				PASS			