

FCC RF EXPOSURE REPORT

FCC ID: 2BALL-EPC11C

Test Report No.....: RF260326671-03-004

Product(s) Name.....: Camtells Cee

Model(s).....: EPC11C

Trade Mark.....: N/A

Applicant.....: Chengdu EAPIL Technology Co.,Ltd

Address.....: Room 1505-1506, Pioneering Building G5, Innovation Center, 1858,
Middle Section of Yizhou Avenue, Gaoxin District, Chengdu,
China(Sichuan)Pilot Free Trade Zone

Receipt Date.....: 2026.05.12

Test Date.....: 2026.05.13 ~ 2026.07.10

Issued Date.....: 2026.07.13

Standards.....: FCC Guidelines for Human Exposure IEEE C95.1
FCC Title 47 Part 2.1091
KDB 447498 D01 General RF Exposure Guidance v06

Testing Laboratory.....: Shenzhen Haiyun Standard Technical Co., Ltd.

Prepared By:	Checked By:	Approved By:	
Lemon He	Black Ding	Tim Zhang	
Lemon He	Black Ding	Tim Zhang	

History of this test report

Original Report Issue Date: 2026.07.13

- ☒ No additional attachment
- ☐ Additional attachments were issued following record

Attachment No.	Issue Date	Description

1. MPE CALCULATION METHOD

Radio Frequency Exposure Limit

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)
300-1,500	--	--	f/1500
1,500-100,000	--	--	1.0

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

For 2.4G WIFI

Antenna gain	Antenna Type
0.86dBi	FPC Antenna

For 5GHz WiFi:

Antenna gain	Antenna Type
2.42dBi	FPC Antenna

For BLE:

Antenna gain	Antenna Type
-0.58dBi	PCB Antenna

2. TEST RESULTS

Worst case as below

Operating Mode	Freq.	Maximum conducted output power	Directional Antenna Gain	Calculated maximum EIRP		MPE Limit	MPE Value
	(MHz)	(dBm)	(dBi)	(dBm)	(mW)	(mW/cm ²)	
BLE	2402-2480	6.78	-0.58	6.20	4.25	1	0.0008
2.4G Wifi	2412-2462	14.84	0.86	15.70	37.15	1	0.0074
5G Wifi	5180-5240	14.81	2.42	17.23	52.84	1	0.0105
5.8G Wifi	5745-5825	15.91	2.42	18.33	68.08	1	0.0135

Note: 1. The calculated distance is 20 cm.

2. The 2.4G Wifi function can not transmit at the same time with the 5G Wifi function

3. The Wifi function can transmit at the same time with the BT function.

Simultaneous transmitting consideration(worst case)

The ratio= $MPE_{BLE}/limit + MPE_{5.8G\ Wifi}/limit = 0.0008/1 + 0.0135/1 = 0.0143 < 1.0$

Result: Complies

Statement

1. The report is invalid without the official seal or special seal of Shenzhen Haiyun Standard Technical Co., Ltd. (hereinafter referred to as the unit).
2. The report is invalid without the signature of the approver.
3. The report is invalid if altered arbitrarily.
4. The report shall not be partially copied without the written approval of the unit.
5. The reported test results are only valid for the tested samples.
6. If there is any objection to the test report, it shall be submitted to the test unit within 15 days from the date of receiving the report, and the overdue shall not be accepted.

Shenzhen Haiyun Standard Technical Co., Ltd.

Address: Room 110, 111, 112, 113, 115, 116, Block B, Jinyuan Business Building, No. 302, Xixiang Avenue, Labor Community, Xixiang Street, Baoan District, Shenzhen, China

(END OF REPORT)