SAR Test Report

For

Applicant Name:	**POSBANK CO., LTD.**
Address:	#805-808, 108, Gasan digital 2-ro, Geumcheon-gu Seoul South Korea
EUT Name:	Tablet
Brand Name:	POSBANK
Model Number:	PAI TAB-1010
The Series Model:	PAI TABN-1010, PAI TAB ORDER, PAI TABN ORDER

Issued By

Company Name:	**BTF Testing Lab (Shenzhen) Co., Ltd.**
Address:	Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China
Report Number:	BTF260609R00201
Test Standards:	FCC 47 CFR§2.1093 IEEE Std. 1528-2013 IEEE C95.1-2019
FCC ID:	2BASH-PAITAB1010
Test Conclusion:	Pass
Test Date:	2026-06-12 to 2026-06-16
Date of Issue:	2026-06-17
Tested By:	Birch Zhang
	Birch Zhang / Tester
Date:	2026-06-17
Prepared By:	Amenda Zhong
	Amenda Zhong / Project Engineer
Date:	2026-06-17
Approved By:	Ryan.CJ
	Ryan.CJ / EMC Manager
Date:	2026-06-17

BTF Testing Lab (Shenzhen) Co., Ltd.

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Revision History		
Version	Issue Date	Revisions Content
R_V0	2026-06-17	Original
Note:	*Once the revision has been made, then previous versions reports are invalid.*	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

Table of Contents

1. Introduction 4
1.1 Identification of Testing Laboratory 4
1.2 Identification of the Responsible Testing Location 4
1.3 Laboratory Condition 4
1.4 Announcement 4
2. Product Information 5
2.1 Application Information 5
2.2 Manufacturer Information 5
2.3 Factory Information 5
2.4 General Description of Equipment under Test (EUT) 5
2.5 Equipment under Test Ancillary Equipment 5
2.6 Technical Information 5
3. Summary of Test Results 6
3.1 Test Standards 6
3.2 Device Category and SAR Limit 7
3.3 Test Result Summary 7
3.4 Test Uncertainty 8
4. Measurement System 10
4.1 Specific Absorption Rate (SAR) Definition 10
4.2 MVG SAR System 10
5. System Verification 15
5.1 Purpose of System Check 15
5.2 System Check Setup 15
6. TEST POSITION CONFIGURATIONS 16
6.1 Head Exposure Conditions 16
6.2 Body-worn Position Conditions 18
6.3 Hotspot Mode Exposure Position Conditions 19
6.4 Product Specific 10g Exposure Consideration 19
7. Measurement Procedure 20
7.1 Measurement Process Diagram 20
7.2 SAR Scan General Requirement 21
7.3 Measurement Procedure 22
7.4 Area & Zoom Scan Procedure 22
8. Conducted RF Output Power 23
8.1 Wi-Fi 23
8.2 Bluetooth 25
9. Test Exclusion Consideration 26
9.1 SAR Test Exclusion Consideration Table 26
10. Test Result 27
11. SAR Measurement Variability 28
12. Simultaneous Transmission 29
12.1 Simultaneous Transmission Mode Considerations 29
13. Test Equipment List 30
ANNEX A Simulating Liquid Verification Result 31
ANNEX B System Check Result 31
ANNEX C Test Data 40
ANNEX D SAR Test Setup Photos 52
ANNEX E EUT External and Internal Photos 52
ANNEX F Calibration Information 52

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

1. Introduction

1.1 Identification of Testing Laboratory

Company Name:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-0755-23146130
Fax Number:	+86-0755-23146130

1.2 Identification of the Responsible Testing Location

Test Location:	BTF Testing Lab (Shenzhen) Co., Ltd.
Address:	Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China
Description:	All measurement facilities used to collect the measurement data are located at Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China
FCC Registration Number	518915
Designation Number	CN1409

1.3 Laboratory Condition

Ambient Temperature:	21℃ to 25℃
Ambient Relative Humidity:	48% to 59%
Ambient Pressure:	100 kPa to 102 kPa

1.4 Announcement

(1) The test report reference to the report template version v0.

(2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.

(3) The test report is invalid if there is any evidence and/or falsification.

(4) This document may not be altered or revised in any way unless done so by BTF and all revisions are duly noted in the revisions section.

(5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

(6) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Product Information

2.1 Application Information

Company Name:	POSBANK CO., LTD.
Address:	#805-808, 108, Gasan digital 2-ro, Geumcheon-gu Seoul South Korea

2.2 Manufacturer Information

Company Name:	POSBANK CO., LTD.
Address:	#805-808, 108, Gasan digital 2-ro, Geumcheon-gu Seoul South Korea

2.3 Factory Information

Company Name:	POSBANK CO., LTD.
Address:	D-1009, 45, DEURIMSANDAN 4-RO, CHEONGBUK-EUP, PYEONGTAEK-SI GYEONGGI-DO, REPUBLIC OF KOREA

2.4 General Description of Equipment under Test (EUT)

EUT Name	Tablet
Under Test Model Name	PAI TAB-1010
Series Model Name	PAI TABN-1010, PAI TAB ORDER, PAI TABN ORDER
Software Version	V1.12_20260203
Hardware Version	F89-V2.0
Description of Model name differentiation	Different sales regions have different names.
Sample No	BTFSN260609001

2.5 Equipment under Test Ancillary Equipment

Ancillary Equipment 1	Rechargeable Battery	
	Capacity	6000mAh
	Nominal Voltage	3.85V

2.6 Technical Information

Network and Wireless connectivity	2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) BT (EDR+BLE)

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	WLAN, Bluetooth	
Frequency Range	802.11b/g/n(HT20)	2412 ~ 2462 MHz
	802.11n(HT40)	2422 ~ 2452 MHz
	802.11a 802.11n(HT20/40) 802.11ac(HT20/40/80)	5150 MHz ~ 5250 MHz 5250 MHz ~ 5350 MHz 5470 MHz ~ 5725 MHz 5725 MHz ~ 5850 MHz
	Bluetooth	2402 ~ 2480 MHz
Antenna Type	WLAN: PIFA Antenna Bluetooth: PIFA Antenna	
Hotspot Function	Not Support	
Power Reduction	Not Support	
Exposure Category	General Population/Uncontrolled exposure	
EUT Stage	Portable Device	
Product	Type	
	☒ Production unit	☐ Identical prototype

3. Summary of Test Results

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
3	IEEE C95.1-2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz
4	KDB447498 D01	General RF Exposure Guidance v06
5	KDB865664 D01	SAR measurement 100MHz to 6GHz v01r04
6	KDB248227 D01	802.11 Wi-Fi SAR v02r02
7	KDB941225 D06	Hotspot Mode v02r01
8	KDB648474 D04	Handset SAR v01r03
9	KDB690783 D01	SAR Listings on Grant v01r03
10	KDB 616217 D04	SAR for laptop and tablets v01r02

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:
General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment- related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

The maximum results of Specific Absorption Rate (SAR) found during test as bellows:

<Highest Reported standalone SAR>

Exposure Position	Frequency Band	Reported SAR (W/kg)	Equipment Class	Highest Reported SAR (W/kg)
Body 1-g SAR (0 mm Gap)	WLAN 2.4 GHz	0.710	DTS	**0.965**
	RLAN 5.2 GHz	0.229	NII	
	RLAN 5.4 GHz	0.580		
	RLAN 5.6 GHz	0.965		
	RLAN 5.8 GHz	0.895		
	Bluetooth	0.081	DSS	

This device is in compliance with Specific Absorption Rate(SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC47 CFR part 2(2.1093) and ANSI/IEEE C95.1-2019, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std. 1528-2013.

3.4 Test Uncertainty

3.4.1 Measurement uncertainly evaluation for SAR test (450MHz to 6GHz)

Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Unc. u(xi)=a(xi)/qi	Ci (1g)	Ci (10g)	1g Ui (+- %)	10 g Ui (+-%)	Vi veff
Measurement System									
Probe calibration	16	N (k = 2)	2	8.00	1	1	8.00	8.00	∞
Probe calibration drift	4	R	√3	2.31	1	1	2.31	2.31	∞
Probe linearity	4.7	R	√3	2.71	1	1	2.71	2.71	∞
detection limit	1	R	√3	0.58	1	1	0.58	0.58	∞
Probe isotropy	3.5	R	√3	2.02	0.71	0.71	1.43	1.43	∞
Hemispherical Isotropy	5.9	N	1	5.90	0.71	0.71	4.19	4.19	∞
Boundary effect	1	R	1.73	0.58	1	1	0.58	0.58	∞
Integration time	1.4	R	1.73	0.81	1	1	0.81	0.81	∞
Response time	0	R	1.73	0.00	1	1	0.00	0.00	∞
Readout electronics	0.5	N	1	0.50	1	1	0.50	0.50	∞
RF ambient and noise	3	R	√3	1.73	1	1	1.73	1.73	∞
Probe positioning errors	3.28	N	1	3.28	0.33	0.33	1.08	1.08	∞
Data processing errors	2.3	R	1	1.33	1	1	1.33	1.33	∞
Conductivity measurement	4.07	N	1	2.35	0.79	0.77	1.86	1.81	∞
Permitivity measurement	5.06	N	1	2.92	0.23	0.26	0.67	0.76	∞
Liquid Conductivity - Temperature Uncertainty	2.5	R	1	1.44	0.79	0.77	1.14	1.11	∞
Liquid Permittivity - Temperature Uncertainty	2.5	R	√3	1.44	0.23	0.26	0.33	0.38	∞
Shell permittivity	2.9	R	√3	1.67	0.25	0.25	0.42	0.42	∞
Repeatability of positioning the DUT or source against the phantom	2.7	N	1	2.70	2	2	5.40	5.40	∞
Uncertainty in accepted power	3	R	1	3.00	1	1	3.00	3.00	∞
Effect of operating mode on probe sensitivity	2.3	R	√3	1.33	1	1	1.33	1.33	∞
Variation in SAR due to drift in output of DUT	2.2	N	1	2.20	1	1	2.20	2.20	∞
Phantom deviation from target (ε',σ)	1.9	N	1	1.90	1	1	1.90	1.90	∞
SAR scaling	0	R	√3	0.00	1	1	0.00	0.00	∞
Combined uncertainty	/						12.56	12.55	
Expanded Uncertainty (95% Confidence interval)	/						25.11	25.11	

* This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

3.4.2 Measurement uncertainly evaluation for system check

Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Unc. u(xi)=a(xi)/qi	Ci (1g)	Ci (10 g)	1g Ui (+- %)	10 g Ui (+-%)	Vi veff
Measurement System									
Probe calibration	16	N (k = 2)	2	8.00	1	1	8.00	8.00	∞
Probe calibration drift	4	R	1.73	2.31	1	1	2.31	2.31	∞
Probe linearity	4.7	R	1.73	2.72	1	1	2.72	2.72	∞
Detection limit	1	R	1.73	0.58	1	1	0.58	0.58	∞
Axial Isotropy	3.5	R	1.73	2.02	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	1.73	3.41	0.71	0.71	2.42	2.42	∞
Boundary effect	1	R	1.73	0.58	0.71	0.71	0.41	0.41	∞
Integration time	1.4	R	1.73	0.81	1	1	0.81	0.81	∞
Response time	0	R	1.73	0.00	1	1	0.00	0.00	∞
Readout electronics	0.5	N	1	0.50	1	1	0.50	0.50	∞
Noise	3	R	1.73	1.73	1	1	1.73	1.73	∞
Reflections	3	R	1.73	1.73	1	1	1.73	1.73	∞
Positioner Mechanical Tolerance	3.28	R	1.73	1.90	0.33	0.33	0.63	0.63	∞
Positioning with respect to Phantom Shell	3.28	R	1.73	1.90	0.33	0.33	0.63	0.63	∞
Data processing errors	2.3	R	1.73	1.33	1	1	1.33	1.33	∞
Conductivity measurement	4.07	N	1	4.07	0.79	0.77	3.22	3.13	∞
Permitivity measurement	5.06	N	1	5.06	0.23	0.26	1.16	1.32	∞
Liquid Conductivity - Temperature Uncertainty	2.5	R	1.73	1.45	0.79	0.77	1.14	1.11	∞
Liquid Permittivity - Temperature Uncertainty	2.5	R	1.73	1.45	0.23	0.26	0.33	0.38	∞
Shell permittivity	2.9	R	1.73	1.68	0.25	0.25	0.42	0.42	∞
Distance between the radiating element of the DUT and the phantom medium	2.7	N	1	2.70	2	2	5.40	5.40	∞
Deviation of experimental antennas	4.5	N	1.73	2.60	1	1	2.60	2.60	∞
Other uncertainty contributions	2	R	1	2.00	1	1	2.00	2.00	∞
Uncertainty in accepted power	3	R	1.73	1.73	1	1	1.73	1.73	∞
Phantom deviation from target (ε',σ)	1.9	N	1	1.90	1	0.87	1.90	1.65	∞
u(ΔSAR)	\						12.51	12.47	
Expanded uncertainty (95% confidence interval)	\						25.02	24.93	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

4. Measurement System

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\mathbf{SAR} = \frac{d}{dt}\left(\frac{dW}{dm}\right) = \frac{d}{dt}\left(\frac{dW}{\rho dv}\right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$\mathbf{SAR} = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,
ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 MVG SAR System

4.2.1 SAR system diagram



4.2.2 Robot

A standard high precision 6-axis robot (Denso) with teaches pendant with Scanning System
· It must be able to scan all the volume of the phantom to evaluate the tridimensional distribution of SAR.
· Must be able to set the probe orthogonal of the surface of the phantom (±30°).
· Detects stresses on the probe and stop itself if necessary to keep the integrity of the probe.

4.2.3 E-Field Probe

For the measurements the Specific Dosimetric E-Field Probe 0125-EPGO-445 with following specifications is used:

- Probe Length: 330 mm
- Length of Individual Dipoles:2mm
- Maximum external diameter. 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity:1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Calibration range: 150 to 6000 MHz for head & body simulating liquid
- Axial Isotropy: <0.10 dB
- Spherical Isotropy:<0.10 dB
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°.

4.2.4 Phantoms

SAM Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The probe scanning of the E-Field is done in the 2 halves of the normalized head. The normalized shape of the phantom corresponds to the dimensions of 90% of an adult head size. It enables the dosimetric evaluation of left and right-hand phone usage and includes an additional flat phantom part for the simplified body performance check.The phantom set-up includes a cover, which prevents the evaporation of the liquid.

The thickness of the phantom amounts to 2 mm±0.2 mm. The materials for the phantom do not affect the radiation of the device under test (DUT) : εr' <5
The head is filled with tissue simulating liquid. The hand do not have to be modeled.

SAM Phantom

TWIN SAM phantom			
Mechanical		Electrical	
Overall thickness	2±0.2 mm(except ear area)	Relative permittivity	3.4
Dimensions	1000 mm(L) x 500 mm(W) x 200 mm(H)	Loss tangent	0.02
Maximum volume	27 L		
Material	Fiberglass based		

ELLIPTICAL Phantom

The phantom is for Body performance check filled with tissue-equivalent liquid to a depth of at least 150 mm, whose shell material is resistant to damage or reaction with tissue-equivalent liquid chemicals.

The shape of the phantom is an ellipse with length 600mm±5mm and width 400mm±5mm.
The phantom shell is made of low-loss and low-permittivity material, having loss tangent tanδ ≤ 0.05 and relative permittivity:
εr' ≤ 5 for f ≤ 3 GHz
3 ≤εr' ≤ 5 for f > 3 GHz
The thickness of the bottom-wall of the flat phantom is 2.0 mm with a tolerance of ± 0.2 mm.

ELLI Phantom

Technical & mechanical characteristics	
Shell thickness	2 mm ± 0.2 mm
Filling volume	25 L
Dimensions	600 mm x 400 mm x 200mm
Permittivity	4.4
Loss tangent	0.017

4.2.5 Device Holder



System Material	Permittivity	Loss tangent
Delrin	3.7	0.005

(The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.)

System Material	Permittivity	Loss tangent
PMMA	2.9	0.028

4.2.6 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.

Head Liquid Depth	Body Liquid Depth

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ε
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ε
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ε
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ε
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

5. System Verification

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. The setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup



6. TEST POSITION CONFIGURATIONS

According to KDB 648474 D04 Handset, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

6.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.

6.1.1 Two Imaginary Lines on the Handset

(a) The vertical center line passes through two points on the front side of the handset - the midpoint of the width w t of the handset at the level of the acoustic output, and the midpoint of the width w b of the bottom of the handset.
(b) The horizontal line is perpendicular to the vertical center line and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
(c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical center line is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.





6.1.2 Two Imaginary Lines on the Handset

(a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

(b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.



6.1.3 Titled Position

(a) To position the device in the “cheek” position described above.

(b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost.

6.2 Body-worn Position Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required. A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance <= 5 mm to support compliance.





6.3 Hotspot Mode Exposure Position Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



6.4 Product Specific 10g Exposure Consideration

According with FCC KDB 648474 D04, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, unless it is confirmed otherwise through KDB inquiries, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance;

The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

7. Measurement Procedure

7.1 Measurement Process Diagram

Body SAR



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

<table>
<tr><th colspan="3"></th><th>≤3GHz</th><th>>3GHz</th></tr>
<tr><td colspan="3">Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface</td><td>5±1 mm</td><td>½·δ·ln(2)±0.5 mm</td></tr>
<tr><td colspan="3">Maximum probe angle from probe axis to phantom surface normal at the measurement location</td><td>30°±1°</td><td>20°±1°</td></tr>
<tr><td colspan="3" rowspan="2">Maximum area scan spatial resolution: Δx Area , Δy Area</td><td>≤ 2 GHz: ≤ 15 mm
2 – 3 GHz: ≤ 12 mm</td><td>3–4 GHz: ≤ 12 mm
4 – 6 GHz: ≤ 10 mm</td></tr>
<tr><td colspan="2">When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.</td></tr>
<tr><td colspan="3">Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom</td><td>≤ 2 GHz: ≤ 8 mm
2 –3 GHz: ≤ 5 mm*</td><td>3–4 GHz: ≤ 5 mm*
4 – 6 GHz: ≤ 4 mm*</td></tr>
<tr><td rowspan="5">Maximum zoom scan spatial resolution, normal to phantom surface</td><td colspan="2" rowspan="2">uniform grid: Δz Zoom (n)</td><td rowspan="2">≤ 5 mm</td><td>3–4 GHz: ≤ 4 mm</td></tr>
<tr><td>4–5 GHz: ≤ 3 mm</td></tr>
<tr><td rowspan="3">graded grid</td><td rowspan="2">Δz Zoom (1): between 1st two points closest to phantom surface</td><td rowspan="2">≤ 4 mm</td><td>5–6 GHz: ≤ 2 mm</td></tr>
<tr><td>3–4 GHz: ≤ 3 mm</td></tr>
<tr><td>4–5 GHz: ≤ 2.5 mm</td></tr>
<tr><td></td><td>Δz Zoom (n>1): between subsequent points</td><td colspan="2">≤ 1.5·Δz Zoom (n-1)</td></tr>
<tr><td rowspan="3">Minimum zoom scan volume</td><td colspan="2" rowspan="3">x, y, z</td><td rowspan="3">≥30 mm</td><td>3–4 GHz: ≥ 28 mm</td></tr>
<tr><td>4–5 GHz: ≥ 25 mm</td></tr>
<tr><td>5–6 GHz: ≥ 22 mm</td></tr>
<tr><td colspan="5">Note:
1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528- 2011 for details.
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</td></tr>
</table>

7.3 Measurement Procedure

The following steps are used for each test position

a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface

b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.

c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.

d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 *32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

8. Conducted RF Output Power

8.1 Wi-Fi

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
2.4g Wifi (2.4~2.4835)	802.11b	1	2412	14.38	14.50	No
		6	2437	**14.51**	**15.00**	Yes
		11	2462	14.45	14.50	No
	802.11g	1	2412	14.37	14.50	No
		6	2437	14.35	14.50	No
		11	2462	14.48	14.50	No
	802.11n(HT20)	1	2412	14.31	14.50	No
		6	2437	14.29	14.50	No
		11	2462	14.42	14.50	No
	802.11n(HT40)	3	2422	14.55	15.00	No
		6	2437	14.55	15.00	No
		9	2452	14.56	15.00	No
Note: SAR is not required for the following 2.4 GHz OFDM conditions as the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2W/kg.						

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-1 (5.150~5.250)	802.11a	36	5180	13.92	14.00	No
		40	5200	14.14	14.50	No
		48	5240	14.75	15.00	No
	802.11n(HT20)	36	5180	14.10	14.50	No
		40	5200	14.19	14.50	No
		48	5240	14.72	15.00	No
	802.11ac(VHT20)	36	5180	14.01	14.50	No
		40	5200	14.21	14.50	No
		48	5240	14.80	15.00	No
	802.11n(HT40)	38	5190	12.22	12.50	No
		46	5230	**15.22**	**15.50**	Yes
	802.11ac(VHT40)	38	5190	12.61	13.00	No
		46	5230	12.58	13.00	No
	802.11ac(VHT80)	42	5210	11.09	11.50	No
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-2a (5.250~5.350)	802.11a	52	5260	15.53	16.00	No
		56	5280	15.80	16.00	No
		64	5320	14.96	15.00	No
	802.11n(HT20)	52	5260	14.99	15.00	No
		56	5280	15.19	15.50	No
		64	5320	12.35	12.50	No
	802.11ac(VHT20)	52	5260	**17.35**	**17.50**	Yes
		56	5280	15.37	15.50	No
		64	5320	13.20	13.50	No
	802.11n(HT40)	54	5270	13.20	13.50	No
		62	5310	11.43	11.50	No
	802.11ac(VHT40)	54	5270	15.73	16.00	No
		62	5310	12.75	13.00	No
	802.11ac(VHT80)	58	5290	9.42	9.50	No

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-2c (5.470~5.725)	802.11a	100	5500	**13.45**	**13.50**	Yes
		116	5580	12.51	13.00	No
		140	5700	10.62	11.00	No
	802.11n(HT20)	100	5500	11.26	11.50	No
		116	5580	10.26	10.50	No
		140	5700	9.93	10.00	No
	802.11ac(VHT20)	100	5500	11.49	11.50	No
		116	5580	10.41	10.50	No
		140	5700	10.60	11.00	No
	802.11n(HT40)	102	5510	9.26	9.50	No
		110	5550	8.77	9.00	No
		134	5670	11.36	11.50	No
	802.11ac(VHT40)	102	5510	11.10	11.50	No
		110	5550	10.36	10.50	No
		134	5670	7.34	7.50	No
	802.11ac(VHT80)	106	5530	9.95	10.00	No
		122	5610	9.50	10.00	No
Band (GHz)	Mode	Channel	Freq. (MHz)	Average Power (dBm)	Maximum Tune-up(dBm)	SAR Test Require.
U-NII-3 (5.725~5.850)	802.11a	149	5745	9.91	10.00	No
		157	5785	9.87	10.00	No
		165	5825	10.20	10.50	No
	802.11n(HT20)	149	5745	8.76	9.00	No
		157	5785	8.67	9.00	No
		165	5825	9.38	9.50	No
	802.11ac(VHT20)	149	5745	9.17	9.50	No
		157	5785	11.38	11.50	No
		165	5825	**11.72**	**12.00**	Yes
	802.11n(HT40)	151	5755	8.91	9.00	No
		159	5795	8.90	9.00	No
	802.11ac(VHT40)	151	5755	11.60	12.00	No
		159	5795	9.33	9.50	No
	802.11ac(VHT80)	155	5775	8.74	9.00	No

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

8.2 Bluetooth

EDR	Mode	Maximum Tune-up(dBm)	Conducted Output Power(dBm)		
			0	39	78
			2402MHz	2441MHz	2480MHz
	GFSK	5.00	4.65	3.97	4.41
	π/4QPSK	4.00	3.69	3.16	3.61
	8DPSK	4.00	3.76	3.25	3.63
BLE	Mode	Maximum Tune-up(dBm)	Conducted Output Power(dBm)		
			0	20	39
			2402MHz	2440MHz	2480MHz
	1Mbps	**6.50**	**6.40**	5.28	5.77

Note

1. Per KDB 447498 D01 General RF Exposure Guidance v06, the 1-g SAR test exclusion thresholds for 300 MHz to 6 GHz at *test separation distances* ≤ 40 cm are determined by:

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	*SAR Test Exclusion Threshold* (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

*When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine estimated SAR. .
The output power of all data rate were prescan, just the worst case (the lowest data rate) of all mode were shown in report.

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

9. Test Exclusion Consideration

Antenna information:



WLAN/BT Antenna	WLAN/BT TX/RX

Note:
1. KDB 447498 D01v06, particular DUT edges were not required to be evaluated for SAR if the antenna-to-edge distance is greater than 2.5cm.
2. Per KDB648474 D04,10-g extremity SAR is not required when Body-Worn mode 1-g reported SAR<1.2W/Kg.
3. KDB 616217 D04 SAR for laptop and tablets v01r02, it doesn't require SAR evaluation for the front surface of a tablet.

Distance of The Antenna to the EUT surface and edge (mm)						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
BT/Wifi	<25	<25	155	<25	55	180
Positions for SAR tests: Hotspot mode						
Antenna	Front Side (mm)	Back Side (mm)	Left Edge (mm)	Right Edge (mm)	Top Edge (mm)	Bottom Edge (mm)
BT/Wifi	No	Yes	No	Yes	No	No

9.1 SAR Test Exclusion Consideration Table

Per KDB 447498 requires when the standalone SAR test exclusion of section 4.3.1 is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following format to determine simultaneous transmission SAR test exclusion:

(max.power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] · [√f(GHz) / x] W/kg for test separation distances ≤ 50 mm;
where x = 7.5 for 1-g SAR, and x= 18.75 for 10-g SAR.
0.4 W/Kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm

10. Test Result

Body(0mm Gap)										
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
2.4g (2.4~2.4835) 802.11b	Back	6	2437	-1.390	0.634	14.51	15.00	1.119	**0.710**	1#
	Right	6	2437	2.520	0.425	14.51	15.00	1.119	0.476	/

Body(0mm Gap)										
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-1 (5.150~5.250) 802.11n(HT40)	Back	46	5230	-2.260	0.215	15.22	15.50	1.067	**0.229**	2#
	Right	46	5230	1.360	0.165	15.22	15.50	1.067	0.176	/

Body(0mm Gap)										
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-2a (5.250~5.350) 802.11ac(VHT20)	Back	52	5260	2.840	0.560	17.35	17.50	1.035	**0.580**	3#
	Right	52	5260	-3.210	0.437	17.35	17.50	1.035	0.452	/

Body(0mm Gap)										
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-2c (5.470~5.725) 802.11a	Back	100	5500	3.500	0.954	13.45	13.50	1.012	**0.965**	4#
	Back-repeat	100	5500	1.200	0.913	13.45	13.50	1.012	0.924	/
	Back	116	5580	-2.650	0.778	12.51	13.00	1.119	0.871	/
	Back	140	5700	-1.470	0.794	10.62	11.00	1.091	0.867	/
	Right	100	5500	3.410	0.652	13.45	13.50	1.012	0.660	/

Body(0mm Gap)										
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
U-NII-3 (5.725~5.850) 802.11ac(VHT20)	Back	165	5825	3.600	0.839	11.72	12.00	1.067	**0.895**	5#
	Back-repeat	165	5825	1.670	0.811	11.72	12.00	1.067	0.865	/
	Back	149	5745	-1.500	0.703	9.17	9.50	1.079	0.758	/
	Back	157	5785	-2.780	0.742	11.38	11.50	1.028	0.763	/
	Right	165	5825	0.600	0.627	11.72	12.00	1.067	0.669	/

Body(0mm Gap)										
Mode	Position	Ch.	Freq. (MHz)	Power Drift (%)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	1g Scaled SAR (W/kg)	Meas. No.
BLE	Back	0	2402	3.630	0.079	6.40	6.50	1.023	**0.081**	6#
	Right	0	2402	1.420	0.055	6.40	6.50	1.023	0.056	/

Note:
1. The maximum SAR Value of each test band is marked bold.
2. SAR plot is provided only for the highest measured SAR in each exposure configuration, wireless mode and frequency band combination.
3. Per KDB 447498 D01 v06, for each exposure position, if the highest output power channel Reported SAR ≤ 0.8W/kg, other channels SAR testing is not necessary.
4. Per KDB 447498 D01 v06, head/body-worn use is evaluated with the device positioned at 0mm from a flat phantom respectively filled with head tissue-equivalent medium.
5. Per KDB 447498 D01 v06, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor=10^[(tune-up limit power(dBm) - Ave.power power (dBm))/10], where tune-up limit is the maximum rated power among all production units.
   Reported SAR(W/kg)=Measured SAR (W/kg)*Scaling Factor.

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

11. SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10, the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is >= 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20, or when the original or repeated measurement is >= 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20, and the original, first or second repeated measurement is >= 1.5 W/kg, perform a third repeated measurement.

Note: For 1g SAR, the highest measured 1g SAR is 0.954>0.80 W/kg, repeated measurement is needs.

Mode	Position	Ch.	Freq. (MHz)	1g Meas SAR (W/kg)	the ratio of largest to smallest SAR for the original and first repeated measurements
U-NII-2c 802.11a	Back	100	5500	0.954	1.044
	Back-repeat	100	5500	0.913	
U-NII-3 802.11ac(VHT20)	Back	165	5825	0.839	1.034
	Back-repeat	165	5825	0.811	

12. Simultaneous Transmission

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

12.1 Simultaneous Transmission Mode Considerations

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. The device has 1 Tx antennas, Wifi/BT antenna supports 2.4G/5G Wi-Fi and BT. Therefore we do not need to consider simultaneous transmission.

13. Test Equipment List

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
E-Field Probe	MVG	SSE2	0125-EPGO-445	2026/03/03	2027/03/02
6 1/2 Digital Multimeter	Keithley	DMM6500	4527164	2025/10/20	2026/10/19
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	161997	2025/10/17	2026/10/16
MXG Vector Signal Generator	Agilent	N5182A	MY46240163	2025/10/17	2026/10/16
E-Series Avg. Power Sensor	KEYSIGHT	E9300A	MY55050017	2026/04/02	2027/04/01
EPM Series Power Meter	KEYSIGHT	E4418B	MY41293435	2026/04/02	2027/04/01
MXA Signal Analyzer	KEYSIGHT	N9020A	MY54410409	2025/10/17	2026/10/16
Low Noise Amplifier	Tongyue	N/A	N/A	2025/07/30	2026/07/29
Coupler	MERRIMAC	CWM-10R-10.8G	LOT-83391	N/A	N/A
2450MHz Validation Dipole	MVG	SID2450	07/22 DIP 2G450-662	2025/05/26	2028/05/25
5200MHz-5800MHz Validation Dipole	MVG	SID5000	07/22 DIP5G000-670	2025/05/26	2028/05/25
LIMESAR Dielectric Probe	MVG	SCLMP	06/22 OCPG88	2026/04/07	2027/04/06
ENA Series Network Analyzer	Agilent	E5071B	MY42301221	2025/10/17	2026/10/16
Thermometer	Riters	DT-232	21A11	2026/04/02	2027/04/01
Antenna network emulator	MVG	ANTA 74	07/22 ANTA 74	N/A	N/A
SAM Phantom	MVG	SAM	07/22 SAM149	N/A	N/A
Mobile Phone Positioning System	MVG	MSH 118	07/22 MSH 118	N/A	N/A
Mechanical Calibration Kit	PNA	N/A	N/A	2025/10/21	2026/10/20
Open SAR test software	MVG	N/A	V5.3.5	N/A	N/A

Note: For dipole antennas, BTF has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

ANNEX A Simulating Liquid Verification Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

Dielectric performance of tissue simulating liquid									
Frequency (MHz)	εr		σ(s/m)		Delta (εr)	Delta (σ)	Limit	Temp (℃)	Date
	Target	Measured	Target	Measured					
2402	39.20	39.57	1.80	1.72	0.94%	-4.44%	±5%	21.4	12/6/2026
2437	39.20	39.54	1.80	1.73	0.87%	-3.89%	±5%	21.4	12/6/2026
2450	39.20	39.52	1.80	1.74	0.82%	-3.33%	±5%	21.4	12/6/2026
5200	36.00	36.11	4.66	4.51	0.31%	-3.22%	±5%	21.1	13/6/2026
5230	36.00	36.04	4.66	4.57	0.11%	-1.93%	±5%	21.1	13/6/2026
5260	36.00	35.97	4.66	4.64	-0.08%	-0.43%	±5%	20.9	13/6/2026
5500	35.50	35.58	5.07	5.04	0.23%	-0.59%	±5%	21.6	15/6/2026
5600	35.50	35.53	5.07	5.14	0.08%	1.38%	±5%	21.6	15/6/2026
5800	35.30	35.36	5.27	5.32	0.17%	0.95%	±5%	21.3	16/6/2026
5825	35.30	35.34	5.27	5.34	0.11%	1.33%	±5%	21.3	16/6/2026
NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 ℃ of the conditions expected during the SAR evaluation to satisfy protocol requirements.									

ANNEX B System Check Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %(for 10 g).

Frequency (MHz)	Input Power (mW)	10g SAR (W/Kg)	1g SAR (W/Kg)	10g SAR 1W input power normalized (W/Kg)	1g SAR 1W input power normalized (W/Kg)	10g SAR Standard target (1W) (W/Kg)	1g SAR Standard target (1W) (W/Kg)	10g SAR Deviation	1g SAR Deviation
2450	100	2.453	5.344	24.53	53.44	24.55	52.72	-0.08%	1.37%
5200	100	2.269	7.225	22.69	72.25	22.78	78.16	-0.40%	-7.56%
5600	100	2.446	8.173	24.46	81.73	23.95	82.72	2.13%	-1.20%
5800	100	2.282	7.709	22.82	77.09	22.71	78.32	0.48%	-1.57%

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

System Performance Check Data (2450 MHz)

System check at 2450 MHz

Date of measurement: 12/6/2026

A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels/Frequency	Middle
Signal	CW

B. Permitivity

Middle TX Frequency (MHz)	2450.000
Relative permitivity (real part)	39.524
Relative permitivity (imaginary part)	13.302
Conductivity (S/m)	1.736

C. SAR Surface and Volume

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-2.00, Y=-1.00 ; SAR Peak: 9.29 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	2.453
SAR 1g (W/Kg)	5.344
Variation (%)	2.820
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	51.294581

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	9.364	5.684	2.915	1.543	0.819	0.432	0.238

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



F. 3D Image

3D screen shot	Hot spot position
	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

System Performance Check Data (5200 MHz)

System check at 5200 MHz

Date of measurement: 13/6/2026

A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.16
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels/Frequency	Middle
Signal	CW

B. Permitivity

Middle TX Frequency (MHz)	5200.000
Relative permitivity (real part)	36.112
Relative permitivity (imaginary part)	16.342
Conductivity (S/m)	4.512

C. SAR Surface and Volume

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-1.00, Y=-1.00 ; SAR Peak: 19.59 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	2.269
SAR 1g (W/Kg)	7.225
Variation (%)	-2.120
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	54.495478

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	18.669	11.483	6.258	3.517	1.950	1.092	0.609	0.346	0.188	0.097	0.060	0.036

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



F. 3D Image

3D screen shot	Hot spot position
	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

System Performance Check Data (5600 MHz)

System check at 5600 MHz

Date of measurement: 15/6/2026

A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	0.99
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5600
Channels/Frequency	Middle
Signal	CW

B. Permitivity

Middle TX Frequency (MHz)	5600.000
Relative permitivity (real part)	35.531
Relative permitivity (imaginary part)	16.868
Conductivity (S/m)	5.142

C. SAR Surface and Volume

SURFACE SAR	VOLUME SAR
	

Maximum location: X=0.00, Y=0.00 ; SAR Peak: 26.28 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	2.446
SAR 1g (W/Kg)	8.173
Variation (%)	-1.500
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	52.395582

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	24.539	14.763	7.735	4.111	2.174	1.163	0.614	0.325	0.169	0.087	0.051	0.021

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



F. 3D Image

3D screen shot	Hot spot position
	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

System Performance Check Data (5800 MHz)

System check at 5800 MHz

Date of measurement: 16/6/2026

A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.10
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels/Frequency	Middle
Signal	CW

B. Permitivity

Middle TX Frequency (MHz)	5800.000
Relative permitivity (real part)	35.361
Relative permitivity (imaginary part)	16.225
Conductivity (S/m)	5.321

C. SAR Surface and Volume

SURFACE SAR	VOLUME SAR
	

Maximum location: X=0.00, Y=0.00 ; SAR Peak: 25.04 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	2.282
SAR 1g (W/Kg)	7.709
Variation (%)	-1.220
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	51.597934

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	23.451	13.966	7.206	3.697	1.920	0.976	0.514	0.240	0.138	0.076	0.022	0.021

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



F. 3D Image

3D screen shot	Hot spot position
	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

ANNEX C Test Data

1-Body with back position in dist. 0mm on Channel 6 in IEEE 802.11b ISM

SAR Measurement at ISM (Body, Validation Plane)

Date of measurement: 12/6/2026

A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	ISM
Channels/Frequency	Middle (6)/ frequency 2437.000 Mhz
Signal	IEEE 802.11 b

B. Permitivity

Middle TX Frequency (MHz)	2437.000
Relative permitivity (real part)	39.537
Relative permitivity (imaginary part)	13.305
Conductivity (S/m)	1.728

C. SAR Surface and Volume

SURFACE SAR	VOLUME SAR
	

Maximum location: X=1.00, Y=-32.00 ; SAR Peak: 1.26 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.266
SAR 1g (W/Kg)	0.634
Variation (%)	-1.390
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	43.057344

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.251	0.685	0.295	0.130	0.063	0.028	0.012

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



F. 3D Image

3D screen shot	Hot spot position
	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

2-Body with back position in dist. 0mm on Channel 46 in IEEE 802.11n U-NII

SAR Measurement at U-NII-1 (Body, Validation Plane)

Date of measurement: 13/6/2026

A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.16
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-1
Channels/Frequency	Middle (46)/ frequency 5230.000 Mhz
Signal	IEEE 802.11 n

B. Permitivity

Middle TX Frequency (MHz)	5230.000
Relative permitivity (real part)	36.039
Relative permitivity (imaginary part)	16.386
Conductivity (S/m)	4.574

C. SAR Surface and Volume

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-17.00, Y=-15.00 ; SAR Peak: 0.86 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.053
SAR 1g (W/Kg)	0.215
Variation (%)	-2.260
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	68.215796

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.714	0.424	0.205	0.114	0.054	0.047	0.018	0.009	0.005	0.008	0.006	0.005

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



F. 3D Image

3D screen shot	Hot spot position
	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

3-Body with back position in dist. 0mm on Channel 52 in IEEE 802.11ac U-NII

SAR Measurement at U-NII-2a (Body, Validation Plane)

Date of measurement: 13/6/2026

A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-2a
Channels/Frequency	Lower (52)/ frequency 5260.000 Mhz
Signal	IEEE 802.11 ac

B. Permitivity

Middle TX Frequency (MHz)	5260.000
Relative permitivity (real part)	35.968
Relative permitivity (imaginary part)	16.430
Conductivity (S/m)	4.637

C. SAR Surface and Volume

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-16.00, Y=-10.00 ; SAR Peak: 2.16 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.127
SAR 1g (W/Kg)	0.560
Variation (%)	2.840
Horizontal validation criteria: minimum distance (mm)	15.656854
Vertical validation criteria: SAR ratio M2/M1 (%)	52.103926

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	1.975	1.184	0.617	0.326	0.162	0.084	0.042	0.023	0.012	0.006	0.006	0.005

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



F. 3D Image

3D screen shot	Hot spot position
	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

4-Body with back position in dist. 0mm on Channel 100 in IEEE 802.11a U-NII

SAR Measurement at U-NII-2c (Body, Validation Plane)

Date of measurement: 15/6/2026

A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	0.99
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-2c
Channels/Frequency	Lower (100)/ frequency 5500.000 Mhz
Signal	IEEE 802.11 a

B. Permitivity

Middle TX Frequency (MHz)	5500.000
Relative permitivity (real part)	35.584
Relative permitivity (imaginary part)	16.752
Conductivity (S/m)	5.038

C. SAR Surface and Volume

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-24.00, Y=-7.00 ; SAR Peak: 3.81 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.197
SAR 1g (W/Kg)	0.954
Variation (%)	3.500
Horizontal validation criteria: minimum distance (mm)	8.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	54.916386

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	3.184	1.956	1.074	0.601	0.300	0.155	0.088	0.043	0.024	0.016	0.010	0.010

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



F. 3D Image

3D screen shot	Hot spot position
	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

5-Body with back position in dist. 0mm on Channel 157 in IEEE 802.11ac U-NII

SAR Measurement at U-NII-3 (Body, Validation Plane)

Date of measurement: 16/6/2026

A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.10
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-3
Channels/Frequency	Higher (165)/ frequency 5825.000 Mhz
Signal	IEEE 802.11 ac

B. Permitivity

Middle TX Frequency (MHz)	5825.000
Relative permitivity (real part)	35.340
Relative permitivity (imaginary part)	16.145
Conductivity (S/m)	5.343

C. SAR Surface and Volume

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-9.00, Y=-25.00 ; SAR Peak: 3.65 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.196
SAR 1g (W/Kg)	0.839
Variation (%)	3.600
Horizontal validation criteria: minimum distance (mm)	16.000000
Vertical validation criteria: SAR ratio M2/M1 (%)	66.530836

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	3.364	1.935	0.900	0.434	0.199	0.095	0.041	0.025	0.012	0.007	0.012	0.007

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



F. 3D Image

3D screen shot	Hot spot position
	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

6-Body with back position in dist. 0mm on Channel 0 in Bluetooth

SAR Measurement at Bluetooth (Body, Validation Plane)

Date of measurement: 12/6/2026

A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5.0mm,Complete
Phantom	Validation plane
Device Position	Body
Band	Bluetooth
Channels/Frequency	Lower (0)/ frequency 2402.000 Mhz
Signal	Bluetooth

B. Permitivity

Middle TX Frequency (MHz)	2402.000
Relative permitivity (real part)	39.571
Relative permitivity (imaginary part)	13.312
Conductivity (S/m)	1.718

C. SAR Surface and Volume

SURFACE SAR	VOLUME SAR
	

Maximum location: X=-9.00, Y=-33.00 ; SAR Peak: 0.16 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.032
SAR 1g (W/Kg)	0.079
Variation (%)	3.630
Horizontal validation criteria: minimum distance (mm)	11.313708
Vertical validation criteria: SAR ratio M2/M1 (%)	43.148468

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.152	0.085	0.036	0.017	0.007	0.001	0.002

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China



F. 3D Image

3D screen shot	Hot spot position
	

Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.
Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

ANNEX D SAR Test Setup Photos

Reference Photo: simulation liquid depth 15.9cm
Please refer to the document “ANNEX D SAR Test Setup Photos.pdf”.

ANNEX E EUT External and Internal Photos

Please refer to RF Report.

ANNEX F Calibration Information

Please refer to the document “Calibration.pdf”.

BTF Testing Lab (Shenzhen) Co., Ltd.

Plant 101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, Guangdong, China

www.btf-lab.com

--END OF REPORT--