

# FCC Test Report

**Report No.** : 1811C50127812501

---

**Applicant** : Alliance Sports Group., LP

---

**Address** : 700 Henrietta Creek Rd. Roanoke, TX 76262,  
United States

---

**Product Name** : POWER STATION 1600

---

**Report Date** : 2025-06-23

---



**Shenzhen Anbotek Compliance Laboratory Limited**



# Contents

|                                                 |    |
|-------------------------------------------------|----|
| 1. General Information .....                    | 5  |
| 1.1. Client Information .....                   | 5  |
| 1.2. Description of Device (EUT) .....          | 5  |
| 1.3. Auxiliary Equipment Used During Test ..... | 7  |
| 1.4. Description of Test Modes .....            | 7  |
| 1.5. Description Of Test Setup .....            | 8  |
| 1.6. Test Equipment List .....                  | 9  |
| 1.7. Measurement Uncertainty .....              | 10 |
| 1.8. Description of Test Facility .....         | 10 |
| 1.9. Disclaimer .....                           | 10 |
| 2. Summary of Test Results .....                | 11 |
| 3. Conducted Emission Test .....                | 12 |
| 3.1. Test Standard and Limit .....              | 12 |
| 3.2. Test Setup .....                           | 12 |
| 3.3. Test Procedure .....                       | 12 |
| 3.4. Test Data .....                            | 12 |
| 4. Radiation Spurious Emission Test .....       | 15 |
| 4.1. Test Standard and Limit .....              | 15 |
| 4.2. Test Setup .....                           | 15 |
| 4.3. Test Procedure .....                       | 16 |
| 4.4. Test Data .....                            | 16 |
| 5. 20dB Occupy Bandwidth Test .....             | 21 |
| 5.1. Test Standard and Limit .....              | 21 |
| 5.2. Test Setup .....                           | 21 |
| 5.3. Test Procedure .....                       | 21 |
| 5.4. Test Data .....                            | 21 |
| 6. Antenna Requirement .....                    | 23 |
| 6.1. Test Standard and Requirement .....        | 23 |
| 6.2. Antenna Connected Construction .....       | 23 |
| APPENDIX I -- TEST SETUP PHOTOGRAPH .....       | 24 |
| APPENDIX II -- EXTERNAL PHOTOGRAPH .....        | 24 |
| APPENDIX III -- INTERNAL PHOTOGRAPH .....       | 24 |

## TEST REPORT

Applicant : Alliance Sports Group., LP  
Manufacturer : IE POWER CO., LTD.  
Product Name : POWER STATION 1600  
Model No. : NP1600PS  
Trade Mark : N/A  
Rating(s) : Please refer to page 6

**Test Standard(s) : FCC Part15 Subpart C**

**Test Method(s) : ANSI C63.10: 2020**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt 2025-05-16

Date of Test 2025-05-16 to 2025-06-12

Prepared By



(Lene Chen)

Approved & Authorized Signer



(Hugo Chen)



Revision History

| Report Version | Description     | Issued Date |
|----------------|-----------------|-------------|
| R00            | Original Issue. | 2025-06-23  |
|                |                 |             |
|                |                 |             |

## 1. General Information

### 1.1. Client Information

|              |   |                                                                                                                                           |
|--------------|---|-------------------------------------------------------------------------------------------------------------------------------------------|
| Applicant    | : | Alliance Sports Group., LP                                                                                                                |
| Address      | : | 700 Henrietta Creek Rd. Roanoke, TX 76262, United States                                                                                  |
| Manufacturer | : | IE POWER CO., LTD.                                                                                                                        |
| Address      | : | 168 Samania Building, Room No. BS-002, Moo. 5, Bang Sao Thong Subdistrict, Bang Sao Thong District, Samut Prakan Province 10570, Thailand |
| Factory      | : | IE POWER CO., LTD.                                                                                                                        |
| Address      | : | 168 Samania Building, Room No. BS-002, Moo. 5, Bang Sao Thong Subdistrict, Bang Sao Thong District, Samut Prakan Province 10570, Thailand |

### 1.2. Description of Device (EUT)

|                                                                                                                                                                                              |   |                                                 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|-------------------------------------------------|
| Product Name                                                                                                                                                                                 | : | POWER STATION 1600                              |
| Model No.                                                                                                                                                                                    | : | NP1600PS                                        |
| Trade Mark                                                                                                                                                                                   | : | N/A                                             |
| Test Power Supply                                                                                                                                                                            | : | AC 120V/60Hz; DC 51.2V Battery inside           |
| Test Sample No.                                                                                                                                                                              | : | 1-2-1(Normal Sample), 1-2-2(Engineering Sample) |
| Adapter                                                                                                                                                                                      | : | N/A                                             |
| <b>RF Specification</b>                                                                                                                                                                      |   |                                                 |
| Operation Frequency                                                                                                                                                                          | : | 112-205kHz                                      |
| Modulation Type                                                                                                                                                                              | : | ASK                                             |
| Antenna Type                                                                                                                                                                                 | : | Inductive loop coil Antenna                     |
| <b>Remark:</b> 1) All of the RF specification are provided by customer. 2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. |   |                                                 |

Rating(s):

**NEBO** PINNACLE™ 1600  
POWER STATION

- Model: NP1600PS
- SKU: NEB-PST-0007
- Battery Energy: 1228.8Wh 51.2V
- Solar Input: 12-75VDC 25A 800W max
- AC Input: 100-130VAC/10A 60Hz, 1200W max
- Total AC and DC Input: 1200W max
- AC Socket(x4) Output: 120VAC 60Hz 1600W, Total: 1600W max
- USB-C(x2) Output: (5V/9V/12V/15V/20V)  $\approx$ 3A, 20V $\approx$ 5A 100W each port, Total: 200W
- USB-A(x2) Output: 5V $\approx$ 3A/9V $\approx$ 2A/12V $\approx$ 1.5A 18W each port, Total: 36W
- DC 5521(x2)+DC Power Socket 12V $\approx$ 10A, Total: 120W max
- LED lighting output: 5W max
- Wireless Output: 10W Total DC Output: 366W
- Total AC and DC Output: 1760W max
- Charge Temperature: 32-104°F (0-40°C)
- Discharge Temperature: 14-104°F (-10-40°C)
- Working Humidity: 10%-85%

3.06.04.0917

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.  
FCC ID: 2BASYNP1600PST

**CAUTION!**

- Risk of electric shock. Do not remove cover.
- No user serviceable parts inside. Refer servicing to qualified service personnel.
- Risk of Injury to persons. Do not use this product if the power cord or the battery cables are damaged in any way.
- This device is not intended for use in a commercial repair facility.

**WARNING!**

- Do not overcharge the internal battery. See Instruction Manual.
- Do not smoke, strike a match, or cause a spark in the vicinity of the power pack.
- Only charge the internal battery in a well ventilated area.
- Risk of Electric shock and risk of fire.

**DANGER!**

- This device is intended to be used indoors only. Do not use outdoors.

**MISE EN GARDE!**

- Risque de décharge électrique. Ne pas enlever le couvercle.
- Aucune des pièces à l'intérieur ne peut être réparée par l'utilisateur. L'entretien courant doit être effectué par un personnel d'entretien qualifié.
- Risque de blessure aux personnes. Ne pas utiliser ce produit si le cordon d'alimentation ou les câbles de batterie sont endommagés de quelque façon.
- Le dispositif n'est pas destiné à être utilisé dans un atelier de réparation commercial.

**AVERTISSEMENT!**

- Ne pas surcharger la batterie interne. Consulter le manuel d'utilisation.
- Il ne faut pas fumer, allumer une allumette ou produire des étincelles à proximité du bloc d'alimentation.
- Charger la batterie uniquement dans un endroit bien aéré.
- Risques de décharge électrique et d'incendie.

**DANGER!**

- Le dispositif est destiné à être utilisé à l'intérieur seulement. Ne pas l'utiliser à l'extérieur.



### 1.3. Auxiliary Equipment Used During Test

| Title                  | Manufacturer                       | Model No. | Serial No. |
|------------------------|------------------------------------|-----------|------------|
| Wireless charging load | Shenzhen Ouju Technology Co., Ltd. | CD2577    | /          |


### 1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.


| Pretest Modes | Descriptions                       |
|---------------|------------------------------------|
| TM1           | Charging + WPT Mode (10W 1% Load)  |
| TM2           | Charging + WPT Mode (10W 50% Load) |
| TM3           | Charging + WPT Mode (10W 99% Load) |
| TM4           | WPT Mode (10W 1% Load)             |
| TM5           | WPT Mode (10W 50% Load)            |
| TM6           | WPT Mode (10W 99% Load)            |
| TM7           | Standby Mode                       |

1.5. Description Of Test Setup

CE



RE



### 1.6. Test Equipment List

| Item | Equipment                                          | Manufacturer    | Model No.         | Serial No.       | Last Cal.  | Cal. Interval |
|------|----------------------------------------------------|-----------------|-------------------|------------------|------------|---------------|
| 1.   | L.I.S.N.<br>Artificial Mains<br>Network            | Rohde & Schwarz | ENV216            | 100055           | 2024-09-09 | 1 Year        |
| 2.   | Three Phase V-<br>type Artificial<br>Power Network | CYBERTEK        | EM5040DT          | E215040DT00<br>1 | 2025-01-13 | 1 Year        |
| 3.   | EMI Test Receiver                                  | Rohde & Schwarz | ESCI              | 100627           | 2025-01-13 | 1 Year        |
| 4.   | EMI Test Receiver                                  | Rohde & Schwarz | ESR26             | 101481           | 2025-01-14 | 1 Year        |
| 5.   | MXA Spectrum<br>Analysis                           | Agilent         | N9020A            | MY51170037       | 2024-09-09 | 1 Year        |
| 6.   | EMI Preamplifier                                   | SKET Electronic | LNPA-0118G-<br>45 | SKET-PA-002      | 2025-01-13 | 1 Year        |
| 7.   | Double Ridged<br>Horn Antenna                      | SCHWARZBECK     | BBHA 9120D        | 02555            | 2022-10-16 | 3 Year        |
| 8.   | Bilog Broadband<br>Antenna                         | Schwarzbeck     | VULB9163          | 345              | 2022-10-23 | 3 Year        |
| 9.   | Loop Antenna(9K-<br>30M)                           | Schwarzbeck     | FMZB1519B         | 00053            | 2024-09-12 | 1 Year        |
| 10.  | Horn Antenna                                       | A-INFO          | LB-180400-KF      | J211060628       | 2024-01-22 | 3 Year        |
| 11.  | Pre-amplifier                                      | SONOMA          | 310N              | 186860           | 2025-01-14 | 1 Year        |
| 12.  | EMI Test Software<br>EZ-EMC                        | SHURPLE         | N/A               | N/A              | N/A        | N/A           |
| 13.  | MXA Spectrum<br>Analysis                           | KEYSIGHT        | N9020A            | MY53280032       | 2024-09-09 | 1 Year        |
| 14.  | MXG RF Vector<br>Signal Generator                  | Agilent         | N5182A            | MY47420647       | 2025-02-21 | 1 Year        |
| 15.  | Signal Generator                                   | Agilent         | E4421B            | MY41000743       | 2025-02-21 | 1 Year        |
| 16.  | DC Power Supply                                    | IVYTECH         | IV3605            | 1804D360510      | 2024-09-09 | 1 Year        |
| 17.  | Constant<br>Temperature<br>Humidity Chamber        | ZHONGJIAN       | ZJ-KHWS80B        | N/A              | 2024-10-14 | 1 Year        |
| 18.  | Spectrum<br>Analyzer                               | Rohde & Schwarz | FSV40-N           | 102150           | 2025-04-25 | 1 Year        |

### 1.7. Measurement Uncertainty

| Parameter                                                                                                                                                                                                                       | Uncertainty                          |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
| Conducted emissions (AMN 150kHz~30MHz)                                                                                                                                                                                          | 3.2dB                                |
| Occupied Bandwidth                                                                                                                                                                                                              | 925Hz                                |
| Radiated spurious emissions (Below 30MHz)                                                                                                                                                                                       | 3.26dB                               |
| Radiated spurious emissions (30MHz~1GHz)                                                                                                                                                                                        | Horizontal: 3.70dB; Vertical: 4.42dB |
| The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032.<br>This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |                                      |

### 1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC-Registration No.: 279531

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 279531.

#### Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

### 1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.
7. The data in this report will be synchronized with the corresponding national market supervision and management departments and cross-border e-commerce platforms as required by regulatory agencies.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2. Summary of Test Results

| Standard Section | Test Item               | Result |
|------------------|-------------------------|--------|
| 15.203           | Antenna Requirement     | PASS   |
| 15.207           | Conducted Emission Test | PASS   |
| 15.205/15.209    | Spurious Emission       | PASS   |
| 15.215(c)        | 20dB Occupy Bandwidth   | PASS   |


Note: N/A” denotes test is not applicable in this Test Report

### 3. Conducted Emission Test

#### 3.1. Test Standard and Limit

| Test Standard                                                                                                                            | FCC Part15 Section 15.207 |                                |               |
|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|--------------------------------|---------------|
| Test Limit                                                                                                                               | Frequency                 | Maximum RF Line Voltage (dBuV) |               |
|                                                                                                                                          |                           | Quasi-peak Level               | Average Level |
|                                                                                                                                          | 150kHz~500kHz             | 66 ~ 56 *                      | 56 ~ 46 *     |
|                                                                                                                                          | 500kHz~5MHz               | 56                             | 46            |
|                                                                                                                                          | 5MHz~30MHz                | 60                             | 50            |
| <b>Remark:</b> (1) *Decreasing linearly with logarithm of the frequency.<br>(2) The lower limit shall apply at the transition frequency. |                           |                                |               |

#### 3.2. Test Setup



#### 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


#### 3.4. Test Data

##### PASS

During the test, pre-scan all modes, only the worst case is recorded in the report.  
Please to see the following pages.

**Conducted Emission Test Data**

Test Site: 1# Shielded Room  
Operating Condition: TM1  
Test Specification: AC 120V/60Hz  
Comment: Live Line  
Temp.(°C)/Hum.(%RH): 24.6°C/59%RH




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1   | 0.1580      | 47.72          | 8.07        | 55.79         | 65.56        | -9.77           | QP       |        |
| 2   | 0.1620      | 42.68          | 8.07        | 50.75         | 55.36        | -4.61           | AVG      |        |
| 3   | 0.3140      | 44.45          | 8.09        | 52.54         | 59.86        | -7.32           | QP       |        |
| 4   | 0.3140      | 36.11          | 8.09        | 44.20         | 49.86        | -5.66           | AVG      |        |
| 5   | 0.5580      | 40.72          | 8.11        | 48.83         | 56.00        | -7.17           | QP       |        |
| 6   | 0.5660      | 31.83          | 8.10        | 39.93         | 46.00        | -6.07           | AVG      |        |
| 7   | 1.3180      | 28.68          | 8.08        | 36.76         | 46.00        | -9.24           | AVG      |        |
| 8   | 1.3900      | 38.73          | 8.08        | 46.81         | 56.00        | -9.19           | QP       |        |
| 9   | 1.6260      | 24.58          | 8.07        | 32.65         | 46.00        | -13.35          | AVG      |        |
| 10  | 1.6980      | 34.24          | 8.07        | 42.31         | 56.00        | -13.69          | QP       |        |
| 11  | 1.9260      | 22.38          | 8.05        | 30.43         | 46.00        | -15.57          | AVG      |        |
| 12  | 2.0820      | 31.53          | 8.05        | 39.58         | 56.00        | -16.42          | QP       |        |

Note: Result = Reading + Factor    Over Limit = Result - Limit



### Conducted Emission Test Data

Test Site: 1# Shielded Room  
Operating Condition: TM1  
Test Specification: AC 120V/60Hz  
Comment: Neutral Line  
Temp.(°C)/Hum.(%RH): 24.6°C/59%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1   | 0.1580      | 41.55          | 8.07        | 49.62         | 55.56        | -5.94           | AVG      |        |
| 2   | 0.1620      | 47.23          | 8.07        | 55.30         | 65.36        | -10.06          | QP       |        |
| 3   | 0.3020      | 45.13          | 8.09        | 53.22         | 60.19        | -6.97           | QP       |        |
| 4   | 0.3140      | 34.61          | 8.09        | 42.70         | 49.86        | -7.16           | AVG      |        |
| 5   | 0.5940      | 40.53          | 8.10        | 48.63         | 56.00        | -7.37           | QP       |        |
| 6   | 0.6060      | 31.31          | 8.10        | 39.41         | 46.00        | -6.59           | AVG      |        |
| 7   | 1.0500      | 38.87          | 8.10        | 46.97         | 56.00        | -9.03           | QP       |        |
| 8   | 1.3540      | 37.20          | 8.08        | 45.28         | 56.00        | -10.72          | QP       |        |
| 9   | 1.3540      | 28.41          | 8.08        | 36.49         | 46.00        | -9.51           | AVG      |        |
| 10  | 1.6900      | 34.11          | 8.07        | 42.18         | 56.00        | -13.82          | QP       |        |
| 11  | 1.7260      | 23.58          | 8.07        | 31.65         | 46.00        | -14.35          | AVG      |        |
| 12  | 29.3300     | 27.45          | 8.13        | 35.58         | 50.00        | -14.42          | AVG      |        |

Note: Result = Reading + Factor    Over Limit = Result - Limit

## 4. Radiation Spurious Emission Test

### 4.1. Test Standard and Limit

| Test Standard | FCC Part15 C Section 15.209 and 15.205 |                                  |                |            |                          |
|---------------|----------------------------------------|----------------------------------|----------------|------------|--------------------------|
| Test Limit    | Frequency (MHz)                        | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark     | Measurement distance (m) |
|               | 0.009MHz~0.490MHz                      | 2400/F(kHz)                      | -              | -          | 300                      |
|               | 0.490MHz-1.705MHz                      | 24000/F(kHz)                     | -              | -          | 30                       |
|               | 1.705MHz-30MHz                         | 30                               | -              | -          | 30                       |
|               | 30MHz~88MHz                            | 100                              | 40.0           | Quasi-peak | 3                        |
|               | 88MHz~216MHz                           | 150                              | 43.5           | Quasi-peak | 3                        |
|               | 216MHz~960MHz                          | 200                              | 46.0           | Quasi-peak | 3                        |
|               | 960MHz~1000MHz                         | 500                              | 54.0           | Quasi-peak | 3                        |
|               | Above 1000MHz                          | 500                              | 54.0           | Average    | 3                        |
|               |                                        | -                                | 74.0           | Peak       | 3                        |

**Remark:**

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

### 4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz

### 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

### 4.4. Test Data


#### PASS

During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.

**Test Results (Between 9KHz – 150KHz)**

Test Mode: TM4  
Distance: 3m  
Power Source: DC 51.2V Battery inside  
Polarization: Coplane  
Temp.(°C)/Hum.(%RH): 25.1°C/49%RH  
Fundamental




| No. | Freq. (MHz) | Reading (dBuV) | Factor ( ) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|------------|-----------------|----------------|-----------------|----------|--------|
| 1   | 0.1190      | 37.45          | 20.34      | 57.79           | 105.34         | -47.55          | peak     |        |
| 2   | 0.0777      | 18.74          | 20.36      | 39.10           | 109.70         | -70.60          | peak     |        |
| 3   | 0.0240      | 24.60          | 20.38      | 44.98           | 119.84         | -74.86          | peak     |        |
| 4   | 0.0480      | 11.86          | 20.42      | 32.28           | 113.86         | -81.58          | peak     |        |
| 5   | 0.0320      | 14.81          | 20.56      | 35.37           | 117.36         | -81.99          | peak     |        |
| 6   | 0.0111      | 10.11          | 20.07      | 30.18           | 126.50         | -96.32          | peak     |        |

Note: Result = Reading + Factor      Over Limit = Result - Limit

**Test Results (Between 0.15MHz – 30MHz)**

Test Mode: TM4  
Distance: 3m  
Power Source: DC 51.2V Battery inside  
Polarization: Coplane  
Temp.(°C)/Hum.(%RH): 25.1°C/49%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor ( ) | Result (dBuV/m) | Limit (dBuV/m) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|------------|-----------------|----------------|-----------------|----------|--------|
| 1   | 0.1565      | 22.34          | 20.33      | 42.67           | 103.65         | -60.98          | peak     |        |
| 2   | 0.2341      | 17.88          | 20.31      | 38.19           | 100.18         | -61.99          | peak     |        |
| 3   | 0.3933      | 12.38          | 20.28      | 32.66           | 95.70          | -63.04          | peak     |        |
| 4   | 3.2411      | 9.77           | 20.33      | 30.10           | 69.50          | -39.40          | peak     |        |
| 5   | 10.1791     | 2.04           | 20.51      | 22.55           | 69.50          | -46.95          | peak     |        |
| 6   | 14.4404     | 3.29           | 20.54      | 23.83           | 69.50          | -45.67          | peak     |        |

Note: Result = Reading + Factor      Over Limit = Result - Limit

**Remark:** According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Results (Between 30MHz –1000 MHz)

Test Mode:

TM4

Distance:

3m

Power Source:


DC 51.2V Battery inside

Polarization:

Horizontal


Temp.(°C)/Hum.(%RH):

24.4°C/48%RH



Note:                Result = Reading + Factor      Over Limit = Result - Limit

Test Mode: TM4  
Distance: 3m  
Power Source: DC 51.2V Battery inside  
Polarization: Vertical  
Temp.(°C)/Hum.(%RH): 24.4°C/48%RH




Note: Result = Reading + Factor      Over Limit = Result - Limit

## 5. 20dB Occupy Bandwidth Test

### 5.1. Test Standard and Limit

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Standard | FCC Part15 C Section 15.215(c)                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Test Limit    | Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. |

### 5.2. Test Setup




### 5.3. Test Procedure

The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=1%-5%OBW, VBW≥3\*RBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

### 5.4. Test Data

|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 24.3 °C | Humidity: | 51 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|

| Freq.<br>(MHz) | Bandwidth (kHz) | Results |
|----------------|-----------------|---------|
| 0.1190         | 0.812           | PASS    |



Note: The measured signal is Cw-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

## 6. Antenna Requirement

### 6.1. Test Standard and Requirement

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Standard | FCC Part15 Section 15.203                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Requirement   | 1) 15.203 requirement:<br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |

### 6.2. Antenna Connected Construction

The antenna is a Inductive loop coil Antenna which permanently attached. It complies with the standard requirement.

## **APPENDIX I -- TEST SETUP PHOTOGRAPH**

Please refer to separated files Appendix I -- Test Setup Photograph\_RF

## **APPENDIX II -- EXTERNAL PHOTOGRAPH**

Please refer to separated files Appendix II -- External Photograph

## **APPENDIX III -- INTERNAL PHOTOGRAPH**

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----