TEST REPORT

Applicant Name :	Shenzhen Wanghe Technology Co., Ltd
Address :	Rm105, Buliding 3, 1970 Technology Park, Minzhi Community, Longhua District, Shenzhen, China
Report Number :	RA230404-16953E-RF
FCC ID:	2BAUG-FWG-01

Test Standard (s)
FCC PART 15.247

Sample Description

Product Type:	Bluetooth Earphone
Model No.:	FWG-01
Trade Mark:	N/A
Date Received:	2023-04-04
Date of Test:	2023-04-11 to 2023-04-28
Report Date:	2023-04-28

Test Result:	Pass*

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Dave Liang

Dave Liang
EMC Engineer

Approved By:

Candy. Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".
Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY **4**

GENERAL INFORMATION **5**

PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 5
OBJECTIVE 5
TEST METHODOLOGY 5
MEASUREMENT UNCERTAINTY 6
TEST FACILITY 6

SYSTEM TEST CONFIGURATION **7**

DESCRIPTION OF TEST CONFIGURATION 7
EUT EXERCISE SOFTWARE 7
SPECIAL ACCESSORIES 7
EQUIPMENT MODIFICATIONS 7
SUPPORT EQUIPMENT LIST AND DETAILS 7
BLOCK DIAGRAM OF TEST SETUP 8

SUMMARY OF TEST RESULTS **9**

TEST EQUIPMENT LIST **10**

FCC §1.1307 (b) & §2.1093 – RF EXPOSURE **11**

TEST RESULT 11

FCC §15.203 – ANTENNA REQUIREMENT **12**

APPLICABLE STANDARD 12
ANTENNA CONNECTOR CONSTRUCTION 12

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS **13**

APPLICABLE STANDARD 13
EUT SETUP 13
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP 14
TEST PROCEDURE 14
FACTOR & MARGIN CALCULATION 14
TEST DATA 14

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST **20**

APPLICABLE STANDARD 20
TEST PROCEDURE 20
TEST DATA 20

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH **23**

APPLICABLE STANDARD 23
TEST PROCEDURE 23
TEST DATA 24

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST **34**

APPLICABLE STANDARD 34
TEST PROCEDURE 34
TEST DATA 34

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME) **37**

APPLICABLE STANDARD 37
TEST PROCEDURE 37
TEST DATA 37

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT **47**

APPLICABLE STANDARD 47
TEST PROCEDURE 47

TEST DATA 47

FCC §15.247(d) - BAND EDGES TESTING 53

APPLICABLE STANDARD 53
TEST PROCEDURE 53
TEST DATA 53

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230404-16953E-RF	Original Report	2023-04-28

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product Type	Bluetooth Earphone
Tested Model	FWG-01
Multiple Model	FWG-XX (XX is from 02 to 89); BSH380,BSH382,BSH383,BSH384,BSH385,BSH-336,BSH-333, BSH-330, BSH-116,BSH-360,BSH-370,BSH-650,BSH-350; N20, N21,N22,N23,N25,BTM22,BTM26,BTM25
Model Difference	Please refer to DOS Letter
Frequency Range	Bluetooth:2402-2480MHz
Maximum conducted Peak output power	3.26dBm
Modulation Technique	BDR(GFSK)/EDR(π/4-DQPSK)/EDR(8DPSK)
Antenna Specification*	Internal Antenna: 2.98dBi(provided by the applicant)
Voltage Range	DC5V from USB port or 3.7V from battery
Sample number	RA230404-16953E-RF-S1(CE&RE) RA230404-16953E-RF-S2(RF Conducted Test) (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		$0.082*10^{-7}$
RF output power, conducted		0.71dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.92dB
Emissions, Radiated	30MHz - 1GHz	5.08dB
	1GHz - 18GHz	4.96dB
	18GHz - 26.5GHz	5.16dB
Temperature		1℃
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189.

Accredited by American Association for Laboratory Accreditation (A2LA). The Certificate Number is 4297.01

Listed by Innovation, Science and Economic Development Canada (ISEDC), the Registration Number is 30241.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

Software “Blue Test3*” was used during testing and the power level was default*.

Special Accessories

N/A.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length(m)	From/Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emission:

Below 1GHz:



Note: the table edge aligned with the center of turntable.

Above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth & 99% Occupied Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

Not Applicable: the device was powered by battery when use Bluetooth.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emissions Test					
Rohde & Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-194	2023/02/14	2026/02/13
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/18G-10SS	5	2022/11/25	2023/11/24
Wainwright	Band Reject Filter	WRCG2400/2485-2375/2510-60/11SS	10	2022/11/25	2023/11/24
Radiated Emission Test Software: e3 191218 (V9)					
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2022/11/25	2023/11/24
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2022/11/25	2023/11/24
WEINSCHEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.33	RF-03	Each time	

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 (b) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.3.1-SAR-Based Exemption:

A more comprehensive exemption, considering a variable power threshold that depends on both the separation distance and power, is provided in § 1.1307(b)(3)(i)(B). This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions.

Accordingly, a RF source is considered an RF exempt device if its available maximum time-averaged (matched conducted) power or its effective radiated power (ERP), whichever is greater, are below a specified threshold. This exemption threshold was derived based on general population 1-g SAR requirements and is detailed in Appendix C.

Test Result

For worst case:

Mode	Frequency	Maximum Tune-up Conducted Power	Antenna Gain		ERP	Distance	SAR-Based Exclusion Threshold		SAR-Based Exclusion
	(MHz)	(dBm)	(dBi)	(dBd)	(dBm)	(mm)	(mW)	(dBm)	
BDR/EDR	2402-2480	3.5	2.98	0.83	4.33	5	2.717	4.34	Yes

Note 1: The tune-up power was declared by the applicant.
Note 2: 0dBd=2.15dBi.

Result: Compliant.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 2.98dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK

For average measurement:

Use the duty cycle factor correction factor method per 15.35(c).
Duty cycle=On time/100milliseconds, On time=N1*L1+N2*L2+…Nn-1*Ln-1+Nn*Ln,
Where N1 is number of type 1 pulses, L1 is length of type 1 pulse, etc.
Average Emission Level=Peak Emission Level+20*log(Duty cycle)

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value complies with the limit, then it is unnecessary to perform an QP/Average measurement

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

Factor = Antenna Factor + Cable Loss - Amplifier Gain

The "**Over Limit/Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

Over Limit/Margin = Level / Corrected Amplitude – Limit
Level / Corrected Amplitude = Read Level + Factor

Test Data

Environmental Conditions

Temperature:	24℃
Relative Humidity:	57%
ATM Pressure:	101kPa

The testing was performed by Jason Liu on 2023-04-11.

EUT operation mode: Transmitting

(Scan with GFSK, π/4-DQPSK, 8DPSK mode at X axis, Y axis, Z axis, the worst case is 8DPSK Mode at Y axis)

Below 1GHz:

Worst case for 8DPSK, High Channel:

Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : RA230404-16953E-RF
Test Mode: BT Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	30.584	-14.35	35.13	20.78	40.00	-19.22	Peak
2	80.046	-13.19	32.75	19.56	40.00	-20.44	Peak
3	122.404	-10.92	35.12	24.20	43.50	-19.30	Peak
4	184.167	-10.29	38.16	27.87	43.50	-15.63	Peak
5	380.081	-11.14	34.60	23.46	46.00	-22.54	Peak
6	683.546	-7.43	32.05	24.62	46.00	-21.38	Peak

Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : RA230404-16953E-RF
Test Mode: BT Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	34.760	-14.44	44.97	30.53	40.00	-9.47	Peak
2	64.348	-13.75	40.65	26.90	40.00	-13.10	Peak
3	80.010	-13.19	40.88	27.69	40.00	-12.31	Peak
4	184.328	-10.29	37.13	26.84	43.50	-16.66	Peak
5	380.081	-11.14	32.06	20.92	46.00	-25.08	Peak
6	892.291	-1.11	29.50	28.39	46.00	-17.61	Peak

Above 1GHz: (worst case for 8DPSK)

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Reading (dBuV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel									
2310	47.57	PK	103	1.8	H	-10.36	37.21	74	-36.79
2310	47.98	PK	233	2.0	V	-10.36	37.62	74	-36.38
2390	48.47	PK	343	2.1	H	-10.71	37.76	74	-36.24
2390	51.87	PK	320	1.1	V	-10.71	41.16	74	-32.84
4804	54.68	PK	306	1.6	H	-6.11	48.57	74	-25.43
4804	53.12	PK	170	1.9	V	-6.11	47.01	74	-26.99
Middle Channel									
4882	53.42	PK	26	2.0	H	-5.9	47.52	74	-26.48
4882	53.68	PK	307	2.2	V	-5.9	47.78	74	-26.22
High Channel									
2483.5	47.51	PK	257	1.8	H	-10.55	36.96	74	-37.04
2483.5	48	PK	9	2.0	V	-10.55	37.45	74	-36.55
2500	46.43	PK	177	1.3	H	-10.42	36.01	74	-37.99
2500	46.93	PK	13	1.9	V	-10.42	36.51	74	-37.49
4960	52.25	PK	301	2.0	H	-5.47	46.78	74	-27.22
4960	53.98	PK	353	1.4	V	-5.47	48.51	74	-25.49

Note:
Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Factor + Reading
Margin = Corrected Amplitude – Limit
The other spurious emission which is in the noise floor level was not recorded.
For above 1GHz, when the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, just peak value was recorded

1 GHz - 18 GHz: (Pre-Scan plots)

Worst case for 8DPSK, Low Channel:

Horizontal



Vertical



18-25GHz: (Pre-Scan plots)

Worst case for 8DPSK, Low Channel:

Horizontal



Vertical



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

According to ANSI C63.10-2013, section 7.8.2

1. Set the EUT in TX mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.



Test Data

Environmental Conditions

Temperature:	24℃
Relative Humidity:	49%
ATM Pressure:	101kPa

The testing was performed by Dave Liang on 2023-04-15.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Mode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	0.994	≥0.514	PASS
2DH5	Ant1	Hop	0.948	≥0.750	PASS
3DH5	Ant1	Hop	1	≥0.854	PASS

Note: The limit = (2/3) * 20dB bandwidth

Please refer to the below plots:

DH5_Ant1_Hop

2DH5_Ant1_Hop



3DH5_Ant1_Hop



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

According to ANSI C63.10-2013, section 7.8.7 and section 6.9.2

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:
• The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

• The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.

• The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not TX continuously.

• The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.
For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



Test Data

Environmental Conditions

Temperature:	24℃
Relative Humidity:	49%
ATM Pressure:	101kPa

The testing was performed by Dave Liang on 2023-04-15.

.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Mode	Antenna	Channel	20db EBW[MHz]	OCB [MHz]	Verdict
DH5	Ant1	2402	0.720	0.782	PASS
		2441	0.711	0.779	PASS
		2480	0.771	0.776	PASS
2DH5	Ant1	2402	1.125	1.091	PASS
		2441	1.125	1.088	PASS
		2480	1.122	1.091	PASS
3DH5	Ant1	2402	1.281	1.175	PASS
		2441	1.278	1.175	PASS
		2480	1.278	1.175	PASS

Please refer to the below plots:

20 dB EMISSION BANDWIDTH_DH5_Ant1_2402

Date: 15.APR.2023 11:10:18

99% OCCUPIED BANDWIDTH_DH5 _Ant1_2402

Date: 15.APR.2023 11:10:20

20 dB EMISSION BANDWIDTH_DH5 _Ant1_2441



99% OCCUPIED BANDWIDTH_DH5 _Ant1_2441



20 dB EMISSION BANDWIDTH_DH5 _Ant1_2480



Date: 15.APR.2023 11:11:56

99% OCCUPIED BANDWIDTH_DH5 _Ant1_2480

Date: 15.APR.2023 11:12:01

20 dB EMISSION BANDWIDTH_2DH5 _Ant1_2402



99% OCCUPIED BANDWIDTH_2DH5 _Ant1_2402



20 dB EMISSION BANDWIDTH_2DH5 _Ant1_2441



99% OCCUPIED BANDWIDTH_2DH5 _Ant1_2441



20 dB EMISSION BANDWIDTH _2DH5_Ant1_2480



99% OCCUPIED BANDWIDTH _2DH5_Ant1_2480



20 dB EMISSION BANDWIDTH _3DH5_Ant1_2402



Date: 15.APR.2023 11:15:15

99% OCCUPIED BANDWIDTH _3DH5_Ant1_2402

Date: 15.APR.2023 11:15:21

20 dB EMISSION BANDWIDTH _3DH5_Ant1_2441



Date: 15.APR.2023 11:16:06

99% OCCUPIED BANDWIDTH _3DH5_Ant1_2441



Date: 15.APR.2023 11:16:11

20 dB EMISSION BANDWIDTH _3DH5_Ant1_2480



99% OCCUPIED BANDWIDTH _3DH5_Ant1_2480



FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

According to ANSI C63.10-2013, section 7.8.3

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

2. Set the EUT in hopping mode from first channel to last.

3. By using the max-hold function record the quantity of the channel.



Test Data

Environmental Conditions

Temperature:	24℃
Relative Humidity:	49%
ATM Pressure:	101kPa

The testing was performed by Dave Liang on 2023-04-15.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Mode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	>=15	PASS
2DH5	Ant1	Hop	79	>=15	PASS
3DH5	Ant1	Hop	79	>=15	PASS

Please refer to the below plots:

DH5_Ant1_Hop



2DH5_Ant1_Hop



3DH5_Ant1_Hop



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

According to ANSI C63.10-2013, section 7.8.4

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW ≥ 3×RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses



Test Data

Environmental Conditions

Temperature:	24℃
Relative Humidity:	50%
ATM Pressure:	101kPa

The testing was performed by Dave Liang on 2023-04-17.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Mode	Antenna	Channel	Burst Width [ms]	Total Hops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.408	330	0.135	<=0.4	PASS
DH3	Ant1	Hop	1.656	200	0.331	<=0.4	PASS
DH5	Ant1	Hop	2.897	100	0.29	<=0.4	PASS
2DH1	Ant1	Hop	0.418	320	0.134	<=0.4	PASS
2DH3	Ant1	Hop	1.661	150	0.249	<=0.4	PASS
2DH5	Ant1	Hop	2.902	90	0.261	<=0.4	PASS
3DH1	Ant1	Hop	0.419	320	0.134	<=0.4	PASS
3DH3	Ant1	Hop	1.661	130	0.216	<=0.4	PASS
3DH5	Ant1	Hop	2.904	110	0.319	<=0.4	PASS

Note 1: A period time=0.4*79=31.6(s), Result=Burst Width*Total Hops
Note 2: Total Hops =Hopping Number in 3.16s*10
Note 3: Hoping Number in 3.16s=Total of highest signals in 3.16s (Second high signals were other channel)

DH1_Ant1_Hop



Date: 17.APR.2023 16:35:20



Date: 17.APR.2023 16:35:25

DH3_Ant1_Hop



Date: 17.APR.2023 16:35:54



Date: 17.APR.2023 16:35:59

DH5_Ant1_Hop



Date: 17.APR.2023 16:40:30



Date: 17.APR.2023 16:40:35

2DH1_Ant1_Hop



Date: 17.APR.2023 16:37:03



Date: 17.APR.2023 16:37:08

2DH3_Ant1_Hop



Date: 17.APR.2023 16:41:03



Date: 17.APR.2023 16:41:14

2DH5_Ant1_Hop



Date: 17.APR.2023 16:36:30



Date: 17.APR.2023 16:36:35

3DH1_Ant1_Hop



Date: 17.APR.2023 16:38:27



Date: 17.APR.2023 16:38:38

3DH3_Ant1_Hop



Date: 17.APR.2023 16:39:07



Date: 17.APR.2023 16:39:12

3DH5_Ant1_Hop



Date: 17.APR.2023 16:37:48



Date: 17.APR.2023 16:38:00

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

According to ANSI C63.10-2013, section 7.8.5

1. Place the EUT on a bench and set in TX mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24℃
Relative Humidity:	49%
ATM Pressure:	101kPa

The testing was performed by Dave Liang on 2023-04-15.

EUT operation mode: Transmitting

Test Result: Compliant.

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	2402	-0.19	≤20.97	PASS
		2441	0.22	≤20.97	PASS
		2480	0.74	≤20.97	PASS
2DH5	Ant1	2402	1.5	≤20.97	PASS
		2441	1.91	≤20.97	PASS
		2480	2.41	≤20.97	PASS
3DH5	Ant1	2402	2.33	≤20.97	PASS
		2441	2.79	≤20.97	PASS
		2480	**3.26**	≤20.97	PASS

Please refer to the below plots:

DH5_Ant1_2402



Date: 15.APR.2023 11:31:00

DH5_Ant1_2441



Date: 15.APR.2023 11:31:19

DH5_Ant1_2480



Date: 15.APR.2023 11:00:58

2DH5_Ant1_2402



Date: 15.APR.2023 11:01:41

2DH5_Ant1_2441



Date: 15.APR.2023 11:02:17

2DH5_Ant1_2480



Date: 15.APR.2023 11:02:49

3DH5_Ant1_2402



Date: 15.APR.2023 11:03:30

3DH5_Ant1_2441



Date: 15.APR.2023 11:04:08

3DH5_Ant1_2480



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013, section 7.8.6 and section 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in TX mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	24℃
Relative Humidity:	49-51%
ATM Pressure:	101kPa

The testing was performed by Dave Liang on 2023-04-15 and 2023-04-28.

EUT operation mode: Transmitting

Test Result: Compliant

Please refer to the below plots:

DH5: Band Edge-Left Side
Hopping



Single



DH5: Band Edge- Right Side Hopping



Single



2DH5: Band Edge-Left Side
Hopping



Date: 15.APR.2023 11:07:25

Single



Date: 15.APR.2023 11:13:06

2DH5: Band Edge- Right Side
Hopping



Date: 15.APR.2023 11:27:45

Single



Date: 15.APR.2023 11:14:38

3DH5: Band Edge-Left Side
Hopping



Single



3DH5: Band Edge- Right Side
Hopping



Single



******* END OF REPORT *******