

RF EXPOSURE EVALUATION

FCC ID:2BAWT-S7

Applicant: Shenzhen Aibaofeng Electronic Technology Co., Ltd.
Address: 301 south of building B7, Xiufeng industrial city, BujiStreet, Longgang District, Shenzhen China

Manufacturer: Shenzhen Aibaofeng Electronic Technology Co., Ltd.
Address: 301 south of building B7, Xiufeng industrial city, BujiStreet, Longgang District, Shenzhen China

EUT: Car-mounted cooling wireless charging clamp arm holder

Trade Mark: N/A
Model Number: S7

Date of Receipt: Oct. 10, 2025

Test Date: Oct. 10, 2025 to Oct. 30, 2025

Date of Report: Oct. 30, 2025

Prepared By: Shenzhen DL Testing Technology Co., Ltd.
Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Roa Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China

Applicable Standards: FCC CFR Title 47 Part 15 Subpart C Section 15.231
ANSI C63.10:2020

Test Result: Pass

Report Number: DLE-250722020R

Prepared (Test Engineer): Dimon Tan

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.

Product Name:	Car-mounted cooling wireless charging clamp arm holder
Model No.:	S7
Serial No.:	N/A
Model Difference:	N/A
Operation Frequency:	115kHz-205kHz
Modulation Type:	ASK
Antenna Type:	Loop Coil Antenna
Power Supply:	Input: 5V $\overline{\text{---}}$ 3A, 9V $\overline{\text{---}}$ 3A Wireless charging output power: 15W/10W/7.5W/5W Battery: 3.7V, 150mAh, 0.555Wh
Battery Capacity:	N/A
Transmitting Mode:	Keep the EUT in continuously wireless charging mode
Date of Test:	Oct. 10, 2025 to Oct. 30, 2025
Date of issue:	Oct. 30, 2025

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Car-mounted cooling wireless charging clamp arm holder	N/A	S7	N/A	EUT
E-2	AC/DC Adapter	Aohai	A895-200150C-CN1	N/A	Auxiliary
E-3	Phone	APPLE	iPhone 13 Pro	N/A	Auxiliary

Test Modes:	Test Coil:	Description:
Mode 1	ANT 1	AC/DC Adapter (9V/3A) + EUT + Phone 15W (Battery Status: <1%)
Mode 2		AC/DC Adapter (9V/3A) + EUT + Phone 15W (Battery Status: 50%)
Mode 3		AC/DC Adapter (9V/3A) + EUT + Phone 15W (Battery Status: >98%)
Mode 4		AC/DC Adapter (5V/3A) + EUT + Phone 15W (Battery Status: <1%)
Mode 5		AC/DC Adapter (5V/3A) + EUT + Phone 15W (Battery Status: 50%)
Mode 6		AC/DC Adapter (5V/3A) + EUT + Phone 15W (Battery Status: >98%)
Mode 7		AC/DC Adapter (9V/3A) + EUT + Phone 10W (Battery Status: <1%)
Mode 8		AC/DC Adapter (9V/3A) + EUT + Phone 10W (Battery Status: 50%)
Mode 9		AC/DC Adapter (9V/3A) + EUT + Phone 10W (Battery Status: >98%)
Mode 10		AC/DC Adapter (5V/3A) + EUT + Phone 10W (Battery Status: <1%)
Mode 11		AC/DC Adapter (5V/3A) + EUT + Phone 10W (Battery Status: 50%)
Mode 12		AC/DC Adapter (5V/3A) + EUT + Phone 10W (Battery Status: >98%)
Mode 13		AC/DC Adapter (9V/3A) + EUT + Phone 7.5W (Battery Status: <1%)
Mode 14		AC/DC Adapter (9V/3A) + EUT + Phone 7.5W (Battery Status: 50%)
Mode 15		AC/DC Adapter (9V/3A) + EUT + Phone 7.5W (Battery Status: >98%)
Mode 16		AC/DC Adapter (5V/3A) + EUT + Phone 7.5W (Battery Status: <1%)
Mode 17		AC/DC Adapter (5V/3A) + EUT + Phone 7.5W (Battery Status: 50%)
Mode 18		AC/DC Adapter (5V/3A) + EUT + Phone 7.5W (Battery Status: >98%)
Mode 19		AC/DC Adapter (9V/3A) + EUT + Phone 5W (Battery Status: <1%)
Mode 20		AC/DC Adapter (9V/3A) + EUT + Phone 5W (Battery Status: 50%)
Mode 21		AC/DC Adapter (9V/3A) + EUT + Phone 5W (Battery Status: >98%)
Mode 22		AC/DC Adapter (5V/3A) + EUT + Phone 5W (Battery Status: <1%)
Mode 23		AC/DC Adapter (5V/3A) + EUT + Phone 5W (Battery Status: 50%)
Mode 24		AC/DC Adapter (5V/3A) + EUT + Phone 5W (Battery Status: >98%)

RF Exposure Evaluation

1 Measuring Standard

1.1 According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to §1.1310 and §2.1091 RF exposure is calculated. According KDB680106 D01: KDB 680106 D01 Wireless Power Transfer v04.

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainly
1	H-filed	$\pm 0.93\text{dB}$
2	E-filed	$\pm 0.51\text{dB}$

2.1 Requirements

The EUT does comply with item 5 (b) of KDB 680106 D01 V04:

1) The power transfer frequency is below 1 MHz.

Yes, the device operate in the frequency range from Phone / Earbuds Coil: 115kHz to 205kHz;

2) The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.

Yes, the maximum output power of the primary coil is 15W.

3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact).

Yes, the surfaces of the transmitter and client device enclosures are in physical contact.

4) Only § 2.1091-Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions)..

Yes, the EUT is a Mobile Wireless Charger.

5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1.

Yes, the EUT field strength levels are less 50% * MPE limit.

6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions.

Yes, the EUT has a coil, all test modes met the conditions specified in (5).

2.2 Limits


The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE):

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
*=Plane-wave equivalent power density
RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

2.3 Test Setup



3 Test Procedure

- 1) The RF exposure test was performed on 360 degree turn table in anechoic chamber.
- 2) The measurement probe was placed at test distance (20 cm and above from all sides and Top) which is between the edge of the charger and the geometric centre of probe.
- 3) The turn table was rotated 360 degree to search of highest strength.
- 4) The highest emission level was recorded and compared with limit as soon as measurement of each points were completed.
- 5) The EUT were measured according to the dictates of KDB 680106 D01 V04.

4 Test Instruments list

Test Equipment	Manufacturer	Model No.	SN.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
Exposure Level Tester	Narda	ELT-400	180ZX10220	Nov. 16, 2025	Nov. 15, 2026
Magnetic field probe 100cm ²	Narda	ELT probe 100cm ²	M0675	Nov. 16, 2025	Nov. 15, 2026

5 Test Result

Mode 1:

H-Filed Strength at 20 cm from the edges surrounding the EUT (uT):

Battery Level:	Frequency Range (MHz)	Test Position Left	Test Position Right	Test Position Rear	Test Position Front	Test Position Top
<1% Battery	0.115-0.205	0.27	0.28	0.32	0.27	0.33
50% Battery	0.115-0.205	0.24	0.27	0.26	0.24	0.25
>98% Battery	0.115-0.205	0.22	0.26	0.24	0.23	0.24

H-Filed Strength at 20 cm from the edges surrounding the EUT (A/m)

Battery Level:	Frequency Range (MHz)	Test Position Left	Test Position Right	Test Position Rear	Test Position Front	Test Position Top	Limits 50% (A/m)	Limits (A/m)
<1% Battery	0.115-0.205	0.22	0.22	0.26	0.22	0.26	0.815	1.63
50% Battery	0.115-0.205	0.19	0.22	0.21	0.19	0.20	0.815	1.63
>98% Battery	0.115-0.205	0.18	0.21	0.19	0.18	0.19	0.815	1.63

Remark: $A/m = uT/1.25$

All modes have been tested, and the report only reflects the worst case data.

2 Test Set-up Photo

