

Label Location On EUT



DEENO GT	DEENO GT S1500	Model: PS151032S
Battery capacity: 1036.8Wh (36Ah/28.8V) Battery type: LiFePO4 Total output power: 1500W AC charging: 750W max AC input voltage: 100-120V~ 50Hz/60Hz, 15A Solar charging: 12V - 32V $\approx$ 8A, 200W max Car charging: 12V/24V $\approx$ 8A, 192W max AC output $\times$3: 1500W (peak 3000W), 120V~ 50Hz/60Hz USB-A $\times$3: 5V $\approx$ 3A, 9V $\approx$ 2A, 12V $\approx$ 1.5A (54W max for the simultaneous output of 3 ports) USB-C $\times$2: 5V, 9V, 12V, 15V $\approx$ 3A, 20V $\approx$ 5A (200W max for the simultaneous output of 2 ports) Car charging output $\times$1: 12V $\approx$ 10A (120W max) DC5.5$\times$2.1 $\times$1: 12V $\approx$ 5A (60W max) DC5.5$\times$2.5 $\times$1: 24V $\approx$ 5A (120W max) Wireless charging $\times$1: 5V $\approx$ 3A, 9V $\approx$ 1.67A (15W max) LED lighting power: 12W (four modes: 25% brightness, 50% brightness, 100% brightness, and SOS) Discharging ambient temperature: -20°C - 45°C (-4°F - 113°F) Charging ambient temperature: 0°C - 45°C (32°F - 113°F)		
CAUTION 1. This product is forbidden to be placed near heat sources, such as fire or heating oven. 2. This product is forbidden to touch any liquids. Do not use this product in the rain or in a humid environment. 3. Do not disassemble or pierce this product in any way. 4. Do not short-circuit this product with wires or other metal objects. 5. Do not stack any heavy objects on this product. 6. Do not forcibly block the fan during use, or place this product in an unventilated and dusty place.		
FC PS E CE RoHS UN38.3 REACH Shenzhen Dineng Technology Co., Ltd. Made in china		