

Test Report

Report No. : MTi250829003-0105E3
Date of issue : 2025-12-15
Applicant : Emlid Tech Kft.
Product : All-band RTK GNSS receiver
Model(s) : RRS-4P, RRS-4
FCC ID : 2BAYERCH4

Shenzhen Microtest Co., Ltd.

TEST REPORT



Report No.: MTi250829003-0105E3

Table of contents

1	General Description	4
1.1	Description of the EUT	4
1.2	Description of test modes	4
1.3	Environmental Conditions	6
1.4	Description of support units	6
1.5	Measurement uncertainty	6
2	Summary of Test Result	7
3	Test Facilities and accreditations	8
3.1	Test laboratory	8
4	List of test equipment	9
5	Evaluation Results (Evaluation)	11
5.1	Antenna requirement	11
6	Radio Spectrum Matter Test Results (RF)	12
6.1	Conducted Emission at AC power line	12
6.2	6dB Bandwidth	15
6.3	Maximum Conducted Output Power	17
6.4	Power Spectral Density	18
6.5	RF conducted spurious emissions and band edge measurement	19
6.6	Band edge emissions (Radiated)	20
6.7	Radiated emissions (below 1GHz)	29
6.8	Radiated emissions (above 1GHz)	33
	Photographs of the test setup	37
	Photographs of the EUT	38
	Appendix A: DTS Bandwidth	40
	Appendix B: Maximum conducted output power	47
	Appendix C: Maximum power spectral density	48
	Appendix D: Band edge measurements	55
	Appendix E: Conducted Spurious Emission	59
	Appendix F: Duty Cycle	77

TEST REPORT

Report No.: MTi250829003-0105E3

Test Result Certification		
Applicant	Emlid Tech Kft.	
Applicant Address	Esztergomi way 31-39, HUB 3 building, 5 floor, 1138 Budapest, Hungary	
Manufacturer	NexPCB Limited	
Manufacturer Address	Room 605A,TCL Industrial Centre, 8 Tai Chung Road, Tsuen Wan,Hong Kong	
Factory1	Ningbo High-tech Zone Ladder Science co., Ltd	
Factory Address	No. 4-1, 5-1, 6-1, Building 3, No. 3, Lane 215, Qingyi Road, Ningbo High-tech Zone, Zhejiang Province,China	
Factory2	PT. NEXFACTORY ERA XCELLENCE	
Factory Address	Jalan T ekno 3, Blok A8-K, Kawasan Industri Jababeka Phase 3, Desa/Kelurahan Pasirgombong, Kec. Cikarang Utara, Kab. Bekasi, Provinsi Jawa Barat,Indonesia	
Product description		
Product name	All-band RTK GNSS receiver	
Trademark	EMLID	
Model name	RRS-4P	
Series Model(s)	RRS-4	
Standards	47 CFR Part 15.247	
Test Method	KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.10-2020	
Testing Information		
Date of test	2025-11-08 to 2025-12-15	
Test result	Pass	
Prepared by:	James Qin	
Reviewed by:	David Lee	
Approved by:	Lewis Lian	

TEST REPORT

Report No.: MTi250829003-0105E3

1 General Description

1.1 Description of the EUT

Product name:	All-band RTK GNSS receiver
Model name:	RRS-4P
Series Model(s):	RRS-4
Model difference:	All models share the same circuit and module. The difference between the models is only the model name and the number of cameras: RRS-4P is equipped with two cameras, while RRS-4 has no cameras.
Electrical rating:	Input: USB Type-C(PD): DC 5V-3A, 9V-3A, 12V-3A, 15V-3A Battery: DC 7.2V 5000mAh 36Wh
Accessories:	Cable: USB-C to USB-C cable*1 Radio antenna 860-930 MHz*1 Radio antenna 410-470 MHz*1
Hardware version:	Revision A
Software version:	34.1
Test sample(s) number:	MTi250829003-01-R001
RF specification	
Operating frequency range:	802.11b/g/n20:2412~2462 MHz 802.11n40:2422~2452 MHz
Channel number:	11
Modulation type:	IEEE 802.11b : DSSS (DBPSK, DQPSK, CCK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna(s) type:	PCB
Antenna(s) gain:	0.58dBi

1.2 Description of test modes

No.	Emission test modes
Mode1	TX-802.11b
Mode2	TX-802.11g
Mode3	TX-802.11N20
Mode4	TX-802.11N40

1.2.1 Operation channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457

TEST REPORT

Report No.: MTi250829003-0105E3

3	2422	7	2442	11	2462
4	2427	8	2447	/	/

Test Channel List

Operation Band: 2400-2483.5 MHz

Bandwidth (MHz)	Lowest Channel (LCH) (MHz)	Middle Channel (MCH) (MHz)	Highest Channel (HCH) (MHz)
20	2412	2437	2462
40	2422	2437	2452

Note: The test software provided by manufacturer is used to control EUT for working in engineering mode, that enables selectable channel, and capable of continuous transmitting mode.

Test Software: Serial port tool

For power setting, refer to below table.

Mode	2412MHz	2437MHz	2462MHz
802.11b	18	18	18
802.11g	18	18	18
802.11n20	18	18	18

Mode	2422MHz	2437MHz	2452MHz
802.11n40	18	18	18

TEST REPORT

Report No.: MTi250829003-0105E3

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

Support equipment list			
Description	Model	Serial No.	Manufacturer
HUAWEI QUICK CHARGE	HW-200325CP1	FL8606P8500764	HUAWEI
Support cable list			
Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	±3.1dB
Occupied channel bandwidth	±3 %
RF output power, conducted	±1 dB
Power Spectral Density, conducted	±1 dB
Unwanted Emissions, conducted	±1 dB
Radiated spurious emissions (above 1GHz)	±5.3dB
Radiated spurious emissions (9kHz~30MHz)	±4.3dB
Radiated spurious emissions (30MHz~1GHz)	±4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

TEST REPORT

Report No.: MTi250829003-0105E3

2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Antenna requirement	47 CFR Part 15.247	47 CFR 15.203	Pass
2	Conducted Emission at AC power line	47 CFR Part 15.247	47 CFR 15.207(a)	Pass
3	6dB Bandwidth	47 CFR Part 15.247	47 CFR 15.247(a)(2)	Pass
4	Maximum Conducted Output Power	47 CFR Part 15.247	47 CFR 15.247(b)(3)	Pass
5	Power Spectral Density	47 CFR Part 15.247	47 CFR 15.247(e)	Pass
6	RF conducted spurious emissions and band edge measurement	47 CFR Part 15.247	47 CFR 15.247(d)	Pass
7	Band edge emissions (Radiated)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
8	Radiated emissions (below 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass
9	Radiated emissions (above 1GHz)	47 CFR Part 15.247	47 CFR 15.247(d), 15.209, 15.205	Pass

TEST REPORT

Report No.: MTi250829003-0105E3

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

TEST REPORT

Report No.: MTi250829003-0105E3

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
Conducted Emission at AC power line						
1	EMI Test Receiver	Rohde&schwarz	ESCI3	101368	2025-03-14	2026-03-13
2	Artificial mains network	Schwarzbeck	NSLK 8127	183	2025-03-18	2026-03-17
3	Artificial Mains Network	Rohde & Schwarz	ESH2-Z5	100263	2025-03-18	2026-03-17
4	EMI Measurement Software	Farad	EZ-EMC Ver.EMEC-3A1	/	/	/
Emissions in non-restricted frequency bands 6dB Bandwidth Maximum Conducted Output Power Power Spectral Density						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2025-03-18	2026-03-17
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2025-03-14	2026-03-13
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2025-03-14	2026-03-13
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2025-03-14	2026-03-13
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2025-03-14	2026-03-13
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2025-03-18	2026-03-17
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2025-03-14	2026-03-13
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2025-03-14	2026-03-13
9	DC Power Supply	Agilent	E3632A	MY40027695	2025-03-18	2026-03-17
10	RF Test System	Tonscend	JS1120-3 Test System Ver. V3.5.39	/	/	/
Emissions in frequency bands (above 1GHz) Band edge emissions (Radiated)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2025-03-14	2026-03-13
2	Double Ridged Broadband Horn Antenna	schwarabeck	BBHA 9120 D	2278	2025-05-27	2027-05-26
3	Amplifier	Agilent	8449B	3008A01120	2025-03-18	2026-03-17
4	MXA signal analyzer	Agilent	N9020A	MY54440859	2025-03-14	2026-03-13
5	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2025-03-14	2026-03-13
6	Horn antenna	Schwarzbeck	BBHA 9170	00987	2025-05-27	2027-05-26

TEST REPORT

Report No.: MTi250829003-0105E3

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
7	Pre-amplifier	Space-Dtronics	EWLAN18 40G	210405001	2025-03-19	2026-03-18
8	EMI Measurement Software	Farad	EZ-EMC Ver.EMEC- 3A1	/	/	/
Emissions in frequency bands (below 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESC17	101166	2025-03-14	2026-03-13
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2025-05-23	2027-05-22
3	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2024-03-23	2026-03-22
4	Amplifier	Hewlett-Packard	8447F	3113A06184	2025-03-18	2026-03-17
5	EMI Measurement Software	Farad	EZ-EMC Ver.EMEC- 3A1	/	/	/

TEST REPORT

Report No.: MTi250829003-0105E3

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

5.1.1 Conclusion:

The antenna of the EUT is permanently attached.
The EUT complies with the requirement of FCC PART 15.203.

TEST REPORT

Report No.: MTi250829003-0105E3

6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
*Decreases with the logarithm of the frequency.			
Test Method:	ANSI C63.10-2020 section 6.2		
Procedure:	Refer to ANSI C63.10-2020 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

6.1.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25 °C	Humidity:	67 %	Atmospheric Pressure:	100 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report				

6.1.2 Test Setup Diagram:




TEST REPORT

Report No.: MTi250829003-0105E3

6.1.3 Test Data:


Mode1 / Line: Line / CH: L



TEST REPORT

Report No.: MTi250829003-0105E3

Mode1 / Line: Neutral / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1515	28.91	10.17	39.08	65.92	-26.84	QP	
2		0.1900	17.52	10.16	27.68	54.04	-26.36	AVG	
3	*	0.4740	22.95	10.17	33.12	46.44	-13.32	AVG	
4		0.4860	26.59	10.17	36.76	56.24	-19.48	QP	
5		1.0660	14.64	10.19	24.83	46.00	-21.17	AVG	
6		1.6300	20.44	10.20	30.64	56.00	-25.36	QP	
7		1.9180	22.29	10.21	32.50	56.00	-23.50	QP	
8		1.9180	18.27	10.21	28.48	46.00	-17.52	AVG	
9		2.5140	14.65	10.23	24.88	46.00	-21.12	AVG	
10		4.6539	19.24	10.30	29.54	56.00	-26.46	QP	
11		9.8500	22.78	10.42	33.20	60.00	-26.80	QP	
12		10.1579	15.77	10.42	26.19	50.00	-23.81	AVG	

TEST REPORT

Report No.: MTi250829003-0105E3

6.2 6dB Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	11.8.1 Option 1 The steps for the first option are as follows: a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max-hold. e) Sweep = No faster than coupled (auto) time. f) Allow the trace to stabilize. g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value. 11.8.2 Option 2 The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.


6.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.8 °C	Humidity:	59 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

TEST REPORT

Report No.: MTi250829003-0105E3

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi250829003-0105E3


6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2020 section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020, section 11.9.1.1 Maximum peak conducted output power

6.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.8 °C	Humidity:	59 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.3.2 Test Setup Diagram:



6.3.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi250829003-0105E3


6.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2020, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020, section 11.10.2 Maximum power spectral density level in the fundamental emission

6.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.8 °C	Humidity:	59 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.4.2 Test Setup Diagram:



6.4.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi250829003-0105E3


6.5 RF conducted spurious emissions and band edge measurement

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020 Section 11.11.1, Section 11.11.2, Section 11.11.3

6.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.8 °C	Humidity:	59 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

Please Refer to Appendix for Details.

TEST REPORT

Report No.: MTi250829003-0105E3


6.6 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 section 6.10.5.2		

6.6.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.6 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
Pre test mode:		Mode1, Mode2, Mode3, Mode4			
Final test mode:		All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report			
Note: The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.					

6.6.2 Test Setup Diagram:



TEST REPORT

Report No.: MTi250829003-0105E3

6.6.3 Test Data:

Mode1 / Polarization: Horizontal / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	53.06	-4.50	48.56	74.00	-25.44	peak
2		2310.000	42.84	-4.50	38.34	54.00	-15.66	AVG
3		2390.000	61.54	-4.31	57.23	74.00	-16.77	peak
4	*	2390.000	53.17	-4.31	48.86	54.00	-5.14	AVG

Mode1 / Polarization: Vertical / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	53.13	-4.50	48.63	74.00	-25.37	peak
2		2310.000	43.20	-4.50	38.70	54.00	-15.30	AVG
3		2390.000	63.23	-4.31	58.92	74.00	-15.08	peak
4	*	2390.000	55.05	-4.31	50.74	54.00	-3.26	AVG

TEST REPORT

Report No.: MTi250829003-0105E3

Mode1 / Polarization: Horizontal / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	54.61	-4.23	50.38	74.00	-23.62	peak
2	*	2483.500	46.31	-4.23	42.08	54.00	-11.92	AVG
3		2500.000	50.43	-4.15	46.28	74.00	-27.72	peak
4		2500.000	40.56	-4.15	36.41	54.00	-17.59	AVG

Mode1 / Polarization: Vertical / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	58.16	-4.23	53.93	74.00	-20.07	peak
2	*	2483.500	48.52	-4.23	44.29	54.00	-9.71	AVG
3		2500.000	56.55	-4.15	52.40	74.00	-21.60	peak
4		2500.000	47.26	-4.15	43.11	54.00	-10.89	AVG

TEST REPORT

Report No.: MTi250829003-0105E3

Mode2 / Polarization: Horizontal / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	52.39	-4.50	47.89	74.00	-26.11	peak
2		2310.000	43.13	-4.50	38.63	54.00	-15.37	AVG
3		2390.000	67.75	-4.31	63.44	74.00	-10.56	peak
4	*	2390.000	53.95	-4.31	49.64	54.00	-4.36	AVG

Mode2 / Polarization: Vertical / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	52.51	-4.50	48.01	74.00	-25.99	peak
2		2310.000	43.05	-4.50	38.55	54.00	-15.45	AVG
3		2390.000	70.24	-4.31	65.93	74.00	-8.07	peak
4	*	2390.000	55.16	-4.31	50.85	54.00	-3.15	AVG

TEST REPORT

Report No.: MTi250829003-0105E3

Mode2 / Polarization: Horizontal / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	65.74	-4.23	61.51	74.00	-12.49	peak
2	*	2483.500	49.61	-4.23	45.38	54.00	-8.62	AVG
3		2500.000	60.40	-4.15	56.25	74.00	-17.75	peak
4		2500.000	44.05	-4.15	39.90	54.00	-14.10	AVG

Mode2 / Polarization: Vertical / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	70.97	-4.23	66.74	74.00	-7.26	peak
2	*	2483.500	54.39	-4.23	50.16	54.00	-3.84	AVG
3		2500.000	64.38	-4.15	60.23	74.00	-13.77	peak
4		2500.000	46.38	-4.15	42.23	54.00	-11.77	AVG

TEST REPORT

Report No.: MTi250829003-0105E3

Mode3 / Polarization: Horizontal / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2309.880	43.15	-4.50	38.65	54.00	-15.35	AVG
2		2310.000	52.73	-4.50	48.23	74.00	-25.77	peak
3	*	2389.960	54.72	-4.31	50.41	54.00	-3.59	AVG
4		2390.000	67.58	-4.31	63.27	74.00	-10.73	peak

Mode3 / Polarization: Vertical / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	53.10	-4.50	48.60	74.00	-25.40	peak
2		2310.000	42.79	-4.50	38.29	54.00	-15.71	AVG
3		2390.000	66.33	-4.31	62.02	74.00	-11.98	peak
4	*	2390.000	54.07	-4.31	49.76	54.00	-4.24	AVG

TEST REPORT

Report No.: MTi250829003-0105E3

Mode3 / Polarization: Horizontal / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	59.90	-4.23	55.67	74.00	-18.33	peak
2	*	2483.500	43.94	-4.23	39.71	54.00	-14.29	AVG
3		2500.000	55.70	-4.15	51.55	74.00	-22.45	peak
4		2500.000	40.70	-4.15	36.55	54.00	-17.45	AVG

Mode3 / Polarization: Vertical / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	64.01	-4.23	59.78	74.00	-14.22	peak
2	*	2483.500	47.16	-4.23	42.93	54.00	-11.07	AVG
3		2500.000	57.15	-4.15	53.00	74.00	-21.00	peak
4		2500.000	42.92	-4.15	38.77	54.00	-15.23	AVG

TEST REPORT

Report No.: MTi250829003-0105E3

Mode4 / Polarization: Horizontal / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	52.54	-4.50	48.04	74.00	-25.96	peak
2		2310.000	42.87	-4.50	38.37	54.00	-15.63	AVG
3		2390.000	64.30	-4.31	59.99	74.00	-14.01	peak
4	*	2390.000	52.77	-4.31	48.46	54.00	-5.54	AVG

Mode4 / Polarization: Vertical / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	54.52	-4.50	50.02	74.00	-23.98	peak
2		2310.000	42.55	-4.50	38.05	54.00	-15.95	AVG
3		2390.000	65.40	-4.31	61.09	74.00	-12.91	peak
4	*	2390.000	53.30	-4.31	48.99	54.00	-5.01	AVG

TEST REPORT

Report No.: MTi250829003-0105E3

Mode4 / Polarization: Horizontal / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	55.95	-4.23	51.72	74.00	-22.28	peak
2	*	2483.500	43.23	-4.23	39.00	54.00	-15.00	AVG
3		2500.000	51.01	-4.15	46.86	74.00	-27.14	peak
4		2500.000	41.09	-4.15	36.94	54.00	-17.06	AVG

Mode4 / Polarization: Vertical / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	60.66	-4.23	56.43	74.00	-17.57	peak
2	*	2483.500	46.33	-4.23	42.10	54.00	-11.90	AVG
3		2500.000	54.88	-4.15	50.73	74.00	-23.27	peak
4		2500.000	43.86	-4.15	39.71	54.00	-14.29	AVG

TEST REPORT

Report No.: MTi250829003-0105E3


6.7 Radiated emissions (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 section 6.6.4		

6.7.1 E.U.T. Operation:


Operating Environment:					
Temperature:	25.6 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
Pre test mode:		Mode1, Mode2, Mode3, Mode4			
Final test mode:		All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report			
Note: The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported. There were no emissions found below 30MHz within 20dB of the limit.					

6.7.2 Test Setup Diagram:



TEST REPORT

Report No.: MTi250829003-0105E3




TEST REPORT

Report No.: MTi250829003-0105E3

6.7.3 Test Data:

Mode1 / Polarization: Horizontal / CH: H



TEST REPORT

Report No.: MTi250829003-0105E3

Mode1 / Polarization: Vertical / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	48.3318	29.35	-7.89	21.46	40.00	-18.54	QP	
2		81.4970	27.01	-12.22	14.79	40.00	-25.21	QP	
3		145.8611	25.82	-7.37	18.45	43.50	-25.05	QP	
4		220.6171	32.65	-10.20	22.45	46.00	-23.55	QP	
5		352.9433	28.08	-5.56	22.52	46.00	-23.48	QP	
6		537.5891	29.81	-2.50	27.31	46.00	-18.69	QP	

TEST REPORT

Report No.: MTi250829003-0105E3


6.8 Radiated emissions (above 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 section 6.6.4		

6.8.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.6 °C	Humidity:	49.7 %	Atmospheric Pressure:	101 kPa
Pre test mode:		Mode1, Mode2, Mode3, Mode4			
Final test mode:		All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report			
Note: Test frequency are from 1GHz to 25GHz, the amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported.					

6.8.2 Test Setup Diagram:



TEST REPORT

Report No.: MTi250829003-0105E3

6.8.3 Test Data:

Mode1 / Polarization: Horizontal / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4824.000	43.03	1.86	44.89	74.00	-29.11	peak
2		4824.000	36.70	1.86	38.56	54.00	-15.44	AVG
3		7236.000	43.15	7.52	50.67	74.00	-23.33	peak
4		7236.000	36.74	7.52	44.26	54.00	-9.74	AVG
5		9648.000	45.25	9.07	54.32	74.00	-19.68	peak
6	*	9648.000	39.60	9.07	48.67	54.00	-5.33	AVG

Mode1 / Polarization: Vertical / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4824.000	44.75	1.86	46.61	74.00	-27.39	peak
2		4824.000	38.50	1.86	40.36	54.00	-13.64	AVG
3		7236.000	43.09	7.52	50.61	74.00	-23.39	peak
4		7236.000	37.07	7.52	44.59	54.00	-9.41	AVG
5		9648.000	44.91	9.07	53.98	74.00	-20.02	peak
6	*	9648.000	38.58	9.07	47.65	54.00	-6.35	AVG

TEST REPORT

Report No.: MTi250829003-0105E3

Mode1 / Polarization: Horizontal / CH: M

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4874.000	42.73	2.07	44.80	74.00	-29.20	peak
2		4874.000	36.49	2.07	38.56	54.00	-15.44	AVG
3		7311.000	42.67	7.82	50.49	74.00	-23.51	peak
4		7311.000	36.44	7.82	44.26	54.00	-9.74	AVG
5		9748.000	44.05	9.38	53.43	74.00	-20.57	peak
6	*	9748.000	38.21	9.38	47.59	54.00	-6.41	AVG

Mode1 / Polarization: Vertical / CH: M

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4874.000	43.05	2.07	45.12	74.00	-28.88	peak
2		4874.000	37.58	2.07	39.65	54.00	-14.35	AVG
3		7311.000	43.24	7.82	51.06	74.00	-22.94	peak
4		7311.000	37.65	7.82	45.47	54.00	-8.53	AVG
5		9748.000	44.33	9.38	53.71	74.00	-20.29	peak
6	*	9748.000	38.24	9.38	47.62	54.00	-6.38	AVG

TEST REPORT

Report No.: MTi250829003-0105E3

Mode1 / Polarization: Horizontal / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4924.000	44.43	2.32	46.75	74.00	-27.25	peak
2		4924.000	38.04	2.32	40.36	54.00	-13.64	AVG
3		7386.000	44.19	7.82	52.01	74.00	-21.99	peak
4		7386.000	38.77	7.82	46.59	54.00	-7.41	AVG
5		9848.000	44.01	9.48	53.49	74.00	-20.51	peak
6	*	9848.000	37.90	9.48	47.38	54.00	-6.62	AVG

Mode1 / Polarization: Vertical / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4924.000	42.87	2.32	45.19	74.00	-28.81	peak
2		4924.000	37.22	2.32	39.54	54.00	-14.46	AVG
3		7386.000	44.41	7.82	52.23	74.00	-21.77	peak
4		7386.000	38.77	7.82	46.59	54.00	-7.41	AVG
5		9848.000	44.43	9.48	53.91	74.00	-20.09	peak
6	*	9848.000	37.78	9.48	47.26	54.00	-6.74	AVG

TEST REPORT

Report No.: MTi250829003-0105E3

Photographs of the test setup

Refer to Appendix - Test Setup Photos

TEST REPORT

Report No.: MTi250829003-0105E3

Photographs of the EUT

Refer to Appendix - EUT Photos

Appendix

TEST REPORT

Report No.: MTi250829003-0105E3

Appendix A: DTS Bandwidth

Test Result

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	9.640	0.5	PASS
		2437	9.240	0.5	PASS
		2462	9.280	0.5	PASS
11G	Ant1	2412	16.480	0.5	PASS
		2437	16.440	0.5	PASS
		2462	16.440	0.5	PASS
11N20SISO	Ant1	2412	17.640	0.5	PASS
		2437	17.600	0.5	PASS
		2462	17.640	0.5	PASS
11N40SISO	Ant1	2422	36.080	0.5	PASS
		2437	36.240	0.5	PASS
		2452	36.080	0.5	PASS

TEST REPORT


Report No.: MTI250829003-0105E3

Test Graphs




TEST REPORT

Report No.: MTi250829003-0105E3




TEST REPORT

Report No.: MTI250829003-0105E3




TEST REPORT

Report No.: MTi250829003-0105E3




TEST REPORT

Report No.: MTI250829003-0105E3



TEST REPORT

Report No.: MTI250829003-0105E3



TEST REPORT

Report No.: MTi250829003-0105E3

Appendix B: Maximum conducted output power

Test Result Peak

Test Mode	Antenna	Frequency [MHz]	Peak Power [dBm]	Conducted Limit [dBm]	Verdict
11B	Ant1	2412	14.16	≤30.00	PASS
		2437	14.37	≤30.00	PASS
		2462	13.89	≤30.00	PASS
11G	Ant1	2412	17.58	≤30.00	PASS
		2437	17.89	≤30.00	PASS
		2462	17.42	≤30.00	PASS
11N20SISO	Ant1	2412	17.74	≤30.00	PASS
		2437	18.05	≤30.00	PASS
		2462	17.62	≤30.00	PASS
11N40SISO	Ant1	2422	18.05	≤30.00	PASS
		2437	17.86	≤30.00	PASS
		2452	17.32	≤30.00	PASS

TEST REPORT

Report No.: MTi250829003-0105E3

Appendix C: Maximum power spectral density


Test Result

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3-100kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-8.18	≤8.00	PASS
		2437	-7.46	≤8.00	PASS
		2462	-7.96	≤8.00	PASS
11G	Ant1	2412	-14.82	≤8.00	PASS
		2437	-14.95	≤8.00	PASS
		2462	-14.72	≤8.00	PASS
11N20SISO	Ant1	2412	-14.06	≤8.00	PASS
		2437	-12.91	≤8.00	PASS
		2462	-14.2	≤8.00	PASS
11N40SISO	Ant1	2422	-16.46	≤8.00	PASS
		2437	-15.7	≤8.00	PASS
		2452	-16.6	≤8.00	PASS

TEST REPORT


Report No.: MTI250829003-0105E3

Test Graphs




TEST REPORT

Report No.: MTi250829003-0105E3



TEST REPORT

Report No.: MTi250829003-0105E3



TEST REPORT

Report No.: MTi250829003-0105E3

