

Appendix IV MPE

FCC ID: 2BAYW-XPAIC001

Prediction of MPE at a given distance

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310(E)(1)

KDB Test Methodology: KDB 447498 D01 v06.

TABLE 1 TO § 1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842/f	4.89/f	*(900/f ²)	<6
30–300	61.4	0.163	1.0	<6
300–1,500			f/300	<6
1,500–100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824/f	2.19/f	*(180/f ²)	<30
30–300	27.5	0.073	0.2	<30
300–1,500			f/1500	<30
1,500–100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

2. Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

3. Result

Mode	Frequency (MHz)	Prediction distance (cm)	RF output power(Max) (dBm)	Tune-up power (Max)		MPE (mW/cm ²)	Limit (mW/cm ²)	SAR Test Exclusion
				dBm	mW			
2.4G WIFI	2412-2462	20	15.47	16	39.8107	0.0140	1.0000	Yes
5G WIFI B1	5180-5240	20	15.15	16	39.8107	0.0166	1.0000	Yes
5G WIFI B2	5260-5320	20	14.48	15	31.6228	0.0132	1.0000	Yes
5G WIFI B3	5500-5700	20	16.69	17	50.1187	0.0209	1.0000	Yes
5G WIFI B4	5745-5825	20	16.65	17	50.1187	0.0209	1.0000	Yes

2.4G WiFi:

Internal antenna, Maximum Gain is 2.46dBi, 1.76(numeric).

5G WiFi:

Internal antenna, Maximum Gain is 3.22dBi, 2.10(numeric).

Then SAR evaluation is not required.