




Power_Spectral_Density_NVNT_ANT1_802_11a_5500





Power_Spectral_Density_NVNT_ANT1_802_11a_5600





Power_Spectral_Density_NVNT_ANT1_802_11a_5700




Power Spectral Density NVNT_ANT1_802_11n(HT20)_5600





Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5500




Power Spectral Density_NVNT_ANT1_802_11ac(VHT20)_5700




Power Spectral Density NVNT ANT1 802 11ax(HE20) 5600




Power Spectral Density NVNT ANT1_802_11n(HT40)_5510




Power Spectral Density NVNT_ANT1_802_11n(HT40)_5670



Power Spectral Density NVNT_ANT1_802_11ac(VHT40)_5590



Power Spectral Density NVNT_ANT1_802_11ax(HE40)_5510




Power Spectral Density NVNT ANT1 802 11ax(HE40) 5670




Band 4 (5725 – 5850 MHz) SISO:

Condition	Antenna	Modulation	Frequency (MHz)	PSD_SA(dBm/RBW)	Duty factor(dB)	RB factor(dB)	PSD(dBm/500kHz)	limit(dBm/500kHz)	Result
NVNT	ANT1	802.11a	5745.00	-1.59	0.18	-0	-1.50	30	Pass
NVNT	ANT1	802.11a	5785.00	-1.86	0.18	-0	-1.76	30	Pass
NVNT	ANT1	802.11a	5825.00	-2.66	0.12	-0	-2.63	30	Pass
NVNT	ANT1	802.11n(HT20)	5745.00	-1.52	0.20	-0	-1.41	30	Pass
NVNT	ANT1	802.11n(HT20)	5785.00	-1.51	0.20	-0	-1.40	30	Pass
NVNT	ANT1	802.11n(HT20)	5825.00	-2.51	0.19	-0	-2.41	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5745.00	-5.73	0.51	-0	-5.30	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5785.00	-4.31	0.35	-0	-4.04	30	Pass
NVNT	ANT1	802.11ac(VHT20)	5825.00	-4.50	0.51	-0	-4.08	30	Pass
NVNT	ANT1	802.11ax(HE20)	5745.00	-3.85	0.56	-0	-3.38	30	Pass
NVNT	ANT1	802.11ax(HE20)	5785.00	-5.18	0.58	-0	-4.68	30	Pass
NVNT	ANT1	802.11ax(HE20)	5825.00	-5.52	0.58	-0	-5.03	30	Pass
NVNT	ANT1	802.11n(HT40)	5755.00	-7.30	0.39	-0	-6.99	30	Pass
NVNT	ANT1	802.11n(HT40)	5795.00	-6.43	0.39	-0	-6.13	30	Pass
NVNT	ANT1	802.11ac(VHT40)	5755.00	-12.66	0.90	-0	-11.85	30	Pass
NVNT	ANT1	802.11ac(VHT40)	5795.00	-10.46	0.62	-0	-9.93	30	Pass
NVNT	ANT1	802.11ax(HE40)	5755.00	-8.12	0.56	-0	-7.65	30	Pass
NVNT	ANT1	802.11ax(HE40)	5795.00	-8.30	0.56	-0	-7.83	30	Pass


Power_Spectral_Density_NVNT_ANT1_802_11a_5745





Power_Spectral_Density_NVNT_ANT1_802_11a_5785




Power_Spectral_Density_NVNT_ANT1_802_11a_5825




Power Spectral Density NVNT_ANT1_802_11n(HT20)_5785




Power Spectral Density NVNT_ANT1_802_11ac(VHT20)_5745



Power Spectral Density_NVNT_ANT1_802_11ac(VHT20)_5825




Power Spectral Density NVNT ANT1 802 11ax(HE20) 5785




Power Spectral Density NVNT ANT1_802_11n(HT40)_5755




Power Spectral Density NVNT_ANT1_802_11n(HT40)_5795



Power Spectral Density NVNT_ANT1_802_11ac(VHT40)_5755




Power Spectral Density_NVNT_ANT1_802_11ax(HE40)_5755



4.6 Band Edge

Test Requirement:	FCC Part15 E Section 15.407 and 15.205, RSS-Gen §8.9																								
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table><tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Remark</td></tr><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>100KHz</td><td>300KHz</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td>AV</td><td>1MHz</td><td>3MHz</td><td>Average Value</td></tr></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	AV	1MHz	3MHz	Average Value	
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	AV	1MHz	3MHz	Average Value																					
Limit:	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td></tr><tr><td>68.2</td><td>Peak Value</td></tr></table> Undesirable emission limits: (1) For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band. (3) For transmitters operating in the 5.47-5.725 GHz band: all emissions outside of the 5.47-5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz. (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	68.2	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.0	Quasi-peak Value																							
88MHz-216MHz	43.5	Quasi-peak Value																							
216MHz-960MHz	46.0	Quasi-peak Value																							
960MHz-1GHz	54.0	Quasi-peak Value																							
Above 1GHz	54.0	Average Value																							
	68.2	Peak Value																							
Test Procedure:	a. The EUT was placed on the top of a rotating table 1.5 m above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values																								

	of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test setup:	Above 1GHz 
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Remark:

According to KDB 789033 D02 v02r01 section G) 1) (d), for For measurements above 1000 MHz @ 3m distance, the limit of field strength is computed as follows:

$$E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2,$$

For example, if EIRP = -27dBm

$$E[\text{dBuV/m}] = -27 + 95.2 = 68.2\text{dBuV/m}.$$

Measurement Data:**Band1**

Mode:		802.11a		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.90	-13.16	41.74	68.20	-26.46	PK
V	5150.00	55.00	-13.16	41.84	68.20	-26.36	PK
Mode:		802.11a		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	46.38	-13.16	33.22	54.00	-20.78	AV
V	5150.00	47.95	-13.16	34.79	54.00	-19.21	AV
Mode:		802.11a		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.86	-12.62	44.24	68.20	-23.96	PK
V	5350.00	55.17	-12.62	42.55	68.20	-25.65	PK
Mode:		802.11a		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.70	-12.62	34.08	54.00	-19.92	AV
V	5350.00	47.82	-12.62	35.20	54.00	-18.80	AV

Mode:		802.11n(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.66	-13.16	42.50	68.20	-25.70	PK
V	5150.00	56.75	-13.16	43.59	68.20	-24.61	PK
Mode:		802.11n(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	45.96	-13.16	32.80	54.00	-21.20	AV
V	5150.00	45.53	-13.16	32.37	54.00	-21.63	AV
Mode:		802.11n(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.29	-12.62	43.67	68.20	-24.53	PK
V	5350.00	57.65	-12.62	45.03	68.20	-23.17	PK
Mode:		802.11n(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	44.54	-12.62	31.92	54.00	-22.08	AV
V	5350.00	47.09	-12.62	34.47	54.00	-19.53	AV

Mode:		802.11ac(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.94	-13.16	42.78	68.20	-25.42	PK
V	5150.00	55.07	-13.16	41.91	68.20	-26.29	PK
Mode:		802.11ac(HT20)		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	46.92	-13.16	33.76	54.00	-20.24	AV
V	5150.00	46.46	-13.16	33.30	54.00	-20.70	AV
Mode:		802.11ac(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.23	-12.62	42.61	68.20	-25.59	PK
V	5350.00	56.10	-12.62	43.48	68.20	-24.72	PK
Mode:		802.11ac(HT20)		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	44.61	-12.62	31.99	54.00	-22.01	AV
V	5350.00	46.87	-12.62	34.25	54.00	-19.75	AV

Mode:		802.11ax20		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.12	-13.16	41.96	68.20	-26.24	PK
V	5150.00	57.25	-13.16	44.09	68.20	-24.11	PK
Mode:		802.11ax20		Frequency:		5180MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.01	-13.16	33.85	54.00	-20.15	AV
V	5150.00	48.29	-13.16	35.13	54.00	-18.87	AV
Mode:		802.11ax20		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	53.79	-12.62	41.17	68.20	-27.03	PK
V	5350.00	60.16	-12.62	47.54	68.20	-20.66	PK
Mode:		802.11ax20		Frequency:		5240MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.23	-12.62	34.61	54.00	-19.39	AV
V	5350.00	46.85	-12.62	34.23	54.00	-19.77	AV

Mode:		802.11n(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.26	-13.16	42.10	68.20	-26.10	PK
V	5150.00	55.64	-13.16	42.48	68.20	-25.72	PK
Mode:		802.11n(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.49	-13.16	34.33	54.00	-19.67	AV
V	5150.00	48.61	-13.16	35.45	54.00	-18.55	AV
Mode:		802.11n(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	53.87	-12.62	41.25	68.20	-26.95	PK
V	5350.00	56.39	-12.62	43.77	68.20	-24.43	PK
Mode:		802.11n(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	44.51	-12.62	31.89	54.00	-22.11	AV
V	5350.00	48.64	-12.62	36.02	54.00	-17.98	AV

Mode:		802.11ac(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	53.67	-13.16	40.51	68.20	-27.69	PK
V	5150.00	56.94	-13.16	43.78	68.20	-24.42	PK
Mode:		802.11ac(HT40)		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.91	-13.16	34.75	54.00	-19.25	AV
V	5150.00	48.52	-13.16	35.36	54.00	-18.64	AV
Mode:		802.11ac(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.87	-12.62	42.25	68.20	-25.95	PK
V	5350.00	57.61	-12.62	44.99	68.20	-23.21	PK
Mode:		802.11ac(HT40)		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	45.04	-12.62	32.42	54.00	-21.58	AV
V	5350.00	48.39	-12.62	35.77	54.00	-18.23	AV

Mode:		802.11ax40		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.09	-13.16	41.93	68.20	-26.27	PK
V	5150.00	58.31	-13.16	45.15	68.20	-23.05	PK
Mode:		802.11ax40		Frequency:		5190MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	48.06	-13.16	34.90	54.00	-19.10	AV
V	5150.00	45.44	-13.16	32.28	54.00	-21.72	AV
Mode:		802.11ax40		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	57.26	-12.62	44.64	68.20	-23.56	PK
V	5350.00	58.35	-12.62	45.73	68.20	-22.47	PK
Mode:		802.11ax40		Frequency:		5230MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.19	-12.62	33.57	54.00	-20.43	AV
V	5350.00	48.98	-12.62	36.36	54.00	-17.64	AV

Band2

Mode:		802.11a		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.80	-13.16	41.64	68.20	-26.56	PK
V	5150.00	56.88	-13.16	43.72	68.20	-24.48	PK
Mode:		802.11a		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	46.60	-13.16	33.44	54.00	-20.56	AV
V	5150.00	46.33	-13.16	33.17	54.00	-20.83	AV
Mode:		802.11a		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	57.06	-12.62	44.44	68.20	-23.76	PK
V	5350.00	58.25	-12.62	45.63	68.20	-22.57	PK
Mode:		802.11a		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	45.68	-12.62	33.06	54.00	-20.94	AV
V	5350.00	46.99	-12.62	34.37	54.00	-19.63	AV

Mode:		802.11n(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.44	-13.16	42.28	68.20	-25.92	PK
V	5150.00	56.46	-13.16	43.30	68.20	-24.90	PK
Mode:		802.11n(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.02	-13.16	33.86	54.00	-20.14	AV
V	5150.00	46.35	-13.16	33.19	54.00	-20.81	AV
Mode:		802.11n(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.66	-12.62	43.04	68.20	-25.16	PK
V	5350.00	60.66	-12.62	48.04	68.20	-20.16	PK
Mode:		802.11n(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	44.62	-12.62	32.00	54.00	-22.00	AV
V	5350.00	46.73	-12.62	34.11	54.00	-19.89	AV

Mode:		802.11ac(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.79	-13.16	41.63	68.20	-26.57	PK
V	5150.00	57.55	-13.16	44.39	68.20	-23.81	PK
Mode:		802.11ac(HT20)		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	44.51	-13.16	31.35	54.00	-22.65	AV
V	5150.00	46.41	-13.16	33.25	54.00	-20.75	AV
Mode:		802.11ac(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.99	-12.62	44.37	68.20	-23.83	PK
V	5350.00	57.59	-12.62	44.97	68.20	-23.23	PK
Mode:		802.11ac(HT20)		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.28	-12.62	33.66	54.00	-20.34	AV
V	5350.00	48.39	-12.62	35.77	54.00	-18.23	AV

Mode:		802.11ax20		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.24	-13.16	41.08	68.20	-27.12	PK
V	5150.00	55.27	-13.16	42.11	68.20	-26.09	PK
Mode:		802.11ax20		Frequency:		5260MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.80	-13.16	34.64	54.00	-19.36	AV
V	5150.00	45.44	-13.16	32.28	54.00	-21.72	AV
Mode:		802.11ax20		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	53.94	-12.62	41.32	68.20	-26.88	PK
V	5350.00	58.89	-12.62	46.27	68.20	-21.93	PK
Mode:		802.11ax20		Frequency:		5320MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	45.18	-12.62	32.56	54.00	-21.44	AV
V	5350.00	49.51	-12.62	36.89	54.00	-17.11	AV

Mode:		802.11n(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.27	-13.16	42.11	68.20	-26.09	PK
V	5150.00	55.61	-13.16	42.45	68.20	-25.75	PK
Mode:		802.11n(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.02	-13.16	33.86	54.00	-20.14	AV
V	5150.00	48.33	-13.16	35.17	54.00	-18.83	AV
Mode:		802.11n(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	56.39	-12.62	43.77	68.20	-24.43	PK
V	5350.00	58.12	-12.62	45.50	68.20	-22.70	PK
Mode:		802.11n(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	47.38	-12.62	34.76	54.00	-19.24	AV
V	5350.00	47.02	-12.62	34.40	54.00	-19.60	AV

Mode:		802.11ac(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	55.37	-13.16	42.21	68.20	-25.99	PK
V	5150.00	56.52	-13.16	43.36	68.20	-24.84	PK
Mode:		802.11ac(HT40)		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	46.14	-13.16	32.98	54.00	-21.02	AV
V	5150.00	47.66	-13.16	34.50	54.00	-19.50	AV
Mode:		802.11ac(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	55.98	-12.62	43.36	68.20	-24.84	PK
V	5350.00	57.47	-12.62	44.85	68.20	-23.35	PK
Mode:		802.11ac(HT40)		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	45.78	-12.62	33.16	54.00	-20.84	AV
V	5350.00	46.48	-12.62	33.86	54.00	-20.14	AV

Mode:		802.11ax40		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	54.44	-13.16	41.28	68.20	-26.92	PK
V	5150.00	55.87	-13.16	42.71	68.20	-25.49	PK
Mode:		802.11ax40		Frequency:		5270MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5150.00	47.09	-13.16	33.93	54.00	-20.07	AV
V	5150.00	45.75	-13.16	32.59	54.00	-21.41	AV
Mode:		802.11ax40		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	54.20	-12.62	41.58	68.20	-26.62	PK
V	5350.00	55.34	-12.62	42.72	68.20	-25.48	PK
Mode:		802.11ax40		Frequency:		5310MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5350.00	46.68	-12.62	34.06	54.00	-19.94	AV
V	5350.00	47.44	-12.62	34.82	54.00	-19.18	AV

Band3

Mode:		802.11a		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5470.00	53.84	-12.29	41.55	68.20	-26.65	PK
V	5470.00	57.25	-12.29	44.96	68.20	-23.24	PK
Mode:		802.11a		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5470.00	44.40	-12.29	32.11	54.00	-21.89	AV
V	5470.00	49.07	-12.29	36.78	54.00	-17.22	AV
Mode:		802.11a		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5725.00	56.98	-11.60	45.38	68.20	-22.82	PK
V	5725.00	55.61	-11.60	44.01	68.20	-24.19	PK
Mode:		802.11a		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5725.00	47.66	-11.60	36.06	54.00	-17.94	AV
V	5725.00	46.64	-11.60	35.04	54.00	-18.96	AV

Mode:		802.11n(HT20)		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5470.00	54.77	-12.29	42.48	68.20	-25.72	PK
V	5470.00	58.62	-12.29	46.33	68.20	-21.87	PK
Mode:		802.11n(HT20)		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5470.00	46.55	-12.29	34.26	54.00	-19.74	AV
V	5470.00	45.81	-12.29	33.52	54.00	-20.48	AV
Mode:		802.11n(HT20)		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5725.00	54.13	-11.60	42.53	68.20	-25.67	PK
V	5725.00	58.10	-11.60	46.50	68.20	-21.70	PK
Mode:		802.11n(HT20)		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Over limit(dB)	Detector
H	5725.00	44.52	-11.60	32.92	54.00	-21.08	AV
V	5725.00	49.19	-11.60	37.59	54.00	-16.41	AV

Mode:		802.11ac(HT20)		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	55.19	-12.29	42.90	68.20	-25.30	PK
V	5470.00	55.93	-12.29	43.64	68.20	-24.56	PK
Mode:		802.11ac(HT20)		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	44.70	-12.29	32.41	54.00	-21.59	AV
V	5470.00	47.33	-12.29	35.04	54.00	-18.96	AV
Mode:		802.11ac(HT20)		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	56.00	-11.60	44.40	68.20	-23.80	PK
V	5725.00	56.08	-11.60	44.48	68.20	-23.72	PK
Mode:		802.11ac(HT20)		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	45.70	-11.60	34.10	54.00	-19.90	AV
V	5725.00	48.49	-11.60	36.89	54.00	-17.11	AV

Mode:		802.11ax20		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	55.22	-12.29	42.93	68.20	-25.27	PK
V	5470.00	55.25	-12.29	42.96	68.20	-25.24	PK
Mode:		802.11ax20		Frequency:		5500MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	48.00	-12.29	35.71	54.00	-18.29	AV
V	5470.00	48.89	-12.29	36.60	54.00	-17.40	AV
Mode:		802.11ax20		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	53.98	-11.60	42.38	68.20	-25.82	PK
V	5725.00	60.52	-11.60	48.92	68.20	-19.28	PK
Mode:		802.11ax20		Frequency:		5700MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	46.72	-11.60	35.12	54.00	-18.88	AV
V	5725.00	48.67	-11.60	37.07	54.00	-16.93	AV

Mode:		802.11n(HT40)		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	53.98	-12.29	41.69	68.20	-26.51	PK
V	5470.00	57.44	-12.29	45.15	68.20	-23.05	PK
Mode:		802.11n(HT40)		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	47.77	-12.29	35.48	54.00	-18.52	AV
V	5470.00	45.57	-12.29	33.28	54.00	-20.72	AV
Mode:		802.11n(HT40)		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	54.33	-11.60	42.73	68.20	-25.47	PK
V	5725.00	57.47	-11.60	45.87	68.20	-22.33	PK
Mode:		802.11n(HT40)		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	47.00	-11.60	35.40	54.00	-18.60	AV
V	5725.00	47.58	-11.60	35.98	54.00	-18.02	AV


Mode:		802.11ac(HT40)		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	56.65	-12.29	44.36	68.20	-23.84	PK
V	5470.00	55.75	-12.29	43.46	68.20	-24.74	PK
Mode:		802.11ac(HT40)		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	46.52	-12.29	34.23	54.00	-19.77	AV
V	5470.00	45.45	-12.29	33.16	54.00	-20.84	AV
Mode:		802.11ac(HT40)		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	55.05	-11.60	43.45	68.20	-24.75	PK
V	5725.00	56.84	-11.60	45.24	68.20	-22.96	PK
Mode:		802.11ac(HT40)		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	47.19	-11.60	35.59	54.00	-18.41	AV
V	5725.00	47.45	-11.60	35.85	54.00	-18.15	AV

Mode:		802.11ax40		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	54.96	-12.29	42.67	68.20	-25.53	PK
V	5470.00	56.98	-12.29	44.69	68.20	-23.51	PK
Mode:		802.11ax40		Frequency:		5510MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5470.00	47.83	-12.29	35.54	54.00	-18.46	AV
V	5470.00	45.55	-12.29	33.26	54.00	-20.74	AV
Mode:		802.11ax40		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	53.70	-11.60	42.10	68.20	-26.10	PK
V	5725.00	56.03	-11.60	44.43	68.20	-23.77	PK
Mode:		802.11ax40		Frequency:		5670MHz	
Antenna Pol.	Frequency (MHz)	Reading Level	Factor	Measure Level	Limit (dBuV/m)	Over limit(dB)	Detector
		(dBuV)	(dB/m)	(dBuV/m)			
H	5725.00	46.00	-11.60	34.40	54.00	-19.60	AV
V	5725.00	46.25	-11.60	34.65	54.00	-19.35	AV


Band4

Condition	Antenna	Modulation	TX_Frequency (MHz)	Frequency Area(MHz)	Frequency(MHz)	Amplitude(dBm)	Limit(dBm)	Result
NVNT	ANT1	802.11a	LCH	5565-5655	5578.770	-49.07	-27.00	Pass
NVNT	ANT1	802.11a	LCH	5655-5700	5666.970	-48.87	-17.16	Pass
NVNT	ANT1	802.11a	LCH	5700-5720	5700.260	-47.62	10.07	Pass
NVNT	ANT1	802.11a	LCH	5720-5725	5722.915	-45.46	22.25	Pass
NVNT	ANT1	802.11a	HCH	5850-5855	5853.535	-47.67	18.94	Pass
NVNT	ANT1	802.11a	HCH	5855-5875	5867.480	-48.37	12.11	Pass
NVNT	ANT1	802.11a	HCH	5875-5920	5906.995	-48.68	-16.31	Pass
NVNT	ANT1	802.11a	HCH	5920-6005	5934.110	-45.13	-27.00	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5565-5655	5584.890	-48.00	-27.00	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5655-5700	5664.225	-48.88	-19.41	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5700-5720	5712.640	-47.49	13.54	Pass
NVNT	ANT1	802.11n(HT20)	LCH	5720-5725	5723.625	-45.27	23.87	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5850-5855	5854.955	-48.10	15.70	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5855-5875	5874.060	-48.65	10.26	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5875-5920	5904.430	-49.25	-14.20	Pass
NVNT	ANT1	802.11n(HT20)	HCH	5920-6005	5985.790	-45.75	-27.00	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5565-5655	5654.100	-48.68	-27.00	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5655-5700	5666.790	-49.02	-17.31	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5700-5720	5713.740	-47.74	13.85	Pass
NVNT	ANT1	802.11ac(VHT20)	LCH	5720-5725	5721.195	-46.04	18.32	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5850-5855	5853.580	-47.15	18.84	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5855-5875	5873.200	-47.63	10.50	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5875-5920	5903.530	-48.50	-13.46	Pass
NVNT	ANT1	802.11ac(VHT20)	HCH	5920-6005	5937.595	-44.96	-27.00	Pass
NVNT	ANT1	802.11ax(HE20)	LCH	5565-5655	5585.610	-49.03	-27.00	Pass
NVNT	ANT1	802.11ax(HE20)	LCH	5655-5700	5661.120	-48.67	-21.97	Pass
NVNT	ANT1	802.11ax(HE20)	LCH	5700-5720	5704.740	-46.33	11.33	Pass
NVNT	ANT1	802.11ax(HE20)	LCH	5720-5725	5721.150	-45.95	18.22	Pass
NVNT	ANT1	802.11ax(HE20)	HCH	5850-5855	5853.535	-47.03	18.94	Pass
NVNT	ANT1	802.11ax(HE20)	HCH	5855-5875	5872.640	-48.09	10.66	Pass
NVNT	ANT1	802.11ax(HE20)	HCH	5875-5920	5910.010	-47.82	-18.79	Pass
NVNT	ANT1	802.11ax(HE20)	HCH	5920-6005	5942.270	-44.39	-27.00	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5595-5655	5595.120	-49.37	-27.00	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5655-5700	5673.855	-48.36	-11.50	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5700-5720	5715.920	-45.02	14.46	Pass
NVNT	ANT1	802.11n(HT40)	LCH	5720-5725	5724.300	-42.24	25.40	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5850-5855	5854.705	-44.79	16.27	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5855-5875	5859.540	-45.56	14.33	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5875-5920	5898.265	-48.34	-9.13	Pass
NVNT	ANT1	802.11n(HT40)	HCH	5920-5955	5932.145	-44.91	-27.00	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5595-5655	5650.980	-49.01	-27.00	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5655-5700	5675.250	-48.64	-10.35	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5700-5720	5718.760	-45.22	15.25	Pass
NVNT	ANT1	802.11ac(VHT40)	LCH	5720-5725	5724.290	-42.39	25.38	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5850-5855	5853.395	-43.88	19.26	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5855-5875	5855.780	-43.52	15.38	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5875-5920	5901.100	-48.50	-11.46	Pass
NVNT	ANT1	802.11ac(VHT40)	HCH	5920-5955	5932.425	-45.63	-27.00	Pass
NVNT	ANT1	802.11ax(HE40)	LCH	5595-5655	5650.440	-48.86	-27.00	Pass
NVNT	ANT1	802.11ax(HE40)	LCH	5655-5700	5668.815	-47.88	-15.64	Pass
NVNT	ANT1	802.11ax(HE40)	LCH	5700-5720	5708.700	-45.94	12.44	Pass
NVNT	ANT1	802.11ax(HE40)	LCH	5720-5725	5724.810	-42.46	26.57	Pass
NVNT	ANT1	802.11ax(HE40)	HCH	5850-5855	5853.245	-42.82	19.60	Pass
NVNT	ANT1	802.11ax(HE40)	HCH	5855-5875	5858.220	-43.54	14.70	Pass
NVNT	ANT1	802.11ax(HE40)	HCH	5875-5920	5885.215	-47.96	1.60	Pass
NVNT	ANT1	802.11ax(HE40)	HCH	5920-5955	5941.210	-44.54	-27.00	Pass



Bandedge_NVNT_ANT1_802_11a_5745





Bandedge_NVNT_ANT1_802_11a_5825





Bandedge_NVNT_ANT1_802_11n(HT20)_5745





Bandedge_NVNT_ANT1_802_11ac(VHT20)_5745





Bandedge_NVNT_ANT1_802_11ax(HE20)_5745





Bandedge NVNT_ANT1_802_11n(HT40)_5755



Bandedge_NVNT_ANT1_802_11ac(VHT40)_5755





Bandedge_NVNT_ANT1_802_11ax(HE40)_5755



4.7 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.209 and 15.205, RSS-Gen §8.9				
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024				
Test Frequency Range:	30MHz to 40GHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		AV	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		74.0		Peak Value
54.0			Average Value		
Test Procedure:	Substitution method was performed to determine the actual ERP emission levels of the EUT. The following test procedure as below:				
	1>.Below 1GHz test procedure:				
	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
	2>.Above 1GHz test procedure:				
	1. On the test site as test setup graph above,the EUT shall be placed at the 1.5m support on the turntable and in the position closest to normal use as declared by the provider. 2. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter.The output of the test antenna shall be connected to the measuring receiver. 3. The transmitter shall be switched on, if possible, without modulation and the measuring receiver shall be tuned to the frequency of the				


	transmitter under test. - The test antenna shall be raised and lowered from 1m to 4m until a maximum signal level is detected by the measuring receiver. Then the turntable should be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver. - Repeat step 4 for test frequency with the test antenna polarized horizontally. - Remove the transmitter and replace it with a substitution antenna - Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a nonradiating cable. With the antennas at both ends vertically polarized, and with the signal generator tuned to a particular test frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output. - Repeat step 7 with both antennas horizontally polarized for each test frequency. - Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps 7 and 8 by the power loss in the cable between the generator and the antenna, and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna by the following formula: $\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$ where: Pg is the generator output power into the substitution antenna.
Test setup:	Below 1GHz  Above 1GHz

	
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test results:	Pass

Measurement Data:

Below 1GHz

Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36.5733	18.10	13.78	31.88	40.00	-8.12	QP
2	40.5236	18.11	14.24	32.35	40.00	-7.65	QP
3	50.8305	17.94	13.70	31.64	40.00	-8.36	QP
4	76.5121	22.71	10.45	33.16	40.00	-6.84	QP
5	101.9120	19.83	11.16	30.99	43.50	-12.51	QP
6 *	218.5000	27.92	12.24	40.16	46.00	-5.84	QP

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	80.4676	24.68	9.98	34.66	40.00	-5.34	QP
2	90.0230	25.84	10.26	36.10	43.50	-7.40	QP
3	103.0349	24.60	11.28	35.88	43.50	-7.62	QP
4	173.0533	17.64	13.88	31.52	43.50	-11.98	QP
5	218.6916	24.14	12.25	36.39	46.00	-9.61	QP
6 *	305.6800	25.72	15.27	40.99	46.00	-5.01	QP

Note: Level = Reading + Factor Margin = Level - Limit

Above 1GHz:**U-NII-1:**

Test Mode: IEEE 802.11a							
Test channel: Low CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10360.00	66.28	-11.79	54.49	68.20	-13.71	V	Peak
15540.00	61.70	-7.28	54.42	68.20	-13.78	V	Peak
10360.00	65.38	-11.79	53.59	68.20	-14.61	H	Peak
15540.00	60.96	-7.28	53.68	68.20	-14.52	H	Peak
10360.00	47.23	-11.79	35.44	54.00	-18.56	V	AVG
15540.00	42.62	-7.28	35.34	54.00	-18.66	V	AVG
10360.00	47.26	-11.79	35.47	54.00	-18.53	H	AVG
15540.00	41.61	-7.28	34.33	54.00	-19.67	H	AVG
Test channel: Middle CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10400.00	65.60	-11.74	53.86	68.20	-14.34	V	Peak
15600.00	60.63	-7.18	53.45	68.20	-14.75	V	Peak
10400.00	64.56	-11.74	52.82	68.20	-15.38	H	Peak
15600.00	59.55	-7.18	52.37	68.20	-15.83	H	Peak
10400.00	47.52	-11.74	35.78	54.00	-18.22	V	AVG
15600.00	43.16	-7.18	35.98	54.00	-18.02	V	AVG
10400.00	46.36	-11.74	34.62	54.00	-19.38	H	AVG
15600.00	42.84	-7.18	35.66	54.00	-18.34	H	AVG
Test channel: High CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10480.00	66.70	-11.63	55.07	68.20	-13.13	V	Peak
15720.00	60.47	-6.97	53.50	68.20	-14.70	V	Peak
10480.00	64.06	-11.63	52.43	68.20	-15.77	H	Peak
15720.00	60.39	-6.97	53.42	68.20	-14.78	H	Peak
10480.00	47.57	-11.63	35.94	54.00	-18.06	V	AVG
15720.00	43.28	-6.97	36.31	54.00	-17.69	V	AVG
10480.00	46.51	-11.63	34.88	54.00	-19.12	H	AVG
15720.00	42.37	-6.97	35.40	54.00	-18.60	H	AVG

Test Mode: IEEE 802.11ac 20M							
Test channel: Low CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10360.00	66.22	-11.79	54.43	68.20	-13.77	V	Peak
15540.00	60.25	-7.28	52.97	68.20	-15.23	V	Peak
10360.00	65.38	-11.79	53.59	68.20	-14.61	H	Peak
15540.00	60.62	-7.28	53.34	68.20	-14.86	H	Peak
10360.00	46.59	-11.79	34.80	54.00	-19.20	V	AVG
15540.00	43.92	-7.28	36.64	54.00	-17.36	V	AVG
10360.00	47.26	-11.79	35.47	54.00	-18.53	H	AVG
15540.00	41.32	-7.28	34.04	54.00	-19.96	H	AVG
Test channel: Middle CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10400.00	65.35	-11.74	53.61	68.20	-14.59	V	Peak
15600.00	61.97	-7.18	54.79	68.20	-13.41	V	Peak
10400.00	65.56	-11.74	53.82	68.20	-14.38	H	Peak
15600.00	59.04	-7.18	51.86	68.20	-16.34	H	Peak
10400.00	46.10	-11.74	34.36	54.00	-19.64	V	AVG
15600.00	43.55	-7.18	36.37	54.00	-17.63	V	AVG
10400.00	46.20	-11.74	34.46	54.00	-19.54	H	AVG
15600.00	42.93	-7.18	35.75	54.00	-18.25	H	AVG
Test channel: High CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10480.00	66.94	-11.63	55.31	68.20	-12.89	V	Peak
15720.00	61.24	-6.97	54.27	68.20	-13.93	V	Peak
10480.00	65.30	-11.63	53.67	68.20	-14.53	H	Peak
15720.00	60.66	-6.97	53.69	68.20	-14.51	H	Peak
10480.00	47.24	-11.63	35.61	54.00	-18.39	V	AVG
15720.00	43.08	-6.97	36.11	54.00	-17.89	V	AVG
10480.00	47.06	-11.63	35.43	54.00	-18.57	H	AVG
15720.00	41.80	-6.97	34.83	54.00	-19.17	H	AVG

Test Mode: IEEE 802.11ax 20M							
Test channel: Low CH							
Frequency (MHz)	Reading (dBUV)	Factor	Result (dBUV/m)	Limit (dBUV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10360.00	66.13	-11.79	54.34	68.20	-13.86	V	Peak
15540.00	61.58	-7.28	54.30	68.20	-13.90	V	Peak
10360.00	65.37	-11.79	53.58	68.20	-14.62	H	Peak
15540.00	60.42	-7.28	53.14	68.20	-15.06	H	Peak
10360.00	46.57	-11.79	34.78	54.00	-19.22	V	AVG
15540.00	43.46	-7.28	36.18	54.00	-17.82	V	AVG
10360.00	47.19	-11.79	35.40	54.00	-18.60	H	AVG
15540.00	41.24	-7.28	33.96	54.00	-20.04	H	AVG
Test channel: Middle CH							
Frequency (MHz)	Reading (dBUV)	Factor	Result (dBUV/m)	Limit (dBUV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10400.00	65.50	-11.74	53.76	68.20	-14.44	V	Peak
15600.00	60.03	-7.18	52.85	68.20	-15.35	V	Peak
10400.00	65.01	-11.74	53.27	68.20	-14.93	H	Peak
15600.00	59.28	-7.18	52.10	68.20	-16.10	H	Peak
10400.00	47.22	-11.74	35.48	54.00	-18.52	V	AVG
15600.00	43.39	-7.18	36.21	54.00	-17.79	V	AVG
10400.00	46.47	-11.74	34.73	54.00	-19.27	H	AVG
15600.00	42.27	-7.18	35.09	54.00	-18.91	H	AVG
Test channel: High CH							
Frequency (MHz)	Reading (dBUV)	Factor	Result (dBUV/m)	Limit (dBUV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10480.00	66.59	-11.63	54.96	68.20	-13.24	V	Peak
15720.00	61.35	-6.97	54.38	68.20	-13.82	V	Peak
10480.00	64.89	-11.63	53.26	68.20	-14.94	H	Peak
15720.00	60.86	-6.97	53.89	68.20	-14.31	H	Peak
10480.00	46.64	-11.63	35.01	54.00	-18.99	V	AVG
15720.00	42.32	-6.97	35.35	54.00	-18.65	V	AVG
10480.00	47.40	-11.63	35.77	54.00	-18.23	H	AVG
15720.00	41.48	-6.97	34.51	54.00	-19.49	H	AVG

Test Mode: IEEE 802.11n(HT20) 20M							
Test channel: Low CH							
Frequency (MHz)	Reading (dBUV)	Factor	Result (dBUV/m)	Limit	Over limit	Antenna	Detector
		(dB/m)		(dBUV/m)	(dB)	Pol.	
10360.00	65.45	-11.79	53.66	68.20	-14.54	V	Peak
15540.00	60.10	-7.28	52.82	68.20	-15.38	V	Peak
10360.00	65.96	-11.79	54.17	68.20	-14.03	H	Peak
15540.00	59.61	-7.28	52.33	68.20	-15.87	H	Peak
10360.00	47.51	-11.79	35.72	54.00	-18.28	V	AVG
15540.00	43.43	-7.28	36.15	54.00	-17.85	V	AVG
10360.00	47.24	-11.79	35.45	54.00	-18.55	H	AVG
15540.00	41.85	-7.28	34.57	54.00	-19.43	H	AVG
Test channel: Middle CH							
Frequency (MHz)	Reading (dBUV)	Factor	Result (dBUV/m)	Limit	Over limit	Antenna	Detector
		(dB/m)		(dBUV/m)	(dB)	Pol.	
10400.00	65.09	-11.74	53.35	68.20	-14.85	V	Peak
15600.00	61.00	-7.18	53.82	68.20	-14.38	V	Peak
10400.00	65.53	-11.74	53.79	68.20	-14.41	H	Peak
15600.00	59.98	-7.18	52.80	68.20	-15.40	H	Peak
10400.00	47.49	-11.74	35.75	54.00	-18.25	V	AVG
15600.00	42.51	-7.18	35.33	54.00	-18.67	V	AVG
10400.00	46.28	-11.74	34.54	54.00	-19.46	H	AVG
15600.00	42.11	-7.18	34.93	54.00	-19.07	H	AVG
Test channel: High CH							
Frequency (MHz)	Reading (dBUV)	Factor	Result (dBUV/m)	Limit	Over limit	Antenna	Detector
		(dB/m)		(dBUV/m)	(dB)	Pol.	
10480.00	66.88	-11.63	55.25	68.20	-12.95	V	Peak
15720.00	60.22	-6.97	53.25	68.20	-14.95	V	Peak
10480.00	64.76	-11.63	53.13	68.20	-15.07	H	Peak
15720.00	59.57	-6.97	52.60	68.20	-15.60	H	Peak
10480.00	47.62	-11.63	35.99	54.00	-18.01	V	AVG
15720.00	42.53	-6.97	35.56	54.00	-18.44	V	AVG
10480.00	46.58	-11.63	34.95	54.00	-19.05	H	AVG
15720.00	42.85	-6.97	35.88	54.00	-18.12	H	AVG

Test Mode: IEEE 802.11ac 40M							
Test channel: Low CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit	Over limit	Antenna	Detector
		(dB/m)		(dBuV/m)	(dB)	Pol.	
10380.00	67.00	-11.77	55.23	68.20	-12.97	V	Peak
15570.00	60.39	-7.24	53.15	68.20	-15.05	V	Peak
10380.00	64.71	-11.77	52.94	68.20	-15.26	H	Peak
15570.00	60.63	-7.24	53.39	68.20	-14.81	H	Peak
10380.00	46.45	-11.77	34.68	54.00	-19.32	V	AVG
15570.00	42.23	-7.24	34.99	54.00	-19.01	V	AVG
10380.00	47.17	-11.77	35.40	54.00	-18.60	H	AVG
15570.00	42.32	-7.24	35.08	54.00	-18.92	H	AVG
Test channel: High CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit	Over limit	Antenna	Detector
		(dB/m)		(dBuV/m)	(dB)	Pol.	
10460.00	65.48	-11.65	53.83	68.20	-14.37	V	Peak
15690.00	61.03	-7.03	54.00	68.20	-14.20	V	Peak
10460.00	65.57	-11.65	53.92	68.20	-14.28	H	Peak
15690.00	59.77	-7.03	52.74	68.20	-15.46	H	Peak
10460.00	47.55	-11.65	35.90	54.00	-18.10	V	AVG
15690.00	43.06	-7.03	36.03	54.00	-17.97	V	AVG
10460.00	47.98	-11.65	36.33	54.00	-17.67	H	AVG
15690.00	41.61	-7.03	34.58	54.00	-19.42	H	AVG

Test Mode: IEEE 802.11ax 40M							
Test channel: Low CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit	Over limit	Antenna	Detector
		(dB/m)		(dBuV/m)	(dB)	Pol.	
10380.00	65.18	-11.77	53.41	68.20	-14.79	V	Peak
15570.00	61.66	-7.24	54.42	68.20	-13.78	V	Peak
10380.00	65.71	-11.77	53.94	68.20	-14.26	H	Peak
15570.00	60.49	-7.24	53.25	68.20	-14.95	H	Peak
10380.00	46.93	-11.77	35.16	54.00	-18.84	V	AVG
15570.00	43.24	-7.24	36.00	54.00	-18.00	V	AVG
10380.00	46.90	-11.77	35.13	54.00	-18.87	H	AVG
15570.00	41.38	-7.24	34.14	54.00	-19.86	H	AVG
Test channel: High CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit	Over limit	Antenna	Detector
		(dB/m)		(dBuV/m)	(dB)	Pol.	
10460.00	65.06	-11.65	53.41	68.20	-14.79	V	Peak
15690.00	61.15	-7.03	54.12	68.20	-14.08	V	Peak
10460.00	65.72	-11.65	54.07	68.20	-14.13	H	Peak
15690.00	59.82	-7.03	52.79	68.20	-15.41	H	Peak
10460.00	46.64	-11.65	34.99	54.00	-19.01	V	AVG
15690.00	42.10	-7.03	35.07	54.00	-18.93	V	AVG
10460.00	46.93	-11.65	35.28	54.00	-18.72	H	AVG
15690.00	42.22	-7.03	35.19	54.00	-18.81	H	AVG

Test Mode: IEEE 802.11n(HT40) 40M							
Test channel: Low CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit	Over limit	Antenna	Detector
		(dB/m)		(dBuV/m)	(dB)	Pol.	
10380.00	65.54	-11.77	53.77	68.20	-14.43	V	Peak
15570.00	60.18	-7.24	52.94	68.20	-15.26	V	Peak
10380.00	65.81	-11.77	54.04	68.20	-14.16	H	Peak
15570.00	60.90	-7.24	53.66	68.20	-14.54	H	Peak
10380.00	46.18	-11.77	34.41	54.00	-19.59	V	AVG
15570.00	42.34	-7.24	35.10	54.00	-18.90	V	AVG
10380.00	47.18	-11.77	35.41	54.00	-18.59	H	AVG
15570.00	41.42	-7.24	34.18	54.00	-19.82	H	AVG
Test channel: High CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit	Over limit	Antenna	Detector
		(dB/m)		(dBuV/m)	(dB)	Pol.	
10460.00	65.47	-11.65	53.82	68.20	-14.38	V	Peak
15690.00	60.09	-7.03	53.06	68.20	-15.14	V	Peak
10460.00	65.87	-11.65	54.22	68.20	-13.98	H	Peak
15690.00	60.51	-7.03	53.48	68.20	-14.72	H	Peak
10460.00	46.12	-11.65	34.47	54.00	-19.53	V	AVG
15690.00	43.75	-7.03	36.72	54.00	-17.28	V	AVG
10460.00	46.76	-11.65	35.11	54.00	-18.89	H	AVG
15690.00	42.12	-7.03	35.09	54.00	-18.91	H	AVG

U-NII-2A:

Test Mode: IEEE 802.11ac 20M							
Test channel: Low CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10520.00	66.34	-11.57	54.77	68.20	-13.43	V	Peak
15780.00	60.35	-6.88	53.47	68.20	-14.73	V	Peak
10520.00	64.65	-11.57	53.08	68.20	-15.12	H	Peak
15780.00	59.47	-6.88	52.59	68.20	-15.61	H	Peak
10520.00	46.46	-11.57	34.89	54.00	-19.11	V	AVG
15780.00	42.21	-6.88	35.33	54.00	-18.67	V	AVG
10520.00	46.13	-11.57	34.56	54.00	-19.44	H	AVG
15780.00	42.59	-6.88	35.71	54.00	-18.29	H	AVG
Test channel: Middle CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10600.00	65.44	-11.46	53.98	68.20	-14.22	V	Peak
15900.00	60.51	-6.67	53.84	68.20	-14.36	V	Peak
10600.00	65.39	-11.46	53.93	68.20	-14.27	H	Peak
15900.00	59.32	-6.67	52.65	68.20	-15.55	H	Peak
10600.00	47.56	-11.46	36.10	54.00	-17.90	V	AVG
15900.00	43.44	-6.67	36.77	54.00	-17.23	V	AVG
10600.00	47.49	-11.46	36.03	54.00	-17.97	H	AVG
15900.00	41.39	-6.67	34.72	54.00	-19.28	H	AVG
Test channel: High CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
10640.00	65.82	-11.41	54.41	68.20	-13.79	V	Peak
15960.00	60.48	-6.57	53.91	68.20	-14.29	V	Peak
10640.00	64.52	-11.41	53.11	68.20	-15.09	H	Peak
15960.00	59.66	-6.57	53.09	68.20	-15.11	H	Peak
10640.00	46.41	-11.41	35.00	54.00	-19.00	V	AVG
15960.00	43.18	-6.57	36.61	54.00	-17.39	V	AVG
10640.00	47.36	-11.41	35.95	54.00	-18.05	H	AVG
15960.00	41.55	-6.57	34.98	54.00	-19.02	H	AVG

U-NII-2C:

Test Mode: IEEE 802.11ac 40M							
Test channel: Low CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
11020.00	65.44	-10.88	54.56	68.20	-13.64	V	Peak
16530.00	61.06	-5.75	55.31	68.20	-12.89	V	Peak
11020.00	65.67	-10.88	54.79	68.20	-13.41	H	Peak
16530.00	60.87	-5.75	55.12	68.20	-13.08	H	Peak
11020.00	47.38	-10.88	36.50	54.00	-17.50	V	AVG
16530.00	43.16	-5.75	37.41	54.00	-16.59	V	AVG
11020.00	47.20	-10.88	36.32	54.00	-17.68	H	AVG
16530.00	42.23	-5.75	36.48	54.00	-17.52	H	AVG
Test channel: Middle CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
11180.00	65.09	-10.78	54.31	68.20	-13.89	V	Peak
16770.00	60.19	-5.42	54.77	68.20	-13.43	V	Peak
11180.00	64.93	-10.78	54.15	68.20	-14.05	H	Peak
16770.00	59.69	-5.42	54.27	68.20	-13.93	H	Peak
11180.00	47.10	-10.78	36.32	54.00	-17.68	V	AVG
16770.00	43.23	-5.42	37.81	54.00	-16.19	V	AVG
11180.00	46.72	-10.78	35.94	54.00	-18.06	H	AVG
16770.00	42.40	-5.42	36.98	54.00	-17.02	H	AVG
Test channel: High CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
11340.00	65.76	-10.67	55.09	68.20	-13.11	V	Peak
17010.00	60.08	-5.11	54.97	68.20	-13.23	V	Peak
11340.00	65.03	-10.67	54.36	68.20	-13.84	H	Peak
17010.00	60.72	-5.11	55.61	68.20	-12.59	H	Peak
11340.00	46.49	-10.67	35.82	54.00	-18.18	V	AVG
17010.00	42.04	-5.11	36.93	54.00	-17.07	V	AVG
11340.00	47.51	-10.67	36.84	54.00	-17.16	H	AVG
17010.00	41.90	-5.11	36.79	54.00	-17.21	H	AVG

U-NII-3:

Test Mode: IEEE 802.11ac 40M							
Test channel: Low CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
11510.00	66.76	-10.54	56.22	68.20	-11.98	V	Peak
17265.00	60.45	-5.24	55.21	68.20	-12.99	V	Peak
11510.00	64.99	-10.54	54.45	68.20	-13.75	H	Peak
17265.00	59.76	-5.24	54.52	68.20	-13.68	H	Peak
11510.00	47.20	-10.54	36.66	54.00	-17.34	V	AVG
17265.00	43.57	-5.24	38.33	54.00	-15.67	V	AVG
11510.00	47.89	-10.54	37.35	54.00	-16.65	H	AVG
17265.00	42.51	-5.24	37.27	54.00	-16.73	H	AVG
Test channel: High CH							
Frequency (MHz)	Reading (dBuV)	Factor	Result (dBuV/m)	Limit (dBuV/m)	Over limit (dB)	Antenna	Detector
		(dB/m)				Pol.	
11550.00	65.26	-10.51	54.75	68.20	-13.45	V	Peak
17325.00	60.66	-5.26	55.40	68.20	-12.80	V	Peak
11550.00	64.68	-10.51	54.17	68.20	-14.03	H	Peak
17325.00	60.32	-5.26	55.06	68.20	-13.14	H	Peak
11550.00	46.82	-10.51	36.31	54.00	-17.69	V	AVG
17325.00	43.20	-5.26	37.94	54.00	-16.06	V	AVG
11550.00	47.03	-10.51	36.52	54.00	-17.48	H	AVG
17325.00	42.64	-5.26	37.38	54.00	-16.62	H	AVG

Note:

1. Level = Read Level + Antenna Factor+ Cable loss- Preamplifier Factor.
2. The test trace is same as the ambient noise (the test frequency range: 18GHz~40GHz), therefore no data appear in the report.
3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.
4. This Report only show the test plots of the worst case.

4.8 Frequency stability

Test Standard	15.407(f), RSS-Gen §6.11
Test limit	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.
Test results:	Pass

Measurement Data:

Mode	Voltage (V)	FHL (5180MHz)	Deviation (KHz)	FHH (5240MHz)	Deviation (KHz)
Band 1 (5150-5250 MHz)	DC 10.8V	5179.996	4	5239.995	5
	DC 12V	5179.998	2	5239.998	2
	DC 13.2V	5179.998	2	5239.998	2
Mode	Voltage (V)	FHL (5260MHz)	Deviation (KHz)	FHH (5320MHz)	Deviation (KHz)
Band 2 (5250-5350 MHz)	DC 10.8V	5259.997	3	5319.991	9
	DC 12V	5259.993	7	5319.998	2
	DC 13.2V	5259.999	1	5319.997	3
Mode	Voltage (V)	FHL (5500MHz)	Deviation (KHz)	FHH (5700MHz)	Deviation (KHz)
Band 3 (5470-5725 MHz)	DC 10.8V	5499.993	7	5699.999	1
	DC 12V	5499.998	2	5699.995	5
	DC 13.2V	5499.994	6	5699.996	4
Mode	Voltage (V)	FHL (5745MHz)	Deviation (KHz)	FHH (5825MHz)	Deviation (KHz)
Band 4 (5725-5850 MHz)	DC 10.8V	5744.992	8	5824.997	3
	DC 12V	5744.991	9	5824.997	3
	DC 13.2V	5744.998	2	5824.992	8

Mode	Temperature (°C)	FHL (5180MHz)	Deviation (KHz)	FHH (5240MHz)	Deviation (KHz)
Band 1 (5150-5250 MHz)	-10°C	5179.992	8	5239.997	3
	0°C	5179.996	4	5239.993	7
	+10°C	5179.997	3	5239.995	5
	+20°C	5179.992	8	5239.995	5
	+30°C	5179.993	7	5239.995	5
	+40°C	5179.995	5	5239.995	5
	+50°C	5179.993	7	5239.991	9
Mode	Temperature (°C)	FHL (5260MHz)	Deviation (KHz)	FHH (5320MHz)	Deviation (KHz)
Band 2 (5250-5350 MHz)	-10°C	5259.993	7	5319.992	8
	0°C	5259.998	2	5319.994	6
	+10°C	5259.999	1	5319.999	1
	+20°C	5259.993	7	5319.999	1
	+30°C	5259.998	2	5319.991	9
	+40°C	5259.995	5	5319.994	6
	+50°C	5259.994	6	5319.998	2
	-10°C	5259.991	9	5319.995	5
Mode	Temperature (°C)	FHL (5500MHz)	Deviation (KHz)	FHH (5700MHz)	Deviation (KHz)
Band 3 (5470-5725 MHz)	-10°C	5499.996	4	5699.993	7
	0°C	5499.995	5	5699.994	6
	+10°C	5499.997	3	5699.993	7
	+20°C	5499.993	7	5699.998	2
	+30°C	5499.993	7	5699.993	7
	+40°C	5499.999	1	5699.999	1
	+50°C	5499.996	4	5699.991	9
	-10°C	5499.999	1	5699.995	5
Mode	Temperature (°C)	FHL (5745MHz)	Deviation (KHz)	FHH (5825MHz)	Deviation (KHz)
Band 4 (5725-5850 MHz)	-10°C	5744.994	6	5824.998	2
	0°C	5744.995	5	5824.996	4
	+10°C	5744.995	5	5824.995	5
	+20°C	5744.999	1	5824.994	6
	+30°C	5744.991	9	5824.993	7
	+40°C	5744.996	4	5824.999	1
	+50°C	5744.992	8	5824.998	2

5 Photos Of Test Setup

Reference to the test report **appendix I Test Setup Photo** for details.

6 Photos Of EUT

Reference to the test report **appendix II external photos** and **appendix III internal photos** for details.

-----END OF REPORT-----

