
Antenna specification


1 、 Antenna introduction

The Bluetooth module antenna is directly used on the PCB.

Manufacturer: Lenze Design Inc

Address : 7th Floor,Ching Po Building,Shenzhen Special Zone Press Group,Futian District,Shenzhen

2 、 Antenna shape



3 、 Antenna parameter

The Bluetooth antenna operates at 2402-2480 MHz and generates resonance in this band. The table below shows the main parameters of the antenna.

Frequency (MHz)	2402 ~ 2480 MHz
VSWR	≤ 1.95
Impedance	50 Ohm Nominal
Return Loss	-15 dB Max
Radiation	Omni-directional
Gain (Peak)	3.63 dBi
Polarization	Linear, Vertical
Admitted Power	1MW
Connector	Tin

4 、 Antenna gain report

Spectrum Detector:	PK	Test Date :	Feb 18, 2019
Test By:	Mark	Temperature :	2 5 C
Test Result:	PASS	Humidity :	52 %
Modulation:	GFSK		

Frequency VNA (MHz)	E Total. dB(dB)	Gain (dBi)
2400MHz	0. 0403503	3. 56
2410MHz	0. 0886264	3. 63
2420MHz	0. 267381	3. 46
2430MHz	0. 193012	3. 35
2440MHz	0. 26366	3. 24
2450MHz	0. 0723139	3. 57
2460MHz	0. 36895	3. 63
2470MHz	0. 551525	3. 41
2480MHz	0. 640702	3. 24
2490MHz	1. 05232	3. 05
2500MHz	1. 08443	2. 91

Direction map:

