



# FCC PART 15.247 TEST REPORT

On Behalf of  
**Shenzhen ComXim Technologies Co.,Ltd.**

2F Block A and B, Donghaiwang IndustrialZone, No. 369 BulongRoad, Longgang  
District, Shenzhen

**FCC ID: 2BB29-UT500RUWXXXL**  
**Model: UT500RUWTPSYL150ProV6-B**

Mar. 13, 2026

|                                                                                                                                                                                                                                                                                  |                                              |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| <b>This Report Concerns:</b><br><input checked="" type="checkbox"/> Original Report                                                                                                                                                                                              | <b>Equipment Type:</b><br>Electric Turntable |
| <b>Test Engineer:</b> Fan Yang / <i>Fan Yang</i>                                                                                                                                                                                                                                 |                                              |
| <b>Report Number:</b> QCT26BR-0008E-01                                                                                                                                                                                                                                           |                                              |
| <b>Test Date:</b> Jan. 21, 2026~Feb. 12, 2026                                                                                                                                                                                                                                    |                                              |
| <b>Test Result:</b> Pass                                                                                                                                                                                                                                                         |                                              |
| <b>Reviewed By:</b> Vincent Yang / <i>Vincent Yang</i>                                                                                                                                                                                                                           |                                              |
| <b>Approved By:</b> Kendy Wang / <i>Kendy Wang</i>                                                                                                                                                                                                                               |                                              |
| <b>Prepared By:</b> Shenzhen QC Testing Laboratory Co., Ltd.<br>East of 1/F., Building E, Xinghong Science Park, No.111,<br>Shuiku Road, Fenghuanggang, Xixiang Street, Bao'an<br>District, Shenzhen, Guangdong, China<br><b>Tel: 0755-23008269</b><br><b>Fax: 0755-23726780</b> |                                              |





# Table of Contents

|                                                                |           |
|----------------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION.....</b>                             | <b>5</b>  |
| 1.1 Product Description for Equipment under Test (EUT) .....   | 5         |
| 1.2 System Test Configuration .....                            | 7         |
| 1.3 Test Facility .....                                        | 8         |
| 1.4 Measurement Uncertainty .....                              | 8         |
| <b>2. SUMMARY OF TEST RESULTS .....</b>                        | <b>9</b>  |
| <b>3. LIST OF TEST AND MEASUREMENT INSTRUMENTS .....</b>       | <b>10</b> |
| 3.1 Conducted Emission Test .....                              | 10        |
| 3.2 Radiated Emission Test .....                               | 10        |
| 3.3 RF Conducted test .....                                    | 11        |
| <b>4. ANTENNA REQUIREMENT.....</b>                             | <b>12</b> |
| <b>5. CONDUCTED EMISSIONS.....</b>                             | <b>13</b> |
| 5.1 Applicable Standard .....                                  | 13        |
| 5.2 Limit .....                                                | 13        |
| 5.3 Test setup.....                                            | 13        |
| 5.4 EMI Test Receiver Setup.....                               | 13        |
| 5.5 Test procedure .....                                       | 13        |
| 5.6 Test Data .....                                            | 13        |
| <b>6. CONDUCTED PEAK OUTPUT POWER.....</b>                     | <b>16</b> |
| 6.1 Applicable Standard .....                                  | 16        |
| 6.2 Limit .....                                                | 16        |
| 6.3 Test setup.....                                            | 16        |
| 6.4 Test Procedure .....                                       | 16        |
| 6.5 Test Data .....                                            | 17        |
| <b>7. CHANNEL BANDWIDTH &amp; 99% OCCUPIED BANDWIDTH .....</b> | <b>19</b> |
| 7.1 Applicable Standard .....                                  | 19        |
| 7.2 Limit .....                                                | 19        |
| 7.3 Test setup.....                                            | 19        |
| 7.4 Test Procedure .....                                       | 19        |
| 7.5 Test Data .....                                            | 19        |
| <b>8. POWER SPECTRAL DENSITY .....</b>                         | <b>33</b> |
| 8.1 Applicable Standard .....                                  | 33        |
| 8.2 Limit .....                                                | 33        |
| 8.3 Test setup.....                                            | 33        |
| 8.4 Test Procedure .....                                       | 33        |
| 8.5 Test Data .....                                            | 33        |



## 9. SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS..... 41

### 9.1 Conducted Emission Method .....41

### 9.2 Radiated Emission Method .....66



## Revision History of This Test Report

[illegible]



## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EUT Description              | Electric Turntable                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Model No.                    | UT500RUWTPSYL150ProV6-B, UT500RUWTPSYL150ProV6-W,<br>UT500RUWPSL150ProV6-B, UT500RUWPSL150ProV6-W,<br>UT500RUWTYL150ProV6-B, UT500RUWTYL150ProV6-W,<br>UT500RUWTL150ProV6-B, UT500RUWTL150ProV6-W,<br>UT500RUWL150ProV6-B, UT500RUWL150ProV6-W,<br>UT500RUTYL150ProV6-B, UT500RUTYL150ProV6-W,<br>UT500RUYL150ProV6-B, UT500RUYL150ProV6-W,<br>UT500RUL150ProV6-B, UT500RUL150ProV6-W, UT500RL150V6-B,<br>UT500RL150V6-W, UT500RL150JV6-B, UT500RL150JV6-W |
| Model Difference:            | PCB board, structure and internal of these model(s) are the same,<br>Just difference is the appearance color and model.                                                                                                                                                                                                                                                                                                                                    |
| Tested Model                 | UT500RUWTPSYL150ProV6-B                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Sample(s) Status             | Engineer sample                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Operation Frequency:         | 802.11b/802.11g/802.11n(HT20): 2412MHz~2462MHz<br>/802.11n(HT40): 2412MHz~2452MHz                                                                                                                                                                                                                                                                                                                                                                          |
| Channel numbers:             | 802.11b/802.11g /802.11n(HT20): 11<br>802.11n(HT40): 7                                                                                                                                                                                                                                                                                                                                                                                                     |
| Channel separation:          | 5MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Modulation type:             | 802.11b: Direct Sequence Spread Spectrum (DSSS)<br>802.11g/802.11n(HT20)/802.11n(HT40):<br>Orthogonal Frequency Division Multiplexing (OFDM)                                                                                                                                                                                                                                                                                                               |
| Antenna Type:                | PCB antenna                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Antenna gain* <sup>1</sup> : | 0dBi                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Power supply:                | Power Input: AC 100-240V/50/60Hz<br>Output:15V=2A, 30W                                                                                                                                                                                                                                                                                                                                                                                                     |
| Trade Mark:                  | COMXIM                                                                                                                                                                                                                                                                                                                                                                                                                                                     |



|               |                                                                                                  |
|---------------|--------------------------------------------------------------------------------------------------|
| Applicant:    | Shenzhen ComXim Technologies Co.,Ltd.                                                            |
| Address:      | 2F Block A and B, Donghaiwang IndustrialZone, No. 369<br>BulongRoad, Longgang District, Shenzhen |
| Manufacturer: | Shenzhen ComXim Technologies Co.,Ltd.                                                            |
| Address:      | 2F Block A and B, Donghaiwang IndustrialZone, No. 369<br>BulongRoad, Longgang District, Shenzhen |
| Sample No.:   | Y26A0008E01WC                                                                                    |

Note: \*1This information provided by Manufacturer, SZ QC Lab is not responsible for the accuracy of this information.

## 1.2 System Test Configuration

### 1.2.1 Channel List

| Operation Frequency each of channel |           |         |           |         |           |         |           |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                             | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1                                   | 2412MHz   | 4       | 2427MHz   | 7       | 2442MHz   | 10      | 2457MHz   |
| 2                                   | 2417MHz   | 5       | 2432MHz   | 8       | 2447MHz   | 11      | 2462MHz   |
| 3                                   | 2422MHz   | 6       | 2437MHz   | 9       | 2452MHz   |         |           |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Test channel    | Frequency (MHz)               |  |
|-----------------|-------------------------------|--|
|                 | 802.11b/802.11g/802.11n(HT20) |  |
| Lowest channel  | 2412MHz                       |  |
| Middle channel  | 2437MHz                       |  |
| Highest channel | 2462MHz                       |  |
| Test channel    | Frequency (MHz)               |  |
|                 | 802.11n(HT40)                 |  |
| Lowest channel  | 2422MHz                       |  |
| Middle channel  | 2437MHz                       |  |
| Highest channel | 2452MHz                       |  |

### 1.2.2 EUT Exercise Software

"adb" exercise software was made to the EUT tested, The power level is 60. The software and power level was provided by the applicant.

### 1.2.3 Support Equipment

| Manufacturer | Description       | Model         | Serial Number |
|--------------|-------------------|---------------|---------------|
| DELL         | Portable computer | InSpiron 3501 | /             |

### 1.2.4 Test mode and test voltage

Transmitting mode: Keep the EUT in continuously transmitting.

Test voltage: DC 15V (Powered by adapter)



### 1.3 Test Facility

Test Firm : Shenzhen QC Testing Laboratory Co., Ltd.

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19. The testing quality system of our laboratory meets with ISO/IEC-17025 requirements. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS – Registration No.: L8464

The EMC Laboratory has been accredited by CNAS, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

A2LA Certificate Number: 6759.01

The EMC Laboratory has been accredited by A2LA, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

FCC Registration Number: 561109

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission.

IC Registration Number: 29628

CAB identifier: CN0141

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada.

### 1.4 Measurement Uncertainty

| Parameter                                          | Uncertainty                 |
|----------------------------------------------------|-----------------------------|
| Occupied Channel Bandwidth                         | $\pm 1.42 \times 10^{-4}\%$ |
| RF output power, conducted                         | $\pm 1.06\text{dB}$         |
| Power Spectral Density, conducted                  | $\pm 1.06\text{dB}$         |
| Unwanted Emissions, conducted                      | $\pm 2.51\text{dB}$         |
| AC Power Line Conducted Emission                   | $\pm 1.80\text{dB}$         |
| Radiated Spurious Emission test (9kHz-30MHz)       | $\pm 2.66\text{dB}$         |
| Radiated Spurious Emission test (30MHz-1000MHz)    | $\pm 4.04\text{dB}$         |
| Radiated Spurious Emission test (1000MHz-18000MHz) | $\pm 4.70\text{ dB}$        |
| Radiated Spurious Emission test (18GHz-40GHz)      | $\pm 4.80\text{dB}$         |
| Temperature                                        | $\pm 0.8^{\circ}\text{C}$   |
| Humidity                                           | $\pm 3.2\%$                 |
| DC and low frequency voltages                      | $\pm 0.1\%$                 |
| Time                                               | $\pm 5\%$                   |
| Duty cycle                                         | $\pm 5\%$                   |

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$



## 2. Summary of Test Results

| Test Item                                  | Section                    | Result |
|--------------------------------------------|----------------------------|--------|
| Antenna Requirement                        | FCC part 15.203/15.247 (c) | Pass   |
| AC Power Line Conducted Emission           | FCC part 15.207            | Pass   |
| Conducted Peak Output Power                | FCC part 15.247 (b)(3)     | Pass   |
| Channel Bandwidth & 99% Occupied Bandwidth | FCC part 15.247 (a)(2)     | Pass   |
| Power Spectral Density                     | FCC part 15.247 (e)        | Pass   |
| Band Edge                                  | FCC part 15.247(d)         | Pass   |
| Spurious Emissions                         | FCC part 15.205/15.209     | Pass   |

- Note:
1. Pass: The EUT complies with the essential requirements in the standard.
  2. Test according to ANSI C63.10:2020
  - 3.. All indications of Pass/Fail in this report are opinions expressed by Shenzhen QC Testing Laboratory Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.



### 3. List of Test and Measurement Instruments

#### 3.1 Conducted Emission Test

| Item | Equipment                | Manufacturer  | Model No. | Serial No. | Last Cal.  | Cal.Due    |
|------|--------------------------|---------------|-----------|------------|------------|------------|
| 1    | EMI Test Receiver        | Rohde&Schwarz | ESIB 7    | 2277573376 | 2025.03.14 | 2026.03.13 |
| 2    | EMI Test Receiver        | Rohde&Schwarz | ESCI3     | 101820     | 2025.08.05 | 2026.08.04 |
| 3    | Artificial Mains Network | SCHWARZBECK   | NSLK8126  | 8126200    | 2025.08.05 | 2026.08.04 |
| 4    | PULSE LIMITER            | Rohde&Schwarz | ESH3-Z2   | 100058     | 2025.03.14 | 2026.03.13 |

Conducted Emission Measurement Software: TS+ JS32-CE Ver 5.0.0

#### 3.2 Radiated Emission Test

| Item | Equipment                     | Manufacturer            | Model No.           | Serial No.   | Last Cal.  | Cal.Due    |
|------|-------------------------------|-------------------------|---------------------|--------------|------------|------------|
| 1.   | EMI Test Receiver             | Rohde&Schwarz           | ESIB 7              | 2277573376   | 2025.03.17 | 2026.03.16 |
| 2.   | EMI Test Receiver             | Rohde&Schwarz           | ESPI                | 101131       | 2025.03.17 | 2026.03.16 |
| 3.   | Spectrum Analyzer             | Rohde&Schwarz           | FSV 40              | 101458       | 2025.03.18 | 2026.03.17 |
| 4.   | TRILOG Broadband Test-Antenna | SCHWARZBECK             | VULB9168            | VULB9168-588 | 2025.03.22 | 2026.03.21 |
| 5.   | Loop Antenna                  | EMCO                    | 6502                | 2133         | 2025.03.19 | 2026.03.18 |
| 6.   | horn antenna                  | SCHWARZBECK             | BBHA9120D           | 2069         | 2024.08.10 | 2026.08.09 |
| 7.   | Horn Antenna                  | COM-MW                  | ZLB7-18-40G-950     | 12221225     | 2024.08.10 | 2026.08.09 |
| 8.   | Pre-amplifier                 | MITEQ                   | TTA0001-18          | 2063645      | 2025.03.17 | 2026.03.16 |
| 9.   | Pre-amplifier                 | COM-MW                  | DLAN-18000-40000-02 | 10229104     | 2025.03.17 | 2026.03.16 |
| 10.  | 966 Camber                    | ZhongYU                 | 9*6*6               | /            | 2025.05.08 | 2026.05.07 |
| 11   | Bandstop filter               | Kangmaiwei              | ZBSF6-C2400-2483.5  | 11210688     | 2025.03.13 | 2026.03.14 |
| 12   | High frequency cable          | TIMES Microwave Ststems | SFT205-NMRA NM 18G  | 20202030-001 | /          | /          |
| 13   | Low frequency cable           | TIMES Microwave Ststems | SFT205PUR-N MRANM   | 558700-0001  | /          | /          |

Radiated Emission Measurement Software: EZ\_EMC Ver QCT03A2 RE+



### 3.3 RF Conducted test

| Item                                                    | Equipment                           | Manufacturer    | Model No.                | Serial No. | Last Cal.  | Cal.Due    |
|---------------------------------------------------------|-------------------------------------|-----------------|--------------------------|------------|------------|------------|
| 1.                                                      | Wideband Radio Communication Tester | Rohde & Schwarz | CW500                    | 151583     | 2025.03.13 | 2026.03.14 |
| 2.                                                      | MXA Signal Analyzer                 | Keysight        | N9020A                   | MY51281805 | 2025.03.13 | 2026.03.14 |
| 3.                                                      | Signal Generator                    | Agilent         | N5182A                   | MY50141563 | 2025.03.13 | 2026.03.14 |
| 4.                                                      | RF Automatic Test System            | MW              | MW100-RFCB/<br>MW100-PSB | MW2007004  | 2025.03.13 | 2026.03.14 |
| RF Conducted Measurement Software: MTS 8310 Ver 2.0.0.0 |                                     |                 |                          |            |            |            |



## 4. Antenna requirement

**Standard requirement:** FCC Part15 C Section 15.203 /247(c)

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

**EUT Antenna:** The Antenna is PCB Antenna, the best case gain of the antenna is 0dBi, reference to the Internal photo for details.

## 5. Conducted Emissions

### 5.1 Applicable Standard


FCC Part15 C Section 15.207

### 5.2 Limit

| Frequency range (MHz) | Limit (dBμV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

Note \*: The level decreases linearly with the logarithm of the frequency.

### 5.3 Test setup



Remark:  
E.U.T: Equipment Under Test  
LISN: Line Impedance Stabilization Network  
Test table height=0.8m

### 5.4 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.  
RBW=9 kHz, VBW=30 kHz, Sweep time=auto

### 5.5 Test procedure

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

### 5.6 Test Data


|              |           |              |      |
|--------------|-----------|--------------|------|
| Temperature  | 24.9 °C   | Humidity     | 59%  |
| ATM Pressure | 101.1kPa  | Antenna Gain | 0dBi |
| Test by      | Zekka Yin | Test result  | PASS |



### Measurement data:

Pre-scan all test modes, found worst case at 11n20 2412MHz, and so only show the test result of 11n20 2412MHz

Line:




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 0.2625          | 34.79          | 10.58       | 45.37        | 61.35        | -15.98      | QP       |
| 2   | 0.2895          | 20.05          | 10.58       | 30.63        | 50.54        | -19.91      | AVG      |
| 3 * | 0.5190          | 40.65          | 10.65       | 51.30        | 56.00        | -4.70       | QP       |
| 4   | 0.5370          | 26.63          | 10.65       | 37.28        | 46.00        | -8.72       | AVG      |
| 5   | 0.8835          | 22.06          | 10.64       | 32.70        | 46.00        | -13.30      | AVG      |
| 6   | 0.9195          | 37.50          | 10.65       | 48.15        | 56.00        | -7.85       | QP       |
| 7   | 3.0255          | 17.55          | 10.71       | 28.26        | 46.00        | -17.74      | AVG      |
| 8   | 3.3720          | 33.00          | 10.72       | 43.72        | 56.00        | -12.28      | QP       |
| 9   | 8.2400          | 18.14          | 10.77       | 28.91        | 50.00        | -21.09      | AVG      |
| 10  | 8.6810          | 32.18          | 10.78       | 42.96        | 60.00        | -17.04      | QP       |
| 11  | 29.5615         | 20.14          | 11.02       | 31.16        | 50.00        | -18.84      | AVG      |
| 12  | 29.7595         | 26.45          | 11.02       | 37.47        | 60.00        | -22.53      | QP       |



Neutral:

80.0 dBuV



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 0.1545          | 18.88          | 10.58       | 29.46        | 55.75        | -26.29      | AVG      |
| 2   | 0.1949          | 36.93          | 10.55       | 47.48        | 63.83        | -16.35      | QP       |
| 3 * | 0.5235          | 38.71          | 10.65       | 49.36        | 56.00        | -6.64       | QP       |
| 4   | 0.5415          | 22.70          | 10.65       | 33.35        | 46.00        | -12.65      | AVG      |
| 5   | 0.7890          | 18.19          | 10.65       | 28.84        | 46.00        | -17.16      | AVG      |
| 6   | 0.9555          | 32.43          | 10.64       | 43.07        | 56.00        | -12.93      | QP       |
| 7   | 2.3055          | 29.54          | 10.72       | 40.26        | 56.00        | -15.74      | QP       |
| 8   | 2.5215          | 13.63          | 10.76       | 24.39        | 46.00        | -21.61      | AVG      |
| 9   | 4.8300          | 30.39          | 10.84       | 41.23        | 56.00        | -14.77      | QP       |
| 10  | 5.2385          | 13.91          | 10.84       | 24.75        | 50.00        | -25.25      | AVG      |
| 11  | 11.3185         | 29.98          | 10.97       | 40.95        | 60.00        | -19.05      | QP       |
| 12  | 11.8495         | 13.70          | 10.98       | 24.68        | 50.00        | -25.32      | AVG      |

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.

## 6. Conducted Peak Output Power

### 6.1 Applicable Standard


FCC Part15 C Section 15.247 (b)(3)

### 6.2 Limit

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

### 6.3 Test setup



### 6.4 Test Procedure

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.



## 6.5 Test Data

|              |           |              |      |
|--------------|-----------|--------------|------|
| Temperature  | 23.8 °C   | Humidity     | 52%  |
| ATM Pressure | 101.1kPa  | Antenna Gain | 0dBi |
| Test by      | Zekka Yin | Test result  | PASS |


Please refer to following table and plots.

### Output Power:

| Modulation    | CH No. | Frequency (MHz) | Output Power (dBm) | Limit (dBm) | Verdict |
|---------------|--------|-----------------|--------------------|-------------|---------|
| 802.11b       | 01     | 2412            | 10.57              | ≤30         | PASS    |
|               | 06     | 2437            | 11.06              | ≤30         | PASS    |
|               | 11     | 2462            | <b>11.15</b>       | ≤30         | PASS    |
| 802.11g       | 01     | 2412            | 11.40              | ≤30         | PASS    |
|               | 06     | 2437            | 11.54              | ≤30         | PASS    |
|               | 11     | 2462            | <b>12.25</b>       | ≤30         | PASS    |
| 802.11n(HT20) | 01     | 2412            | 14.74              | ≤30         | PASS    |
|               | 06     | 2437            | <b>16.93</b>       | ≤30         | PASS    |
|               | 11     | 2462            | 15.43              | ≤30         | PASS    |
| 802.11n(HT40) | 03     | 2422            | 14.85              | ≤30         | PASS    |
|               | 06     | 2437            | <b>14.89</b>       | ≤30         | PASS    |
|               | 09     | 2452            | 14.89              | ≤30         | PASS    |

**Duty cycle:**

| Test Mode | Antenna | Channel | Total Time (Ton)<br>[ms] | Test Period(Tp)<br>[ms] | Duty Cycle<br>[%] |
|-----------|---------|---------|--------------------------|-------------------------|-------------------|
| 11B       | Ant1    | 2437    | 1.92                     | 2.05                    | 93.66             |
| 11G       | Ant1    | 2437    | 2.06                     | 2.19                    | 94.06             |
| 11N20SISO | Ant1    | 2437    | 1.92                     | 2.05                    | 93.66             |
| 11N40SISO | Ant1    | 2437    | 0.95                     | 1.08                    | 87.96             |



## 7. Channel Bandwidth & 99% Occupied Bandwidth


### 7.1 Applicable Standard

FCC Part15 C Section 15.247 (a)(2)

### 7.2 Limit

The minimum 6 dB bandwidth shall be 500 kHz.

### 7.3 Test setup



### 7.4 Test Procedure

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

### 7.5 Test Data

|              |           |              |      |
|--------------|-----------|--------------|------|
| Temperature  | 23.8 °C   | Humidity     | 52%  |
| ATM Pressure | 101.1kPa  | Antenna Gain | 0dBi |
| Test by      | Zekka Yin | Test result  | PASS |

Please refer to following table and plots.



**DTS Bandwidth:**

| Modulation    | CH No. | Frequency (MHz) | DTS Bandwidth (MHz) | Limit (MHz) | Verdict |
|---------------|--------|-----------------|---------------------|-------------|---------|
| 802.11b       | 01     | 2412            | 10.120              | 0.5         | PASS    |
|               | 06     | 2437            | 10.080              | 0.5         | PASS    |
|               | 11     | 2462            | 10.080              | 0.5         | PASS    |
| 802.11g       | 01     | 2412            | 16.440              | 0.5         | PASS    |
|               | 06     | 2437            | 16.360              | 0.5         | PASS    |
|               | 11     | 2462            | 16.400              | 0.5         | PASS    |
| 802.11n(HT20) | 01     | 2412            | 17.440              | 0.5         | PASS    |
|               | 06     | 2437            | 17.440              | 0.5         | PASS    |
|               | 11     | 2462            | 17.480              | 0.5         | PASS    |
| 802.11n(HT40) | 03     | 2422            | 35.600              | 0.5         | PASS    |
|               | 06     | 2437            | 35.680              | 0.5         | PASS    |
|               | 09     | 2452            | 35.600              | 0.5         | PASS    |

**99% Occupied Bandwidth:**

| Modulation    | CH No. | Frequency (MHz) | 99% Bandwidth (MHz) | Limit (MHz) | Verdict |
|---------------|--------|-----------------|---------------------|-------------|---------|
| 802.11b       | 01     | 2412            | 14.483              | ---         | PASS    |
|               | 06     | 2437            | 14.472              | ---         | PASS    |
|               | 11     | 2462            | 14.519              | ---         | PASS    |
| 802.11g       | 01     | 2412            | 16.549              | ---         | PASS    |
|               | 06     | 2437            | 16.539              | ---         | PASS    |
|               | 11     | 2462            | 16.600              | ---         | PASS    |
| 802.11n(HT20) | 01     | 2412            | 17.705              | ---         | PASS    |
|               | 06     | 2437            | 17.749              | ---         | PASS    |
|               | 11     | 2462            | 17.767              | ---         | PASS    |
| 802.11n(HT40) | 03     | 2422            | 35.773              | ---         | PASS    |
|               | 06     | 2437            | 35.789              | ---         | PASS    |
|               | 09     | 2452            | 35.885              | ---         | PASS    |

**DTS Bandwidth:**

-6dB Bandwidth NVNT 11B Ant1 2412



-6dB Bandwidth NVNT 11B Ant1 2437





-6dB Bandwidth NVNT 11B Ant1 2462



-6dB Bandwidth NVNT 11G Ant1 2412





-6dB Bandwidth NVNT 11G Ant1 2437



-6dB Bandwidth NVNT 11G Ant1 2462



## -6dB Bandwidth NVNT 11N20 Ant1 2412



## -6dB Bandwidth NVNT 11N20 Ant1 2437





### -6dB Bandwidth NVNT 11N20 Ant1 2462



### -6dB Bandwidth NVNT 11N40 Ant1 2422





### -6dB Bandwidth NVNT 11N40 Ant1 2437




### -6dB Bandwidth NVNT 11N40 Ant1 2452





99% Occupied Bandwidth:

### OBW NVNT 11B Ant1 2412



### OBW NVNT 11B Ant1 2437






### OBW NVNT 11B\_Ant1 2462




### OBW NVNT 11G\_Ant1 2412






## OBW NVNT 11G Ant1 2437




## OBW NVNT 11G Ant1 2462






### OBW NVNT 11N20 Ant1 2412




### OBW NVNT 11N20 Ant1 2437






### OBW NVNT 11N20 Ant1 2462




### OBW NVNT 11N40 Ant1 2422






### OBW NVNT 11N40 Ant1 2437



### OBW NVNT 11N40 Ant1 2452



## 8. Power Spectral Density


### 8.1 Applicable Standard

FCC Part15 C Section 15.247 (e)

### 8.2 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### 8.3 Test setup



### 8.4 Test Procedure

Refer to KDB558074 D01 15.247 Meas Guidance v05r02

### 8.5 Test Data


|              |           |              |      |
|--------------|-----------|--------------|------|
| Temperature  | 23.8 °C   | Humidity     | 52%  |
| ATM Pressure | 101.1kPa  | Antenna Gain | 0dBi |
| Test by      | Zekka Yin | Test result  | PASS |


Please refer to following table and plots.




Power Spectral Density:

| Modulation     | Frequency (MHz) | Max PSD (dBm/3kHz) | Limit (dBm/3kHz) |
|----------------|-----------------|--------------------|------------------|
| 802.11b        | 2412            | -13.11             | ≤8               |
|                | 2437            | -13.14             | ≤8               |
|                | 2462            | -13.33             | ≤8               |
| 802.11g        | 2412            | -20.53             | ≤8               |
|                | 2437            | -20.37             | ≤8               |
|                | 2462            | -19.50             | ≤8               |
| 802.11 n(HT20) | 2412            | -17.30             | ≤8               |
|                | 2437            | -15.26             | ≤8               |
|                | 2462            | -16.11             | ≤8               |
| 802.11 n(HT40) | 2422            | -18.87             | ≤8               |
|                | 2437            | -20.27             | ≤8               |
|                | 2452            | -20.66             | ≤8               |










### 11N20SISO\_Ant1\_2412




### 11N20SISO\_Ant1\_2437








### 11N40SISO\_Ant1\_2437



### 11N40SISO\_Ant1\_2452



## 9. Spurious Emission in Non-restricted & restricted Bands

### 9.1 Conducted Emission Method


#### 9.1.1 Applicable Standard

FCC Part15 C Section 15.247 (d)

#### 9.1.2 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### 9.1.3 Test setup



#### 9.1.4 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

#### 9.1.5 Test Data

|              |           |              |      |
|--------------|-----------|--------------|------|
| Temperature  | 23.8 °C   | Humidity     | 52%  |
| ATM Pressure | 101.1kPa  | Antenna Gain | 0dBi |
| Test by      | Zekka Yin | Test result  | PASS |

Please refer to following plots.




Band Edge:


| Modulation | Frequency (MHz) | Max Value (dBc) | Limit (dBc) | Verdict |
|------------|-----------------|-----------------|-------------|---------|
| b          | 2412            | -46.12          | -20         | Pass    |
| b          | 2462            | -52.18          | -20         | Pass    |
| g          | 2412            | -54.31          | -20         | Pass    |
| g          | 2462            | -57.94          | -20         | Pass    |
| n20        | 2412            | -40.62          | -20         | Pass    |
| n20        | 2462            | -49.35          | -20         | Pass    |
| N40        | 2422            | -49.94          | -20         | Pass    |
| N40        | 2452            | -49.12          | -20         | Pass    |



### 11B Ant1 Low 2412




### 11B Ant1 High 2462






### 11G Ant1 Low 2412




### 11G Ant1 High 2462






### 11N20SISO Ant1 Low 2412




### 11N20SISO Ant1 High 2462






### 11N40SISO Ant1 Low 2422




### 11N40SISO Ant1 High 2452








Conducted RF Spurious Emission:


| Modulation | Frequency (MHz) | FreqRange (MHz) | Max Value (dBc) | Limit (dBc) | Verdict |
|------------|-----------------|-----------------|-----------------|-------------|---------|
| b          | 2412            | 30~1000         | -63.76          | -20         | Pass    |
|            |                 | 1000~26500      | -38.16          | -20         | Pass    |
|            | 2437            | 30~1000         | -63.84          | -20         | Pass    |
|            |                 | 1000~26500      | -39.32          | -20         | Pass    |
|            | 2462            | 30~1000         | -63.31          | -20         | Pass    |
|            |                 | 1000~26500      | -39.18          | -20         | Pass    |
| g          | 2412            | 30~1000         | -62.94          | -20         | Pass    |
|            |                 | 1000~26500      | -38.52          | -20         | Pass    |
|            | 2437            | 30~1000         | -63.79          | -20         | Pass    |
|            |                 | 1000~26500      | -38.76          | -20         | Pass    |
|            | 2462            | 30~1000         | -63.82          | -20         | Pass    |
|            |                 | 1000~26500      | -38.03          | -20         | Pass    |
| n20        | 2412            | 30~1000         | -62.92          | -20         | Pass    |
|            |                 | 1000~26500      | -39.47          | -20         | Pass    |
|            | 2437            | 30~1000         | -63.86          | -20         | Pass    |
|            |                 | 1000~26500      | -39.9           | -20         | Pass    |
|            | 2462            | 30~1000         | -64.04          | -20         | Pass    |
|            |                 | 1000~26500      | -39.09          | -20         | Pass    |
| n40        | 2422            | 30~1000         | -63.55          | -20         | Pass    |
|            |                 | 1000~26500      | -38.59          | -20         | Pass    |
|            | 2437            | 30~1000         | -62.72          | -20         | Pass    |
|            |                 | 1000~26500      | -38.99          | -20         | Pass    |
|            | 2452            | 30~1000         | -63.68          | -20         | Pass    |
|            |                 | 1000~26500      | -39.26          | -20         | Pass    |

















































## 9.2 Radiated Emission Method

### 9.2.1 Applicable Standard

FCC Part15 C Section 15.209 and 15.205

### 9.2.2 Limit


| Frequency         | Limit (uV/m) | Value | Measurement Distance |
|-------------------|--------------|-------|----------------------|
| 0.009MHz-0.490MHz | 2400/F(KHz)  | QP    | 300m                 |
| 0.490MHz-1.705MHz | 24000/F(KHz) | QP    | 30m                  |
| 1.705MHz-30MHz    | 30           | QP    | 30m                  |

| Frequency  | Field Strengths Limits<br>( $\mu\text{V/m}$ at 3 m) | Field Strengths Limits<br>(dB $\mu\text{V/m}$ at 3 m) | Remark     |
|------------|-----------------------------------------------------|-------------------------------------------------------|------------|
| 30 – 88    | 100                                                 | 40.0                                                  | Quasi-peak |
| 88 – 216   | 150                                                 | 43.5                                                  | Quasi-peak |
| 216 – 960  | 200                                                 | 46.0                                                  | Quasi-peak |
| Above 960  | 500                                                 | 54.0                                                  | Quasi-peak |
| Above 1GHz | /                                                   | 54.0                                                  | Peak       |
|            |                                                     | 74.0                                                  | Average    |


Note: dB $\mu\text{V/m}$  = 20log( $\mu\text{V/m}$ )

### 9.2.3 Test setup


For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



#### 9.2.4 EMI Test Receiver Setup

| Frequency         | RBW     | VBW     | IF B/W  | Measurement |
|-------------------|---------|---------|---------|-------------|
| 9KHz-150KHz       | 200Hz   | 600Hz   | /       | QP          |
| 150KHz-30MHz      | 9KHz    | 30KHz   | /       | QP          |
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz | 120 kHz | QP          |
| Above 1 GHz       | 1 MHz   | 3 MHz   | /       | Peak        |
|                   | 1 MHz   | 10 Hz   | /       | Average     |

Remark: For the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission test in these three bands are based on measurements employing an average detector.

#### 9.2.5 Test procedure

- The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna



are set to make the measurement.

For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

#### 9.2.6 Test Data

|              |           |              |         |
|--------------|-----------|--------------|---------|
| Temperature  | 25-26 °C  | Humidity     | 49-54 % |
| ATM Pressure | 101.1kPa  | Antenna Gain | 0dBi    |
| Test by      | Zekka Yin | Test result  | PASS    |

#### Remarks:


1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y- axis which it is worse case.
2. Data of measurement within frequency range 9kHz-30MHz, 18-26GHz are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report.



**Below 1GHz**

Pre-scan all test modes, found worst case at 802.11g mode 2412MHz, and so only show the test result of 802.11g mode 2412MHz

**Horizontal:**




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 42.8922         | 29.67          | -14.38        | 15.29          | 40.00          | -24.71      | QP       |
| 2   | 87.3258         | 37.61          | -18.61        | 19.00          | 40.00          | -21.00      | QP       |
| 3   | 145.9123        | 41.74          | -13.74        | 28.00          | 43.50          | -15.50      | QP       |
| 4   | 170.5830        | 46.54          | -14.61        | 31.93          | 43.50          | -11.57      | QP       |
| 5   | 354.4316        | 36.00          | -12.62        | 23.38          | 46.00          | -22.62      | QP       |
| 6 * | 948.5947        | 37.78          | -1.72         | 36.06          | 46.00          | -9.94       | QP       |



Vertical:

80.0 dBuV/m



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 44.0893         | 34.34          | -14.51        | 19.83          | 40.00          | -20.17      | QP       |
| 2   | 127.8437        | 42.51          | -15.03        | 27.48          | 43.50          | -16.02      | QP       |
| 3   | 154.1164        | 41.49          | -13.43        | 28.06          | 43.50          | -15.44      | QP       |
| 4   | 191.7786        | 40.81          | -17.28        | 23.53          | 43.50          | -19.97      | QP       |
| 5   | 355.3027        | 35.01          | -12.61        | 22.40          | 46.00          | -23.60      | QP       |
| 6 * | 782.0710        | 34.50          | -3.55         | 30.95          | 46.00          | -15.05      | QP       |



## Above 1GHz

| Frequency (MHz)    | Read Level (dBμV) | polarization | Factor (dB/m) | Level (dBμV/m) | Limit Line (dBμV/m) | Margin (dB) | Detector |
|--------------------|-------------------|--------------|---------------|----------------|---------------------|-------------|----------|
| 11b Low Channel    |                   |              |               |                |                     |             |          |
| 2390               | 79.77             | V            | -20.22        | 59.55          | 74                  | -14.45      | peak     |
| 2400               | 76.35             | H            | -20.22        | 56.13          | 74                  | -17.87      | peak     |
| 2390               | 42.44             | V            | -4.89         | 37.55          | 54                  | -16.45      | AVG      |
| 2400               | 41.31             | V            | -4.89         | 36.42          | 54                  | -17.58      | AVG      |
| 4824               | 66.59             | H            | -18.44        | 48.15          | 74                  | -25.85      | peak     |
| 4824               | 67.89             | V            | -18.44        | 49.45          | 74                  | -24.55      | peak     |
| 7236               | 68.99             | H            | -16.55        | 52.44          | 74                  | -21.56      | peak     |
| 7236               | 69.96             | V            | -16.55        | 53.41          | 74                  | -20.59      | peak     |
| 9648               | 53.22             | H            | -14.15        | 39.07          | 74                  | -34.93      | peak     |
| 9648               | 58.88             | V            | -14.15        | 44.73          | 74                  | -29.27      | peak     |
| 12060              | 51.26             | H            | -10.08        | 41.18          | 74                  | -32.82      | peak     |
| 12060              | 53.37             | V            | -10.08        | 43.29          | 74                  | -30.71      | peak     |
| 11b Middle Channel |                   |              |               |                |                     |             |          |
| 4874               | 63.69             | H            | -18.22        | 45.47          | 74                  | -28.53      | peak     |
| 4874               | 60.45             | V            | -18.22        | 42.23          | 74                  | -31.77      | peak     |
| 7311               | 58.79             | H            | -16.46        | 42.33          | 74                  | -31.67      | peak     |
| 7311               | 56.79             | V            | -16.46        | 40.33          | 74                  | -33.67      | peak     |
| 9748               | 54.19             | H            | -14.02        | 40.17          | 74                  | -33.83      | peak     |
| 9748               | 56.38             | V            | -14.02        | 42.36          | 74                  | -31.64      | peak     |
| 12185              | 54.63             | H            | -9.96         | 44.67          | 74                  | -29.33      | peak     |
| 12185              | 52.09             | V            | -9.96         | 42.13          | 74                  | -31.87      | peak     |
| 11b High Channel   |                   |              |               |                |                     |             |          |
| 2483.5             | 78.63             | H            | -22.20        | 56.43          | 74                  | -17.57      | peak     |
| 2500               | 79.11             | V            | -22.20        | 56.91          | 74                  | -17.09      | peak     |
| 2483.5             | 42.11             | H            | -4.43         | 37.68          | 54                  | -16.32      | AVG      |
| 2500               | 44.18             | V            | -4.43         | 39.75          | 54                  | -14.25      | AVG      |
| 4924               | 65.89             | H            | -18.38        | 47.51          | 74                  | -26.49      | peak     |
| 4924               | 56.39             | V            | -18.38        | 38.01          | 74                  | -35.99      | peak     |
| 7386               | 53.44             | H            | -16.49        | 36.95          | 74                  | -37.05      | peak     |
| 7386               | 56.36             | V            | -16.49        | 39.87          | 74                  | -34.13      | peak     |
| 9848               | 59.33             | H            | -14.23        | 45.10          | 74                  | -28.90      | peak     |
| 9848               | 56.32             | V            | -14.23        | 42.09          | 74                  | -31.91      | peak     |
| 12310              | 52.47             | H            | -10.15        | 42.32          | 74                  | -31.68      | peak     |
| 12310              | 50.39             | V            | -10.15        | 40.24          | 74                  | -33.76      | peak     |



| 11g Low Channel    |       |   |        |       |    |        |      |
|--------------------|-------|---|--------|-------|----|--------|------|
| 2390               | 76.55 | V | -20.22 | 56.33 | 74 | -17.67 | peak |
| 2400               | 78.88 | H | -20.22 | 58.66 | 74 | -15.34 | peak |
| 2390               | 43.25 | V | -4.89  | 38.36 | 54 | -15.64 | AVG  |
| 2400               | 43.56 | V | -4.89  | 38.67 | 54 | -15.33 | AVG  |
| 4824               | 67.89 | H | -18.44 | 49.45 | 74 | -24.55 | peak |
| 4824               | 66.79 | V | -18.44 | 48.35 | 74 | -25.65 | peak |
| 7236               | 64.13 | H | -16.55 | 47.58 | 74 | -26.42 | peak |
| 7236               | 65.89 | V | -16.55 | 49.34 | 74 | -24.66 | peak |
| 9648               | 55.69 | H | -14.15 | 41.54 | 74 | -32.46 | peak |
| 9648               | 58.09 | V | -14.15 | 43.94 | 74 | -30.06 | peak |
| 12060              | 53.63 | H | -10.08 | 43.55 | 74 | -30.45 | peak |
| 12060              | 54.52 | V | -10.08 | 44.44 | 74 | -29.56 | peak |
| 11g Middle Channel |       |   |        |       |    |        |      |
| 4874               | 69.98 | H | -18.22 | 51.76 | 74 | -22.24 | peak |
| 4874               | 68.74 | V | -18.22 | 50.52 | 74 | -23.48 | peak |
| 7311               | 56.98 | H | -16.46 | 40.52 | 74 | -33.48 | peak |
| 7311               | 58.79 | V | -16.46 | 42.33 | 74 | -31.67 | peak |
| 9748               | 59.63 | H | -14.02 | 45.61 | 74 | -28.39 | peak |
| 9748               | 62.14 | V | -14.02 | 48.12 | 74 | -25.88 | peak |
| 12185              | 56.39 | H | -9.96  | 46.43 | 74 | -27.57 | peak |
| 12185              | 54.88 | V | -9.96  | 44.92 | 74 | -29.08 | peak |
| 11g High Channel   |       |   |        |       |    |        |      |
| 2483.5             | 76.88 | H | -22.20 | 54.68 | 74 | -19.32 | peak |
| 2500               | 76.98 | V | -22.20 | 54.78 | 74 | -19.22 | peak |
| 2483.5             | 45.88 | H | -4.43  | 41.45 | 54 | -12.55 | AVG  |
| 2500               | 43.10 | V | -4.43  | 38.67 | 54 | -15.33 | AVG  |
| 4924               | 68.96 | H | -18.38 | 50.58 | 74 | -23.42 | peak |
| 4924               | 57.22 | V | -18.38 | 38.84 | 74 | -35.16 | peak |
| 7386               | 55.69 | H | -16.49 | 39.20 | 74 | -34.80 | peak |
| 7386               | 58.63 | V | -16.49 | 42.14 | 74 | -31.86 | peak |
| 9848               | 63.21 | H | -14.23 | 48.98 | 74 | -25.02 | peak |
| 9848               | 58.08 | V | -14.23 | 43.85 | 74 | -30.15 | peak |
| 12310              | 60.07 | H | -10.15 | 49.92 | 74 | -24.08 | peak |
| 12310              | 53.36 | V | -10.15 | 43.21 | 74 | -30.79 | peak |



| 11n20 Low Channel    |       |   |        |       |    |        |      |
|----------------------|-------|---|--------|-------|----|--------|------|
| 2390                 | 75.06 | V | -20.22 | 54.84 | 74 | -19.16 | peak |
| 2400                 | 79.19 | H | -20.22 | 58.97 | 74 | -15.03 | peak |
| 2390                 | 46.35 | V | -4.89  | 41.46 | 54 | -12.54 | AVG  |
| 2400                 | 45.26 | V | -4.89  | 40.37 | 54 | -13.63 | AVG  |
| 4824                 | 65.10 | H | -18.44 | 46.66 | 74 | -27.34 | peak |
| 4824                 | 63.28 | V | -18.44 | 44.84 | 74 | -29.16 | peak |
| 7236                 | 66.98 | H | -16.55 | 50.43 | 74 | -23.57 | peak |
| 7236                 | 60.14 | V | -16.55 | 43.59 | 74 | -30.41 | peak |
| 9648                 | 56.88 | H | -14.15 | 42.73 | 74 | -31.27 | peak |
| 9648                 | 54.69 | V | -14.15 | 40.54 | 74 | -33.46 | peak |
| 12060                | 56.68 | H | -10.08 | 46.60 | 74 | -27.40 | peak |
| 12060                | 58.99 | V | -10.08 | 48.91 | 74 | -25.09 | peak |
| 11n20 Middle Channel |       |   |        |       |    |        |      |
| 4874                 | 64.88 | H | -18.22 | 46.66 | 74 | -27.34 | peak |
| 4874                 | 59.78 | V | -18.22 | 41.56 | 74 | -32.44 | peak |
| 7311                 | 54.76 | H | -16.46 | 38.3  | 74 | -35.70 | peak |
| 7311                 | 55.89 | V | -16.46 | 39.43 | 74 | -34.57 | peak |
| 9748                 | 63.12 | H | -14.02 | 49.1  | 74 | -24.90 | peak |
| 9748                 | 64.18 | V | -14.02 | 50.16 | 74 | -23.84 | peak |
| 12185                | 54.89 | H | -9.96  | 44.93 | 74 | -29.07 | peak |
| 12185                | 55.69 | V | -9.96  | 45.73 | 74 | -28.27 | peak |
| 11n20 High Channel   |       |   |        |       |    |        |      |
| 2483.5               | 81.69 | H | -22.20 | 59.49 | 74 | -14.51 | peak |
| 2500                 | 79.59 | V | -22.20 | 57.39 | 74 | -16.61 | peak |
| 2483.5               | 44.10 | H | -4.43  | 39.67 | 54 | -14.33 | AVG  |
| 2500                 | 45.63 | V | -4.43  | 41.20 | 54 | -12.80 | AVG  |
| 4924                 | 69.28 | H | -18.38 | 50.90 | 74 | -23.10 | peak |
| 4924                 | 60.28 | V | -18.38 | 41.90 | 74 | -32.10 | peak |
| 7386                 | 56.88 | H | -16.49 | 40.39 | 74 | -33.61 | peak |
| 7386                 | 59.36 | V | -16.49 | 42.87 | 74 | -31.13 | peak |
| 9848                 | 65.01 | H | -14.23 | 50.78 | 74 | -23.22 | peak |
| 9848                 | 60.28 | V | -14.23 | 46.05 | 74 | -27.95 | peak |
| 12310                | 56.89 | H | -10.15 | 46.74 | 74 | -27.26 | peak |
| 12310                | 55.88 | V | -10.15 | 45.73 | 74 | -28.27 | peak |



| 11n40 Low Channel    |       |   |        |       |    |        |      |
|----------------------|-------|---|--------|-------|----|--------|------|
| 2390                 | 79.69 | V | -20.22 | 59.47 | 74 | -14.53 | peak |
| 2400                 | 80.29 | H | -20.22 | 60.07 | 74 | -13.93 | peak |
| 2390                 | 44.69 | V | -4.89  | 39.80 | 54 | -14.20 | AVG  |
| 2400                 | 48.77 | V | -4.89  | 43.88 | 54 | -10.12 | AVG  |
| 4844                 | 68.96 | H | -18.44 | 50.52 | 74 | -23.48 | peak |
| 4844                 | 65.44 | V | -18.44 | 47.00 | 74 | -27.00 | peak |
| 7266                 | 62.01 | H | -16.55 | 45.46 | 74 | -28.54 | peak |
| 7266                 | 58.96 | V | -16.55 | 42.41 | 74 | -31.59 | peak |
| 9688                 | 55.09 | H | -14.15 | 40.94 | 74 | -33.06 | peak |
| 9688                 | 56.98 | V | -14.15 | 42.83 | 74 | -31.17 | peak |
| 12110                | 57.49 | H | -10.08 | 47.41 | 74 | -26.59 | peak |
| 12110                | 56.36 | V | -10.08 | 46.28 | 74 | -27.72 | peak |
| 11n40 Middle Channel |       |   |        |       |    |        |      |
| 4874                 | 65.39 | H | -18.22 | 47.17 | 74 | -26.83 | peak |
| 4874                 | 62.03 | V | -18.22 | 43.81 | 74 | -30.19 | peak |
| 7311                 | 55.69 | H | -16.46 | 39.23 | 74 | -34.77 | peak |
| 7311                 | 67.19 | V | -16.46 | 50.73 | 74 | -23.27 | peak |
| 9748                 | 56.33 | H | -14.02 | 42.31 | 74 | -31.69 | peak |
| 9748                 | 59.38 | V | -14.02 | 45.36 | 74 | -28.64 | peak |
| 12185                | 57.19 | H | -9.96  | 47.23 | 74 | -26.77 | peak |
| 12185                | 56.89 | V | -9.96  | 46.93 | 74 | -27.07 | peak |
| 11n40 High Channel   |       |   |        |       |    |        |      |
| 2483.5               | 82.36 | H | -22.20 | 60.16 | 74 | -13.84 | peak |
| 2500                 | 80.00 | V | -22.20 | 57.80 | 74 | -16.20 | peak |
| 2483.5               | 46.23 | H | -4.43  | 41.80 | 54 | -12.20 | AVG  |
| 2500                 | 45.10 | V | -4.43  | 40.67 | 54 | -13.33 | AVG  |
| 4904                 | 63.58 | H | -18.38 | 45.20 | 74 | -28.80 | peak |
| 4904                 | 63.28 | V | -18.38 | 44.90 | 74 | -29.10 | peak |
| 7356                 | 48.77 | H | -16.49 | 32.28 | 74 | -41.72 | peak |
| 7356                 | 54.09 | V | -16.49 | 37.60 | 74 | -36.40 | peak |
| 9808                 | 63.02 | H | -14.23 | 48.79 | 74 | -25.21 | peak |
| 9808                 | 63.28 | V | -14.23 | 49.05 | 74 | -24.95 | peak |
| 12260                | 65.99 | H | -10.15 | 55.84 | 74 | -18.16 | peak |
| 12260                | 48.76 | V | -10.15 | 38.61 | 74 | -35.39 | peak |

## Remarks:

1. Level = Receiver Read level + Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. If the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in above table if the peak value complies with average limit.

----- THE END OF TEST REPORT -----