

TEST REPORT

Report No.: BCTC2606534141E

Applicant: SHENZHEN JUNYE ELECTRONICS CO LTD

Product Name: Vivitar TWS Headphones

Test Model: Y138

Tested Date: 2026-06-16 to 2026-06-30

Issued Date: 2026-07-07



Shenzhen BCTC Technology Co., Ltd.



FCC ID: 2BB3B-HDQ4TWS

Product Name: Vivitar TWS Headphones

Trademark: NA

Model/Type Reference: Y138,Y145,Y146,Y147,Y148,HDQ4TWS-YET,HDQ4TWS-NRW,HDQ4TWS-PN
G,HDQ4TWS-SKI,HDQ4TWS-SNT

Prepared For: SHENZHEN JUNYE ELECTRONICS CO LTD

Address: 201,Building 7,Xingye er Road,Fenghuang Village, Fuyong Town,Baoan District,
Shenzhen City,Guangdong Province,China

Manufacturer: SHENZHEN JUNYE ELECTRONICS CO LTD

Address: 201,Building 7,Xingye er Road,Fenghuang Village, Fuyong Town,Baoan District,
Shenzhen City,Guangdong Province,China

Prepared By: Shenzhen BCTC Technology Co., Ltd.

Address: Room 101M, Unit 1, Building1, Pengyuan, No.18, Lilang Road, Shanglilang,
Nanwan Subdistrict, Longgang District, Shenzhen, Guangdong, China.

Sample Received Date: 2026-06-16

Sample Tested Date: 2026-06-16 to 2026-06-30


Report No.: BCTC2606534141E

Test Standards: FCC Part15.247
ANSI C63.10-2020

Test Results: PASS


Remark: This is Bluetooth Classic radio test report.

Prepared by :



Mike Zheng

Reviewer by :



Louis Zeng

Approved by:




Sewen Guo

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Technology Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table of Content


Test Report Declaration	Page
1. Version	5
2. Test Summary	6
3. Measurement Uncertainty	7
4. Product Information and Test Setup	8
4.1 Product Information	8
4.2 Test Setup Configuration	9
4.3 Support Equipment	9
4.4 Channel List	10
4.5 Test Mode	10
4.6 Table Of Parameters Of Text Software Setting	11
5. Test Facility And Test Instrument Used	12
5.1 Test Facility	12
5.2 Test Instrument Used	12
6. Conducted Emissions	15
6.1 Block Diagram Of Test Setup	15
6.2 Limit	15
6.3 Test procedure	15
6.4 EUT operating Conditions	15
6.5 Test Result	16
7. Radiated emissions	18
7.1 Block Diagram Of Test Setup	18
7.2 Limit	19
7.3 Test procedure	20
7.4 EUT operating Conditions	21
7.5 Test Result	22
8. Radiated Band Emission Measurement and Restricted Bands of Operation	28
8.1 Block Diagram Of Test Setup	28
8.2 Limit	28
8.3 Test procedure	29
8.4 EUT operating Conditions	29
8.5 Test Result	30
9. Spurious RF Conducted Emissions	31
9.1 Block Diagram Of Test Setup	31
9.2 Limit	31
9.3 Test procedure	31
9.4 Test Result	32
10. 20 dB Bandwidth	53
10.1 Block Diagram Of Test Setup	53
10.2 Limit	53
10.3 Test procedure	53
10.4 Test Result	54
11. Maximum Peak Output Power	60
11.1 Block Diagram Of Test Setup	60
11.2 Limit	60
11.3 Test procedure	60

11.4	Test Result.....	60
12.	Hopping Channel Separation	66
12.1	Block Diagram Of Test Setup.....	66
12.2	Limit	66
12.3	Test procedure	66
12.4	Test Result.....	66
13.	Number of Hopping Frequency	71
13.1	Block Diagram Of Test Setup.....	71
13.2	Limit	71
13.3	Test procedure	71
13.4	Test Result.....	71
14.	Dwell Time.....	74
14.1	Block Diagram Of Test Setup.....	74
14.2	Limit	74
14.3	Test procedure	74
14.4	Test Result.....	74
15.	Antenna Requirement	80
15.1	Limit	80
15.2	Test Result.....	80
16.	EUT Test Setup Photographs.....	81



1. Version

Report No.	Issue Date	Description	Approved
BCTC2606534141E	2026-07-07	Original	Valid



2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	Conducted emission AC power port	§15.207	PASS*
2	Conducted peak output power for FHSS	§15.247(b)(1)	PASS*
3	20dB Occupied bandwidth	§15.247(a)(1)	PASS*
4	Number of hopping frequencies	§15.247(a)(1)(iii)	PASS*
5	Dwell Time	§15.247(a)(1)(iii)	PASS*
6	Spurious RF conducted emissions	§15.247(d)	PASS*
7	Band edge	§15.247(d)	PASS*
8	Spurious radiated emissions for transmitter	§15.247(d) & §15.209 & §15.205	PASS*
9	Antenna Requirement	15.203	PASS

NOTE1: N/A (Not Applicable)

NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.

Note 3: "*" indicates that the test results are determined base on CFR 47 FCC Part 15 Subpart C (clause 15.247). And the test results are took into account measurement uncertainty (see section 3 for measurement uncertainty information)

BCTC CO., LTD

3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2:2011/AMD2:2018. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9kHz-30MHz)	U=3.7dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=5.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=5.0dB
5	Conducted Emission(150kHz-30MHz)	U=3.0dB
6	Power Spectral Density	U=3.46dB
7	Peak Power	U=0.31dB
8	Occupied Bandwidth/Frequency Range	U=3.46%
9	Conducted output power uncertainty	U=0.55dB
10	Frequency Error	U= 53.50 Hz
11	Frequency Drift	U=0.64 KHz
12	Temperature	U= 0.59 °C
13	Humidity	U= 5.3 %

4. Product Information and Test Setup


4.1 Product Information

Model/Type reference:	Y138,Y145,Y146,Y147,Y148,HDQ4TWS-YET,HDQ4TWS-NRW,HDQ4TWS-PNG,H DQ4TWS-SKI,HDQ4TWS-SNT
Model differences:	The devices of the following models that we produce are identical in electrical, mechanical, and physical structure; the differences lie in the exterior shape of the charging case, the model name, and the color. Ultimately, we use Y138 as the test model.
Bluetooth Version:	N/A
Hardware Version:	N/A
Software Version:	N/A
Operation Frequency:	Bluetooth: 2402-2480MHz
Type of Modulation:	GFSK modulation for BR(1Mbps) pi/4-DQPSK modulation for EDR(2Mbps) 8DPSK modulation for BT EDR (3Mbps)
Number Of Channel	79 channels
Antenna installation:	Internal antenna
Antenna Gain:	2.7dBi
	Remark: ☒ The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information. Antenna gain information is provided by the client and the laboratory is not responsible for its authenticity ☐ The antenna gain of the product is provided by the customer, and the test data is affected by the customer information. Antenna gain information is provided by the client and the laboratory is not responsible for its authenticity
power supply:	DC 5V,1A
Battery:	DC 3.7V,30mAh

4.2 Test Setup Configuration

See test photographs attached in eut test setup photographs for the actual connections between product and support equipment.

Conducted Emission:



Radiated Spurious Emission:



4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Vivitar TWS Headphones	N/A	Y138	N/A	EUT
E-2	Adapter	N/A	N/A	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	N/A	N/A	N/A	N/A

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
0	2402	1	2403	2	2404	3	2405
4	2406	5	2407	6	2408	7	2409
8	2410	9	2411	10	2412	11	2413
12	2414	13	2415	14	2416	15	2417
16	2418	17	2419	18	2420	19	2421
20	2422	21	2423	22	2424	23	2425
24	2426	25	2427	26	2428	27	2429
28	2430	29	2431	30	2432	31	2433
32	2434	33	2435	34	2436	35	2437
36	2438	37	2439	38	2440	39	2441
40	2442	41	2443	42	2444	43	2445
44	2446	45	2447	46	2448	47	2449
48	2450	49	2451	50	2452	51	2453
52	2454	53	2455	54	2456	55	2457
56	2458	57	2459	58	2460	59	2461
60	2462	61	2463	62	2464	63	2465
64	2466	65	2467	66	2468	67	2469
68	2470	69	2471	70	2472	71	2473
72	2474	73	2475	74	2476	75	2477
76	2478	77	2479	78	2480	/	/

4.5 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Mode	Test mode	Low channel	Middle channel	High channel
1	Transmitting(GFSK)	2402MHz	2441MHz	2480MHz
2	Transmitting($\pi/4$ DQPSK)	2402MHz	2441MHz	2480MHz
3	Transmitting(8DPSK)	2402MHz	2441MHz	2480MHz
4	Transmitting (Conducted emission & Radiated emission)			

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

4.6 Table Of Parameters Of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

RF Function	Mode Or Modulation type	Power Class	Software For Testing
BT	GFSK	7	bt_tool_v1.1.4
	$\pi/4$ -DQPSK	7	
	8DPSK	7	

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Technology Co., Ltd.

Address: Room 101M, Unit 1, Building1, Pengyuan, No.18, Lilang Road, Shanglilang, Nanwan Subdistrict, Longgang District, Shenzhen, Guangdong, China.

The site and apparatus are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-1:2019 other equivalent standards.

FCC Test Firm Registration Number: 754702

ANAB certificate registration number is: CN3479

5.2 Test Instrument Used


Conducted emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESCI	101421	2025.08.30	2026.08.29
AMN	SCHWHRZBECK	NSLK8128	05152	2026.01.22	2027.01.21
AMN	SCHWHRZBECK	NSLK8127	8127739	2025.09.16	2026.09.15
Pulse Limiter	SCHWHRZBECK	VTSD 9561-F-N	00547	2025.08.30	2026.08.29
Temperature & Humidity	Wetest	HTC-1	/	2025.09.01	2026.08.31
Software	EZ-EMC	Ver.EMC-CON 3A1	/	/	/

Radiated disturbance 1#					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Shielded room	CRT	9*6*6	/	2023.08.02	2026.08.01
Broadband antenna	Schwarzbeck	VULB9160	3369	2026.05.16	2027.05.15
Receiver	R&S	ESPI	101396	2025.08.30	2026.08.29
Preamplifier	Schwarzbeck	BBV9744	00342	2025.08.30	2026.08.29
Loop Antenna	Schwarzbeck	FMZB1519B	00014	2026.01.05	2027.01.04
RF cable 5# (9kHz-6GHz)	Yunyi	3M	/	2025.08.30	2026.08.29
RF cable 8# (9kHz-1GHz)	Yunyi	7M	/	2025.10.28	2026.10.27

Temperature & Humidity	Wetest	HTC-1	/	2025.09.01	2026.08.31
Software	EZ-EMC	Ver.FA-03A2	/	/	/


Radiated disturbance 2#					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Shielded room	ChengYu	9*6*6	/	2023.09.25	2026.09.24
Loop Antenna	Schwarzbeck	FMZB1519B	00014	2026.01.05	2027.01.04
Broadband antenna	SCHWHRZBECK	VULB9168	01620	2025.08.29	2026.08.28
Horn antenna(1 GHz -18GHz)	SCHWARZBECK	BBHA 9120 D	2792	2025.08.29	2026.08.28
Horn antenna (18 GHz -40GHz)	SCHWARZBECK	BBHA9170	00822	2025.12.29	2026.12.28
Receiver	R&S	ESR	1316	2025.08.30	2026.08.29
Spectrum Analyzer	R&S	FSV40	101328	2026.01.22	2027.01.21
Amplifier	SCHWHRZBECK	BBV9744	568	2025.08.30	2026.08.29
Amplifier	EMC INSTRUMENTS CORPORATION	EMC0518A45SE E	EMT-SZ2 233	2025.08.30	2026.08.29
Amplifier (18GHz-40GHz)	MITEQ	TTA1840-35-HG	2034381	2026.05.09	2027.05.08
RF cable 3# (9kHz-6GHz)	Yunyi	10M	/	2025.08.30	2026.08.29
RF cable 9# (9kHz-1GHz)	Yunyi	2M	/	2025.10.28	2026.10.27
RF cable 5# (1GHz -18GHz)	SKET	9M	18038626	2025.08.30	2026.08.29
RF cable 6# (1GHz -18GHz)	SKET	5M	#10	2025.09.05	2026.09.04
RF cable 10# (18GHz-40GHz)	/	2M	2M	2026.05.09	2027.05.08
RF cable 11# (18GHz-40GHz)	/	2.5M	2.5M	2026.05.09	2027.05.08
Temperature & Humidity	Wetest	HTC-1	/	2025.09.05	2026.09.04
Software	EZ-EMC	Ver.FA-03A2	/	/	/

RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Spectrum Analyzer	Keysight	N9020A	MY51287403	2025.08.30	2026.08.29
Signal Generator	Keysight	N5182A	MY50144088	2025.08.30	2026.08.29
Power Sensor	Keysight	U2001	MY51250006	2025.10.28	2026.10.27
Temperature & Humidity	Wetest	HTC-1	/	2025.09.01	2026.08.31
Communication test set	R&S	CMW500	157483	2025.08.30	2026.08.29
Radio frequency control box	MWRFtest	MW100-RFCB	\	\	\
Software	MWRFtest	MTS 8310	V 3.0.0.0	\	\
D.C. Power Supply	Elektro-Automatik GmbH & Co.KG	D-41747 Viersen	6230316	2025.09.30	2026.08.29
Temperature and humidity test chamber	Auchno	OJN-9606-408 L	19120183	2025.07.09	2026.07.08



6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

Frequency (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:
1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

6.3 Test procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

6.5 Test Result

Temperature:	27.1 °C	Relative Humidity:	52%
Pressure:	101KPa	Phase :	L
Test Mode:	Mode 4	Test Voltage :	AC 120V/60Hz




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = LISN factor + Cable Loss+ Limiter (10dB).
3. Margin = (Reading+ Factor)–Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	32.00	10.51	42.51	66.00	-23.49	QP
2	0.1500	12.44	10.51	22.95	56.00	-33.05	AVG
3	0.2535	28.05	10.51	38.56	61.64	-23.08	QP
4	0.2535	10.03	10.51	20.54	51.64	-31.10	AVG
5	0.4560	18.75	10.52	29.27	56.77	-27.50	QP
6	0.4560	2.93	10.52	13.45	46.77	-33.32	AVG
7	0.8340	24.20	10.54	34.74	56.00	-21.26	QP
8 *	0.8340	14.70	10.54	25.24	46.00	-20.76	AVG
9	2.3550	10.06	10.55	20.61	56.00	-35.39	QP
10	2.3550	1.10	10.55	11.65	46.00	-34.35	AVG
11	3.8400	9.47	10.64	20.11	56.00	-35.89	QP
12	3.8400	-2.80	10.64	7.84	46.00	-38.16	AVG

* Indicates the worst data.

Temperature:	27.1 °C	Relative Humidity:	52%
Pressure:	101KPa	Phase :	N
Test Mode:	Mode 4	Test Voltage :	AC 120V/60Hz



Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = LISN factor + Cable Loss+ Limiter (10dB).
3. Margin = (Reading+ Factor)–Limit


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1 *	0.1770	30.54	10.50	41.04	64.63	-23.59	QP
2	0.1770	9.42	10.50	19.92	54.63	-34.71	AVG
3	0.2805	25.98	10.51	36.49	60.80	-24.31	QP
4	0.2805	8.15	10.51	18.66	50.80	-32.14	AVG
5	0.7845	21.35	10.54	31.89	56.00	-24.11	QP
6	0.7845	11.74	10.54	22.28	46.00	-23.72	AVG
7	1.1400	13.88	10.53	24.41	56.00	-31.59	QP
8	1.1400	3.06	10.53	13.59	46.00	-32.41	AVG
9	1.9230	10.07	10.55	20.62	56.00	-35.38	QP
10	1.9230	-0.35	10.55	10.20	46.00	-35.80	AVG
11	3.1110	11.06	10.56	21.62	56.00	-34.38	QP
12	3.1110	-0.21	10.56	10.35	46.00	-35.65	AVG

* Indicates the worst data.


7. Radiated emissions

7.1 Block Diagram Of Test Setup


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



7.2 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength uV/m	Distance (m)	Field Strength Limit at 3m Distance	
			uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	$10000 * 2400/F(kHz)$	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	$100 * 24000/F(kHz)$	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

Limits Of Radiated Emission Measurement (Above 1000MHz)

Frequency (MHz)	Limit (dBuV/m) (at 3M)	
	Peak	Average
Above 1000	74	54

Notes:

- (1)The limit for radiated test was performed according to FCC PART 15C.
- (2)The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Frequency Range Of Radiated Measurement

(a) For an intentional radiator the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator operates at or above 95 GHz: To the third harmonic of the highest fundamental frequency or to 750 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (5) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a) (1)through (4) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this section, whichever is the higher frequency range of investigation.

7.3 Test procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP

Spectrum Parameter	Setting
1-25GHz	RBW 1 MHz /VBW 1 MHz for Peak, RBW 1 MHz / VBW 10Hz for Average

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel, the middlest channel, the Highest channel.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

7.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

7.5 Test Result

Below 30MHz

Temperature:	24.5 °C	Relative Humidity:	50%
Pressure:	101KPa	Test Voltage :	DC 3.7V
Test Mode:	Mode 4		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS


Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

Temperature:	24.5 °C	Relative Humidity:	50%
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 4	Test Voltage:	DC 3.7V



Remark:


Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Margin = (Reading + Factor) – Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	40.5023	25.88	-10.84	15.04	40.00	-24.96	QP
2	68.0241	26.50	-12.39	14.11	40.00	-25.89	QP
3	160.1770	25.37	-9.76	15.61	43.50	-27.89	QP
4	546.6502	25.78	-5.47	20.31	46.00	-25.69	QP
5	692.7150	26.03	-2.71	23.32	46.00	-22.68	QP
6 *	798.9797	25.02	0.43	25.45	46.00	-20.55	QP

* Indicates the worst data.

Temperature:	24.5 °C	Relative Humidity:	50%
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 4	Test Voltage:	DC 3.7V



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Margin = (Reading + Factor)–Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	31.0743	27.77	-11.48	16.29	40.00	-23.71	QP
2	47.8092	26.41	-10.50	15.91	40.00	-24.09	QP
3	144.5711	25.62	-10.70	14.92	43.50	-28.58	QP
4	505.6510	25.47	-5.28	20.19	46.00	-25.81	QP
5	801.2242	24.34	0.48	24.82	46.00	-21.18	QP
6 *	948.6501	24.82	0.66	25.48	46.00	-20.52	QP

* Indicates the worst data.

Between 1GHz – 25GHz

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measureme nt	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
GFSK Low channel							
V	4804.00	67.92	-9.61	58.31	74.00	-15.69	PK
V	4804.00	58.41	-9.61	48.80	54.00	-5.20	AV
V	7206.00	57.44	-4.13	53.31	74.00	-20.69	PK
V	7206.00	47.24	-4.13	43.11	54.00	-10.89	AV
H	4804.00	65.24	-9.61	55.63	74.00	-18.37	PK
H	4804.00	56.20	-9.61	46.59	54.00	-7.41	AV
H	7206.00	54.45	-4.13	50.32	74.00	-23.68	PK
H	7206.00	47.14	-4.13	43.01	54.00	-10.99	AV
GFSK Middle channel							
V	4882.00	65.85	-8.84	57.01	74.00	-16.99	PK
V	4882.00	57.41	-8.84	48.57	54.00	-5.43	AV
V	7323.00	55.71	-3.41	52.30	74.00	-21.70	PK
V	7323.00	46.13	-3.41	42.72	54.00	-11.28	AV
H	4882.00	63.43	-8.84	54.59	74.00	-19.41	PK
H	4882.00	54.37	-8.84	45.53	54.00	-8.47	AV
H	7323.00	52.92	-3.41	49.51	74.00	-24.49	PK
H	7323.00	44.97	-3.41	41.56	54.00	-12.44	AV
GFSK High channel							
V	4960.00	68.14	-8.65	59.49	74.00	-14.51	PK
V	4960.00	59.97	-8.65	51.32	54.00	-2.68	AV
V	7440.00	60.59	-3.4	57.19	74.00	-16.81	PK
V	7440.00	49.69	-3.4	46.29	54.00	-7.71	AV
H	4960.00	65.18	-8.65	56.53	74.00	-17.47	PK
H	4960.00	55.38	-8.65	46.73	54.00	-7.27	AV
H	7440.00	57.75	-3.4	54.35	74.00	-19.65	PK
H	7440.00	49.87	-3.4	46.47	54.00	-7.53	AV

Remark:

1. Measurement = Reading Level + Correct Factor, Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Over= Measurement - Limit
- 2.If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measureme nt	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
π/4-DQPSK Low channel							
V	4804.00	68.25	-9.61	58.64	74.00	-15.36	PK
V	4804.00	59.79	-9.61	50.18	54.00	-3.82	AV
V	7206.00	58.80	-4.13	54.67	74.00	-19.33	PK
V	7206.00	49.61	-4.13	45.48	54.00	-8.52	AV
H	4804.00	65.91	-9.61	56.30	74.00	-17.70	PK
H	4804.00	55.67	-9.61	46.06	54.00	-7.94	AV
H	7206.00	56.01	-4.13	51.88	74.00	-22.12	PK
H	7206.00	47.39	-4.13	43.26	54.00	-10.74	AV
π/4-DQPSK Middle channel							
V	4882.00	64.50	-8.84	55.66	74.00	-18.34	PK
V	4882.00	57.84	-8.84	49.00	54.00	-5.00	AV
V	7323.00	53.60	-3.41	50.19	74.00	-23.81	PK
V	7323.00	44.03	-3.41	40.62	54.00	-13.38	AV
H	4882.00	61.40	-8.84	52.56	74.00	-21.44	PK
H	4882.00	50.90	-8.84	42.06	54.00	-11.94	AV
H	7323.00	52.38	-3.41	48.97	74.00	-25.03	PK
H	7323.00	45.36	-3.41	41.95	54.00	-12.05	AV
π/4-DQPSK High channel							
V	4960.00	65.86	-8.65	57.21	74.00	-16.79	PK
V	4960.00	55.82	-8.65	47.17	54.00	-6.83	AV
V	7440.00	59.74	-3.4	56.34	74.00	-17.66	PK
V	7440.00	50.63	-3.4	47.23	54.00	-6.77	AV
H	4960.00	64.37	-8.65	55.72	74.00	-18.28	PK
H	4960.00	54.75	-8.65	46.10	54.00	-7.90	AV
H	7440.00	57.66	-3.4	54.26	74.00	-19.74	PK
H	7440.00	49.70	-3.4	46.30	54.00	-7.70	AV

Remark:

1. Measurement = Reading Level + Correct Factor, Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Over= Measurement - Limit
- 2.If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measureme nt	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
8DPSK Low channel							
V	4804.00	68.47	-9.61	58.86	74.00	-15.14	PK
V	4804.00	58.63	-9.61	49.02	54.00	-4.98	AV
V	7206.00	60.13	-4.13	56.00	74.00	-18.00	PK
V	7206.00	49.80	-4.13	45.67	54.00	-8.33	AV
H	4804.00	65.96	-9.61	56.35	74.00	-17.65	PK
H	4804.00	55.44	-9.61	45.83	54.00	-8.17	AV
H	7206.00	57.77	-4.13	53.64	74.00	-20.36	PK
H	7206.00	49.92	-4.13	45.79	54.00	-8.21	AV
8DPSK Middle channel							
V	4882.00	66.56	-8.84	57.72	74.00	-16.28	PK
V	4882.00	58.16	-8.84	49.32	54.00	-4.68	AV
V	7323.00	56.49	-3.41	53.08	74.00	-20.92	PK
V	7323.00	48.48	-3.41	45.07	54.00	-8.93	AV
H	4882.00	62.38	-8.84	53.54	74.00	-20.46	PK
H	4882.00	52.34	-8.84	43.50	54.00	-10.50	AV
H	7323.00	54.32	-3.41	50.91	74.00	-23.09	PK
H	7323.00	46.62	-3.41	43.21	54.00	-10.79	AV
8DPSK High channel							
V	4960.00	68.41	-8.65	59.76	74.00	-14.24	PK
V	4960.00	59.76	-8.65	51.11	54.00	-2.89	AV
V	7440.00	59.85	-3.4	56.45	74.00	-17.55	PK
V	7440.00	50.01	-3.4	46.61	54.00	-7.39	AV
H	4960.00	66.08	-8.65	57.43	74.00	-16.57	PK
H	4960.00	56.68	-8.65	48.03	54.00	-5.97	AV
H	7440.00	57.15	-3.4	53.75	74.00	-20.25	PK
H	7440.00	48.92	-3.4	45.52	54.00	-8.48	AV


Remark:

1. Measurement = Reading Level + Correct Factor, Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Over= Measurement - Limit
- 2.If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8. Radiated Band Emission Measurement and Restricted Bands of Operation

8.1 Block Diagram Of Test Setup

Radiated Emission Test-Up Frequency Above 1GHz



8.2 Limit

FCC Part15 C Section 15.209 and 15.205

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Limits Of Radiated Emission Measurement (Above 1000MHz)

Frequency (MHz)	Limit (dBuV/m) (at 3M)	
	Peak	Average
Above 1000	74	54

Notes:

- (1)The limit for radiated test was performed according to FCC PART 15C.
- (2)The tighter limit applies at the band edges.
- (3)Emission level (dBuV/m)=20log Emission level (uV/m).

8.3 Test procedure

Receiver Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (Emission In Restricted Band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Above 1GHz test procedure as below:

a.The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b.The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c.The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d.For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e.The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel, the middlest channel, the Highest channel.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

8.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

8.5 Test Result

Test mode	Polar (H/V)	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)		Result
					PK	PK	AV	
GFSK	Low Channel 2402MHz							
	H	2390.00	62.89	-17.27	45.62	74.00	54.00	PASS
	H	2400.00	65.81	-17.23	48.58	74.00	54.00	PASS
	V	2390.00	63.08	-17.27	45.81	74.00	54.00	PASS
	V	2400.00	65.39	-17.23	48.16	74.00	54.00	PASS
	High Channel 2480MHz							
	H	2483.50	65.09	-16.91	48.18	74.00	54.00	PASS
	H	2500.00	63.14	-16.71	46.43	74.00	54.00	PASS
	V	2483.50	66.48	-16.91	49.57	74.00	54.00	PASS
	V	2500.00	62.99	-16.71	46.28	74.00	54.00	PASS
π/4DQPSK	Low Channel 2402MHz							
	H	2390.00	62.71	-17.27	45.44	74.00	54.00	PASS
	H	2400.00	65.22	-17.23	47.99	74.00	54.00	PASS
	V	2390.00	62.01	-17.27	44.74	74.00	54.00	PASS
	V	2400.00	65.73	-17.23	48.50	74.00	54.00	PASS
	High Channel 2480MHz							
	H	2483.50	66.87	-16.91	49.96	74.00	54.00	PASS
	H	2500.00	63.01	-16.71	46.30	74.00	54.00	PASS
	V	2483.50	66.59	-16.91	49.68	74.00	54.00	PASS
	V	2500.00	62.21	-16.71	45.50	74.00	54.00	PASS
8DPSK	Low Channel 2402MHz							
	H	2390.00	62.08	-17.27	44.81	74.00	54.00	PASS
	H	2400.00	66.37	-17.23	49.14	74.00	54.00	PASS
	V	2390.00	63.34	-17.27	46.07	74.00	54.00	PASS
	V	2400.00	65.16	-17.23	47.93	74.00	54.00	PASS
	High Channel 2480MHz							
	H	2483.50	65.79	-16.91	48.88	74.00	54.00	PASS
	H	2500.00	62.67	-16.71	45.96	74.00	54.00	PASS
	V	2483.50	66.78	-16.91	49.87	74.00	54.00	PASS
	V	2500.00	62.07	-16.71	45.36	74.00	54.00	PASS
Remark:								
1. Emission Level = Meter Reading + Factor, Factor = Antenna Factor + Cable Loss – Pre-amplifier. Over= Emission Level - Limit								
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.								
3 In restricted bands of operation, The spurious emissions below the permissible value more than 20dB								
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.								

9. Spurious RF Conducted Emissions

9.1 Block Diagram Of Test Setup




9.2 Limit



Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))



9.3 Test procedure



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
 Below 30MHz:
 RBW = 100kHz, VBW = 300kHz, Sweep = auto
 Detector function = peak, Trace = max hold
 Above 30MHz:
 RBW = 100KHz, VBW = 300KHz, Sweep = auto
 Detector function = peak, Trace = max hold



9.4 Test Result

















CO., LTD






















CO., LTD

















CO., LTD



SHENZHEN








10. 20 dB Bandwidth

10.1 Block Diagram Of Test Setup



10.2 Limit

N/A


10.3 Test procedure

1. Set RBW = 30kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


10.4 Test Result


Condition	Mode	Frequency (MHz)	-20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH5	2402	0.944	Pass
NVNT	1-DH5	2441	0.936	Pass
NVNT	1-DH5	2480	0.943	Pass
NVNT	2-DH5	2402	1.273	Pass
NVNT	2-DH5	2441	1.266	Pass
NVNT	2-DH5	2480	1.311	Pass
NVNT	3-DH5	2402	1.253	Pass
NVNT	3-DH5	2441	1.268	Pass
NVNT	3-DH5	2480	1.257	Pass


BCTC CO., LTD.














NOLOG
C
ED
al

11. Maximum Peak Output Power

11.1 Block Diagram Of Test Setup



11.2 Limit


FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(1)	Peak Output Power	0.125 watt or 21dBm	2400-2483.5	PASS

11.3 Test procedure



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: BDR:RBW = 1MHz. VBW = 3MHz. Sweep = auto; Detector Function = Peak.EDR:RBW = 2MHz. VBW = 6MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.



11.4 Test Result



Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH5	2402	1.97	21	Pass
NVNT	1-DH5	2441	2.1	21	Pass
NVNT	1-DH5	2480	2.17	21	Pass
NVNT	2-DH5	2402	2.8	21	Pass
NVNT	2-DH5	2441	2.94	21	Pass
NVNT	2-DH5	2480	3.05	21	Pass
NVNT	3-DH5	2402	3.39	21	Pass
NVNT	3-DH5	2441	3.54	21	Pass
NVNT	3-DH5	2480	3.62	21	Pass





SHENZHEN










12. Hopping Channel Separation

12.1 Block Diagram Of Test Setup



12.2 Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 0.125W.

12.3 Test procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 30kHz. VBW = 100kHz , Span = 2.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

12.4 Test Result


Condition	Mode	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH5	2401.822	2402.824	1.002	0.629	Pass
NVNT	1-DH5	2440.837	2441.821	0.984	0.624	Pass
NVNT	1-DH5	2478.825	2480.007	1.182	0.635	Pass
NVNT	2-DH5	2401.819	2402.824	1.005	0.849	Pass
NVNT	2-DH5	2440.822	2442.013	1.191	0.844	Pass
NVNT	2-DH5	2478.822	2480.01	1.188	0.889	Pass
NVNT	3-DH5	2401.834	2402.824	0.99	0.835	Pass
NVNT	3-DH5	2440.831	2441.833	1.002	0.861	Pass
NVNT	3-DH5	2478.834	2479.833	0.999	0.849	Pass

Test Graphs



CFS NVNT 1-DH5 2402MHz Ant1







CFS NVNT 1-DH5 2441MHz Ant1



SHENZHEN







13. Number of Hopping Frequency

13.1 Block Diagram Of Test Setup



13.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

13.3 Test procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

13.4 Test Result


Condition	Mode	Hopping Number	Limit	Verdict
NVNT	1-DH5	79	15	Pass
NVNT	2-DH5	79	15	Pass
NVNT	3-DH5	79	15	Pass


Test Graphs

Hopping No. NVNT 1-DH5 2402MHz Ant1




Hopping No. NVNT 2-DH5 2402MHz Ant1





14. Dwell Time

14.1 Block Diagram Of Test Setup



14.2 Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

14.3 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. Centred on a hopping channel;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

14.4 Test Result

DH5 Packet permit maximum $1600 / 79 / 6$ hops per second in each channel
(5 time slots RX, 1 time slot TX).

DH3 Packet permit maximum $1600 / 79 / 4$ hops per second in each channel
(3 time slots RX, 1 time slot TX).

DH1 Packet permit maximum $1600 / 79 / 2$ hops per second in each channel
(1 time slot RX, 1 time slot TX). So, the Dwell Time can be calculated as follows:


DH5: $1600/79/6 \times 0.4 \times 79 \times (\text{MkrDelta})/1000$



DH3: $1600/79/4 \times 0.4 \times 79 \times (\text{MkrDelta})/1000$



DH1: $1600/79/2 \times 0.4 \times 79 \times (\text{MkrDelta})/1000$



Remark: Mkr Delta is once pulse time.



Condition	Mode	Frequency (MHz)	Pulse Time (ms)	Total Dwell Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	0.399	127.281	400	Pass
NVNT	1-DH3	2441	1.658	273.57	400	Pass
NVNT	1-DH5	2441	2.906	281.882	400	Pass
NVNT	2-DH1	2441	0.409	130.471	400	Pass
NVNT	2-DH3	2441	1.663	251.113	400	Pass
NVNT	2-DH5	2441	2.912	349.44	400	Pass
NVNT	3-DH1	2441	0.41	130.79	400	Pass
NVNT	3-DH3	2441	1.661	277.387	400	Pass
NVNT	3-DH5	2441	2.915	314.82	400	Pass











SHENZHEN

15. Antenna Requirement

15.1 Limit

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.


15.2 Test Result

The EUT antenna is Internal antenna, fulfill the requirement of this section.





16. EUT Test Setup Photographs

Conducted emissions



Radiated Measurement Photos



STATEMENT

1. The equipment lists are traceable to the International System of Units (SI)
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC 17025:2017.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

Room 101M, Unit 1, Building1, Pengyuan, No.18, Lilang Road, Shanglilang, Nanwan Subdistrict, Longgang District, Shenzhen, Guangdong, China

TEL:400-788-9558

P.C.: 518116

FAX:0755-33229357

Website: <http://www.chnbctc.com>

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

***** END *****