

Label size:210*100mm

RUNHOOD | RESIDENTIAL ESS & PORTABLE POWER STATION (Li-ion·Battery)

Model	F2400-US
Net Weight	29kg / 63.9 lbs. Approx.
Dimension	50.3cm*32.3cm*34.4cm/19.8in*12.7in*13.5in
Capacity	2400Wh (48Vdc, 50Ah)
Chemical Formulas	LiFePO4 IFpR65/155[1P15S]M/-20+50/95
Battery Pack	Max. Charging Current 40A
	Max. Discharging Current 80A
	Max. Short-Circuit Current And Duration xxA xxms
	Voltage Range 40.5Vdc ~ 54Vdc
	Discharging Temperature -25°C ~ 55°C
DC Input	Charging Temperature -15°C ~ 55°C
	12-60Vdc, 25A, 1200W Max.
	120Vac, 60Hz, 15A, 1800W Max.
	USB-A(*2) 5V $\overline{=}$ 2.4A 12W
	USB-A(*2) QC3.0 5V $\overline{=}$ 3A, 9V $\overline{=}$ 3A, 12V $\overline{=}$ 2.4A, 28W
DC Output	USB-C(*2) PD3.0 5V $\overline{=}$ 3A, 9V $\overline{=}$ 3A, 15V $\overline{=}$ 3A, 20V $\overline{=}$ 5A, 100W
	Car Port 12V $\overline{=}$ 10A, 120W
	LED Output 6W Max.
	120Vac, 60Hz, total 2400W Max.
	-20°C ~ 40°C
AC Output (Socket * 5)	-10°C ~ 40°C
Discharging Temperature	8000 Cycles To 70%+ Capacity@25°C
Charging Temperature	10 Years
Cycle Life	
Warranty	

WARNING

a) Risk of Fire. This device contains energy higher than 1 kWh. Do not use in a sleeping room or any habitable space of a dwelling unit

CAUTION

a) Risk of Electric Shock. Connect only to properly grounded outlets
b) Risk of Injury To Persons. Do not use this product if the power cord or the battery cables are damaged in any way
c) This device is not intended for use in a commercial repair facility
d) Risk of Electric Shock. Never use portable power pack to supply power tools to cut or access live parts or live wirings

DANGER

a) This device is intended to be used indoors only. Do not use outdoors.

RUNHOOD POWER INC.
3980- D Valley Blvd, Walnut,
CA 91789
866-685-9868(toll free)
service@runhoodpower.com
www.runhoodpower.com

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC ID: 2BB59-F2400-US



SN

Made-in-China

AVERTISSEMENT

a) Risque d'incendie. L'énergie de l'appareil est supérieure à 1 kWh. Ne doit pas être utilisé dans une chambre à coucher ou dans un espace habitable dans une unité d'habitation

MISE EN GARDE

a) Risque de décharge électrique. Brancher l'unité uniquement à des prises de courant correctement mises à la masse.
b) Risque de blessure aux personnes. Ne pas utiliser ce produit si le cordon d'alimentation ou les câbles de batterie sont endommagés de quelque façon.
c) Le dispositif n'est pas destiné à être utilisé dans un atelier de réparation commercial
d) Risque de choc électrique. Ne jamais alimenter avec un bloc d'alimentation portable Outils électriques pour couper ou toucher des parties sous tension ou des fils sous tension

DANGER

a) Le dispositif est destiné à être utilisé à l'intérieur seulement. Ne pas l'utiliser à l'extérieur



UN38.3

Intertek
XXXXXXXX

Label location:

