

Modular Approval Request FCC(KDB996369D01&Part 15.212)

FCCID: 2BB64CQS290NA

<i>Items to be covered by Single modular transmitters.</i>	<i>Answer from applicant</i>
1. The modular transmitter must have its own RF shielding.	Yes, the modular has its own RF shielding.
2. The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with Part15 requirements under conditions of excessive data rates or over-modulation.	Yes, the modular has buffer modulation/data inputs
3. The modular transmitter must have its own power supply regulation.	Yes, the modular has its own power supply regulation
4. The modular transmitter must comply with the antenna requirements of Section of 15.203 and 15.204(b)(c). The antenna must either be permanently attached or employ a “unique” antenna coupler(at all connections between the module and antenna, including the cable)	Yes, The requirements of antenna connector and the spurious emission have been fulfilled.
5. The modular transmitter must be tested in a stand-alone configuration, i.e., the Module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part15 emission limits regardless of the device into which it is eventually installed.	Yes, test lab did the test in a stand-alone configuration.
6. The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number in accordance with 15.212(a)(1)(vi)(A)/ (B).	Yes, the Module will be label with its own FCC ID and the instruction on the labelling rule of the end product has been stated in the user manual of this module.
7. The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation Under Section 15.231(e), in which case there are separate field strength level and Timing requirements. Compliance with these requirements must be assured.	Yes, the required FCC rule has been fulfilled and all the instruction for maintaining compliance have been clearly stated in the user manual.
8. The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in sections 1.1310, 2.1091, 2.1093, and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance. Modular transmitters approved under other sections of Part 15, when necessary, may also need to Address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.	Yes, test lab assessment the RF exposure by power density, the RF exposure of this modular is compliance of MPE RF exposure rule.

<i>Items to be covered by Split modular transmitters.</i>	<i>Answer from applicant</i>
1. The modular transmitter must comply with all requirements of a single modular transmitter except for items(1)&(5) of the above single modular approval requirements.	
2. Only the radio front end must be shielded. The physical crystal and tuning capacitors may be located external to the shielded radio elements. The interface between the split sections of the modular system must be digital with a minimum signalling amplitude of 150mVpeak-to-peak.	
3. Control information and other data may be exchanged between the transmitter control elements and radio frontend.	
4. The sections of a split modular transmitter must be tested installed in a host device(s) similar to that which is representative of the platform(s) intended for use.	
5. Manufacturers must ensure that only transmitter control elements and radio front end components that have been approved together are capable of operating together. The transmitter module must not operate unless it has verified that the installed transmitter control elements and radio front end have been authorized together. Manufacturers may use means including, but not limited to, coding in hardware and electronic signatures in software to meet these requirements, and must describe the methods in their application for equipment authorization.	

Note: A limited modular approval (LMA) may be granted for single or split modular transmitters that comply partially with the requirements above.

Name and surname of applicant (or authorized representative): Wu Xuewen

Date: 2025/09/26