



SPECIFICATION

APPLICATION FOR APPROVAL

PART NAME : FPC Antenna
PART NO : ANTFP2-CC0700B5
DATE : 2024/10/23

Release : Full release

Customer Approval	
Program Manager	R & D director
Supplier Approval	
Program Manager	R & D director
Jingqiang Hao	GaoHe Sun

Confidential

This message contains information that may be confidential and privileged. Unless you are the addressee (or authorized to receive messages for the addressee), you can not use, copy or disclose to any third party or any information contained in the message. If you have received the message in error, please advise the sender by reply e-mail and delete the message. Nothing in this message should be interpreted as a digital or electronic signature that can be used to authenticate a contract or other legal document. Thank you very much.

Ad: 2-805, Fubao Industrial Park, Fubao Road, Xiqing District, Tianjin Tel: 022-89545892



NTS

0.	DEFINITIONS	1
1.	ELECTRICAL SPECIFICATIONS	1~2
1-1.	FREQUENCY BAND	1
1-2.	IMPEDANCE	1
1-3.	MATCHING REQUIREMENTS	1
1-4.	VSWR	2, 5
2.	MECHANICAL SPECIFICATION	3, 4
2-1.	MECHANICAL CONFIGURATION	
3.	ENVIRONMENT CHARACTERISTICS	3
4.	PACKAGING	3
5.	APPENDIX	5~6

REVISION

REV. NO.	DATE	DESCRIPTION
A	2024/10/23	APPROVAL



0. DEFINITIONS

dBi	Decibel relative isotropic antenna
Tx	Transmit frequency
Rx	Receive frequency
VSWR	Voltage Standing Wave Ratio
GSM	Global Service for Mobile communication
DCS	Digital Communication System
PCS	Personal Communication System
CDMA	Code Division Multiple Access
WCDMA	Wideband Code Division Multiple Access
PHS	Personal Handly-phone System
SAR	Specific Absorption Rate
PCB	Printed Circuit Board
TBD	To Be Defined
P	Parallel connection
S	Series connection

1. ELECTRICAL SPECIFICATIONS

1-1 FREQUENCY BAND

Freq. Band	Freq. (MHz)
WiFi	2400-2500/5150-5850

1-2 IMPEDANCE


Nominal Impedance(including matching circuit) : 50 ohms



1-3 MATCHING REQUIREMENTS

The matching circuit on the PCB of the handset is according to Figure 1-3. Optimum matching circuit is highly dependent on the handset and thus.

Final matching circuit layout and values will be defined when handset is available



1-4 VSWR

FREE SPAC

Freq. Band	spec
2400-2500/5150-5850MHz	VSWR<2

※Measuring a 50Ω test jig is connected to a network analyzer to measure the VSWR.

※※All test value is done in customer approval fixture.



2. MECHANICAL SPECIFICATIONS

2-1 MECHANICAL CONFIGURATION

The appearance of the antenna is according to Figure 2-1

3. ENVIRONMENTAL CHARACTERISTICS

NO.	ITEM	TEST CONDITION	SPECIFICATION
3-1	Low Temperature Test	1. Temperature: $-40\pm 2^{\circ}\text{C}$ 2. Time: 48hrs	No material deformation is allowed.
3-2	High Temperature Test	1. Temperature: $+85^{\circ}\text{C} \pm 2^{\circ}\text{C}$ 2. Time: 48hrs	
3-3	High Temperature/Humidity Storage Test (non operating)	1. Temperature: $+60 \pm 2^{\circ}\text{C}$ 2. Humidity: $93\% \pm 2\% \text{RH}$ 3. Time: 48hrss	
3-4	Salt-Spray Test	35°C, 85%RH, 48Hours (According to MIL-STD-810E) The salt-spray is generated from a 5% salt (NaCl) solution.,	NO appear rusting phenomenon is allowed

4. PACKAGING

Antenna to be packed in a PE bag. Each 100 pcs per bag.

5. APPENDIX

All of the specifications are shown as the attached files.




Figure 2-1



Customer No: HuaLai Tec.	File: 2024/10/23
Supplier NO:	Note: VSWR/RL/Smith Chart
Sample No:	
Test Condition:	
FREE SPACE	Matching: N/A
Confirmation: Jing Qiang Hao	Engineer: Jing Qiang Hao






Antenna Test Data

一: Antenna Efficiency&PeakGain


Freq (MHz)	Effi (%)	Gain (dBi)
2400	53.24	2.82
2410	53.98	2.56
2420	55.48	2.51
2430	57.53	2.56
2440	59.34	2.34
2450	60.93	2.02
2460	62.02	1.88
2470	60.65	1.99
2480	59.33	2.04
2490	58.05	1.99
2500	56.92	1.95
5150	63.93	3.80
5200	74.48	4.75
5250	74.45	4.72
5300	77.06	5.04
5350	70.66	4.52
5400	72.36	4.81
5450	77.37	5.38
5500	74.22	5.37
5550	79.77	5.43
5600	81.30	5.40
5650	75.75	5.17
5700	72.14	4.79
5750	75.24	4.85
5800	73.30	4.66
5850	62.56	4.13



三：Antenna 2D—2400/2450/2500MHz



四：Antenna 3D—2400/2450/2500MHz



Antenna 3D—5150/5500/5850MHz

