

# FCC TEST REPORT

## FCC ID:2BB7G-VM01

Applicant: Shenzhen Xiaowei Intelligent Technology Co., Ltd

Address: B5C, Building 29, Yintian Industrial Zone, Yantian Community, Xixiang Street, Baoan District, Shenzhen, Guangdong Province, China

Manufacturer: Shenzhen Xiaowei Intelligent Technology Co., Ltd

Address: B5C, Building 29, Yintian Industrial Zone, Yantian Community, Xixiang Street, Baoan District, Shenzhen, Guangdong Province, China

EUT: Dash Cam Front and Inside

Trade Mark: N/A

Model Number: VM01

Date of Receipt: Dec. 16, 2025

Test Date: Dec. 16, 2025 to Dec. 23, 2025

Date of Report: Dec. 31, 2025

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

Applicable Standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247  
ANSI C63.10:2020

Test Result: Pass

Report Number: DLE-251231012R

Prepared (Test Engineer): Dimon Tan

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



*This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.*

## Table of Contents

|                                                                   | Page      |
|-------------------------------------------------------------------|-----------|
| <b>1. VERSION .....</b>                                           | <b>4</b>  |
| <b>2. SUMMARY OF TEST RESULTS .....</b>                           | <b>5</b>  |
| 2.1 TEST FACILITY .....                                           | 6         |
| 2.2 MEASUREMENT UNCERTAINTY .....                                 | 6         |
| <b>3. GENERAL INFORMATION .....</b>                               | <b>7</b>  |
| 3.1 GENERAL DESCRIPTION OF EUT .....                              | 7         |
| 3.2 DESCRIPTION OF TEST MODES .....                               | 8         |
| 3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED ..... | 9         |
| 3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) .....            | 9         |
| 3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS .....                      | 10        |
| <b>4. EMC EMISSION TEST .....</b>                                 | <b>11</b> |
| 4.1 CONDUCTED EMISSION MEASUREMENT .....                          | 11        |
| 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS .....                  | 11        |
| 4.1.2 TEST PROCEDURE .....                                        | 11        |
| 4.1.3 DEVIATION FROM TEST STANDARD .....                          | 11        |
| 4.1.4 TEST SETUP .....                                            | 12        |
| 4.1.5 EUT OPERATING CONDITIONS .....                              | 12        |
| 4.1.6 TEST RESULT .....                                           | 12        |
| 4.2 RADIATED EMISSION MEASUREMENT .....                           | 13        |
| 4.2.1 RADIATED EMISSION LIMITS .....                              | 13        |
| 4.2.2 TEST PROCEDURE .....                                        | 13        |
| 4.2.3 DEVIATION FROM TEST STANDARD .....                          | 14        |
| 4.2.4 TEST SETUP .....                                            | 14        |
| 4.2.5 EUT OPERATING CONDITIONS .....                              | 15        |
| 4.2.6 TEST RESULTS .....                                          | 15        |
| <b>5. RADIATED BAND EMISSIONMEASUREMENT .....</b>                 | <b>26</b> |
| 5.1 TEST REQUIREMENT .....                                        | 26        |
| 5.2 TEST PROCEDURE .....                                          | 26        |
| 5.3 DEVIATION FROM TEST STANDARD .....                            | 27        |
| 5.4 TEST SETUP .....                                              | 27        |
| 5.5 EUT OPERATING CONDITIONS .....                                | 27        |
| 5.6 TEST RESULT .....                                             | 28        |
| 6.1 APPLIED PROCEDURES / LIMIT .....                              | 32        |
| 6.2 TEST PROCEDURE .....                                          | 32        |
| 6.3 DEVIATION FROM STANDARD .....                                 | 32        |
| 6.4 TEST SETUP .....                                              | 32        |
| 6.5 EUT OPERATION CONDITIONS .....                                | 32        |

|                                                     |           |
|-----------------------------------------------------|-----------|
| <b>6.6 TEST RESULT</b>                              | <b>33</b> |
| <b>7. 6DB OCCUPIED BANDWIDTH</b>                    | <b>38</b> |
| 7.1 APPLIED PROCEDURES / LIMIT                      | 38        |
| 7.2 TEST PROCEDURE                                  | 38        |
| 7.3 DEVIATION FROM STANDARD                         | 38        |
| 7.4 TEST SETUP                                      | 39        |
| 7.5 EUT OPERATION CONDITIONS                        | 39        |
| 7.6 TEST RESULT                                     | 39        |
| <b>8. PEAK OUTPUT POWER TEST</b>                    | <b>44</b> |
| 8.1 APPLIED PROCEDURES/LIMIT                        | 44        |
| 8.2 TEST PROCEDURE                                  | 44        |
| 8.3 DEVIATION FROM STANDARD                         | 44        |
| 8.4 TEST SETUP                                      | 44        |
| 8.5 EUT OPERATION CONDITIONS                        | 44        |
| 8.6 TEST RESULT                                     | 45        |
| <b>9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION</b> | <b>46</b> |
| 9.1 APPLICABLE STANDARD                             | 46        |
| 9.2 TEST PROCEDURE                                  | 46        |
| 9.3 DEVIATION FROM STANDARD                         | 47        |
| 9.4 TEST SETUP                                      | 47        |
| 9.5 EUT OPERATION CONDITIONS                        | 47        |
| 9.6 TEST RESULTS                                    | 48        |
| <b>10. DUTY CYCLE</b>                               | <b>56</b> |
| 10.1 APPLIED PROCEDURES / LIMIT                     | 56        |
| 10.2 DEVIATION FROM STANDARD                        | 56        |
| 10.3 TEST SETUP                                     | 56        |
| 10.4 EUT OPERATION CONDITIONS                       | 56        |
| 10.5 TEST RESULTS                                   | 57        |
| <b>11. ANTENNA REQUIREMENT</b>                      | <b>60</b> |
| <b>12. TEST SETUP PHOTO</b>                         | <b>61</b> |
| <b>13. EUT CONSTRUCTIONAL DETAILS</b>               | <b>61</b> |

**1. VERSION**

| Report No.     | Version | Description             | Approved      |
|----------------|---------|-------------------------|---------------|
| DLE-251231012R | Rev.01  | Initial issue of report | Dec. 31, 2025 |
|                |         |                         |               |

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.247) , Subpart C |                                                  |        |        |
|---------------------------------|--------------------------------------------------|--------|--------|
| Standard Section                | Test Item                                        | Result | Remark |
| FCC part 15.203/15.247 (c)      | Antenna requirement                              | PASS   |        |
| FCC part 15.207                 | AC Power Line Conducted Emission                 | N/A    |        |
| FCC part 15.247 (b)(3)          | Conducted Peak Output Power                      | PASS   |        |
| FCC part 15.247 (a)(2)          | 6dB Occupied Bandwidth                           | PASS   |        |
| FCC part 15.247 (e)             | Power Spectral Density                           | PASS   |        |
| FCC part 15.247 (d)             | Conducted Band Edge & Unwanted Spurious Emission | PASS   |        |
| FCC part 15.205/15.209          | Radiated Band Edge & Unwanted Spurious Emission  | PASS   |        |
| ANSI C63.10:2020                | Duty Cycle                                       | PASS   |        |

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

## 2.1 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.

Add. : 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1 Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District, Shenzhen, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB identifier: CN0118

## 2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

| No. | Item                                               | Uncertainty |
|-----|----------------------------------------------------|-------------|
| 1   | 3m chamber Radiated spurious emission (9KHz-30MHz) | U=4.5dB     |
| 2   | 3m chamber Radiated spurious emission (30MHz-1GHz) | U=4.8dB     |
| 3   | 3m chamber Radiated spurious emission (1GHz-6GHz)  | U=4.9dB     |
| 4   | 3m chamber Radiated spurious emission (6GHz-40GHz) | U=5.0dB     |
| 5   | Conducted Disturbance                              | U=3.2dB     |
| 6   | RF Band Edge                                       | U=1.68dB    |
| 7   | RF Power Conducted                                 | U=1.86dB    |
| 8   | RF Conducted Spurious Emission                     | U=2.2dB     |
| 9   | RF Occupied Bandwidth                              | U=1.8MHz    |
| 10  | RF Power Spectral Density                          | U=1.75dB    |
| 11  | Humidity Uncertainty                               | U=5.3%      |
| 12  | Temperature Uncertainty                            | U=0.59°C    |

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                        |                                                                                                               |
|------------------------|---------------------------------------------------------------------------------------------------------------|
| Product Name:          | Dash Cam Front and Inside                                                                                     |
| Trade Mark:            | N/A                                                                                                           |
| Model No.:             | VM01                                                                                                          |
| Serial No.:            | N/A                                                                                                           |
| Model Different.:      | N/A                                                                                                           |
| Hardware Version:      | V1.0                                                                                                          |
| Software Version:      | V1.0                                                                                                          |
| Sample(s) Status:      | Engineer sample                                                                                               |
| Frequency Range:       | 2412-2462MHz for 802.11 b/g/n20<br>2422-2452MHz for 802.11 n40                                                |
| Channel Numbers:       | 802.11b/g/n (20M): 11 Channels<br>802.11n (40M): 7 Channels                                                   |
| Channel Separation:    | 5MHz                                                                                                          |
| Modulation Technology: | 802.11b: Direct Sequence Spread Spectrum(DSSS)<br>802.11g/n: Orthogonal Frequency Division Multiplexing(OFDM) |
| Data Rate:             | 802.11b: 1/2/5.5/11Mbit/s<br>802.11g: 6/9/12/24/18/36/48/54Mbit/s<br>802.11n: MCS0-MCS7                       |
| Antenna Type:          | PCB Antenna                                                                                                   |
| Antenna Gain:          | 2.02dBi                                                                                                       |
| Power Supply:          | Input: DC 12V or 24V                                                                                          |

Note1: For a more detailed features description, please refer to the manufacturer' s specifications or the User's Manual.

Note2: The EUT's all information provided by client.

| Operation Frequency each of channel |           |         |           |         |           |         |           |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel                             | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1                                   | 2412MHz   | 4       | 2427MHz   | 7       | 2442MHz   | 10      | 2457MHz   |
| 2                                   | 2417MHz   | 5       | 2432MHz   | 8       | 2447MHz   | 11      | 2462MHz   |
| 3                                   | 2422MHz   | 6       | 2437MHz   | 9       | 2452MHz   |         |           |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Test channel    | Frequency         |               |
|-----------------|-------------------|---------------|
|                 | 802.11b/g/n (20M) | 802.11n (40M) |
| Lowest channel  | 2412MHz           | 2422MHz       |
| Middle channel  | 2437MHz           | 2437MHz       |
| Highest channel | 2462MHz           | 2452MHz       |

### 3.2 DESCRIPTION OF TEST MODES

|                                                                                                                                                                                                                                                                                                                                      |                                                |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| Transmitting mode                                                                                                                                                                                                                                                                                                                    | Keep the EUT in continuously transmitting mode |
| Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.<br>For battery operated equipment, the equipment tests shall be performed using a new battery. |                                                |

|                                                                                                                                                                                                              |         |         |           |           |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------|-----------|-----------|
| We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows: |         |         |           |           |
| Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.                                                                                                         |         |         |           |           |
| Mode                                                                                                                                                                                                         | 802.11b | 802.11g | 802.11n20 | 802.11n40 |
| Data rate                                                                                                                                                                                                    | 1Mbps   | 6Mbps   | MCS0(HT0) | MCS0(HT0) |


|                   |         |
|-------------------|---------|
| Test Software     | CMD     |
| Power level setup | Default |

### 3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

#### Radiated Emission



#### Conducted Spurious



### 3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment                 | Mfr/Brand | Model/Type No. | Series No. | Note      |
|------|---------------------------|-----------|----------------|------------|-----------|
| E-1  | Dash Cam Front and Inside | N/A       | VM01           | N/A        | EUT       |
| E-2  | Storage Battery           | NANFU     | ZKT-00         | N/A        | Auxiliary |

| Item | Shielded Type | Ferrite Core | Length | Note     |
|------|---------------|--------------|--------|----------|
| C1   | NO            | NO           | 3M     | DC Cable |
| C2   | NO            | NO           | 0.3M   | RF Line  |

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

## 3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

## Radiation test, Band-edge test and 6db bandwidth test equipment

| Item | Equipment                        | Manufacturer    | Type No.  | Serial No. | Last calibration | Calibrated until |
|------|----------------------------------|-----------------|-----------|------------|------------------|------------------|
| 1    | Spectrum Analyzer (9kHz-26.5GHz) | Agilent         | E4408B    | MY50140780 | Oct. 25, 2025    | Oct. 24, 2026    |
| 2    | Test Receiver (9kHz-7GHz)        | R&S             | ESRP7     | 101393     | Oct. 25, 2025    | Oct. 24, 2026    |
| 3    | Bilog Antenna (30MHz-1GHz)       | R&S             | VULB9162  | 00306      | Oct. 27, 2025    | Oct. 26, 2026    |
| 4    | Horn Antenna (1GHz-18GHz)        | Schwarzbeck     | BBHA9120D | 02139      | Oct. 27, 2025    | Oct. 26, 2026    |
| 5    | Horn Antenna (18GHz-40GHz)       | A.H. Systems    | SAS-574   | 588        | Oct. 25, 2025    | Oct. 24, 2026    |
| 6    | Amplifier (9KHz-6GHz)            | Schwarzbeck     | BBV9743B  | 00153      | Oct. 25, 2025    | Oct. 24, 2026    |
| 7    | Amplifier (1GHz-18GHz)           | EMEC            | EM01G8GA  | 00270      | Oct. 25, 2025    | Oct. 24, 2026    |
| 8    | Amplifier (18GHz-40GHz)          | Quanjuda        | DLE-161   | 97         | Oct. 25, 2025    | Oct. 24, 2026    |
| 9    | Loop Antenna (9KHz-30MHz)        | Schwarzbeck     | FMZB1519B | 00014      | Oct. 25, 2025    | Oct. 24, 2026    |
| 10   | RF cables1 (9kHz-1GHz)           | ChengYu         | 966       | 004        | Oct. 25, 2025    | Oct. 24, 2026    |
| 11   | RF cables2 (1GHz-40GHz)          | ChengYu         | 966       | 003        | Oct. 25, 2025    | Oct. 24, 2026    |
| 12   | Antenna connector                | Florida RF Labs | N/A       | RF 01#     | Oct. 25, 2025    | Oct. 24, 2026    |
| 13   | Power probe                      | KEYSIGHT        | U2021XA   | MY55210018 | Oct. 25, 2025    | Oct. 24, 2026    |
| 14   | Signal Analyzer 9kHz-26.5GHz     | Agilent         | N9020A    | MY55370280 | Oct. 25, 2025    | Oct. 24, 2026    |
| 15   | Test Receiver 20kHz-40GHz        | R&S             | ESU 40    | 100376     | Oct. 25, 2025    | Oct. 24, 2026    |
| 16   | D.C. Power Supply                | LongWei         | PS-305D   | 010964729  | Oct. 25, 2025    | Oct. 24, 2026    |

## Conduction Test equipment

| Item | Equipment         | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|------------------|
| 1    | 843 Shielded Room | YIHENG       | 843 Room | 843        | Nov. 05, 2023    | Nov. 04, 2026    |
| 2    | EMI Receiver      | R&S          | ESR      | 101421     | Oct. 25, 2025    | Oct. 24, 2026    |
| 3    | LISN              | R&S          | ENV216   | 102417     | Oct. 25, 2025    | Oct. 24, 2026    |
| 4    | 843 Cable 1#      | ChengYu      | CE Cable | 001        | Oct. 25, 2025    | Oct. 24, 2026    |

## Other

| Item | Name                         | Manufacturer | Model   | Software version |
|------|------------------------------|--------------|---------|------------------|
| 1    | EMC Conduction Test System   | FALA         | EZ EMC  | EMC-CON 3A1.1    |
| 2    | EMC radiation test system    | FALA         | EZ EMC  | FA-03A2          |
| 3    | RF test system               | MAIWEI       | MTS8310 | 2.0.0.0          |
| 4    | RF communication test system | MAIWEI       | MTS8200 | 2.0.0.0          |

#### 4. EMC EMISSION TEST

##### 4.1 CONDUCTED EMISSION MEASUREMENT

|                       |                                      |
|-----------------------|--------------------------------------|
| Test Requirement:     | FCC Part15 C Section 15.207          |
| Test Method:          | ANSI C63.10:2020                     |
| Test Frequency Range: | 150KHz to 30MHz                      |
| Receiver setup:       | RBW=9KHz, VBW=30KHz, Sweep time=auto |

##### 4.1.1 POWER LINE CONDUCTED EMISSION LIMITS

| FREQUENCY (MHz) | Limit (dBuV) |           | Standard |
|-----------------|--------------|-----------|----------|
|                 | Quasi-peak   | Average   |          |
| 0.15 -0.5       | 66 - 56 *    | 56 - 46 * | FCC      |
| 0.50 -5.0       | 56.00        | 46.00     | FCC      |
| 5.0 -30.0       | 60.00        | 50.00     | FCC      |

Note:

(1) \*Decreases with the logarithm of the frequency.


##### 4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

##### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.4 TEST SETUP



**Note: 1.Support units were connected to second LISN.**

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

#### 4.1.6 TEST RESULT

N/A

Note: Only AC products need to test this item; DC products are not applicable.

## 4.2 RADIATED EMISSION MEASUREMENT

|                       |                             |            |        |        |            |
|-----------------------|-----------------------------|------------|--------|--------|------------|
| Test Requirement:     | FCC Part15 C Section 15.209 |            |        |        |            |
| Test Method:          | ANSI C63.10:2020            |            |        |        |            |
| Test Frequency Range: | 9kHz to 25GHz               |            |        |        |            |
| Test site:            | Measurement Distance: 3m    |            |        |        |            |
| Receiver setup:       | Frequency                   | Detector   | RBW    | VBW    | Value      |
|                       | 9KHz-150KHz                 | Quasi-peak | 200Hz  | 600Hz  | Quasi-peak |
|                       | 150KHz-30MHz                | Quasi-peak | 9KHz   | 30KHz  | Quasi-peak |
|                       | 30MHz-1GHz                  | Quasi-peak | 120KHz | 300KHz | Quasi-peak |
|                       | Above 1GHz                  | Peak       | 1MHz   | 3MHz   | Peak       |
|                       |                             | Peak       | 1MHz   | 10Hz   | Average    |

## 4.2.1 RADIATED EMISSION LIMITS

| Frequencies<br>(MHz) | Field Strength<br>(micorvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                          | 300                              |
| 0.490~1.705          | 24000/F(KHz)                         | 30                               |
| 1.705~30.0           | 30                                   | 30                               |
| 30~88                | 100                                  | 3                                |
| 88~216               | 150                                  | 3                                |
| 216~960              | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

## LIMITS OF RADIATED EMISSION MEASUREMENT

| Frequency<br>(MHz) | Limit (dBuV/m) (at 3M) |         |
|--------------------|------------------------|---------|
|                    | Peak                   | Average |
| Above 1000         | 74                     | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

## 4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter( Above 18GHz the distance is 1 meter and table is 1.5 meter).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

#### 4.2.3 DEVIATION FROM TEST STANDARD


No deviation

#### 4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



## (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



## (C) Radiated Emission Test-Up Frequency Above 1GHz



## 4.2.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


## 4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

|               |         |                    |                        |
|---------------|---------|--------------------|------------------------|
| Temperature:  | 26℃     | Relative Humidity: | 54%                    |
| Pressure:     | 101 kPa | Polarization:      | Horizontal             |
| Test Voltage: | DC 12V  | Test Mode :        | TX 802.11n40 - 2422MHz |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 151.5971        | 48.99          | -22.91        | 26.08          | 43.50          | -17.42      | QP       |
| 2   | 187.7529        | 48.35          | -23.15        | 25.20          | 43.50          | -18.30      | QP       |
| 3   | 262.8955        | 64.27          | -23.60        | 40.67          | 46.00          | -5.33       | QP       |
| 4   | 269.4282        | 59.24          | -23.46        | 35.78          | 46.00          | -10.22      | QP       |
| 5   | 326.7395        | 52.92          | -22.08        | 30.84          | 46.00          | -15.16      | QP       |
| 6   | 383.9318        | 53.44          | -20.35        | 33.09          | 46.00          | -12.91      | QP       |

## Remarks:

1. An initial pre-scan was performed on the peak detector.
2. Quasi - Peak measurement were performed at the frequencies with maximized peak emission.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Final Level = Reading level + Correct Factor.
5. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
6. Margin = Measurement Level-Limit.
7. The test data shows only the worst case TX 802.11n40 - 2422MHz.

|               |        |                    |                        |
|---------------|--------|--------------------|------------------------|
| Temperature:  | 26°C   | Relative Humidity: | 54%                    |
| Pressure:     | 101kPa | Polarization:      | Vertical               |
| Test Voltage: | DC 12V | Test Mode :        | TX 802.11n40 - 2422MHz |



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 151.0663        | 58.90          | -22.92        | 35.98          | 43.50          | -7.52       | QP       |
| 2   | 258.3263        | 57.48          | -23.69        | 33.79          | 46.00          | -12.21      | QP       |
| 3   | 263.8190        | 59.17          | -23.58        | 35.59          | 46.00          | -10.41      | QP       |
| 4   | 326.7395        | 57.03          | -22.08        | 34.95          | 46.00          | -11.05      | QP       |
| 5   | 366.8231        | 50.64          | -20.86        | 29.78          | 46.00          | -16.22      | QP       |
| 6   | 382.5878        | 51.44          | -20.39        | 31.05          | 46.00          | -14.95      | QP       |

## Remarks:

1. An initial pre-scan was performed on the peak detector.
2. Quasi - Peak measurement were performed at the frequencies with maximized peak emission.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Final Level = Reading level + Correct Factor.
5. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
6. Margin = Measurement Level-Limit.
7. The test data shows only the worst case TX 802.11n40 - 2422MHz.

1GHz~25GHz

802.11b

| Polar<br>(H/V)      | Frequency | Meter<br>Reading | Pre-ampl<br>ifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits       | Margin | Detect<br>or<br>Type |
|---------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|--------------|--------|----------------------|
|                     | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/<br>m) | (dB)   |                      |
| Low Channel:2412MHz |           |                  |                   |               |                   |                   |              |        |                      |
| V                   | 4824.00   | 51.90            | 30.55             | 5.77          | 24.66             | 51.78             | 74.00        | -22.22 | PK                   |
| V                   | 4824.00   | 43.89            | 30.55             | 5.77          | 24.66             | 43.77             | 54.00        | -10.23 | AV                   |
| V                   | 7236.00   | 50.85            | 30.33             | 6.32          | 24.55             | 51.39             | 74.00        | -22.61 | PK                   |
| V                   | 7236.00   | 43.99            | 30.33             | 6.32          | 24.55             | 44.53             | 54.00        | -9.47  | AV                   |
| V                   | 9648.00   | 54.65            | 30.85             | 7.45          | 24.69             | 55.94             | 74.00        | -18.06 | PK                   |
| V                   | 9648.00   | 43.73            | 30.85             | 7.45          | 24.69             | 45.02             | 54.00        | -8.98  | AV                   |
| V                   | 12060.00  | 51.88            | 31.02             | 8.99          | 25.57             | 55.42             | 74.00        | -18.58 | PK                   |
| V                   | 12060.00  | 43.21            | 31.02             | 8.99          | 25.57             | 46.75             | 54.00        | -7.25  | AV                   |
| H                   | 4824.00   | 53.67            | 30.55             | 5.77          | 24.66             | 53.55             | 74.00        | -20.45 | PK                   |
| H                   | 4824.00   | 43.71            | 30.55             | 5.77          | 24.66             | 43.59             | 54.00        | -10.41 | AV                   |
| H                   | 7236.00   | 51.79            | 30.33             | 6.32          | 24.55             | 52.33             | 74.00        | -21.67 | PK                   |
| H                   | 7236.00   | 43.74            | 30.33             | 6.32          | 24.55             | 44.28             | 54.00        | -9.72  | AV                   |
| H                   | 9648.00   | 53.42            | 30.85             | 7.45          | 24.69             | 54.71             | 74.00        | -19.29 | PK                   |
| H                   | 9648.00   | 43.28            | 30.85             | 7.45          | 24.69             | 44.57             | 54.00        | -9.43  | AV                   |
| H                   | 12060.00  | 52.34            | 31.02             | 8.99          | 25.57             | 55.88             | 74.00        | -18.12 | PK                   |
| H                   | 12060.00  | 43.01            | 31.02             | 8.99          | 25.57             | 46.55             | 54.00        | -7.45  | AV                   |

| Polar<br>(H/V)         | Frequency | Meter<br>Reading | Pre-ampl<br>ifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits       | Margin | Detect<br>or<br>Type |
|------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|--------------|--------|----------------------|
|                        | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/<br>m) | (dB)   |                      |
| Middle Channel:2437MHz |           |                  |                   |               |                   |                   |              |        |                      |
| V                      | 4874.00   | 51.41            | 30.55             | 5.77          | 24.66             | 51.29             | 74.00        | -22.71 | PK                   |
| V                      | 4874.00   | 43.62            | 30.55             | 5.77          | 24.66             | 43.50             | 54.00        | -10.50 | AV                   |
| V                      | 7311.00   | 54.93            | 30.33             | 6.32          | 24.55             | 55.47             | 74.00        | -18.53 | PK                   |
| V                      | 7311.00   | 43.02            | 30.33             | 6.32          | 24.55             | 43.56             | 54.00        | -10.44 | AV                   |
| V                      | 9748.00   | 51.67            | 30.85             | 7.45          | 24.69             | 52.96             | 74.00        | -21.04 | PK                   |
| V                      | 9748.00   | 43.50            | 30.85             | 7.45          | 24.69             | 44.79             | 54.00        | -9.21  | AV                   |
| V                      | 12185.00  | 51.35            | 31.02             | 8.99          | 25.57             | 54.89             | 74.00        | -19.11 | PK                   |
| V                      | 12185.00  | 43.55            | 31.02             | 8.99          | 25.57             | 47.09             | 54.00        | -6.91  | AV                   |
| H                      | 4874.00   | 50.40            | 30.55             | 5.77          | 24.66             | 50.28             | 74.00        | -23.72 | PK                   |
| H                      | 4874.00   | 43.02            | 30.55             | 5.77          | 24.66             | 42.90             | 54.00        | -11.10 | AV                   |
| H                      | 7311.00   | 50.60            | 30.33             | 6.32          | 24.55             | 51.14             | 74.00        | -22.86 | PK                   |
| H                      | 7311.00   | 43.57            | 30.33             | 6.32          | 24.55             | 44.11             | 54.00        | -9.89  | AV                   |
| H                      | 9748.00   | 54.15            | 30.85             | 7.45          | 24.69             | 55.44             | 74.00        | -18.56 | PK                   |
| H                      | 9748.00   | 43.15            | 30.85             | 7.45          | 24.69             | 44.44             | 54.00        | -9.56  | AV                   |
| H                      | 12185.00  | 54.96            | 31.02             | 8.99          | 25.57             | 58.50             | 74.00        | -15.50 | PK                   |
| H                      | 12185.00  | 43.76            | 31.02             | 8.99          | 25.57             | 47.30             | 54.00        | -6.70  | AV                   |

| Polar<br>(H/V)       | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-ampli<br>fier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/<br>m) | Margin<br>(dB) | Detect<br>or<br>Type |
|----------------------|--------------------|----------------------------|---------------------------|-----------------------|---------------------------|-------------------------------|------------------------|----------------|----------------------|
| High Channel:2462MHz |                    |                            |                           |                       |                           |                               |                        |                |                      |
| V                    | 4924.00            | 52.68                      | 30.55                     | 5.77                  | 24.66                     | 52.56                         | 74.00                  | -21.44         | PK                   |
| V                    | 4924.00            | 43.15                      | 30.55                     | 5.77                  | 24.66                     | 43.03                         | 54.00                  | -10.97         | AV                   |
| V                    | 7386.00            | 52.86                      | 30.33                     | 6.32                  | 24.55                     | 53.40                         | 74.00                  | -20.60         | PK                   |
| V                    | 7386.00            | 43.08                      | 30.33                     | 6.32                  | 24.55                     | 43.62                         | 54.00                  | -10.38         | AV                   |
| V                    | 9848.00            | 51.81                      | 30.85                     | 7.45                  | 24.69                     | 53.10                         | 74.00                  | -20.90         | PK                   |
| V                    | 9848.00            | 43.89                      | 30.85                     | 7.45                  | 24.69                     | 45.18                         | 54.00                  | -8.82          | AV                   |
| V                    | 12310.00           | 52.10                      | 31.02                     | 8.99                  | 25.57                     | 55.64                         | 74.00                  | -18.36         | PK                   |
| V                    | 12310.00           | 43.39                      | 31.02                     | 8.99                  | 25.57                     | 46.93                         | 54.00                  | -7.07          | AV                   |
| H                    | 4924.00            | 53.40                      | 30.55                     | 5.77                  | 24.66                     | 53.28                         | 74.00                  | -20.72         | PK                   |
| H                    | 4924.00            | 43.33                      | 30.55                     | 5.77                  | 24.66                     | 43.21                         | 54.00                  | -10.79         | AV                   |
| H                    | 7386.00            | 52.17                      | 30.33                     | 6.32                  | 24.55                     | 52.71                         | 74.00                  | -21.29         | PK                   |
| H                    | 7386.00            | 43.29                      | 30.33                     | 6.32                  | 24.55                     | 43.83                         | 54.00                  | -10.17         | AV                   |
| H                    | 9848.00            | 54.94                      | 30.85                     | 7.45                  | 24.69                     | 56.23                         | 74.00                  | -17.77         | PK                   |
| H                    | 9848.00            | 43.65                      | 30.85                     | 7.45                  | 24.69                     | 44.94                         | 54.00                  | -9.06          | AV                   |
| H                    | 12310.00           | 51.88                      | 31.02                     | 8.99                  | 25.57                     | 55.42                         | 74.00                  | -18.58         | PK                   |
| H                    | 12310.00           | 43.03                      | 31.02                     | 8.99                  | 25.57                     | 46.57                         | 54.00                  | -7.43          | AV                   |

## Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

## 802.11g

| Polar (H/V)         | Frequency (MHz) | Meter Reading (dBuV) | Pre-amplifier (dB) | Cable Loss (dB) | Antenna Factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detect or Type |
|---------------------|-----------------|----------------------|--------------------|-----------------|---------------------|-------------------------|-----------------|-------------|----------------|
| Low Channel:2412MHz |                 |                      |                    |                 |                     |                         |                 |             |                |
| V                   | 4824.00         | 50.13                | 30.55              | 5.77            | 24.66               | 50.01                   | 74.00           | -23.99      | PK             |
| V                   | 4824.00         | 43.96                | 30.55              | 5.77            | 24.66               | 43.84                   | 54.00           | -10.16      | AV             |
| V                   | 7236.00         | 51.97                | 30.33              | 6.32            | 24.55               | 52.51                   | 74.00           | -21.49      | PK             |
| V                   | 7236.00         | 43.25                | 30.33              | 6.32            | 24.55               | 43.79                   | 54.00           | -10.21      | AV             |
| V                   | 9648.00         | 54.79                | 30.85              | 7.45            | 24.69               | 56.08                   | 74.00           | -17.92      | PK             |
| V                   | 9648.00         | 43.70                | 30.85              | 7.45            | 24.69               | 44.99                   | 54.00           | -9.01       | AV             |
| V                   | 12060.00        | 50.41                | 31.02              | 8.99            | 25.57               | 53.95                   | 74.00           | -20.05      | PK             |
| V                   | 12060.00        | 43.57                | 31.02              | 8.99            | 25.57               | 47.11                   | 54.00           | -6.89       | AV             |
| H                   | 4824.00         | 53.92                | 30.55              | 5.77            | 24.66               | 53.80                   | 74.00           | -20.20      | PK             |
| H                   | 4824.00         | 43.85                | 30.55              | 5.77            | 24.66               | 43.73                   | 54.00           | -10.27      | AV             |
| H                   | 7236.00         | 51.12                | 30.33              | 6.32            | 24.55               | 51.66                   | 74.00           | -22.34      | PK             |
| H                   | 7236.00         | 43.20                | 30.33              | 6.32            | 24.55               | 43.74                   | 54.00           | -10.26      | AV             |
| H                   | 9648.00         | 52.00                | 30.85              | 7.45            | 24.69               | 53.29                   | 74.00           | -20.71      | PK             |
| H                   | 9648.00         | 43.73                | 30.85              | 7.45            | 24.69               | 45.02                   | 54.00           | -8.98       | AV             |
| H                   | 12060.00        | 52.58                | 31.02              | 8.99            | 25.57               | 56.12                   | 74.00           | -17.88      | PK             |
| H                   | 12060.00        | 43.76                | 31.02              | 8.99            | 25.57               | 47.30                   | 54.00           | -6.70       | AV             |

| Polar (H/V)            | Frequency (MHz) | Meter Reading (dBuV) | Pre-amplifier (dB) | Cable Loss (dB) | Antenna Factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detect or Type |
|------------------------|-----------------|----------------------|--------------------|-----------------|---------------------|-------------------------|-----------------|-------------|----------------|
| Middle Channel:2437MHz |                 |                      |                    |                 |                     |                         |                 |             |                |
| V                      | 4874.00         | 51.68                | 30.55              | 5.77            | 24.66               | 51.56                   | 74.00           | -22.44      | PK             |
| V                      | 4874.00         | 43.07                | 30.55              | 5.77            | 24.66               | 42.95                   | 54.00           | -11.05      | AV             |
| V                      | 7311.00         | 54.30                | 30.33              | 6.32            | 24.55               | 54.84                   | 74.00           | -19.16      | PK             |
| V                      | 7311.00         | 43.87                | 30.33              | 6.32            | 24.55               | 44.41                   | 54.00           | -9.59       | AV             |
| V                      | 9748.00         | 52.34                | 30.85              | 7.45            | 24.69               | 53.63                   | 74.00           | -20.37      | PK             |
| V                      | 9748.00         | 43.67                | 30.85              | 7.45            | 24.69               | 44.96                   | 54.00           | -9.04       | AV             |
| V                      | 12185.00        | 52.74                | 31.02              | 8.99            | 25.57               | 56.28                   | 74.00           | -17.72      | PK             |
| V                      | 12185.00        | 43.04                | 31.02              | 8.99            | 25.57               | 46.58                   | 54.00           | -7.42       | AV             |
| H                      | 4874.00         | 52.70                | 30.55              | 5.77            | 24.66               | 52.58                   | 74.00           | -21.42      | PK             |
| H                      | 4874.00         | 43.39                | 30.55              | 5.77            | 24.66               | 43.27                   | 54.00           | -10.73      | AV             |
| H                      | 7311.00         | 52.63                | 30.33              | 6.32            | 24.55               | 53.17                   | 74.00           | -20.83      | PK             |
| H                      | 7311.00         | 43.53                | 30.33              | 6.32            | 24.55               | 44.07                   | 54.00           | -9.93       | AV             |
| H                      | 9748.00         | 53.43                | 30.85              | 7.45            | 24.69               | 54.72                   | 74.00           | -19.28      | PK             |
| H                      | 9748.00         | 43.97                | 30.85              | 7.45            | 24.69               | 45.26                   | 54.00           | -8.74       | AV             |
| H                      | 12185.00        | 51.74                | 31.02              | 8.99            | 25.57               | 55.28                   | 74.00           | -18.72      | PK             |
| H                      | 12185.00        | 43.97                | 31.02              | 8.99            | 25.57               | 47.51                   | 54.00           | -6.49       | AV             |

| Polar<br>(H/V)       | Frequency | Meter<br>Reading | Pre-ampl<br>ifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits       | Margin | Detect<br>or<br>Type |
|----------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|--------------|--------|----------------------|
|                      | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/<br>m) | (dB)   |                      |
| High Channel:2462MHz |           |                  |                   |               |                   |                   |              |        |                      |
| V                    | 4924.00   | 50.14            | 30.55             | 5.77          | 24.66             | 50.02             | 74.00        | -23.98 | PK                   |
| V                    | 4924.00   | 43.44            | 30.55             | 5.77          | 24.66             | 43.32             | 54.00        | -10.68 | AV                   |
| V                    | 7386.00   | 52.84            | 30.33             | 6.32          | 24.55             | 53.38             | 74.00        | -20.62 | PK                   |
| V                    | 7386.00   | 43.51            | 30.33             | 6.32          | 24.55             | 44.05             | 54.00        | -9.95  | AV                   |
| V                    | 9848.00   | 51.60            | 30.85             | 7.45          | 24.69             | 52.89             | 74.00        | -21.11 | PK                   |
| V                    | 9848.00   | 43.75            | 30.85             | 7.45          | 24.69             | 45.04             | 54.00        | -8.96  | AV                   |
| V                    | 12310.00  | 53.58            | 31.02             | 8.99          | 25.57             | 57.12             | 74.00        | -16.88 | PK                   |
| V                    | 12310.00  | 43.92            | 31.02             | 8.99          | 25.57             | 47.46             | 54.00        | -6.54  | AV                   |
| H                    | 4924.00   | 51.58            | 30.55             | 5.77          | 24.66             | 51.46             | 74.00        | -22.54 | PK                   |
| H                    | 4924.00   | 43.81            | 30.55             | 5.77          | 24.66             | 43.69             | 54.00        | -10.31 | AV                   |
| H                    | 7386.00   | 54.25            | 30.33             | 6.32          | 24.55             | 54.79             | 74.00        | -19.21 | PK                   |
| H                    | 7386.00   | 43.37            | 30.33             | 6.32          | 24.55             | 43.91             | 54.00        | -10.09 | AV                   |
| H                    | 9848.00   | 53.95            | 30.85             | 7.45          | 24.69             | 55.24             | 74.00        | -18.76 | PK                   |
| H                    | 9848.00   | 43.74            | 30.85             | 7.45          | 24.69             | 45.03             | 54.00        | -8.97  | AV                   |
| H                    | 12310.00  | 50.60            | 31.02             | 8.99          | 25.57             | 54.14             | 74.00        | -19.86 | PK                   |
| H                    | 12310.00  | 43.28            | 31.02             | 8.99          | 25.57             | 46.82             | 54.00        | -7.18  | AV                   |

## Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

## 802.11n20

| Polar<br>(H/V)      | Frequency | Meter<br>Reading | Pre-ampl<br>ifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits       | Margin | Detect<br>or<br>Type |
|---------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|--------------|--------|----------------------|
|                     | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/<br>m) | (dB)   |                      |
| Low Channel:2412MHz |           |                  |                   |               |                   |                   |              |        |                      |
| V                   | 4824.00   | 51.05            | 30.55             | 5.77          | 24.66             | 50.93             | 74.00        | -23.07 | PK                   |
| V                   | 4824.00   | 43.72            | 30.55             | 5.77          | 24.66             | 43.60             | 54.00        | -10.40 | AV                   |
| V                   | 7236.00   | 51.77            | 30.33             | 6.32          | 24.55             | 52.31             | 74.00        | -21.69 | PK                   |
| V                   | 7236.00   | 43.17            | 30.33             | 6.32          | 24.55             | 43.71             | 54.00        | -10.29 | AV                   |
| V                   | 9648.00   | 51.75            | 30.85             | 7.45          | 24.69             | 53.04             | 74.00        | -20.96 | PK                   |
| V                   | 9648.00   | 43.33            | 30.85             | 7.45          | 24.69             | 44.62             | 54.00        | -9.38  | AV                   |
| V                   | 12060.00  | 52.83            | 31.02             | 8.99          | 25.57             | 56.37             | 74.00        | -17.63 | PK                   |
| V                   | 12060.00  | 43.84            | 31.02             | 8.99          | 25.57             | 47.38             | 54.00        | -6.62  | AV                   |
| H                   | 4824.00   | 51.97            | 30.55             | 5.77          | 24.66             | 51.85             | 74.00        | -22.15 | PK                   |
| H                   | 4824.00   | 43.80            | 30.55             | 5.77          | 24.66             | 43.68             | 54.00        | -10.32 | AV                   |
| H                   | 7236.00   | 54.02            | 30.33             | 6.32          | 24.55             | 54.56             | 74.00        | -19.44 | PK                   |
| H                   | 7236.00   | 43.13            | 30.33             | 6.32          | 24.55             | 43.67             | 54.00        | -10.33 | AV                   |
| H                   | 9648.00   | 51.74            | 30.85             | 7.45          | 24.69             | 53.03             | 74.00        | -20.97 | PK                   |
| H                   | 9648.00   | 43.06            | 30.85             | 7.45          | 24.69             | 44.35             | 54.00        | -9.65  | AV                   |
| H                   | 12060.00  | 53.71            | 31.02             | 8.99          | 25.57             | 57.25             | 74.00        | -16.75 | PK                   |
| H                   | 12060.00  | 43.36            | 31.02             | 8.99          | 25.57             | 46.90             | 54.00        | -7.10  | AV                   |

| Polar<br>(H/V)         | Frequency | Meter<br>Reading | Pre-ampl<br>ifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits       | Margin | Detect<br>or<br>Type |
|------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|--------------|--------|----------------------|
|                        | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB)              | (dBuV/m)          | (dBuV/<br>m) | (dB)   |                      |
| Middle Channel:2437MHz |           |                  |                   |               |                   |                   |              |        |                      |
| V                      | 4874.00   | 53.28            | 30.55             | 5.77          | 24.66             | 53.16             | 74.00        | -20.84 | PK                   |
| V                      | 4874.00   | 43.51            | 30.55             | 5.77          | 24.66             | 43.39             | 54.00        | -10.61 | AV                   |
| V                      | 7311.00   | 55.00            | 30.33             | 6.32          | 24.55             | 55.54             | 74.00        | -18.46 | PK                   |
| V                      | 7311.00   | 43.83            | 30.33             | 6.32          | 24.55             | 44.37             | 54.00        | -9.63  | AV                   |
| V                      | 9748.00   | 54.07            | 30.85             | 7.45          | 24.69             | 55.36             | 74.00        | -18.64 | PK                   |
| V                      | 9748.00   | 43.85            | 30.85             | 7.45          | 24.69             | 45.14             | 54.00        | -8.86  | AV                   |
| V                      | 12185.00  | 54.14            | 31.02             | 8.99          | 25.57             | 57.68             | 74.00        | -16.32 | PK                   |
| V                      | 12185.00  | 43.65            | 31.02             | 8.99          | 25.57             | 47.19             | 54.00        | -6.81  | AV                   |
| H                      | 4874.00   | 50.55            | 30.55             | 5.77          | 24.66             | 50.43             | 74.00        | -23.57 | PK                   |
| H                      | 4874.00   | 43.20            | 30.55             | 5.77          | 24.66             | 43.08             | 54.00        | -10.92 | AV                   |
| H                      | 7311.00   | 50.04            | 30.33             | 6.32          | 24.55             | 50.58             | 74.00        | -23.42 | PK                   |
| H                      | 7311.00   | 43.65            | 30.33             | 6.32          | 24.55             | 44.19             | 54.00        | -9.81  | AV                   |
| H                      | 9748.00   | 54.32            | 30.85             | 7.45          | 24.69             | 55.61             | 74.00        | -18.39 | PK                   |
| H                      | 9748.00   | 43.74            | 30.85             | 7.45          | 24.69             | 45.03             | 54.00        | -8.97  | AV                   |
| H                      | 12185.00  | 54.74            | 31.02             | 8.99          | 25.57             | 58.28             | 74.00        | -15.72 | PK                   |
| H                      | 12185.00  | 43.79            | 31.02             | 8.99          | 25.57             | 47.33             | 54.00        | -6.67  | AV                   |

| Polar<br>(H/V)       | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-ampl<br>ifier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/<br>m) | Margin<br>(dB) | Detect<br>or<br>Type |
|----------------------|--------------------|----------------------------|---------------------------|-----------------------|---------------------------|-------------------------------|------------------------|----------------|----------------------|
| High Channel:2462MHz |                    |                            |                           |                       |                           |                               |                        |                |                      |
| V                    | 4924.00            | 52.23                      | 30.55                     | 5.77                  | 24.66                     | 52.11                         | 74.00                  | -21.89         | PK                   |
| V                    | 4924.00            | 43.68                      | 30.55                     | 5.77                  | 24.66                     | 43.56                         | 54.00                  | -10.44         | AV                   |
| V                    | 7386.00            | 52.22                      | 30.33                     | 6.32                  | 24.55                     | 52.76                         | 74.00                  | -21.24         | PK                   |
| V                    | 7386.00            | 43.30                      | 30.33                     | 6.32                  | 24.55                     | 43.84                         | 54.00                  | -10.16         | AV                   |
| V                    | 9848.00            | 51.96                      | 30.85                     | 7.45                  | 24.69                     | 53.25                         | 74.00                  | -20.75         | PK                   |
| V                    | 9848.00            | 43.96                      | 30.85                     | 7.45                  | 24.69                     | 45.25                         | 54.00                  | -8.75          | AV                   |
| V                    | 12310.00           | 52.28                      | 31.02                     | 8.99                  | 25.57                     | 55.82                         | 74.00                  | -18.18         | PK                   |
| V                    | 12310.00           | 43.30                      | 31.02                     | 8.99                  | 25.57                     | 46.84                         | 54.00                  | -7.16          | AV                   |
| H                    | 4924.00            | 52.48                      | 30.55                     | 5.77                  | 24.66                     | 52.36                         | 74.00                  | -21.64         | PK                   |
| H                    | 4924.00            | 43.75                      | 30.55                     | 5.77                  | 24.66                     | 43.63                         | 54.00                  | -10.37         | AV                   |
| H                    | 7386.00            | 52.22                      | 30.33                     | 6.32                  | 24.55                     | 52.76                         | 74.00                  | -21.24         | PK                   |
| H                    | 7386.00            | 43.26                      | 30.33                     | 6.32                  | 24.55                     | 43.80                         | 54.00                  | -10.20         | AV                   |
| H                    | 9848.00            | 51.10                      | 30.85                     | 7.45                  | 24.69                     | 52.39                         | 74.00                  | -21.61         | PK                   |
| H                    | 9848.00            | 43.79                      | 30.85                     | 7.45                  | 24.69                     | 45.08                         | 54.00                  | -8.92          | AV                   |
| H                    | 12310.00           | 52.77                      | 31.02                     | 8.99                  | 25.57                     | 56.31                         | 74.00                  | -17.69         | PK                   |
| H                    | 12310.00           | 43.29                      | 31.02                     | 8.99                  | 25.57                     | 46.83                         | 54.00                  | -7.17          | AV                   |

## Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

## 802.11n40

| Polar (H/V)         | Frequency (MHz) | Meter Reading (dBuV) | Pre-amplifier (dB) | Cable Loss (dB) | Antenna Factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detect or Type |
|---------------------|-----------------|----------------------|--------------------|-----------------|---------------------|-------------------------|-----------------|-------------|----------------|
| Low Channel:2422MHz |                 |                      |                    |                 |                     |                         |                 |             |                |
| V                   | 4844.00         | 53.49                | 30.55              | 5.77            | 24.66               | 53.37                   | 74.00           | -20.63      | PK             |
| V                   | 4844.00         | 43.54                | 30.55              | 5.77            | 24.66               | 43.42                   | 54.00           | -10.58      | AV             |
| V                   | 7266.00         | 51.53                | 30.33              | 6.32            | 24.55               | 52.07                   | 74.00           | -21.93      | PK             |
| V                   | 7266.00         | 43.94                | 30.33              | 6.32            | 24.55               | 44.48                   | 54.00           | -9.52       | AV             |
| V                   | 9688.00         | 51.74                | 30.85              | 7.45            | 24.69               | 53.03                   | 74.00           | -20.97      | PK             |
| V                   | 9688.00         | 43.85                | 30.85              | 7.45            | 24.69               | 45.14                   | 54.00           | -8.86       | AV             |
| V                   | 12110.00        | 54.82                | 31.02              | 8.99            | 25.57               | 58.36                   | 74.00           | -15.64      | PK             |
| V                   | 12110.00        | 43.79                | 31.02              | 8.99            | 25.57               | 47.33                   | 54.00           | -6.67       | AV             |
| H                   | 4844.00         | 54.41                | 30.55              | 5.77            | 24.66               | 54.29                   | 74.00           | -19.71      | PK             |
| H                   | 4844.00         | 43.88                | 30.55              | 5.77            | 24.66               | 43.76                   | 54.00           | -10.24      | AV             |
| H                   | 7266.00         | 52.59                | 30.33              | 6.32            | 24.55               | 53.13                   | 74.00           | -20.87      | PK             |
| H                   | 7266.00         | 43.62                | 30.33              | 6.32            | 24.55               | 44.16                   | 54.00           | -9.84       | AV             |
| H                   | 9688.00         | 54.57                | 30.85              | 7.45            | 24.69               | 55.86                   | 74.00           | -18.14      | PK             |
| H                   | 9688.00         | 43.62                | 30.85              | 7.45            | 24.69               | 44.91                   | 54.00           | -9.09       | AV             |
| H                   | 12110.00        | 53.74                | 31.02              | 8.99            | 25.57               | 57.28                   | 74.00           | -16.72      | PK             |
| H                   | 12110.00        | 43.49                | 31.02              | 8.99            | 25.57               | 47.03                   | 54.00           | -6.97       | AV             |

| Polar (H/V)            | Frequency (MHz) | Meter Reading (dBuV) | Pre-amplifier (dB) | Cable Loss (dB) | Antenna Factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detect or Type |
|------------------------|-----------------|----------------------|--------------------|-----------------|---------------------|-------------------------|-----------------|-------------|----------------|
| Middle Channel:2437MHz |                 |                      |                    |                 |                     |                         |                 |             |                |
| V                      | 4874.00         | 52.90                | 30.55              | 5.77            | 24.66               | 52.78                   | 74.00           | -21.22      | PK             |
| V                      | 4874.00         | 43.49                | 30.55              | 5.77            | 24.66               | 43.37                   | 54.00           | -10.63      | AV             |
| V                      | 7311.00         | 54.35                | 30.33              | 6.32            | 24.55               | 54.89                   | 74.00           | -19.11      | PK             |
| V                      | 7311.00         | 43.04                | 30.33              | 6.32            | 24.55               | 43.58                   | 54.00           | -10.42      | AV             |
| V                      | 9748.00         | 54.32                | 30.85              | 7.45            | 24.69               | 55.61                   | 74.00           | -18.39      | PK             |
| V                      | 9748.00         | 43.68                | 30.85              | 7.45            | 24.69               | 44.97                   | 54.00           | -9.03       | AV             |
| V                      | 12185.00        | 51.64                | 31.02              | 8.99            | 25.57               | 55.18                   | 74.00           | -18.82      | PK             |
| V                      | 12185.00        | 43.97                | 31.02              | 8.99            | 25.57               | 47.51                   | 54.00           | -6.49       | AV             |
| H                      | 4874.00         | 54.68                | 30.55              | 5.77            | 24.66               | 54.56                   | 74.00           | -19.44      | PK             |
| H                      | 4874.00         | 43.94                | 30.55              | 5.77            | 24.66               | 43.82                   | 54.00           | -10.18      | AV             |
| H                      | 7311.00         | 50.69                | 30.33              | 6.32            | 24.55               | 51.23                   | 74.00           | -22.77      | PK             |
| H                      | 7311.00         | 43.74                | 30.33              | 6.32            | 24.55               | 44.28                   | 54.00           | -9.72       | AV             |
| H                      | 9748.00         | 51.02                | 30.85              | 7.45            | 24.69               | 52.31                   | 74.00           | -21.69      | PK             |
| H                      | 9748.00         | 43.95                | 30.85              | 7.45            | 24.69               | 45.24                   | 54.00           | -8.76       | AV             |
| H                      | 12185.00        | 53.50                | 31.02              | 8.99            | 25.57               | 57.04                   | 74.00           | -16.96      | PK             |
| H                      | 12185.00        | 43.53                | 31.02              | 8.99            | 25.57               | 47.07                   | 54.00           | -6.93       | AV             |

| Polar<br>(H/V)       | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-amp<br>lifier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/<br>m) | Margin<br>(dB) | Detect<br>or<br>Type |
|----------------------|--------------------|----------------------------|---------------------------|-----------------------|---------------------------|-------------------------------|------------------------|----------------|----------------------|
| High Channel:2452MHz |                    |                            |                           |                       |                           |                               |                        |                |                      |
| V                    | 4904.00            | 52.93                      | 30.55                     | 5.77                  | 24.66                     | 52.81                         | 74.00                  | -21.19         | PK                   |
| V                    | 4904.00            | 43.66                      | 30.55                     | 5.77                  | 24.66                     | 43.54                         | 54.00                  | -10.46         | AV                   |
| V                    | 7356.00            | 53.80                      | 30.33                     | 6.32                  | 24.55                     | 54.34                         | 74.00                  | -19.66         | PK                   |
| V                    | 7356.00            | 43.48                      | 30.33                     | 6.32                  | 24.55                     | 44.02                         | 54.00                  | -9.98          | AV                   |
| V                    | 9808.00            | 54.20                      | 30.85                     | 7.45                  | 24.69                     | 55.49                         | 74.00                  | -18.51         | PK                   |
| V                    | 9808.00            | 43.68                      | 30.85                     | 7.45                  | 24.69                     | 44.97                         | 54.00                  | -9.03          | AV                   |
| V                    | 12260.00           | 54.96                      | 31.02                     | 8.99                  | 25.57                     | 58.50                         | 74.00                  | -15.50         | PK                   |
| V                    | 12260.00           | 43.03                      | 31.02                     | 8.99                  | 25.57                     | 46.57                         | 54.00                  | -7.43          | AV                   |
| H                    | 4904.00            | 53.80                      | 30.55                     | 5.77                  | 24.66                     | 53.68                         | 74.00                  | -20.32         | PK                   |
| H                    | 4904.00            | 43.80                      | 30.55                     | 5.77                  | 24.66                     | 43.68                         | 54.00                  | -10.32         | AV                   |
| H                    | 7356.00            | 54.00                      | 30.33                     | 6.32                  | 24.55                     | 54.54                         | 74.00                  | -19.46         | PK                   |
| H                    | 7356.00            | 43.99                      | 30.33                     | 6.32                  | 24.55                     | 44.53                         | 54.00                  | -9.47          | AV                   |
| H                    | 9808.00            | 53.53                      | 30.85                     | 7.45                  | 24.69                     | 54.82                         | 74.00                  | -19.18         | PK                   |
| H                    | 9808.00            | 43.85                      | 30.85                     | 7.45                  | 24.69                     | 45.14                         | 54.00                  | -8.86          | AV                   |
| H                    | 12260.00           | 53.96                      | 31.02                     | 8.99                  | 25.57                     | 57.50                         | 74.00                  | -16.50         | PK                   |
| H                    | 12260.00           | 43.54                      | 31.02                     | 8.99                  | 25.57                     | 47.08                         | 54.00                  | -6.92          | AV                   |

## Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

## 5. RADIATED BAND EMISSION MEASUREMENT

### 5.1 TEST REQUIREMENT

|                       |                                                                                                    |          |      |      |         |
|-----------------------|----------------------------------------------------------------------------------------------------|----------|------|------|---------|
| Test Requirement:     | FCC Part 15 C Section 15.209 and 15.205 and 15.247(d)                                              |          |      |      |         |
| Test Method:          | ANSI C63.10:2020                                                                                   |          |      |      |         |
| Test Frequency Range: | All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed. |          |      |      |         |
| Test site:            | Measurement Distance: 3m                                                                           |          |      |      |         |
| Receiver setup:       | Frequency                                                                                          | Detector | RBW  | VBW  | Value   |
|                       | Above                                                                                              | Peak     | 1MHz | 3MHz | Peak    |
|                       | 1GHz                                                                                               | Average  | 1MHz | 3MHz | Average |

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| Frequency<br>(MHz) | Class B (dBuV/m) (at 3M) |         |
|--------------------|--------------------------|---------|
|                    | Peak                     | Average |
| Above 1000         | 74                       | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m) = 20log Emission level (uV/m).

| Spectrum Parameter                    | Setting                                          |
|---------------------------------------|--------------------------------------------------|
| Attenuation                           | Auto                                             |
| Start Frequency                       | 2310MHz                                          |
| Stop Frequency                        | 2500MHz                                          |
| RB / VB (emission in restricted band) | 1 MHz / 3 MHz for Peak, 1 MHz / 3MHz for Average |

### 5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 5.3 DEVIATION FROM TEST STANDARD

No deviation

### 5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



### 5.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

## 5.6 TEST RESULT

|                                                                                                                                | Polar<br>(H/V)      | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-<br>amplifier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB/m) | Emission<br>level<br>(dBuV/m) | Limit<br>(dBu<br>V/m) | Margin<br>(dB) | Dete<br>ctor<br>Type | Result |
|--------------------------------------------------------------------------------------------------------------------------------|---------------------|--------------------|----------------------------|---------------------------|-----------------------|-----------------------------|-------------------------------|-----------------------|----------------|----------------------|--------|
| 802.11b                                                                                                                        | LowChannel 2412MHz  |                    |                            |                           |                       |                             |                               |                       |                |                      |        |
|                                                                                                                                | H                   | 2310.00            | 54.13                      | 30.22                     | 4.85                  | 23.98                       | 52.74                         | 74.00                 | -21.26         | PK                   | PASS   |
|                                                                                                                                | H                   | 2310.00            | 44.87                      | 30.22                     | 4.85                  | 23.98                       | 43.48                         | 54.00                 | -10.52         | AV                   | PASS   |
|                                                                                                                                | H                   | 2350.00            | 53.15                      | 30.22                     | 4.85                  | 23.98                       | 51.76                         | 74.00                 | -22.24         | PK                   | PASS   |
|                                                                                                                                | H                   | 2350.00            | 44.05                      | 30.22                     | 4.85                  | 23.98                       | 42.66                         | 54.00                 | -11.34         | AV                   | PASS   |
|                                                                                                                                | H                   | 2390.00            | 53.75                      | 30.22                     | 4.85                  | 23.98                       | 52.36                         | 74.00                 | -21.64         | PK                   | PASS   |
|                                                                                                                                | H                   | 2390.00            | 44.64                      | 30.22                     | 4.85                  | 23.98                       | 43.25                         | 54.00                 | -10.75         | AV                   | PASS   |
|                                                                                                                                | V                   | 2310.00            | 54.82                      | 30.22                     | 4.85                  | 23.98                       | 53.43                         | 74.00                 | -20.57         | PK                   | PASS   |
|                                                                                                                                | V                   | 2310.00            | 44.70                      | 30.22                     | 4.85                  | 23.98                       | 43.31                         | 54.00                 | -10.69         | AV                   | PASS   |
|                                                                                                                                | V                   | 2350.00            | 53.02                      | 30.22                     | 4.85                  | 23.98                       | 51.63                         | 74.00                 | -22.37         | PK                   | PASS   |
|                                                                                                                                | V                   | 2350.00            | 44.88                      | 30.22                     | 4.85                  | 23.98                       | 43.49                         | 54.00                 | -10.51         | AV                   | PASS   |
|                                                                                                                                | V                   | 2390.00            | 53.10                      | 30.22                     | 4.85                  | 23.98                       | 51.71                         | 74.00                 | -22.29         | PK                   | PASS   |
|                                                                                                                                | V                   | 2390.00            | 44.71                      | 30.22                     | 4.85                  | 23.98                       | 43.32                         | 54.00                 | -10.68         | AV                   | PASS   |
|                                                                                                                                | HighChannel 2462MHz |                    |                            |                           |                       |                             |                               |                       |                |                      |        |
|                                                                                                                                | H                   | 2483.50            | 53.57                      | 30.22                     | 4.85                  | 23.98                       | 52.18                         | 74.00                 | -21.82         | PK                   | PASS   |
|                                                                                                                                | H                   | 2483.50            | 44.86                      | 30.22                     | 4.85                  | 23.98                       | 43.47                         | 54.00                 | -10.53         | AV                   | PASS   |
|                                                                                                                                | H                   | 2490.00            | 53.54                      | 30.22                     | 4.85                  | 23.98                       | 52.15                         | 74.00                 | -21.85         | PK                   | PASS   |
|                                                                                                                                | H                   | 2490.00            | 44.77                      | 30.22                     | 4.85                  | 23.98                       | 43.38                         | 54.00                 | -10.62         | AV                   | PASS   |
|                                                                                                                                | H                   | 2500.00            | 54.81                      | 30.22                     | 4.85                  | 23.98                       | 53.42                         | 74.00                 | -20.58         | PK                   | PASS   |
|                                                                                                                                | H                   | 2500.00            | 44.83                      | 30.22                     | 4.85                  | 23.98                       | 43.44                         | 54.00                 | -10.56         | AV                   | PASS   |
|                                                                                                                                | V                   | 2483.50            | 53.88                      | 30.22                     | 4.85                  | 23.98                       | 52.49                         | 74.00                 | -21.51         | PK                   | PASS   |
|                                                                                                                                | V                   | 2483.50            | 44.24                      | 30.22                     | 4.85                  | 23.98                       | 42.85                         | 54.00                 | -11.15         | AV                   | PASS   |
|                                                                                                                                | V                   | 2490.00            | 54.02                      | 30.22                     | 4.85                  | 23.98                       | 52.63                         | 74.00                 | -21.37         | PK                   | PASS   |
|                                                                                                                                | V                   | 2490.00            | 44.61                      | 30.22                     | 4.85                  | 23.98                       | 43.22                         | 54.00                 | -10.78         | AV                   | PASS   |
|                                                                                                                                | V                   | 2500.00            | 53.97                      | 30.22                     | 4.85                  | 23.98                       | 52.58                         | 74.00                 | -21.42         | PK                   | PASS   |
|                                                                                                                                | V                   | 2500.00            | 44.46                      | 30.22                     | 4.85                  | 23.98                       | 43.07                         | 54.00                 | -10.93         | AV                   | PASS   |
| <b>Remark:</b><br>Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit |                     |                    |                            |                           |                       |                             |                               |                       |                |                      |        |

|         | Polar<br>(H/V)       | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-<br>amplifier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB/m) | Emission<br>level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Dete<br>ctor<br>Type | Result |
|---------|----------------------|--------------------|----------------------------|---------------------------|-----------------------|-----------------------------|-------------------------------|-------------------|----------------|----------------------|--------|
| 802.11g | LowChannel 2412MHz   |                    |                            |                           |                       |                             |                               |                   |                |                      |        |
|         | H                    | 2310.00            | 53.62                      | 30.22                     | 4.85                  | 23.98                       | 52.23                         | 74.00             | -21.77         | PK                   | PASS   |
|         | H                    | 2310.00            | 44.21                      | 30.22                     | 4.85                  | 23.98                       | 42.82                         | 54.00             | -11.18         | AV                   | PASS   |
|         | H                    | 2350.00            | 53.08                      | 30.22                     | 4.85                  | 23.98                       | 51.69                         | 74.00             | -22.31         | PK                   | PASS   |
|         | H                    | 2350.00            | 44.60                      | 30.22                     | 4.85                  | 23.98                       | 43.21                         | 54.00             | -10.79         | AV                   | PASS   |
|         | H                    | 2390.00            | 53.43                      | 30.22                     | 4.85                  | 23.98                       | 52.04                         | 74.00             | -21.96         | PK                   | PASS   |
|         | H                    | 2390.00            | 44.55                      | 30.22                     | 4.85                  | 23.98                       | 43.16                         | 54.00             | -10.84         | AV                   | PASS   |
|         | V                    | 2310.00            | 53.17                      | 30.22                     | 4.85                  | 23.98                       | 51.78                         | 74.00             | -22.22         | PK                   | PASS   |
|         | V                    | 2350.00            | 44.85                      | 30.22                     | 4.85                  | 23.98                       | 43.46                         | 54.00             | -10.54         | AV                   | PASS   |
|         | V                    | 2350.00            | 54.60                      | 30.22                     | 4.85                  | 23.98                       | 53.21                         | 74.00             | -20.79         | PK                   | PASS   |
|         | V                    | 2310.00            | 44.55                      | 30.22                     | 4.85                  | 23.98                       | 43.16                         | 54.00             | -10.84         | AV                   | PASS   |
|         | V                    | 2390.00            | 54.10                      | 30.22                     | 4.85                  | 23.98                       | 52.71                         | 74.00             | -21.29         | PK                   | PASS   |
|         | V                    | 2390.00            | 44.09                      | 30.22                     | 4.85                  | 23.98                       | 42.70                         | 54.00             | -11.30         | AV                   | PASS   |
|         | High Channel 2462MHz |                    |                            |                           |                       |                             |                               |                   |                |                      |        |
|         | H                    | 2483.50            | 54.59                      | 30.22                     | 4.85                  | 23.98                       | 53.20                         | 74.00             | -20.80         | PK                   | PASS   |
|         | H                    | 2483.50            | 44.14                      | 30.22                     | 4.85                  | 23.98                       | 42.75                         | 54.00             | -11.25         | AV                   | PASS   |
|         | H                    | 2490.00            | 54.00                      | 30.22                     | 4.85                  | 23.98                       | 52.61                         | 74.00             | -21.39         | PK                   | PASS   |
|         | H                    | 2490.00            | 44.71                      | 30.22                     | 4.85                  | 23.98                       | 43.32                         | 54.00             | -10.68         | AV                   | PASS   |
|         | H                    | 2500.00            | 54.10                      | 30.22                     | 4.85                  | 23.98                       | 52.71                         | 74.00             | -21.29         | PK                   | PASS   |
|         | H                    | 2500.00            | 44.38                      | 30.22                     | 4.85                  | 23.98                       | 42.99                         | 54.00             | -11.01         | AV                   | PASS   |
|         | V                    | 2483.50            | 53.70                      | 30.22                     | 4.85                  | 23.98                       | 52.31                         | 74.00             | -21.69         | PK                   | PASS   |
|         | V                    | 2483.50            | 44.87                      | 30.22                     | 4.85                  | 23.98                       | 43.48                         | 54.00             | -10.52         | AV                   | PASS   |
|         | V                    | 2490.00            | 54.02                      | 30.22                     | 4.85                  | 23.98                       | 52.63                         | 74.00             | -21.37         | PK                   | PASS   |
|         | V                    | 2490.00            | 44.82                      | 30.22                     | 4.85                  | 23.98                       | 43.43                         | 54.00             | -10.57         | AV                   | PASS   |
|         | V                    | 2500.00            | 54.07                      | 30.22                     | 4.85                  | 23.98                       | 52.68                         | 74.00             | -21.32         | PK                   | PASS   |
|         | V                    | 2500.00            | 44.02                      | 30.22                     | 4.85                  | 23.98                       | 42.63                         | 54.00             | -11.37         | AV                   | PASS   |

**Remark:**

Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

|                                                                                                                                | Polar<br>(H/V)      | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-<br>amplifier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB/m) | Emission<br>level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Dete<br>ctor<br>Type | Result |
|--------------------------------------------------------------------------------------------------------------------------------|---------------------|--------------------|----------------------------|---------------------------|-----------------------|-----------------------------|-------------------------------|-------------------|----------------|----------------------|--------|
| 802.11<br>n20                                                                                                                  | LowChannel 2412MHz  |                    |                            |                           |                       |                             |                               |                   |                |                      |        |
|                                                                                                                                | H                   | 2310.00            | 54.46                      | 30.22                     | 4.85                  | 23.98                       | 53.07                         | 74.00             | -20.93         | PK                   | PASS   |
|                                                                                                                                | H                   | 2310.00            | 45.00                      | 30.22                     | 4.85                  | 23.98                       | 43.61                         | 54.00             | -10.39         | AV                   | PASS   |
|                                                                                                                                | H                   | 2350.00            | 53.32                      | 30.22                     | 4.85                  | 23.98                       | 51.93                         | 74.00             | -22.07         | PK                   | PASS   |
|                                                                                                                                | H                   | 2350.00            | 44.27                      | 30.22                     | 4.85                  | 23.98                       | 42.88                         | 54.00             | -11.12         | AV                   | PASS   |
|                                                                                                                                | H                   | 2390.00            | 53.77                      | 30.22                     | 4.85                  | 23.98                       | 52.38                         | 74.00             | -21.62         | PK                   | PASS   |
|                                                                                                                                | H                   | 2390.00            | 44.89                      | 30.22                     | 4.85                  | 23.98                       | 43.50                         | 54.00             | -10.50         | AV                   | PASS   |
|                                                                                                                                | V                   | 2310.00            | 53.94                      | 30.22                     | 4.85                  | 23.98                       | 52.55                         | 74.00             | -21.45         | PK                   | PASS   |
|                                                                                                                                | V                   | 2310.00            | 44.77                      | 30.22                     | 4.85                  | 23.98                       | 43.38                         | 54.00             | -10.62         | AV                   | PASS   |
|                                                                                                                                | V                   | 2350.00            | 54.35                      | 30.22                     | 4.85                  | 23.98                       | 52.96                         | 74.00             | -21.04         | PK                   | PASS   |
|                                                                                                                                | V                   | 2350.00            | 44.34                      | 30.22                     | 4.85                  | 23.98                       | 42.95                         | 54.00             | -11.05         | AV                   | PASS   |
|                                                                                                                                | V                   | 2390.00            | 54.33                      | 30.22                     | 4.85                  | 23.98                       | 52.94                         | 74.00             | -21.06         | PK                   | PASS   |
|                                                                                                                                | V                   | 2390.00            | 44.46                      | 30.22                     | 4.85                  | 23.98                       | 43.07                         | 54.00             | -10.93         | AV                   | PASS   |
|                                                                                                                                | HighChannel 2462MHz |                    |                            |                           |                       |                             |                               |                   |                |                      |        |
|                                                                                                                                | H                   | 2483.50            | 54.92                      | 30.22                     | 4.85                  | 23.98                       | 53.53                         | 74.00             | -20.47         | PK                   | PASS   |
|                                                                                                                                | H                   | 2483.50            | 44.10                      | 30.22                     | 4.85                  | 23.98                       | 42.71                         | 54.00             | -11.29         | AV                   | PASS   |
|                                                                                                                                | H                   | 2490.00            | 54.08                      | 30.22                     | 4.85                  | 23.98                       | 52.69                         | 74.00             | -21.31         | PK                   | PASS   |
|                                                                                                                                | H                   | 2490.00            | 44.74                      | 30.22                     | 4.85                  | 23.98                       | 43.35                         | 54.00             | -10.65         | AV                   | PASS   |
|                                                                                                                                | H                   | 2500.00            | 53.95                      | 30.22                     | 4.85                  | 23.98                       | 52.56                         | 74.00             | -21.44         | PK                   | PASS   |
|                                                                                                                                | H                   | 2500.00            | 44.05                      | 30.22                     | 4.85                  | 23.98                       | 42.66                         | 54.00             | -11.34         | AV                   | PASS   |
|                                                                                                                                | V                   | 2483.50            | 54.80                      | 30.22                     | 4.85                  | 23.98                       | 53.41                         | 74.00             | -20.59         | PK                   | PASS   |
|                                                                                                                                | V                   | 2483.50            | 44.86                      | 30.22                     | 4.85                  | 23.98                       | 43.47                         | 54.00             | -10.53         | AV                   | PASS   |
|                                                                                                                                | V                   | 2490.00            | 53.17                      | 30.22                     | 4.85                  | 23.98                       | 51.78                         | 74.00             | -22.22         | PK                   | PASS   |
|                                                                                                                                | V                   | 2490.00            | 44.60                      | 30.22                     | 4.85                  | 23.98                       | 43.21                         | 54.00             | -10.79         | AV                   | PASS   |
|                                                                                                                                | V                   | 2500.00            | 53.96                      | 30.22                     | 4.85                  | 23.98                       | 52.57                         | 74.00             | -21.43         | PK                   | PASS   |
|                                                                                                                                | V                   | 2500.00            | 44.32                      | 30.22                     | 4.85                  | 23.98                       | 42.93                         | 54.00             | -11.07         | AV                   | PASS   |
| <b>Remark:</b><br>Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit |                     |                    |                            |                           |                       |                             |                               |                   |                |                      |        |

|               | Polar<br>(H/V)       | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-<br>amplifier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB/m) | Emission<br>level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Dete<br>ctor<br>Type | Result |
|---------------|----------------------|--------------------|----------------------------|---------------------------|-----------------------|-----------------------------|-------------------------------|-------------------|----------------|----------------------|--------|
| 802.11<br>n40 | LowChannel 2422MHz   |                    |                            |                           |                       |                             |                               |                   |                |                      |        |
|               | H                    | 2310.00            | 54.75                      | 30.22                     | 4.85                  | 23.98                       | 53.36                         | 74.00             | -20.64         | PK                   | PASS   |
|               | H                    | 2310.00            | 44.97                      | 30.22                     | 4.85                  | 23.98                       | 43.58                         | 54.00             | -10.42         | AV                   | PASS   |
|               | H                    | 2350.00            | 54.08                      | 30.22                     | 4.85                  | 23.98                       | 52.69                         | 74.00             | -21.31         | PK                   | PASS   |
|               | H                    | 2350.00            | 44.71                      | 30.22                     | 4.85                  | 23.98                       | 43.32                         | 54.00             | -10.68         | AV                   | PASS   |
|               | H                    | 2390.00            | 53.06                      | 30.22                     | 4.85                  | 23.98                       | 51.67                         | 74.00             | -22.33         | PK                   | PASS   |
|               | H                    | 2390.00            | 44.65                      | 30.22                     | 4.85                  | 23.98                       | 43.26                         | 54.00             | -10.74         | AV                   | PASS   |
|               | V                    | 2310.00            | 53.25                      | 30.22                     | 4.85                  | 23.98                       | 51.86                         | 74.00             | -22.14         | PK                   | PASS   |
|               | V                    | 2310.00            | 44.23                      | 30.22                     | 4.85                  | 23.98                       | 42.84                         | 54.00             | -11.16         | AV                   | PASS   |
|               | V                    | 2350.00            | 54.36                      | 30.22                     | 4.85                  | 23.98                       | 52.97                         | 74.00             | -21.03         | PK                   | PASS   |
|               | V                    | 2350.00            | 44.94                      | 30.22                     | 4.85                  | 23.98                       | 43.55                         | 54.00             | -10.45         | AV                   | PASS   |
|               | V                    | 2390.00            | 53.98                      | 30.22                     | 4.85                  | 23.98                       | 52.59                         | 74.00             | -21.41         | PK                   | PASS   |
|               | V                    | 2390.00            | 44.28                      | 30.22                     | 4.85                  | 23.98                       | 42.89                         | 54.00             | -11.11         | AV                   | PASS   |
|               | High Channel 2452MHz |                    |                            |                           |                       |                             |                               |                   |                |                      |        |
|               | H                    | 2483.50            | 53.74                      | 30.22                     | 4.85                  | 23.98                       | 52.35                         | 74.00             | -21.65         | PK                   | PASS   |
|               | H                    | 2483.50            | 44.01                      | 30.22                     | 4.85                  | 23.98                       | 42.62                         | 54.00             | -11.38         | AV                   | PASS   |
|               | H                    | 2490.00            | 54.86                      | 30.22                     | 4.85                  | 23.98                       | 53.47                         | 74.00             | -20.53         | PK                   | PASS   |
|               | H                    | 2490.00            | 44.79                      | 30.22                     | 4.85                  | 23.98                       | 43.40                         | 54.00             | -10.60         | AV                   | PASS   |
|               | H                    | 2500.00            | 53.19                      | 30.22                     | 4.85                  | 23.98                       | 51.80                         | 74.00             | -22.20         | PK                   | PASS   |
|               | H                    | 2500.00            | 44.44                      | 30.22                     | 4.85                  | 23.98                       | 43.05                         | 54.00             | -10.95         | AV                   | PASS   |
|               | V                    | 2483.50            | 54.41                      | 30.22                     | 4.85                  | 23.98                       | 53.02                         | 74.00             | -20.98         | PK                   | PASS   |
|               | V                    | 2483.50            | 44.66                      | 30.22                     | 4.85                  | 23.98                       | 43.27                         | 54.00             | -10.73         | AV                   | PASS   |
|               | V                    | 2490.00            | 53.69                      | 30.22                     | 4.85                  | 23.98                       | 52.30                         | 74.00             | -21.70         | PK                   | PASS   |
|               | V                    | 2490.00            | 44.27                      | 30.22                     | 4.85                  | 23.98                       | 42.88                         | 54.00             | -11.12         | AV                   | PASS   |
|               | V                    | 2500.00            | 53.07                      | 30.22                     | 4.85                  | 23.98                       | 51.68                         | 74.00             | -22.32         | PK                   | PASS   |
|               | V                    | 2500.00            | 44.19                      | 30.22                     | 4.85                  | 23.98                       | 42.80                         | 54.00             | -11.20         | AV                   | PASS   |

**Remark:**

Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

## 6. POWER SPECTRAL DENSITY TEST

|                   |                                         |
|-------------------|-----------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (e)         |
| Test Method:      | KDB558074 D0115.247 Meas Guidancev05r02 |

### 6.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C |                        |           |                       |        |
|---------------------------------|------------------------|-----------|-----------------------|--------|
| Section                         | Test Item              | Limit     | Frequency Range (MHz) | Result |
| 15.247                          | Power Spectral Density | 8dBm/3kHz | 2400-2483.5           | PASS   |


### 6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
4. Set the VBW  $\geq 3 \times \text{RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 6.3 DEVIATION FROM STANDARD

No deviation.

### 6.4 TEST SETUP



### 6.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.

## 6.6 TEST RESULT


|               |        |                     |        |
|---------------|--------|---------------------|--------|
| Temperature : | 26°C   | Relative Humidity : | 54%    |
| Pressure :    | 101kPa | Test Voltage :      | DC 12V |

| Test Mode | Frequency<br>(MHz) | Power Spectral Density<br>(dBm/3kHz) | Limit<br>(dBm/3kHz) | Result |
|-----------|--------------------|--------------------------------------|---------------------|--------|
| 802.11b   | 2412               | -15.949                              | 8                   | PASS   |
|           | 2437               | -16.194                              | 8                   | PASS   |
|           | 2462               | -17.396                              | 8                   | PASS   |
| 802.11g   | 2412               | -20.806                              | 8                   | PASS   |
|           | 2437               | -20.721                              | 8                   | PASS   |
|           | 2462               | -21.523                              | 8                   | PASS   |
| 802.11n20 | 2412               | -19.942                              | 8                   | PASS   |
|           | 2437               | -20.343                              | 8                   | PASS   |
|           | 2462               | -21.648                              | 8                   | PASS   |
| 802.11n40 | 2422               | -21.559                              | 8                   | PASS   |
|           | 2437               | -21.369                              | 8                   | PASS   |
|           | 2452               | -21.440                              | 8                   | PASS   |

802.11b - CH01




802.11b - CH06




802.11b - CH11




802.11g - CH01




802.11g - CH06




802.11g - CH11




802.11n20 - CH01




802.11n20 - CH06




802.11n20 - CH11




802.11n40 - CH03



802.11n40 - CH06



802.11n40 - CH09



**7. 6DB OCCUPIED BANDWIDTH**

|                   |                                         |
|-------------------|-----------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2)      |
| Test Method:      | KDB558074 D0115.247 Meas Guidancev05r02 |

**7.1 APPLIED PROCEDURES / LIMIT**

| FCC Part15 (15.247) , Subpart C |           |                                                  |                       |        |
|---------------------------------|-----------|--------------------------------------------------|-----------------------|--------|
| Section                         | Test Item | Limit                                            | Frequency Range (MHz) | Result |
| 15.247(a)(2)                    | Bandwidth | $\geq 500\text{KHz}$<br>(6dB Occupied Bandwidth) | 2400-2483.5           | PASS   |

**7.2 TEST PROCEDURE**

A. The steps for the first option 1 are as follows:

- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW  $\geq [3 \times \text{RBW}]$ .
- Detector = peak.
- Trace mode = max-hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.


B. The steps for the first option 2 are as follows:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW  $\geq 3 \times \text{RBW}$ , and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.

**7.3 DEVIATION FROM STANDARD**

No deviation.

## 7.4 TEST SETUP



## 7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.

## 7.6 TEST RESULT


|               |        |                     |        |
|---------------|--------|---------------------|--------|
| Temperature : | 26°C   | Relative Humidity : | 54%    |
| Pressure :    | 101kPa | Test Voltage :      | DC 12V |
| Test Mode :   | TX     |                     |        |

| Test Mode | Test Channel<br>(MHz) | 6dB Occupied Bandwidth<br>(MHz) | Limit<br>(kHz) | Result |
|-----------|-----------------------|---------------------------------|----------------|--------|
| 802.11b   | 2412                  | 8.662                           | >500           | Pass   |
|           | 2437                  | 10.00                           |                |        |
|           | 2462                  | 10.07                           |                |        |
| 802.11g   | 2412                  | 15.98                           | >500           | Pass   |
|           | 2437                  | 15.93                           |                |        |
|           | 2462                  | 15.63                           |                |        |
| 802.11n20 | 2412                  | 16.33                           | >500           | Pass   |
|           | 2437                  | 15.98                           |                |        |
|           | 2462                  | 16.32                           |                |        |
| 802.11n40 | 2422                  | 31.27                           | >500           | Pass   |
|           | 2437                  | 32.19                           |                |        |
|           | 2452                  | 31.97                           |                |        |


## 802.11b - CH01




## 802.11b - CH06




## 802.11b - CH11




## 802.11g - CH01




## 802.11g - CH06




## 802.11g - CH11




## 802.11n20 - CH01




## 802.11n20 - CH06




## 802.11n20 - CH11




## 802.11n40 - CH03



## 802.11n40 - CH06



## 802.11n40 - CH09



**8. PEAK OUTPUT POWER TEST**

|                   |                                         |
|-------------------|-----------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3)      |
| Test Method:      | KDB558074 D0115.247 Meas Guidancev05r02 |

**8.1 APPLIED PROCEDURES/LIMIT**

| FCC Part15 (15.247) , Subpart C |                   |                 |                       |        |
|---------------------------------|-------------------|-----------------|-----------------------|--------|
| Section                         | Test Item         | Limit           | Frequency Range (MHz) | Result |
| 15.247(b)(3)                    | Peak Output Power | 1 watt or 30dBm | 2400-2483.5           | PASS   |

**8.2 TEST PROCEDURE**

- a. The EUT was directly connected to the Power meter

**8.3 DEVIATION FROM STANDARD**

No deviation.

**8.4 TEST SETUP****8.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.

## 8.6 TEST RESULT

|               |        |                     |        |
|---------------|--------|---------------------|--------|
| Temperature : | 26°C   | Relative Humidity : | 54%    |
| Pressure :    | 101kPa | Test Voltage :      | DC 12V |

| Test Mode | Test Channel<br>(MHz) | Peak Output Power<br>(dBm) | Limit<br>(dBm) | Result |
|-----------|-----------------------|----------------------------|----------------|--------|
| 802.11b   | 2412                  | 11.323                     | 30.00          | Pass   |
|           | 2437                  | 11.103                     |                |        |
|           | 2462                  | 10.024                     |                |        |
| 802.11g   | 2412                  | 10.921                     | 30.00          | Pass   |
|           | 2437                  | 10.658                     |                |        |
|           | 2462                  | 9.721                      |                |        |
| 802.11n20 | 2412                  | 10.965                     | 30.00          | Pass   |
|           | 2437                  | 10.513                     |                |        |
|           | 2462                  | 9.747                      |                |        |
| 802.11n40 | 2422                  | 10.982                     | 30.00          | Pass   |
|           | 2437                  | 10.177                     |                |        |
|           | 2452                  | 9.818                      |                |        |

**9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION**

|                   |                                         |
|-------------------|-----------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)         |
| Test Method:      | KDB558074 D0115.247 Meas Guidancev05r02 |

**9.1 APPLICABLE STANDARD**

Typical regulatory requirements specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions<sup>89</sup>:

The maximum peak conducted output power procedure was used to determine compliance as described in 11.9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

**9.2 TEST PROCEDURE**

A. Reference level measurement, establish a reference level by using the following procedure:

- Set instrument center frequency to DTS channel center frequency.
- Set the span to  $\geq 1.5$  times the DTS bandwidth.
- Set the RBW = 100 kHz.
- Set the VBW  $\geq [3 \times \text{RBW}]$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

B. Emission level measurement, establish an emission level by using the following procedure:


- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW  $\geq [3 \times \text{RBW}]$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

### 9.3 DEVIATION FROM STANDARD

No deviation.

### 9.4 TEST SETUP



### 9.5 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.

## 9.6 TEST RESULTS



Band edge test plot as follows:

|               |        |                     |        |
|---------------|--------|---------------------|--------|
| Temperature : | 26°C   | Relative Humidity : | 54%    |
| Pressure :    | 101kPa | Test Voltage :      | DC 12V |



## 802.11b - Lowest channel





## 802.11b - Highest channel





## 802.11g - Lowest channel





## 802.11g - Highest channel





## 802.11n20 - Lowest channel





## 802.11n20 - Highest channel



## 802.11n40 - Lowest channel





## 802.11n40 - Highest channel





## Spurious emission test plot as follows:

802.11b



Lowest channel



Middle channel





Highest channel





30MHz ~ 26.5GHz

802.11g



## Lowest channel



## Middle channel





## Highest channel





30MHz ~ 26.5GHz

802.11n20



## Lowest channel



## Middle channel





## Highest channel





30MHz ~ 26.5GHz

802.11n40



## Lowest channel



## Middle channel



## Highest channel



30MHz ~ 26.5GHz

## 10. DUTY CYCLE

|              |                  |
|--------------|------------------|
| Test Method: | ANSI C63.10:2020 |
|--------------|------------------|

### 10.1 APPLIED PROCEDURES / LIMIT


Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
  - 1) Set the center frequency of the instrument to the center frequency of the transmission.
  - 2) Set  $RBW \geq OBW$  if possible; otherwise, set RBW to the largest available value.
  - 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
  - 4) The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration  $T$  exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)

### 10.2 DEVIATION FROM STANDARD

No deviation.

### 10.3 TEST SETUP



### 10.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of chapter 3, Unless otherwise a special operating condition is specified in the follows during the testing.

## 10.5 TEST RESULTS


|               |        |                     |        |
|---------------|--------|---------------------|--------|
| Temperature : | 26°C   | Relative Humidity : | 54%    |
| Pressure :    | 101kPa | Test Voltage :      | DC 12V |

| Test Mode | Test Frequency<br>(MHz) | Duty Cycle<br>(%) | Factor<br>(dB) | Result |
|-----------|-------------------------|-------------------|----------------|--------|
| 802.11b   | 2412                    | 100               | 0.00           | Pass   |
| 802.11g   | 2412                    | 100               | 0.00           | Pass   |
| 802.11n20 | 2412                    | 100               | 0.00           | Pass   |
| 802.11n40 | 2422                    | 100               | 0.00           | Pass   |

Note: Duty Cycle = Ton / Total \* 100%;  
Duty Cycle Correction Factor = 10log (1/Duty Cycle).


802.11b

2412MHz




802.11g

2412MHz




802.11n20

2412MHz



802.11n40

2422MHz



Note: All channel have been tested, and the report only reflects the worst case data.

**11. ANTENNA REQUIREMENT**

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| Standard requirement:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | FCC Part15 C Section 15.203 /247(c) |
| <p>15.203 requirement:<br/>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement:<br/>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p> |                                     |
| <p>EUT Antenna:<br/>The antenna is PCB antenna, the best case gain of the antenna is 2.02dBi, reference to the appendix II for details.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                     |

## 12. TEST SETUP PHOTO

Reference to the appendix I for details.

## 13. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

\*\*\*\*\* END OF REPORT \*\*\*\*\*