

TEST REPORT

Applicant: Anona Security Technology Limited.
Address: 8 The Green, Ste A Dover DE 19901,America
Equipment Type: Anona Dual Cam Doorbell
Model Name: HM5502
Brand Name: Anona
FCC ID: 2BB7K-5502
Test Standard: 47 CFR Part 2.1091
KDB 447498 D04 v01
Sample Arrival Date N/A
Test Date: N/A
Date of Issue: Apr. 29, 2026

ISSUED BY:

Shanghai Tejet Communications Technology Co., Ltd. Testing Center

**Prepared by:** Huang Xiaoqin**Reviewed by:** Cai Xueguo**Approved by:** Zhang Yanqing
(Laboratory Manager)*Huang Xiaoqin**Cai Xueguo**Zhang Yanqing*

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Apr. 29, 2026</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information.....	4
2.2	Manufacturer Information	4
2.3	General Description for Equipment under Test (EUT)	4
2.4	Technical Information	4
3	SUMMARY OF TEST RESULT	5
3.1	Test Standards.....	5
4	DEVICE CATEGORY AND LEVELS LIMITS	6
5	ASSESSMENT RESULT	8
5.1	Output power	8
5.2	Tune-up power.....	9
5.3	RF Exposure Evaluation Result.....	9
5.4	Collocated Power Calculation.....	9
5.5	Conclusion	10

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Address	1-2/F., Building 1, No. 222 Xuanlan Road, Xuanqiao Town, Pudong New District, Shanghai, China

1.2 Test Location

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Location	1-2/F., Building 1, No. 222 Xuanlan Road, Xuanqiao Town, Pudong New District, Shanghai, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352. The laboratory is a testing organization accredited by ISED as a accredited testing laboratory. The company number is 29671 and CAB identifier number is CN0142.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Anona Security Technology Limited.
Address	8 The Green, Ste A Dover DE 19901,America

2.2 Manufacturer Information

Manufacturer	Anona Security Technology Limited.
Address	8 The Green, Ste A Dover DE 19901,America

2.3 General Description for Equipment under Test (EUT)

EUT Name	Anona Dual Cam Doorbell
Model Name Under Test	HM5502
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	LCBM047C
Software Version	35WW
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	Bluetooth (BLE:1M) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20), 802.11ax(HE20) 433MHz
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	Bluetooth, WIFI, 433MHz	
Frequency Range	Bluetooth	2402 ~ 2480 MHz
	2.4G WIFI	2412 ~ 2462 MHz
	433MHz	433.92 MHz
Antenna Type	Bluetooth	PIFA Antenna
	WIFI	PIFA Antenna
	433MHz	Coil antenna
Exposure Category	General Population/Uncontrolled Exposure	
Product Type	Mobile Device	

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices
2	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01

4 DEVICE CATEGORY AND LEVELS LIMITS

Mobile Devices:

CFR Title 47 §2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

FCC KDB 447498 D04 General RF Exposure Guidance v01 Limit

Evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i. e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
300		39	65	88	110	129	148	166	184	201	217
450		22	44	67	89	112	135	158	180	203	226
835		9	25	44	66	90	116	145	175	207	240
1900		3	12	26	44	66	92	122	157	195	236
2450		3	10	22	38	59	83	111	143	179	219
3600		2	8	18	32	49	71	96	125	158	195
5800		1	6	14	25	40	58	80	106	136	169

According with FCC KDB 447498 D04, Appendix A, Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

When maximum available power each individual transmitting antenna within the same time averaging period is ≤ 1 mW, and the nearest parts of the antenna structures of the simultaneously operating transmitters are separated by at least 2 cm.

When the aggregate maximum available power of all transmitting antennas is ≤ 1 mW in the same time-averaging period.

5 ASSESSMENT RESULT

5.1 Output power

Bluetooth	
Mode	BLE 1Mbps
Conducted Power (dBm)	9.61
Antenna Gain (dBi)	3.33
EIRP (dBm)	12.94
Note: This report listed the worst case conducted power value, please refer to RF test report No.Ti-EE26030626-601 for more details.	

2.4GWIFI	
Mode	2.4G WIFI Max
Conducted Power (dBm)	27.22
Antenna Gain (dBi)	3.33
EIRP (dBm)	30.55
Note: This report listed the worst case conducted power value, please refer to RF test report No.Ti-EE26030626-602 for more details.	

433MHz	
Mode	433.92MHz
Field Strength(dBuV/m)	92.18
Conducted Power (dBm)	9.36
Antenna Gain (dBi)	-5.59
ERP (dBm)	1.62
Note: This report listed the worst case conducted power value, please refer to RF test report No.Ti-EE26030626-603 for more details.	

5.2 Tune-up power

Mode	Conducted Power Range (dBm)		EIRP Range (dBm)		ERP Range (dBm)	
Bluetooth	9.00	11.00	12.33	14.33	10.18	12.18
2.4G WIFI	26.00	28.00	29.33	31.33	27.18	29.18
433MHz	8.00	10.00	2.41	4.41	0.26	2.26
Note1: ERP= EIRP -2.15dB.						
Note2: According KDB 447498 D04, used the greater of maximum conducted power and ERP to compare with the threshold value Pth.						

5.3 RF Exposure Evaluation Result

Evolution mode	f(MHz)	Distance (cm)	Maximum power (dBm)	Threshold Power (mW)	Plimit(mW)	P/Plimit	Verdict
Bluetooth	2402	20	12.38	17.30	3060.00	0.0057	PASS
2.4G WIFI	2412	20	29.18	827.94	3060.00	0.2706	PASS
433MHz	433.92	20	10.00	10.00	885.20	0.0113	PASS

5.4 Collocated Power Calculation

Evolution mode	Frequency(MHz)	Power /Limit	$\Sigma(\text{Power} / \text{Limit})$	Verdict
2.4G WIFI	2412 ~ 2462 MHz	0.2706	0.2819	Pass
433MHz	433.92MHz	0.0113		

Note:

- $\Sigma(\text{Power} / \text{Limit})$: This is a summation of [(power for each transmitter/ antenna included in the simultaneous transmission)/ (corresponding Power limit)], for 2.4G WIFI + 433MHz.
- Both of the 2.4G WIFI + 433MHz can transmit simultaneously, the formula of calculated the Power is $CP1 / LP1 + CP2 / LP2 + \dots \text{etc.} < 1$
 CP = Calculation power
 LP = Limit of power
- The worst-case situation is 0.2819, which is less than "1". This confirmed that the device comply with FCC KDB 447498 D04 Power limit.
- More power list please refer to RF test report.

5.5 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

Statement

1. The Testing Center guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. For the report with Accreditation Symbol, the items marked with "☆" are not within the accredited scope.
3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the test report stamp.
4. The test data and results are only valid for the tested samples provided by the customer.
5. This report shall not be partially reproduced without the written permission of the Testing Center.
6. Any objection shall be raised to the Testing Center within 30 days after receiving the report.

--END OF REPORT--