



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

TEST REPORT

Report No.: CQASZ20251202831E-01
Applicant: Shenzhen Shuying Technology Co., Ltd.
Address of Applicant: Room 01, 13th Floor, No. 9988 Shennan District, Shenzhen, China
Equipment Under Test (EUT):
Product: wan AIChef ultra (Smart Microwave Oven)
Model No.: DW226-B, DW226-G
Test Model No.: DW226-B
Brand Name: N/A
FCC ID: 2BB9R-DW226
Standards: 47 CFR Part 15, Subpart C
KDB558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10:2020
Date of Receipt: 2025-12-08
Date of Test: 2025-12-08 to 2025-12-29
Date of Issue: 2026-4-8
Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20251202831E-01	Rev.01	Initial report	2026-4-8

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15.203	N/A	PASS
AC Power Line Conducted Emission	47 CFR Part 15.207	ANSI C63.10-2020	PASS
Conducted Peak & Average Output Power	47 CFR Part 15.247	ANSI C63.10-2020	PASS
6dB Occupied Bandwidth	47 CFR Part 15.247	ANSI C63.10-2020	PASS
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10-2020	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15.247	ANSI C63.10-2020	PASS
RF Conducted Spurious Emissions	47 CFR Part 15.247	ANSI C63.10-2020	PASS
Radiated Spurious Emissions	47 CFR Part 15.209	ANSI C63.10-2020	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15.205/15.209	ANSI C63.10-2020	PASS

Remark:

The tested sample(s) and the sample information are provided by the client.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

CH: In this whole report CH means channel.

Volt: In this whole report Volt means Voltage.

Temp: In this whole report Temp means Temperature.

Humid: In this whole report Humid means humidity.

Press: In this whole report Press means Pressure.

N/A: In this whole report not application

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 CLIENT INFORMATION	6
4.2 GENERAL DESCRIPTION OF EUT	6
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	6
4.4 TEST ENVIRONMENT AND MODE	9
4.5 DESCRIPTION OF SUPPORT UNITS	18
4.6 TEST LOCATION	18
4.7 TEST FACILITY	18
4.8 TEST CONFIGURATION	18
4.9 STATEMENT OF THE MEASUREMENT UNCERTAINTY	19
4.10 DEVIATION FROM STANDARDS	19
4.11 ABNORMALITIES FROM STANDARD CONDITIONS	19
4.12 OTHER INFORMATION REQUESTED BY THE CUSTOMER	19
4.13 EQUIPMENT LIST	20
5 TEST RESULTS AND MEASUREMENT DATA	21
5.1 ANTENNA REQUIREMENT	21
5.2 CONDUCTED EMISSIONS	22
5.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER	26
Test Result	27
ANT1:	27
ANT2:	28
ANT1+ANT2:	29
Note: Duty cycle correction factor details please see section 4.4.	29
When Duty cycle >98%, D.C.F is not required.	29
Test Graphs	30
5.4 99% OCCUPIED BANDWIDTH	45
Test Result	46
Test Graphs	48
5.5 6dB OCCUPIED BANDWIDTH	63
Test Result	64
Test Graphs	66
5.6 POWER SPECTRAL DENSITY	81
Test Result	82
Test Graphs	85
5.7 BAND-EDGE FOR RF CONDUCTED EMISSIONS	100
Test Result	101
5.7.1 Test Graphs	102
5.8 RF CONDUCTED SPURIOUS EMISSIONS	112
Test Result	113
Test Graphs	117
5.9 RADIATED SPURIOUS EMISSIONS	161
5.9.1 Radiated emission below 1GHz	164
5.9.2 Transmitter emission above 1GHz	166
5.10 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	182
6 PHOTOGRAPHS - EUT TEST SETUP	192

6.1 RADIATED SPURIOUS EMISSION	192
6.2 CONDUCTED EMISSION	193
6.3 RF CONDUCTED MEASUREMENT	194
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	195

4 General Information

4.1 Client Information

Applicant:	Shenzhen Shuying Technology Co., Ltd.
Address of Applicant:	Room 01, 13th Floor, No. 9988 Shennan District, Shenzhen, China
Manufacturer:	Shenzhen Shuying Technology Co., Ltd.
Address of Manufacturer:	Room 01, 13th Floor, No. 9988 Shennan District, Shenzhen, China
Factory:	Jiangmen Jens Smart Appliances Co., Ltd.
Address of Factory:	No.88 Heshun Road Hechen Town Heshan City Jiangmen Guangdong Province China

4.2 General Description of EUT

Product Name:	wan AIChef ultra (Smart Microwave Oven)
Model No.:	DW226-B, DW226-G
Test Model No.:	DW226-B
Trade Mark:	N/A
Software Version:	5.10.14
Hardware Version:	3.0
Power Supply:	Power supply AC 120V
EUT Supports Radios application:	2.4GHz: Wi-Fi: 802.11b/g/n(HT20)/ax(HE20): 2412MHz~2462MHz; 802.11n(HT40)/ax(HE40): 2422MHz~2452MHz
Simultaneous Transmission	☐ Simultaneous TX is supported and evaluated in this report. ☒ Simultaneous TX is not supported.

4.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20)/ax(HE20): 2412MHz to 2462MHz IEEE 802.11n(HT40)/ax(HE40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20/ax HE20: 11 Channels IEEE 802.11n HT40/ax HE40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11ax(HE20 and HE40): OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Transfer Rate:	2.4G WIFI: IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : SISO

	6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps 2×2 MIMO 13Mbps/26Mbps/39Mbps/52Mbps/78Mbps/104Mbps/117Mbps/130Mbps IEEE for 802.11n(HT40) : SISO 13.5Mbps/27Mbps/40.5Mbps/54Mbps/81Mbps/108Mbps/121.5Mbps/135Mbps 2×2 MIMO 27Mbps/54Mbps/81Mbps/108Mbps/162Mbps/216Mbps/243Mbps/270Mbps IEEE for 802.11ax(HE20): SISO 8.6M/17.2M/25.8M/34.4M/51.6M/68.8M/77.4M/86M/103.2M/114.7M/129M/ 143.4Mbps 2×2 MIMO 17.2M/34.4M/51.6M/68.8M/103.2M/137.6M/154.8M/173.4M/206.6M/229.4M/258M/ 286.8Mbps IEEE for 802.11ax(HE40): SISO 17.2M/34.4M/51.6M/68.8M/103.2M/137.6M/154.9M/172.1M/206.5M/229.4M/ 258.1M/286.8Mbps 2×2 MIMO 34.4M/68.8M/103.2M/137.6M/206.4M/275.2M/309.8M/346.6M/413M/458.8M/ 516.2M/573.6Mbps
Product Type:	☒ Mobile ☐ Portable ☐ Fix Location
Test Software of EUT:	Serial
Antenna Type:	FPC antenna
Antenna Gain:	Ant1:4.56dBi Ant2:4.56dBi Ant1+Ant2:7.57dBi

Operation Frequency each of channel(802.11b/g/n HT20/ax HE20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		
Operation Frequency each of channel(802.11n HT40/ax HE40)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
3	2422MHz	6	2437MHz	9	2452MHz		
4	2427MHz	7	2442MHz				
5	2432MHz	8	2447MHz				

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20)/ax(HE20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz


For 802.11n (HT40)/ax(HE40):

Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz

Note:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.4 Test Environment and Mode

Operating Environment:	
Radiated Emissions:	
Temperature:	25.3 °C
Humidity:	55 % RH
Atmospheric Pressure:	1009 mbar
Conducted Emissions:	
Temperature:	25.6 °C
Humidity:	60 % RH
Atmospheric Pressure:	1009 mbar
Radio conducted item test (RF Conducted test room):	
Temperature:	25.5 °C
Humidity:	52 % RH
Atmospheric Pressure:	1009 mbar
Test mode:	
Transmitting mode:	EUT is set in RF test mode in all supported modulation types, bandwidth and data rate, etc.
EUT Power level:	Class0
Run Software:	
	


ANT1:

Operated Mode for Worst Duty Cycle:				
Test Mode	On time [Ton] (ms)	Period [Ttotal] ms)	Duty Cycle(%)	Average correction factor(dB)
IEEE802.11b	0.99	1.00	99.00	0.04
IEEE802.11g	0.69	0.70	98.57	0.06
IEEE802.11n (HT20)	0.65	0.66	98.48	0.07
IEEE802.11n (HT40)	0.33	0.34	97.06	0.13
IEEE802.11ax (HE20)	1.31	1.36	96.32	0.16
IEEE802.11ax (HE40)	0.65	0.70	92.86	0.32

Remark:


- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = $10 * \log(1/ \text{Duty cycle})$;

Test Graph_IEEE802.11b Duty Cycle:




Date: 16 DEC 2025 19:50:30

Test Graph_IEEE802.11g Duty Cycle:




Date: 16 DEC 2025 19:55:15

Test Graph_IEEE802.11 n (HT20) Duty Cycle:




Date: 16 DEC 2025 20:00:37

Test Graph_IEEE802.11 n (HT40) Duty Cycle:




Date: 16 DEC 2025 20:05:32

Test Graph_IEEE802.11 ax (HE20) Duty Cycle:



Date: 24.DEC.2025 16:14:10

Test Graph_IEEE802.11 ax (HE40) Duty Cycle:



Date: 24.DEC.2025 16:27:33


ANT2:

Operated Mode for Worst Duty Cycle:				
Test Mode	On time [Ton] (ms)	Period [Ttotal] ms)	Duty Cycle(%)	Average correction factor(dB)
IEEE802.11b	32.95	32.97	99.94	0.003
IEEE802.11g	5.45	5.48	99.45	0.02
IEEE802.11n (HT20)	5.05	5.08	99.41	0.03
IEEE802.11n (HT40)	0.64	0.69	92.75	0.33
IEEE802.11ax (HE20)	1.31	1.35	97.04	0.13
IEEE802.11ax (HE40)	0.65	0.69	94.20	0.26

Remark:


- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor = $10 * \log(1/ \text{Duty cycle})$;

Test Graph_IEEE802.11b Duty Cycle:




Date: 23 DEC 2025 15:45:41

Test Graph_IEEE802.11g Duty Cycle:




Date: 23 DEC 2025 15:52:49

Test Graph_IEEE802.11 n (HT20) Duty Cycle:




Date: 23 DEC 2025 16:15:17

Test Graph_IEEE802.11 n (HT40) Duty Cycle:




Date: 25 DEC 2025 11:32:33

Test Graph_IEEE802.11 ax (HE20) Duty Cycle:



Date: 24 DEC 2025 16:46:41

Test Graph_IEEE802.11 ax (HE40) Duty Cycle:



Date: 24 DEC 2025 16:54:45

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
/	/	/	/	/

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.6 Test Location

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:


• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.8 Test configuration



4.9 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.10 Deviation from Standards

None.

4.11 Abnormalities from Standard Conditions

None.

4.12 Other Information Requested by the Customer

None.

4.13 Equipment List


Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2025/9/1	2026/8/31
Spectrum analyzer	R&S	FSU26	CQA-038	2025/9/1	2026/8/31
Spectrum analyzer	R&S	FSU40	CQA-075	2025/9/1	2026/8/31
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2025/9/1	2026/8/31
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2025/9/1	2026/8/31
Preamplifier	EMCI	EMC184055SE	CQA-089	2025/9/1	2026/8/31
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2023/9/8	2026/9/7
Bilog Antenna	R&S	HL562	CQA-011	2023/11/01	2026/10/31
Horn Antenna	R&S	HF906	CQA-012	2023/11/01	2026/10/31
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2023/9/7	2026/9/6
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2025/9/1	2026/8/31
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2025/9/1	2026/8/31
Antenna Connector	CQA	RFC-01	CQA-080	2025/9/1	2026/8/31
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2025/9/1	2026/8/31
Power meter	R&S	NRVD	CQA-029	2025/9/1	2026/8/31
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2025/9/1	2026/8/31
EMI Test Receiver	R&S	ESR7	CQA-005	2025/9/1	2026/8/31
LISN	R&S	ENV216	CQA-003	2025/9/1	2026/8/31
Coaxial cable	CQA	N/A	CQA-C009	2025/9/1	2026/8/31
DC power	KEYSIGHT	E3631A	CQA-028	2025/9/1	2026/8/31

Test software:


	Manufacturer	Software brand	Software version
Radiated Emissions test software	Tonscend	JS1120-3	Version:8
Conducted Emissions test software	Audix	e3	Version:9
RF Conducted test software	Audix	e3	V3.5.39

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is FPC antenna. The connection/connection type between the antenna to the EUT's antenna port is: unique coupling. This is either permanently attachment or a unique coupling that satisfies the requirement.	


5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2020		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2020 on conducted measurement.		
Test Setup:			

Exploratory Test Mode:	Transmitting in full-bandwidth single-user mode (Full RU) with all kinds of modulations, and at the lowest, middle, and highest data rates across the channel.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at middle channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC120V/60Hz
Test Results:	Pass

Measurement Data

Live Line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.150	15.03	9.49	24.52	56.00	-31.48	Average	Line
2	0.150	26.96	9.49	36.45	66.00	-29.55	QP	Line
3	0.185	12.61	9.49	22.10	54.26	-32.16	Average	Line
4	0.185	21.55	9.49	31.04	64.26	-33.22	QP	Line
5	0.430	9.80	9.51	19.31	47.25	-27.94	Average	Line
6	0.430	19.36	9.51	28.87	57.25	-28.38	QP	Line
7	0.940	10.06	9.59	19.65	46.00	-26.35	Average	Line
8	0.940	20.01	9.59	29.60	56.00	-26.40	QP	Line
9	1.070	10.25	9.53	19.78	46.00	-26.22	Average	Line
10	1.070	20.70	9.53	30.23	56.00	-25.77	QP	Line
11 PP	1.240	11.31	9.52	20.83	46.00	-25.17	Average	Line
12 QP	1.240	20.88	9.52	30.40	56.00	-25.60	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:




	Freq	Read	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.150	15.54	9.70	25.24	56.00	-30.76	Average	Neutral
2	0.150	24.98	9.70	34.68	66.00	-31.32	QP	Neutral
3	0.540	10.15	9.74	19.89	46.00	-26.11	Average	Neutral
4	0.540	20.06	9.74	29.80	56.00	-26.20	QP	Neutral
5	1.090	10.42	9.70	20.12	46.00	-25.88	Average	Neutral
6	1.090	20.81	9.70	30.51	56.00	-25.49	QP	Neutral
7 PP	1.200	11.24	9.71	20.95	46.00	-25.05	Average	Neutral
8	1.200	21.18	9.71	30.89	56.00	-25.11	QP	Neutral
9	3.840	-0.83	9.78	8.95	46.00	-37.05	Average	Neutral
10 QP	3.840	21.12	9.78	30.90	56.00	-25.10	QP	Neutral
11	11.900	12.87	9.83	22.70	50.00	-27.30	Average	Neutral
12	11.900	19.79	9.83	29.62	60.00	-30.38	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak & Average Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2020
Test Setup:	<i>Setup for Power meter measurement method</i>  <i>Setup for Spectrum analyser measurement method</i> 
Exploratory Test Mode:	Transmitting in full-bandwidth single-user mode (Full RU) with all kinds of modulations, and at the lowest, middle, and highest data rates across the channel.
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass

Test Result

ANT1:

Test Mode	Frequency[MHz]	Result [dBm]	Limit [dBm]	Verdict
11B	2412	13.38	≤30.00	PASS
	2437	13.24	≤30.00	PASS
	2462	12.74	≤30.00	PASS
11G	2412	8.37	≤30.00	PASS
	2437	8.24	≤30.00	PASS
	2462	7.67	≤30.00	PASS
11N20SISO	2412	8.16	≤30.00	PASS
	2437	8.02	≤30.00	PASS
	2462	7.45	≤30.00	PASS
11N40SISO	2422	6.89	≤30.00	PASS
	2437	6.71	≤30.00	PASS
	2452	6.15	≤30.00	PASS
11AX20SISO	2412	7.82	≤30.00	PASS
	2437	10.45	≤30.00	PASS
	2462	10.75	≤30.00	PASS
11AX40SISO	2422	9.74	≤30.00	PASS
	2437	10.43	≤30.00	PASS
	2452	11.06	≤30.00	PASS

ANT2:

Test Mode	Frequency[MHz]	Result [dBm]	Limit [dBm]	Verdict
11B	2412	9.48	≤30.00	PASS
	2437	9.42	≤30.00	PASS
	2462	10.82	≤30.00	PASS
11G	2412	13.86	≤30.00	PASS
	2437	13.84	≤30.00	PASS
	2462	15.28	≤30.00	PASS
11N20SISO	2412	11.22	≤30.00	PASS
	2437	11.58	≤30.00	PASS
	2462	12.99	≤30.00	PASS
11N40SISO	2422	10.49	≤30.00	PASS
	2437	11.04	≤30.00	PASS
	2452	11.89	≤30.00	PASS
11AX20SISO	2412	8.84	≤30.00	PASS
	2437	10.54	≤30.00	PASS
	2462	10.77	≤30.00	PASS
11AX40SISO	2422	9.76	≤30.00	PASS
	2437	10.35	≤30.00	PASS
	2452	11.23	≤30.00	PASS


ANT1+ANT2:


Test Mode	Frequency[MHz]	Result [dBm]	Limit [dBm]	Verdict
11N20MIMO	2412	12.96	≤28.43	PASS
	2437	13.17	≤28.43	PASS
	2462	14.06	≤28.43	PASS
11N40MIMO	2422	12.06	≤28.43	PASS
	2437	12.40	≤28.43	PASS
	2452	12.92	≤28.43	PASS
11AX20MIMO	2412	11.37	≤28.43	PASS
	2437	13.51	≤28.43	PASS
	2462	13.77	≤28.43	PASS
11AX40MIMO	2422	12.76	≤28.43	PASS
	2437	13.40	≤28.43	PASS
	2452	14.16	≤28.43	PASS

Note: Duty cycle correction factor details please see section 4.4.


When Duty cycle >98%, D.C.F is not required.

Test Graphs







11G_Ant1_2412



11G_Ant1_2437




11G_Ant1_2462




Date: 16 DEC.2025 19:58:51

11N20SISO_Ant1_2412




Date: 16 DEC.2025 20:00:51

11N20SISO_Ant1_2437




Date: 16 DEC.2025 20:02:19

11N20SISO_Ant1_2462




Date: 16 DEC.2025 20:04:36

11N40SISO_Ant1_2422




Date: 16 DEC.2025 20:05:49

11N40SISO_Ant1_2437




Date: 16 DEC.2025 20:07:13

11N40SISO_Ant1_2452




Date: 16 DEC.2025 20:09:51


11AX20SISO_Ant1_2412




11AX20SISO_Ant1_2437



11AX20SISO_Ant1_2462




11AX40SISO_Ant1_2422




Date: 24 DEC. 2025 16:28:01

11AX40SISO_Ant1_2437




Date: 24 DEC. 2025 16:30:54


11AX40SISO_Ant1_2452




11B_Ant2_2412




11B_Ant2_2437




11B_Ant2_2462



11G_Ant2_2412




11G_Ant2_2437




Date: 23 DEC.2025 16:12:49

11G_Ant2_2462




Date: 23 DEC.2025 16:13:54


11N20SISO_Ant2_2412




11N20SISO_Ant2_2437



11N20SISO_Ant2_2462




11N40SISO_Ant2_2422




Date: 25 DEC 2025 11:32:49

11N40SISO_Ant2_2437




Date: 25 DEC 2025 11:34:25


11N40SISO_Ant2_2452




11AX20SISO_Ant2_2412



11AX20SISO_Ant2_2437




11AX20SISO_Ant2_2462




Date: 24 DEC 2025 16:53:19

11AX40SISO_Ant2_2422




Date: 24 DEC 2025 16:55:13


11AX40SISO_Ant2_2437



11AX40SISO_Ant2_2452



5.4 99% Occupied Bandwidth

Test Requirement:	47 CFR Part 15C
Test Method:	ANSI C63.10: 2020
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting in full-bandwidth single-user mode (Full RU) with all kinds of modulations, and at the lowest, middle, and highest data rates across the channel.
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Test Result

Ant1:


TestMode	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]
11B	2412	15.265	2404.4076	2419.6723
	2437	15.225	2429.4076	2444.6324
	2462	15.185	2454.3277	2469.5125
11G	2412	16.983	2403.4086	2420.3916
	2437	16.903	2428.3686	2445.2717
	2462	17.183	2453.4086	2470.5914
11N20SISO	2412	17.423	2403.3686	2420.7912
	2437	17.502	2428.3287	2445.8312
	2462	17.782	2453.2887	2471.0709
11N40SISO	2422	35.644	2404.1778	2439.8222
	2437	35.804	2419.0979	2454.9021
	2452	35.884	2434.0979	2469.9820
11AX20SISO	2412	17.942	2403.3287	2421.2707
	2437	18.501	2427.8092	2446.3107
	2462	18.262	2452.6893	2470.9510
11AX40SISO	2422	35.485	2404.4975	2439.9820
	2437	37.083	2418.4585	2455.5415
	2452	35.724	2434.1778	2469.9021

Ant2:

TestMode	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]
11B	2412	12.627	2405.6863	2418.3137
	2437	12.587	2430.7263	2443.3137
	2462	12.667	2455.5664	2468.2338
11G	2412	16.424	2403.8082	2420.2318
	2437	16.464	2428.7682	2445.2318
	2462	16.344	2453.7682	2470.1119
11N20SISO	2412	17.263	2403.4086	2420.6713
	2437	17.303	2428.4086	2445.7113
	2462	17.183	2453.3686	2470.5514
11N40SISO	2422	35.405	2404.4975	2439.9021
	2437	36.923	2418.5385	2455.4615
	2452	35.804	2434.0979	2469.9021
11AX20SISO	2412	17.782	2403.4086	2421.1908
	2437	18.422	2427.8492	2446.2707
	2462	18.222	2452.6893	2470.9111
11AX40SISO	2422	35.485	2404.4975	2439.9820
	2437	37.243	2418.3786	2455.6214
	2452	35.724	2434.1778	2469.9021


Test Graphs

11B_Ant1_2412




Date: 16 DEC.2025 19:50:40

11B_Ant1_2437




Date: 16 DEC.2025 19:52:08


11B_Ant1_2462




11G_Ant1_2412



11G_Ant1_2437




11G_Ant1_2462




Date: 16 DEC 2025 19:58:46

11N20SISO_Ant1_2412




Date: 16 DEC 2025 20:00:46

11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



11N40SISO_Ant1_2422




11N40SISO_Ant1_2437




Date: 16 DEC 2025 20:07:08

11N40SISO_Ant1_2452




Date: 16 DEC 2025 20:09:45


11AX20SISO_Ant1_2412




11AX20SISO_Ant1_2437




11AX20SISO_Ant1_2462





11AX40SISO_Ant1_2422




11AX40SISO_Ant1_2437




11AX40SISO_Ant1_2452







11B_Ant2_2462



11G_Ant2_2412




11G_Ant2_2437




Date: 23 DEC 2025 16:12:43

11G_Ant2_2462




Date: 23 DEC 2025 16:13:49

11N20SISO_Ant2_2412




11N20SISO_Ant2_2437




11N20SISO_Ant2_2462



11N40SISO_Ant2_2422




11N40SISO_Ant2_2437




11N40SISO_Ant2_2452




11AX20SISO_Ant2_2412



11AX20SISO_Ant2_2437




11AX20SISO_Ant2_2462




Date: 24 DEC 2025 16:53:13

11AX40SISO_Ant2_2422




Date: 24 DEC 2025 16:55:07


11AX40SISO_Ant2_2437



11AX40SISO_Ant2_2452



5.5 6dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2020
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting in full-bandwidth single-user mode (Full RU) with all kinds of modulations, and at the lowest, middle, and highest data rates across the channel.
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	≥ 500 kHz
Test Results:	Pass

Test Result

Ant1:


TestMode	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	2412	12.24	2405.88	2418.12	0.5	PASS
	2437	12.28	2430.84	2443.12	0.5	PASS
	2462	11.28	2455.88	2467.16	0.5	PASS
11G	2412	16.96	2403.60	2420.56	0.5	PASS
	2437	16.36	2429.20	2445.56	0.5	PASS
	2462	16.88	2453.60	2470.48	0.5	PASS
11N20SISO	2412	17.24	2403.92	2421.16	0.5	PASS
	2437	15.00	2429.64	2444.64	0.5	PASS
	2462	15.60	2453.96	2469.56	0.5	PASS
11N40SISO	2422	32.96	2405.52	2438.48	0.5	PASS
	2437	34.96	2419.96	2454.92	0.5	PASS
	2452	33.76	2434.88	2468.64	0.5	PASS
11AX20SISO	2412	12.16	2408.24	2420.40	0.5	PASS
	2437	17.56	2428.24	2445.80	0.5	PASS
	2462	16.32	2453.20	2469.52	0.5	PASS
11AX40SISO	2422	22.64	2410.64	2433.28	0.5	PASS
	2437	36.08	2419.08	2455.16	0.5	PASS
	2452	20.08	2443.20	2463.28	0.5	PASS

Ant2:

TestMode	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	2412	8.52	2407.96	2416.48	0.5	PASS
	2437	9.44	2431.88	2441.32	0.5	PASS
	2462	9.48	2456.92	2466.40	0.5	PASS
11G	2412	16.44	2403.76	2420.20	0.5	PASS
	2437	16.28	2428.88	2445.16	0.5	PASS
	2462	16.36	2453.84	2470.20	0.5	PASS
11N20SISO	2412	16.96	2403.52	2420.48	0.5	PASS
	2437	16.76	2428.72	2445.48	0.5	PASS
	2462	16.60	2453.60	2470.20	0.5	PASS
11N40SISO	2422	17.04	2411.92	2428.96	0.5	PASS
	2437	36.24	2419.00	2455.24	0.5	PASS
	2452	21.20	2444.64	2465.84	0.5	PASS
11AX20SISO	2412	11.68	2408.20	2419.88	0.5	PASS
	2437	17.60	2428.20	2445.80	0.5	PASS
	2462	16.36	2453.20	2469.56	0.5	PASS
11AX40SISO	2422	23.84	2410.64	2434.48	0.5	PASS
	2437	36.32	2418.84	2455.16	0.5	PASS
	2452	21.28	2443.20	2464.48	0.5	PASS


Test Graphs

11B_Ant1_2412




Date: 16 DEC 2025 19:50:36

11B_Ant1_2437




Date: 16 DEC 2025 19:52:04


11B_Ant1_2462




11G_Ant1_2412



11G_Ant1_2437




11G_Ant1_2462




Date: 16 DEC 2025 19:58:42

11N20SISO_Ant1_2412




Date: 16 DEC 2025 20:00:42


11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



11N40SISO_Ant1_2422




11N40SISO_Ant1_2437




Date: 16 DEC 2025 20:07:03

11N40SISO_Ant1_2452




Date: 16 DEC 2025 20:09:41

11AX20SISO_Ant1_2412




Date: 24 DEC 2025 16:14:28

11AX20SISO_Ant1_2437




Date: 24 DEC 2025 16:16:53

11AX20SISO_Ant1_2462




Date: 24 DEC 2025 16:23:01

11AX40SISO_Ant1_2422




Date: 24 DEC 2025 16:27:45

11AX40SISO_Ant1_2437




Date: 24 DEC 2025 16:30:38


11AX40SISO_Ant1_2452




11B_Ant2_2412




11B_Ant2_2437




11B_Ant2_2462



11G_Ant2_2412




11G_Ant2_2437




Date: 23 DEC 2025 16:12:39

11G_Ant2_2462




Date: 23 DEC 2025 16:13:45


11N20SISO_Ant2_2412




11N20SISO_Ant2_2437



11N20SISO_Ant2_2462




11N40SISO_Ant2_2422




Date: 25 DEC 2025 11:32:39

11N40SISO_Ant2_2437




Date: 25 DEC 2025 11:34:15


11N40SISO_Ant2_2452




11AX20SISO_Ant2_2412



11AX20SISO_Ant2_2437




11AX20SISO_Ant2_2462




Date: 24 DEC 2025 16:53:03

11AX40SISO_Ant2_2422




Date: 24 DEC 2025 16:54:57


11AX40SISO_Ant2_2437



11AX40SISO_Ant2_2452



5.6 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10: 2020
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting in full-bandwidth single-user mode (Full RU) with all kinds of modulations, and at the lowest, middle, and highest data rates across the channel.
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	≤8.00dBm/3kHz
Test Results:	Pass

Test Result

Ant1:

TestMode	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	-8.44	≤8.00	PASS
	2437	-8.33	≤8.00	PASS
	2462	-8.69	≤8.00	PASS
11G	2412	-12.09	≤8.00	PASS
	2437	-12.12	≤8.00	PASS
	2462	-13.44	≤8.00	PASS
11N20SISO	2412	-13.95	≤8.00	PASS
	2437	-12.79	≤8.00	PASS
	2462	-14.66	≤8.00	PASS
11N40SISO	2422	-13.11	≤8.00	PASS
	2437	-12.60	≤8.00	PASS
	2452	-13.21	≤8.00	PASS
11AX20SISO	2412	-20.25	≤8.00	PASS
	2437	-19.52	≤8.00	PASS
	2462	-22.39	≤8.00	PASS
11AX40SISO	2422	-21.90	≤8.00	PASS
	2437	-24.56	≤8.00	PASS
	2452	-20.52	≤8.00	PASS

Ant2:

TestMode	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	2412	-21.62	≤8.00	PASS
	2437	-21.87	≤8.00	PASS
	2462	-20.36	≤8.00	PASS
11G	2412	-18.45	≤8.00	PASS
	2437	-18.11	≤8.00	PASS
	2462	-15.53	≤8.00	PASS
11N20SISO	2412	-21.15	≤8.00	PASS
	2437	-21.08	≤8.00	PASS
	2462	-18.93	≤8.00	PASS
11N40SISO	2422	-17.71	≤8.00	PASS
	2437	-20.35	≤8.00	PASS
	2452	-15.54	≤8.00	PASS
11AX20SISO	2412	-20.38	≤8.00	PASS
	2437	-19.49	≤8.00	PASS
	2462	-22.47	≤8.00	PASS
11AX40SISO	2422	-22.30	≤8.00	PASS
	2437	-24.28	≤8.00	PASS
	2452	-20.41	≤8.00	PASS

Ant1+Ant2:


TestMode	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11N20MIMO	2412	-13.19	≤6.43	PASS
	2437	-12.19	≤6.43	PASS
	2462	-13.28	≤6.43	PASS
11N40MIMO	2422	-11.82	≤6.43	PASS
	2437	-11.93	≤6.43	PASS
	2452	-11.21	≤6.43	PASS
11AX20MIMO	2412	-17.30	≤6.43	PASS
	2437	-16.49	≤6.43	PASS
	2462	-19.42	≤6.43	PASS
11AX40MIMO	2422	-19.09	≤6.43	PASS
	2437	-21.41	≤6.43	PASS
	2452	-17.45	≤6.43	PASS

Note: Duty cycle correction factor details please see section 4.4.


When Duty cycle >98%, D.C.F is not required.

Test Graphs


11B_Ant1_2412




11B_Ant1_2437




11B_Ant1_2462




11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462



11N40SISO_Ant1_2422




11N40SISO_Ant1_2437




Date: 16 DEC 2025 20:07:23

11N40SISO_Ant1_2452




Date: 16 DEC 2025 20:10:00


11AX20SISO_Ant1_2412




11AX20SISO_Ant1_2437



11AX20SISO_Ant1_2462




11AX40SISO_Ant1_2422




Date: 24 DEC 2025 16:28:24

11AX40SISO_Ant1_2437




Date: 24 DEC 2025 16:31:17


11AX40SISO_Ant1_2452




11B_Ant2_2412




11B_Ant2_2437




11B_Ant2_2462



11G_Ant2_2412




11G_Ant2_2437




Date: 23 DEC 2025 16:12:56

11G_Ant2_2462




Date: 23 DEC 2025 16:14:02


11N20SISO_Ant2_2412




11N20SISO_Ant2_2437



11N20SISO_Ant2_2462




11N40SISO_Ant2_2422




Date: 25 DEC 2025 11:32:59

11N40SISO_Ant2_2437




Date: 25 DEC 2025 11:34:34


11N40SISO_Ant2_2452




11AX20SISO_Ant2_2412



11AX20SISO_Ant2_2437




11AX20SISO_Ant2_2462




Date: 24 DEC 2025 16:53:40

11AX40SISO_Ant2_2422




Date: 24 DEC 2025 16:55:36


11AX40SISO_Ant2_2437



11AX40SISO_Ant2_2452



5.7 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2020
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting in full-bandwidth single-user mode (Full RU) with all kinds of modulations, and at the lowest, middle, and highest data rates across the channel.
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass