


承认书项目表

NO.	内 容 (Contents)	页数 (Number of Page)	页码 (Page Code)
1	承认书封面 (Spec Cover)	1	1
2	承认书项目表 (Spec Item)	1	2
3	工程成品图 (Drawing)	1	3
4	电性测试报告 (Test Reports)	1	4
5	S 参数测试 (S Parameter)	1	5
6	增益测试 (Gain Test)	1	6
7			
8			
9			
10	-	-	-
11	-	-	-
12	-	-	-

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			



注意：

1. 带"※"为重要尺寸
2. 无标注公差请参考公差详情
3. 接头强度>=1.0kg
4. 注意接头方向

4	NB004-A02	Paster	SONY-G9000	1
3	NB004-A01	PCB	PCB 47.5*7.2*T0.6mm	1
2	R-CB-113B	Coaxial Cable	SHOWA-O.D. 1.13mm Black	1
1	CI-113	Connector	Mini Connector	1
No.	Part Number	Name	Material	Qty

东莞市脉讯电子有限公司

TITLE: 2.4GHz Antenna			
PART NO.: NB004-113B-125IX		DWG NAME: NB004-113B-125IX.DWG	
APPROVED BY	CHECKED BY	DESIGNED BY	
jeff 2014-10-08	leon 2014-10-08	YD 2014-10-08	
		UNITS: mm	Tolerance
		SCALE: 1/1	XXX ±0.20
		REVISION: A	XXX ±0.10
			XX ±3°

电性测试报告



Test Reports

Electrical Properties	
Frequency	2.4GHz
Impedance	50 OhmNominal
V.S.W.R	1.92 : 1 Max
Return Loss	-10 dB Max
Radiation	Omni-directional
Gain (Peak)	4dBi
Cable Loss	3.2 dB / m Max@ 2450 MHz
Polarization	Linear, Vertical
Admitted Power	1 W
Connector	ipex
Physical Properties	
Antenna Material	PCB
Cable Type	O.D. 1.13mm /125 mm
Operating Temp.	-10 ~ +60 °C
Storage Temp.	-10 ~ +70 °C

S 参数测试

S Parameter Test

Agilent E5071C



增益测试

Gain Test

*Antenna
Radiation
Pattern
VS
Gain*

