







Bandwidth	
2 GSM+ 1 LTE_10MHz_GMSK+QPSK (TC66) 	2 GSM+ 1 LTE_10MHz_GMSK+QPSK (TC66) 
2 GSM+ 1 LTE_10MHz_GMSK+QPSK (TC66) 	/

Remark:


1. All test configurations had been tested, only show the worst-case of 3 carries (2 GSM+1 LTE)in this report.
2. ANT1 port was measured.

Bandwidth	
2 GSM+ 1 LTE_10MHz_QPSK+GMSK (TC72) 	2 GSM+ 1 LTE_10MHz_QPSK+GMSK (TC72) 
2 GSM+ 1 LTE_10MHz_QPSK+GMSK (TC72) 	/

Remark:

1. All test configurations had been tested, only show the worst-case of 3 carries (2 GSM+1 LTE)in this report.
2. ANT1 port was measured.

4 Spurious emissions at antenna terminals




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Spurious emissions at antenna terminals


1 LTE_5MHz_QPSK_M (TC00)




1 LTE_5MHz_QPSK_M (TC00)



1 LTE_5MHz_QPSK_M (TC00)



1 LTE_5MHz_QPSK_M (TC00)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


1 LTE_5MHz_QPSK_T (TC00)




1 LTE_5MHz_QPSK_T (TC00)



1 LTE_5MHz_QPSK_T (TC00)



1 LTE_5MHz_QPSK_T (TC00)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{ dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


1 LTE_10MHz_QPSK_B (TC03)




1 LTE_10MHz_QPSK_B (TC03)



1 LTE_10MHz_QPSK_B (TC03)



1 LTE_10MHz_QPSK_B (TC03)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


1 LTE_10MHz_QPSK_M (TC03)




1 LTE_10MHz_QPSK_M (TC03)



1 LTE_10MHz_QPSK_M (TC03)



1 LTE_10MHz_QPSK_M (TC03)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


1 LTE_10MHz_QPSK_T (TC03)




1 LTE_10MHz_QPSK_T (TC03)



1 LTE_10MHz_QPSK_T (TC03)



1 LTE_10MHz_QPSK_T (TC03)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed -13dBm- $10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


1 LTE_15MHz_QPSK_B (TC06)




1 LTE_15MHz_QPSK_B (TC06)



1 LTE_15MHz_QPSK_B (TC06)



1 LTE_15MHz_QPSK_B (TC06)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


1 LTE_15MHz_QPSK_M (TC06)




1 LTE_15MHz_QPSK_M (TC06)



1 LTE_15MHz_QPSK_M (TC06)



1 LTE_15MHz_QPSK_M (TC06)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


1 LTE_15MHz_QPSK_T (TC06)




1 LTE_15MHz_QPSK_T (TC06)



1 LTE_15MHz_QPSK_T (TC06)



1 LTE_15MHz_QPSK_T (TC06)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


1 LTE_20MHz_QPSK_B (TC09)




1 LTE_20MHz_QPSK_B (TC09)



1 LTE_20MHz_QPSK_B (TC09)



1 LTE_20MHz_QPSK_B (TC09)




Remark:

1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.




Spurious emissions at antenna terminals


1 LTE_20MHz_QPSK_M (TC09)




1 LTE_20MHz_QPSK_M (TC09)



1 LTE_20MHz_QPSK_M (TC09)



1 LTE_20MHz_QPSK_M (TC09)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{ dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


1 LTE_20MHz_QPSK_T (TC09)




1 LTE_20MHz_QPSK_T (TC09)



1 LTE_20MHz_QPSK_T (TC09)



1 LTE_20MHz_QPSK_T (TC09)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


2 LTE_5+5MHz_QPSK_B (TC12)




2 LTE_5+5MHz_QPSK_B (TC12)



2 LTE_5+5MHz_QPSK_B (TC12)



2 LTE_5+5MHz_QPSK_B (TC12)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


2 LTE_5+5MHz_QPSK_M (TC12)




2 LTE_5+5MHz_QPSK_M (TC12)



2 LTE_5+5MHz_QPSK_M (TC12)



2 LTE_5+5MHz_QPSK_M (TC12)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


2 LTE_5+5MHz_QPSK_T (TC12)




2 LTE_5+5MHz_QPSK_T (TC12)



2 LTE_5+5MHz_QPSK_T (TC12)



2 LTE_5+5MHz_QPSK_T (TC12)




Remark:


1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{ dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.

Spurious emissions at antenna terminals


2 LTE_5+5MHz_QPSK (TC15)




2 LTE_5+5MHz_QPSK (TC15)



2 LTE_5+5MHz_QPSK (TC15)



2 LTE_5+5MHz_QPSK (TC15)




Remark:

1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.




Spurious emissions at antenna terminals


2 LTE_5+10MHz_QPSK_B (TC18)




2 LTE_5+10MHz_QPSK_B (TC18)



2 LTE_5+10MHz_QPSK_B (TC18)



2 LTE_5+10MHz_QPSK_B (TC18)



Remark:

1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB,
 $P = 46\text{dBm} = 39.8\text{W}$
 $\text{Limit} = 46\text{dBm} - [43 + 10 \log_{10}(39.8\text{W})] \text{ dB} = -13\text{dBm}$
2. For 4x4 MIMO, ANT1 port was measured and the limit was showed $-13\text{dBm} - 10\lg(4) = -19\text{dBm}$ in order to determine the test result conveniently.
3. The spurious emissions 9kHz to 30MHz were very low and not displayed in this report.
4. All test configurations had been tested, only show the worst-case in this report.