

Label Location:



Product Name: Portable Power Station
Model: E 300
Capacity: 258Wh 22.2V 11.6Ah
USB-C Output: 65W 5V $\overline{\text{---}}$ 3A, 9V $\overline{\text{---}}$ 3A, 12V $\overline{\text{---}}$ 3A, 15V $\overline{\text{---}}$ 3A, 20V $\overline{\text{---}}$ 3.25A
USB Output: USB-A(x2) 5V $\overline{\text{---}}$ 2.4A
USB-A Fast Charge :5V $\overline{\text{---}}$ 3A, 9V $\overline{\text{---}}$ 2A, 12V $\overline{\text{---}}$ 1.5A 18W max
AC Output: 300W 120VAC 60Hz
DC Output: 13V $\overline{\text{---}}$ 10A
DC Input: 12V-30V $\overline{\text{---}}$ 8.5A (max)
Wireless: 10W
Discharging temperature: 14°F-104°F(-10°C-40°C)
Charging temperature: 42.8°F-104°F(6°C-40°C)
DC Total output: 247W
AC output: 300W
FCC ID: 2BBM4-E300
IC ID: 32411-E300



Intertek
022215
CONFORME TO ANSI CANUL
STD. 2743

ENGINEUTY
FLEXIBLE POWER SOLUTIONS

To ensure safe and proper use of the power station, always follow the manufacturer's instructions as improper use can increase risks.

CALIFORNIA PROPOSITION

⚠ 65 WARNING ⚠

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

ADVERTENCIA: Este producto contiene productos químicos reconocidos por el estado de California que provocan cáncer, defectos de nacimiento u otros daños reproductivos.

For more information:
www.P65Warnings.ca.gov