

Label Location:



Product Name: Portable Power Station

Model: E600

Capacity: 515Wh 22.2V 23.2Ah

USB-C Output: 65W 5V $\approx$ 3A, 9V $\approx$ 3A, 12V $\approx$ 3A, 15V $\approx$ 3A, 20V $\approx$ 3.25A

USB Output: USB-A(x3) 5V $\approx$ 2.4A

USB-A Fast Charge :5V $\approx$ 3A, 9V $\approx$ 2A, 12V $\approx$ 1.5A 18W max

AC Output(x2): 600W 120VAC 60Hz

DC Output: 13V $\approx$ 10A

DC Input: 12V-30V $\approx$ 8.5A (max)

Wireless: 10W

Discharging temperature: 14°F-104°F(-10°C-40°C)

Charging temperature: 42.8°F-104°F(6°C-40°C)

DC Total output: 259W

AC output: 600W

FCC ID: 2BBM4-E600

IC ID: 32411-E600



Intertek
8022215
CONFORME TO ANSI CANUL
STD.2748

ENGINUTY
FLEXIBLE POWER SOLUTIONS

To ensure safe and proper use of the power station, always follow the manufacturer's instructions as improper use can increase risks.

CALIFORNIA PROPOSITION

⚠ 65 WARNING ⚠

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

ADVERTENCIA: Este producto contiene productos químicos reconocidos por el estado de California que provocan cáncer, defectos de nacimiento u otros daños reproductivos.

For more information:
www.P65Warnings.ca.gov