FCC Part 15 C TEST REPORT

Product Name	:	RGB Soundbar Speaker
Brand Mark	:	N/A
Model No.	:	25207BLK
Extension model	:	BT-2367A
Report Number	:	BLA-EMC-202312-A7202
FCC ID	:	2BBM5-BT2367A
Date of Sample Receipt	:	2023/12/29
Date of Test	:	2023/12/29 to 2024/1/25
Date of Issue	:	2024/1/25
Test Standard	:	47 CFR Part 15, Subpart C 15.247
Test Result	:	Pass

Prepared for:

Huizhou CCA Industrial Co.,LTD
1st-4th Floor, Building A, No.122, Hongchuan Avenue North, Tongqiao, Zhongkai state, Huizhou city

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: Jozu

Review by: Sweet

Approved by: Blue Zheng

Date: 2024/1/25

BlueAsia Technical Services (Shenzhen) Co.,Ltd. BLA

REPORT REVISE RECORD

Version No.	Date	Description
00	2024/1/25	Original

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY 5

2 GENERAL INFORMATION 6

3 GENERAL DESCRIPTION OF E.U.T. 6

4 TEST ENVIRONMENT 8

5 TEST MODE 8

6 MEASUREMENT UNCERTAINTY 8

7 DESCRIPTION OF SUPPORT UNIT 9

8 TEST FACILITY 9

9 LABORATORY LOCATION 9

10 TEST INSTRUMENTS LIST 10

11 ANTENNA REQUIREMENT 12

11.1 CONCLUSION 12

12 CONDUCTED SPURIOUS EMISSIONS 13

12.1 LIMITS 13
12.2 BLOCK DIAGRAM OF TEST SETUP 13
12.3 TEST DATA 13

13 20DB BANDWIDTH 14

13.1 BLOCK DIAGRAM OF TEST SETUP 14
13.2 TEST DATA 14

14 CONDUCTED PEAK OUTPUT POWER 15

14.1 LIMITS 15
14.2 BLOCK DIAGRAM OF TEST SETUP 15
14.3 TEST DATA 15

15 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) 16

15.1 LIMITS 16
15.2 BLOCK DIAGRAM OF TEST SETUP 16
15.3 PROCEDURE 16
15.4 TEST DATA 18

16 RADIATED SPURIOUS EMISSIONS 21

BlueAsia

16.1 LIMITS 21
16.2 BLOCK DIAGRAM OF TEST SETUP 22
16.3 PROCEDURE 22
16.4 TEST DATA 24

17 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 33

17.1 LIMITS 33
17.2 BLOCK DIAGRAM OF TEST SETUP 34
17.3 PROCEDURE 34
17.4 TEST DATA 36

18 CONDUCTED BAND EDGES MEASUREMENT 41

18.1 LIMITS 41
18.2 BLOCK DIAGRAM OF TEST SETUP 41
18.3 TEST DATA 41

19 DWELL TIME 42

19.1 LIMITS 42
19.2 BLOCK DIAGRAM OF TEST SETUP 42
19.3 TEST DATA 42

20 HOPPING CHANNEL NUMBER 43

20.1 LIMITS 43
20.2 BLOCK DIAGRAM OF TEST SETUP 43
20.3 TEST DATA 43

21 CARRIER FREQUENCIES SEPARATION 44

21.1 LIMITS 44
21.2 BLOCK DIAGRAM OF TEST SETUP 44
21.3 TEST DATA 44

22 APPENDIX1 45

APPENDIX A: PHOTOGRAPHS OF TEST SETUP 94

APPENDIX B: PHOTOGRAPHS OF EUT 96

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass

BlueAsia

2 GENERAL INFORMATION

Applicant	Huizhou CCA Industrial Co.,LTD
Address	1st-4th Floor,Building A,No.122,Hongchuan Avenue North,Tongqiao,Zhongkai state,Huizhou city
Manufacturer	Huizhou CCA Industrial Co.,LTD
Address	1st-4th Floor,Building A,No.122,Hongchuan Avenue North,Tongqiao,Zhongkai state,Huizhou city
Factory	Huizhou CCA Industrial Co.,LTD
Address	1st-4th Floor,Building A,No.122,Hongchuan Avenue North,Tongqiao,Zhongkai state,Huizhou city
Product Name	RGB Soundbar Speaker
Test Model No.	25207BLK
Extension model	BT-2367A
Note	The above models are identical in PCB layout, internal structure and circuit. The difference is the commercial use model

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V1.0
Software Version	V1.0

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8-DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	PCB Antenna
Antenna Gain:	-0.68dBi (Provided by the applicant)

BlueAsia

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

BlueAsia

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	3.7Vdc

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE)
Remark: Full battery is used during all test except ac conducted emission, DH1,DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned only GFSK worse case is reported.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %
Unwanted Radiated Emission (30MHz ~ 1000MHz)	±4.35 dB
Unwanted Radiated Emission (1GHz ~ 18GHz)	±4.44 dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

BlueAsia

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter	UGREEN	CD112	N/A	N/A

8 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:
● FCC — Designation No.: CN1252
BlueAsia of Technical Services(Shenzhen) Co., Ltd has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Designation CN1252.
●ISED — CAB identifier No.: CN0028

BlueAsia of Technical Services(Shenzhen) Co., Ltd has been registered by Certification and Engineering

Bureau of ISED for radio equipment testing with CAB identifier CN0028.

9 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

BlueAsia

10 TEST INSTRUMENTS LIST

Test Equipment Of Radiated Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Chamber 1	SKET	966	N/A	2023/11/16	2026/11/15
Chamber 2	SKET	966	N/A	2021/07/20	2024/07/19
Spectrum	R&S	FSP40	100817	2023/08/30	2024/08/29
Receiver	R&S	ESR7	101199	2023/08/30	2024/08/29
Receiver	R&S	ESPI7	101477	2023/07/07	2024/07/06
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2022/10/12	2025/10/11
Horn Antenna	Schwarzbeck	BBHA9120D	01892 P:00331	2022/09/13	2025/09/12
Horn Antenna	Schwarzbeck	BBHA 9170	1106	2022/04/24	2024/04/23
Amplifier	SKET	LNPA_30M01G-30	SK2021060801	2023/07/07	2024/07/06
Amplifier	SKET	PA-000318G-45	N/A	2023/08/30	2024/08/29
Amplifier	SKET	LNPA_18G40G-50	SK2022071301	2023/07/14	2024/07/13
Filter group	SKET	2.4G/5G Filter group r	N/A	2023/07/07	2024/07/06
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2022/09/14	2025/09/13
1kHZ calibration audio source	SKET	MCS-ABT-C35	N/A	2023/09/04	2024/09/03
Free Field Microphone	SKET	MGS MP 663	0414	2023/09/04	2024/09/03
Audio shielding box	SKET	SB-ABT-C35	N/A	2023/03/30	2024/03/29
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A
Signal Generator DTV	ECREDIX	DSG-1000	N/A	N/A	N/A

BlueAsia

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Shield room	SKET	833	N/A	2023/11/16	2025/11/15
Receiver	R&S	ESPI3	101082	2023/08/30	2024/08/29
LISN	R&S	ENV216	3560.6550.15	2023/08/30	2024/08/29
LISN	AT	AT166-2	AKK1806000003	2023/08/30	2024/08/29
ISN	TESEQ	ISNT8-cat6	53580	2023/08/30	2024/08/29
Single-channel vehicle artificial power network	Schwarzbeck	NNBM 8124	01045	2023/07/07	2024/07/06
Single-channel vehicle artificial power network	Schwarzbeck	NNBM 8124	01075	2023/07/07	2024/07/06
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

Test Equipment Of RF Conducted Test					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	2023/08/30	2024/08/29
Spectrum	Agilent	N9020A	MY49100060	2023/08/30	2024/08/29
Spectrum	Agilent	N9020A	MY54420161	2023/08/30	2024/08/29
Signal Generator	Agilent	N5182A	MY47420955	2023/08/30	2024/08/29
Signal Generator	Agilent	N5181A	MY46240904	2023/07/07	2024/07/06
Signal Generator	R&S	CMW500	132429	2023/08/30	2024/08/29
BluetoothTester	Anritsu	MT8852B	06262047872	2023/08/30	2024/08/29
Power probe	DARE	RPR3006W	14I00889SN042	2023/09/01	2024/08/31
Power detection box	CDKMV	MW100-PSB	MW201020JYT	2023/07/07	2024/07/06
DCPowersupply	zhaoxin	KXN-305D	20K305D1221363	2023/08/30	2024/08/29
DCPowersupply	zhaoxin	RXN-1505D	19R1505D050168	2023/08/30	2024/08/29
2.4GHz/5GHz RF Test software	MTS	MTS 8310	Version 2.0.0.0	N/A	N/A
Audio Analyzer	Audio Precision	ATS-1	ATS141094	2023/07/07	2024/07/06

BlueAsia

11 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

11.1 CONCLUSION

Standard Requirement:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -0.68dBi.

BlueAsia

12 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

12.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

12.2 BLOCK DIAGRAM OF TEST SETUP



12.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

13 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

13.1 BLOCK DIAGRAM OF TEST SETUP



13.2 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

14 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

14.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥50 hopping channels
	0.25 for 25≤ hopping channels <50
	1 for digital modulation
2400-2483.5	1 for ≥75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

15 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	BT mode
Test Mode (Final Test)	BT mode
Tester	Jozu
Temperature	25℃
Humidity	60%

15.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 PROCEDURE

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

15.4 TEST DATA

[TestMode: TX]; [Line: Line] ;[Power:AC120V/60Hz]

Conducted Emission Measurement

Project No.: CE Data :#12 2024/1/4



Site		Phase:	*L1*	Temperature:	(C)
Limit:	FCC Class B Conduction(QP)	Power:		Humidity:	%RH
EUT:	RGB Soundbar Speaker	Distance:	RBW: 9 KHz		
M/N:	25207BLK		VBW: 30 KHz	Sweep Time: 10 ms	
Mode:	TX Mode				
Note:					

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	cm	degree	Comment
1		0.4260	26.25	9.94	36.19	57.33	-21.14	QP			
2		0.4260	17.41	9.94	27.35	47.33	-19.98	AVG			
3	*	0.7180	39.37	10.02	49.39	56.00	-6.61	QP			
4		0.7180	28.08	10.02	38.10	46.00	-7.90	AVG			
5		1.1700	25.60	9.85	35.45	56.00	-20.55	QP			
6		1.1700	16.83	9.85	26.68	46.00	-19.32	AVG			
7		2.3620	25.10	10.12	35.22	56.00	-20.78	QP			
8		2.3620	15.55	10.12	25.67	46.00	-20.33	AVG			
9		3.1020	25.36	10.06	35.42	56.00	-20.58	QP			
10		3.1020	15.48	10.06	25.54	46.00	-20.46	AVG			
11		13.7820	44.67	-1.05	43.62	60.00	-16.38	QP			
12		13.7820	35.84	-1.05	34.79	50.00	-15.21	AVG			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESPI_1 Spectrum Analyzer: ESPI

L.I.S.N: Engineer Signature:

Test Result: Pass

[TestMode: TX]; [Line: Nutral] ;[Power:AC120V/60Hz]



Site		Phase:	N	Temperature:	(C)
Limit:	FCC Class B Conduction(QP)	Power:		Humidity:	%RH
EUT:	RGB Soundbar Speaker	Distance:	RBW: 9 KHz		
M/N:	25207BLK		VBW: 30 KHz	Sweep Time: 10 ms	
Mode:	TX Mode				
Note:					

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	cm	degree	Comment
1		0.7220	35.90	9.95	45.85	56.00	-10.15	QP			
2	*	0.7220	27.20	9.95	37.15	46.00	-8.85	AVG			
3		1.1420	23.25	9.88	33.13	56.00	-22.87	QP			
4		1.1420	17.35	9.88	27.23	46.00	-18.77	AVG			
5		1.7980	21.97	9.99	31.96	56.00	-24.04	QP			
6		1.7980	15.32	9.99	25.31	46.00	-20.69	AVG			
7		3.0860	21.88	10.05	31.93	56.00	-24.07	QP			
8		3.0860	14.97	10.05	25.02	46.00	-20.98	AVG			
9		6.3220	19.88	10.78	30.66	60.00	-29.34	QP			
10		6.3220	13.34	10.78	24.12	50.00	-25.88	AVG			
11		13.2060	38.15	-0.75	37.40	60.00	-22.60	QP			
12		13.2060	32.08	-0.75	31.33	50.00	-18.67	AVG			

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESPI_1 Spectrum Analyzer: ESPI

L.I.S.N: Engineer Signature:

Test Result: Pass

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.

BlueAsia

16 RADIATED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

16.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BlueAsia

16.2 BLOCK DIAGRAM OF TEST SETUP







16.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.

Remark:
1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.fundamental frequency is blocked by filter, and only spurious emission is shown.
4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

16.4 TEST DATA

[TestMode: TX below 1G]; [Polarity: Horizontal]



Site
Limit: FCC Part15 Class B
EUT: RGB Soundbar Speaker
M/N: 25207BLK
Mode: TX Mode
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	31.2892	5.74	18.64	24.38	40.00	-15.62	QP	P	
2	49.0144	0.36	19.20	19.56	40.00	-20.44	QP	P	
3	103.8054	3.19	15.79	18.98	43.50	-24.52	QP	P	
4	158.1123	4.87	19.18	24.05	43.50	-19.45	QP	P	
5	372.0045	0.44	21.07	21.51	46.00	-24.49	QP	P	
6 *	839.1817	2.31	29.94	32.25	46.00	-13.75	QP	P	

*:Maximum data x:Over limit !:over margin

Test Result: Pass

[TestMode: TX below 1G]; [Polarity: Vertical]



Site
Limit: FCC Part15 Class B
EUT: RGB Soundbar Speaker
M/N: 25207BLK
Mode: TX Mode
Note:

Polarization: ***Vertical***
Power:

Temperature: (C)
Humidity: %RH

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	32.5197	6.25	18.86	25.11	40.00	-14.89	QP	P	
2	47.6584	4.14	19.00	23.14	40.00	-16.86	QP	P	
3	103.8054	6.83	15.79	22.62	43.50	-20.88	QP	P	
4	175.0365	1.63	18.45	20.08	43.50	-23.42	QP	P	
5	449.5557	0.51	23.26	23.77	46.00	-22.23	QP	P	
6 *	903.3093	3.70	30.84	34.54	46.00	-11.46	QP	P	

*:Maximum data x:Over limit !:over margin

Test Result: Pass

Above 1GHz:

[TestMode: TX low channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: RGB Soundbar Speaker
M/N: 25207BLK
Mode: TX-2402
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4807.000	50.21	5.64	55.85	74.00	-18.15	peak	
2	*	4807.000	43.66	5.64	49.30	54.00	-4.70	AVG	
3		7206.000	39.40	9.24	48.64	74.00	-25.36	peak	
4		8484.750	39.54	10.84	50.38	74.00	-23.62	peak	
5		9608.000	37.13	12.31	49.44	74.00	-24.56	peak	
6		10999.25	37.49	13.48	50.97	74.00	-23.03	peak	
7		12620.75	38.43	13.04	51.47	74.00	-22.53	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESR_1
Antenna: EZ 9120D 1G-18G
Spectrum Analyzer: FSP40
Engineer Signature:

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: RGB Soundbar Speaker
M/N: 25207BLK
Mode: TX-2402
Note:

Polarization: ***Vertical***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4807.000	43.59	5.64	49.23	74.00	-24.77	peak	
2		5735.250	40.52	8.11	48.63	74.00	-25.37	peak	
3		7206.000	39.67	9.24	48.91	74.00	-25.09	peak	
4		9608.000	38.43	12.31	50.74	74.00	-23.26	peak	
5	*	10717.250	39.37	13.08	52.45	74.00	-21.55	peak	
6		12385.750	38.14	12.19	50.33	74.00	-23.67	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESR_1
Antenna: EZ 9120D 1G-18G
Spectrum Analyzer: FSP40
Engineer Signature:

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: RGB Soundbar Speaker
M/N: 25207BLK
Mode: TX-2441
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4882.000	40.20	5.73	45.93	74.00	-28.07	peak	
2		7323.000	38.28	9.43	47.71	74.00	-26.29	peak	
3	*	8508.250	40.70	10.97	51.67	74.00	-22.33	peak	
4		9764.000	38.07	12.21	50.28	74.00	-23.72	peak	
5		11022.75	37.88	13.32	51.20	74.00	-22.80	peak	
6		11763.00	39.07	11.78	50.85	74.00	-23.15	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESR_1
Antenna: EZ 9120D 1G-18G
Spectrum Analyzer: FSP40
Engineer Signature:

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: RGB Soundbar Speaker
M/N: 25207BLK
Mode: TX-2441
Note:

Polarization: ***Vertical***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4882.000	39.81	5.73	45.54	74.00	-28.46	peak	
2		5946.750	39.33	8.71	48.04	74.00	-25.96	peak	
3		7323.000	38.36	9.43	47.79	74.00	-26.21	peak	
4	*	8896.000	39.64	12.03	51.67	74.00	-22.33	peak	
5		9764.000	37.66	12.21	49.87	74.00	-24.13	peak	
6		11034.50	37.44	13.24	50.68	74.00	-23.32	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESR_1
Antenna: EZ 9120D 1G-18G
Spectrum Analyzer: FSP40
Engineer Signature:

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: RGB Soundbar Speaker
M/N: 25207BLK
Mode: TX-2480
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4959.750	48.05	6.60	54.65	74.00	-19.35	peak	
2	*	4959.750	41.67	6.60	48.27	54.00	-5.73	AVG	
3		5888.000	40.07	8.60	48.67	74.00	-25.33	peak	
4		7440.000	39.27	9.64	48.91	74.00	-25.09	peak	
5		8943.000	39.48	12.23	51.71	74.00	-22.29	peak	
6		9920.000	36.20	12.14	48.34	74.00	-25.66	peak	
7		11316.50	39.18	12.69	51.87	74.00	-22.13	peak	

*:Maximum data x:Over limit !:over margin 〈Reference Only

Receiver: ESR_1
Antenna: EZ 9120D 1G-18G
Spectrum Analyzer: FSP40
Engineer Signature:

Test Result: Pass