

MPE TEST REPORT

Applicant	Deer Management Systems LLC
FCC ID	2BBNQ-RVG3CD
Product	Reveal X 3.0
Brand	Reveal
Model	Reveal X 3.0
Report No.	EFTA25120156-IE-03-M1
Issue Date	February 3, 2026

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 §1.1310, §2.1091**. The test results show that the equipment tested can demonstrate compliance with the requirements as documented in this report.

Prepared by: Wei Fangying

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory	3
1.1	Notes of the Test Report.....	3
1.2	Test Facility.....	3
1.3	Testing Location.....	3
1.4	Laboratory Environment	3
2	Description of Equipment Under Test	4
3	Maximum Tune up and Antenna Gain	5
4	MPE Limit.....	6
5	RF Exposure Evaluation Result.....	8
	ANNEX A: The EUT Appearance	9

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Deer Management Systems LLC
Applicant address	1668 Jordan West Road Decorah, IA 52101 United State
Manufacturer	Deer Management Systems LLC
Manufacturer address	1668 Jordan West Road Decorah, IA 52101 United State

General Technologies

EUT Description			
Model	Reveal X 3.0		
SN	ACD2508140008005		
Hardware Version	1		
Software Version	1.0.1		
Frequency	Band	TX (MHz)	RX (MHz)
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 12	699 ~ 716	729 ~ 746
	LTE Band 13	777 ~ 787	746 ~ 756
	LTE Band 14	788 ~ 798	758 ~ 768
	LTE Band 25	1850 ~ 1915	1930 ~ 1995
	LTE Band 66	1710 ~ 1780	2110 ~ 2180
	Wi-Fi 2.4G	2400 ~ 2483.5	2400 ~ 2483.5
	Bluetooth LE	2400 ~ 2483.5	2400 ~ 2483.5
Date of Testing	December 20, 2025~ January 22, 2026		
Date of Sample Received	December 11, 2025		
Note: 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant. 2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

3 Maximum Tune up and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

$$\text{Numeric gain (G)} = 10^{(\text{antenna gain}/10)}$$

So, the maximum tune up results for each band are as follows:

Band	Maximum Tune up Tolerance		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
LTE Band 2	24.00	251.19	4.59	2.88
LTE Band 4	24.00	251.19	3.05	2.02
LTE Band 5	22.00	158.49	4.44	2.78
LTE Band 12	22.00	158.49	0.71	1.18
LTE Band 13	20.00	100.00	3.58	2.28
LTE Band 14	22.00	158.49	4.04	2.54
LTE Band 25	24.00	251.19	4.59	2.88
LTE Band 66	24.00	251.19	3.28	2.13
Wi-Fi 2.4G	12.00	15.85	3.39	2.18
Bluetooth LE	3.00	2.00	2.56	1.80

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

*f = frequency in MHz. * = Plane-wave equivalent power density.*

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is $f/1500$, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
LTE Band 2	1.000
LTE Band 4	1.000
LTE Band 5	0.549
LTE Band 12	0.466
LTE Band 13	0.518
LTE Band 14	0.525
LTE Band 25	1.000
LTE Band 66	1.000
Wi-Fi 2.4GHz	1.000
Bluetooth LE	1.000

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE Ratio
LTE Band 2	24.00	4.59	28.590	722.770	0.144	1.000	0.144
LTE Band 4	24.00	3.05	27.050	506.991	0.101	1.000	0.101
LTE Band 5	22.00	4.44	26.440	440.555	0.088	0.549	0.160
LTE Band 12	22.00	0.71	22.710	186.638	0.037	0.466	0.080
LTE Band 13	20.00	3.58	23.580	228.034	0.045	0.518	0.088
LTE Band 14	22.00	4.04	26.040	401.791	0.080	0.525	0.152
LTE Band 25	24.00	4.59	28.590	722.770	0.144	1.000	0.144
LTE Band 66	24.00	3.28	27.280	534.564	0.106	1.000	0.106
Wi-Fi 2.4GHz	12.00	3.39	15.390	34.594	0.007	1.000	0.007
Bluetooth LE	3.00	2.56	5.560	3.60	0.001	1.000	0.001
Note: R = 20cm $\pi = 3.1416$ The MPE Ratio = Mac Result ÷ Limit Value							

This device supports simultaneous transmission as following two combinations:

1. Wi-Fi 2.4GHz and WWAN.
2. Bluetooth and WWAN

Accordingly, the maximum cumulative ratio of simultaneous transmitting antennas is calculated as follows:

$$TER = \text{Wi-Fi 2.4GHz Antenna MPE Ratio} + \text{WWAN Antenna MPE Ratio} = 0.160 + 0.007 = 0.167 < 1$$

So, the limit is kept.

Note: For this device, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT *****