Report No.: DDT-RE23052906-2E01

Issued Date: Jun. 10, 2023

FCC CERTIFICATION TEST REPORT

FOR

Applicant	:	MING YUNG HUNG MATERIAL OF LIGHTS CO.,LTD
Address	:	Du Bi Village Duruan Town Jiangmen, Guangdong Province, China
Equipment under Test	:	RF remote
Model No.	:	MYH-R
Trade Mark	:	N/A
FCC ID	:	2BBO7-MYH-R
Manufacturer	:	MING YUNG HUNG MATERIAL OF LIGHTS CO.,LTD
Address	:	Du Bi Village Duruan Town Jiangmen, Guangdong Province, China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, http://www.dgddt.com

REPORT

Table of Contents

Test report declares....3
1 Summary of test results 6
2 General test information 7
2.1. Description of EUT 7
2.2. Accessories of EUT 7
2.3. Assistant equipment used for test 7
2.4. Block diagram of EUT configuration for test 7
2.5. Deviations of test standard 7
2.6. Test environment conditions 7
2.7. Test laboratory 8
2.8. Measurement uncertainty 8
3 Equipment Used During Test 9
4. On Time and Duty Cycle 10
4.1. Block diagram of test setup 10
4.2. Limits 10
4.3. Test Procedure 10
4.4. Test Result 10
4.5. Original test data 11
5. 20dB Bandwidth and 99% Bandwidth 12
5.1. Block diagram of test setup 12
5.2. Limits 12
5.3. Test Procedure 12
5.4. Test Result 12
5.5. Original test data 13
6 Stop transmitting time test 14
6.1. Block diagram of test setup 14
6.2. Limits 14
6.3. Test Procedure 14
6.4. Test Result 14
6.5. Original test data 14
7 Radiated emission 15
7.1. Block diagram of test setup 15
7.2. Limit 16
7.3. Test Procedure 17
7.4. Test result 19
8 Power Line Conducted Emission 25
8.1. Block diagram of test setup 25

8.2. Power Line Conducted Emission Limits 25
8.3. Test Procedure 25
8.4. Test Result 26
9 Antenna Requirements 27
9.1. Result 27
10 Test setup photograph 28
11 Photos of the EUT 30

Test Report Declare

Applicant	:	MING YUNG HUNG MATERIAL OF LIGHTS CO.,LTD
Address	:	Du Bi Village Duruan Town Jiangmen, Guangdong Province, China
Equipment under Test	:	RF remote
Model No.	:	MYH-R
Trade mark	:	N/A
Manufacturer	:	MING YUNG HUNG MATERIAL OF LIGHTS CO.,LTD
Address	:	Du Bi Village Duruan Town Jiangmen, Guangdong Province, China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C

Test procedure used:

ANSI C63.10:2013

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No.:	DDT-RE23052906-2E01		
Date of Receipt:	May 29, 2023	**Date of Test:**	May 29, 2023 ~ Jun. 10, 2023

Prepared By: ***Approved By:***

Tiger Mo Damon Hu

Tiger Mo/Engineer ***Damon Hu/EMC Manager***

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jun. 10, 2023	

1 Summary of test results

Description of Test Item	Standard	Results
20dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.231	PASS
Stop Transmitting Time Test	FCC Part 15C: 15.231(a)	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.231(b)	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207	N/A
Antenna requirement	FCC Part 15: 15.203	PASS
Note: N/A is an abbreviation for Not Applicable.		

2 General test information

2.1. Description of EUT

EUT Name	:	RF remote
Model Number	:	MYH-R
EUT function description	:	Please reference user manual of this device
Power supply	:	Battery 1.5V*2(Size: AAA)
Operation frequency	:	433.92MHz
Modulation	:	OOK
Antenna Type	:	PCB antenna, maximum PK gain:-7.76 dBi
Sample Number	:	S23052906-02 for conductive S23052906-03 for radiation

Note: EUT is the ab. of equipment under test.

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
N/A	N/A	N/A	N/A	N/A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Serial No.	Other
N/A	N/A	N/A	N/A	N/A

2.4. Block diagram of EUT configuration for test

EUT

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
TX mode	/	433.92

Note：New battery is used during all test

2.5. Deviations of test standard

No Deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25℃
Humidity range:	40-75%
Pressure range:	86-106kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, http://www.dgddt.com, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Frequencies Stability	6.7×10^{-8} (Antenna couple method)
	5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.40 dB (3.6 GHz ≤ f < 8 GHz)
	1.66 dB (8 GHz ≤ f < 26.5 GHz)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 ℃
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz)
	4.40 dB (6 GHz - 18 GHz)
	3.54 dB (18 GHz - 26 GHz)
	4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3 Equipment Used During Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☒RF Connected Test (Tonscend RF Measurement System 4#)					
Signal &Spectrum analyzer	R&S	FSV3044	101173	Apr. 23, 2023	1 Year
Wideband Radio Communication tester	R&S	CMW500	168801	Apr. 27, 2023	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Apr. 27, 2023	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Sep. 28, 2022	1 Year
RF Control Unit	Tonsend	JS0806-2	21I8060485	Apr. 27, 2023	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150 L	ZX170110-A	May 15, 2023	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.3.2.22	N/A	N/A
☒Radiation 3#chamber					
EMI Test Receiver	R&S	ESU26	100472	Apr. 23, 2023	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Apr. 23, 2023	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Sep. 29, 2022	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	01429	Jul. 22, 2022	1 Year
Double Ridged Horn Antenna	Schwarzbeck	BBHA9120 D	02468	Sep. 29, 2022	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Apr. 26, 2023	1 Year
Pre-amplifier	COM-POWER	PAM-118A	18040084	Aug.17, 2022	1 Year
Pre-amplifier	COM-POWER	PAM-840A	461369	Apr. 27, 2023	1 Year
RE Cable	N/A	W23.02 CP1-X2 + W23.09 AP1-X8+ JCT26S-NJ-NJ-1.5M+ JCT26S-NJ-NJ-1.5M	4.5M+8M+1.5M+1.5M	Apr. 21, 2023	1 Year
RF Cable	Yuhu Technology	JCTB810-NJ-NJ-9M+ ZT26S-SMAJ-SMAJ-1M	21123964	Apr. 23, 2023	1 Year
Micro-Tronics filters	REBES	BRM50702	G555	N/A	N/A
Micro-Tronics filters	REBES	BRM50716	G392	N/A	N/A
High Pass filter	XB	XBLBQ-GTA 67	210820-2-3	N/A	N/A
Test software	Tonscend	JS32-RE	V 5.0.0.1	N/A	N/A

4. On Time and Duty Cycle

4.1. Block diagram of test setup



4.2. Limits

None: for reporting purposes only.

4.3. Test Procedure

Set the Centre frequency of the spectrum analyzer to the transmitting frequency;

Set the span=0MHz, RBW=10MHz, VBW=10MHz, Sweep time=100ms;

Trace mode = Single hold.

4.4. Test Result

Test Channel	Duty Cycle[%]	20 log(duty cycle)
433.92	30.45	-10.33

Note 1: The transmitter duty cycle was measured using a spectrum analyser in the time domain and calculated by below Equation:
Δ=(0.924x7)+(0.3x18)=11.868ms
δ(dB) = 20log(Δ)= 20 log(11.868/38.972)= -10.33 dB
δ is the duty cycle correction factor (dB)
Δ is the duty cycle (dimensionless)
Note 2: In cases where the pulse train exceeds 0.1 s, the measured field strength shall be determined during a 0.1 s interval

4.5. Original test data

Duty Cycle(100ms)



Duty Cycle



5. 20dB Bandwidth and 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

The bandwidth of the emission shall be no wider than 0.25% of the center frequency of devices operation above 70MHz and below 900MHz.

5.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 1kHz RBW and 3kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

5.4. Test Result

Frequency (MHz)	20 dB Bandwidth (kHz)	99% Bandwidth (kHz)	Limit (MHz): No wider than 0.25% of the center frequency	Conclusion
433.92	9.89	51.08	1.0848	PASS

5.5. Original test data

20 dB Bandwidth



99% Bandwidth



6 Stop transmitting time test

6.1. Block diagram of test setup



6.2. Limits

15.231(a), A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

6.3. Test Procedure

(1) The EUT's RF signal was coupled to spectrum analyzer by antenna connected to spectrum analyzer.

(2) Set the spectrum to zero span mode, and centered of EUT frequency.

(3) Measure the stop transmitting time after release EUT button.

6.4. Test Result

Frequency (MHz)	Burst Duration[s]	Limit [s]	Verdict
433.92	0.229	≤5	PASS

6.5. Original test data

Graphs



7 Radiated emission

7.1. Block diagram of test setup

In 3m Anechoic Chamber Test Setup Diagram for 9kHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

7.2. Limit

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.G
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

[1]Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

[2]Above 38.6

(2) FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

(3) FCC 15.231 section (b) limit

Fundamental Frequency (MHz)	Field Strength of Fundamental	Field strength of spurious emission
433.92	AV:80.83dBuV/m @3m PK:100.83dBuV/m @3m	AV:60.83dBuV/m @3m PK:80.83dBuV/m @3m

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$Limit_{3m}(dBuV/m) = Limit_{30m}(dBuV/m) + 40Log(30m/3m)$$

(4) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits.

7.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for blow 1G and 150 cm above the ground plane inside a semi-anechoic chamber for above 1G.

(2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9kHz-30MHz	Active Loop antenna	3m
30MHz-1GHz	Trilog Broadband Antenna	3m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9kHz to 5GHz (tenth harmonic of fundamental frequency):

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

(5) The emissions from 9kHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz, for emissions from 9kHz-90kHz,110kHz-490kHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9kHz to 1GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9kHz-150kHz	200Hz
150kHz-30MHz	9kHz
30MHz-1GHz	120kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RMS detector RBW 1MHz VBW 3MHz for Average measure(according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure).

7.4. Test result

PASS. (See below detailed test result)
All the emissions except fundamental emission from 9 kHz to 25 GHz were comply with 15.209 limits.
Note1: According exploratory test no any obvious emission were detected from 9kHz to 30MHz.

Note2: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Date:	2023-06-05	**Tested By**:	Bairong
EUT:	RF remote	**Model Number**:	MYH-R
Test Mode:	TX Mode	**Power Supply**:	Battery
Condition:	Temp:24.0°C;Humi:62.3%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2023 report data\Q23052906-2E MYH-R\FCC BELOW 1G\20230605-134431_H		
Memo:	433.92MHz		



Final Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable Loss [dB]**	**AMP [dB]**	**Result [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	44.68	33.1	12.97	4.66	-32.28	18.45	40.00	21.55	QP	Horizontal
2	69.78	29.83	8.59	4.79	-32.27	10.94	40.00	29.06	QP	Horizontal
3	100.06	25.42	10.91	5.07	-32.24	9.16	43.50	34.34	QP	Horizontal
4	379.72	27.92	15.00	6.59	-32.35	17.16	46.00	28.84	QP	Horizontal
5	542.20	29.62	17.64	7.10	-32.61	21.75	46.00	24.25	QP	Horizontal
6	867.94	47.52	22.16	8.22	-32.41	45.49	80.83	35.34	PK	Horizontal
7	867.94	/	/	/	/	35.16	60.83	25.67	AV	Horizontal

Note:
1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.
4. AV Result = PK Result + Duty cycle factor.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2023-06-05	**Tested By**:	Bairong
EUT:	RF remote	**Model Number**:	MYH-R
Test Mode:	TX Mode	**Power Supply**:	Battery
Condition:	Temp:24.0°C;Humi:62.3%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2023 report data\Q23052906-2E MYH-R\FCC BELOW 1G\20230605-134519_V		
Memo:	433.92MHz		



Final Data List										
NO.	**Freq. [MHz]**	**Reading [dBµV/m]**	**Antenna Factor [dB]**	**Cable Loss [dB]**	**AMP [dB]**	**Result [dBµV/m]**	**Limit [dBµV/m]**	**Margin [dB]**	**Detector**	**Polarity**
1	42.39	39.32	12.58	4.63	-32.28	24.25	40.00	15.75	QP	Vertical
2	44.65	40.63	12.96	4.66	-32.28	25.97	40.00	14.03	QP	Vertical
3	63.70	40.55	10.96	4.77	-32.27	24.01	40.00	15.99	QP	Vertical
4	69.44	41.33	8.72	4.79	-32.27	22.57	40.00	17.43	QP	Vertical
5	542.20	34.06	17.64	7.10	-32.61	26.19	46.00	19.81	QP	Vertical
6	867.94	53.34	22.16	8.22	-32.41	51.31	80.83	29.52	PK	Vertical
7	867.94	/	/	/	/	40.98	60.83	19.85	AV	Vertical

Note:
1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.
4. AV Result = PK Result + Duty cycle factor.

Field Strength Of The Fundamental Signal

Frequency (MHz)	PK Level (dBuV/m)	PK Limit Line (dBuV/m)	Over Limit (dB)	Polarization
433.92	70.35	100.83	-30.48	Horizontal
433.92	76.34	100.83	-24.49	Vertical

Frequency (MHz)	AV Level (dBuV/m)	AV Limit Line (dBuV/m)	Over Limit (dB)	Polarization
433.92	60.02	80.83	-20.81	Horizontal
433.92	66.01	80.83	-14.82	Vertical
Note: AV Level= PK Level+ Duty factor				

Radiated Emission test (above 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Date:	2023-06-05	**Tested By**:	Bairong
EUT:	RGB RF remote control	**Model Number**:	MYH-R
Test Mode:	TX Mode	**Power Supply**:	Battery
Condition:	Temp:24.0°C;Humi:62.3%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2023 report data\Q23052906-2E MYH-R\FCC ABOVE 1G\3		
Memo:	433.92MHz		

Test Graph



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	1301.53	64.36	2.86	25.60	-38.65	54.17	74.00	19.83	PK	Horizontal
2	2169.51	61.54	3.70	27.20	-39.89	52.55	74.00	21.45	PK	Horizontal
3	2603.57	68.98	4.03	28.11	-40.36	60.76	74.00	13.24	PK	Horizontal
4	3037.27	56.85	4.36	29.45	-40.82	49.84	74.00	24.16	PK	Horizontal
5	3470.96	59.80	4.66	29.50	-41.08	52.88	74.00	21.12	PK	Horizontal
6	4339.08	53.26	5.20	31.38	-41.30	48.54	74.00	25.46	PK	Horizontal

Final Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Cable loss[dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit[dBµV/m]	Margin[dB]	Detector	Polarity
1	1301.53	54.03	2.86	25.60	-38.65	43.84	54.00	10.16	AV	Horizontal

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:	2023-06-05	**Tested By**:	Bairong
EUT:	RGB RF remote control	**Model Number**:	MYH-R
Test Mode:	TX Mode	**Power Supply**:	Battery
Condition:	Temp:24.0°C;Humi:62.3%	**Test Site**:	DDT 3# Chamber
File Path:	d:\ts\2023 report data\Q23052906-2E MYH-R\FCC ABOVE 1G\4		
Memo:	433.92MHz		

Test Graph



Suspected Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Cable loss [dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	1301.53	68.09	2.86	25.60	-38.65	57.90	74.00	16.10	PK	Vertical
2	1735.45	51.03	3.30	25.40	-39.30	40.43	74.00	33.57	PK	Vertical
3	2169.51	63.83	3.70	27.20	-39.89	54.84	74.00	19.16	PK	Vertical
4	2604.04	60.62	4.03	28.11	-40.36	52.40	74.00	21.60	PK	Vertical
5	3470.96	60.69	4.66	29.50	-41.08	53.77	74.00	20.23	PK	Vertical
6	4339.08	58.41	5.20	31.38	-41.30	53.69	74.00	20.31	PK	Vertical

Final Data List										
NO.	Freq. [MHz]	Reading [dBµV/m]	Cable loss[dB]	Antenna Factor [dB]	AMP [dB]	Level [dBµV/m]	Limit[dBµV/m]	Margin[dB]	Detector	Polarity
1	1301.53	57.76	2.86	25.60	-38.65	47.57	54.00	6.43	AV	Vertical

Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

8 Power Line Conducted Emission

8.1. Block diagram of test setup



8.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

8.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 8.1 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

8.4. Test Result

Not Applicable

Conducted limits are not required for devices which only employ battery power for operation according to 15.207(C)

9 Antenna Requirements

For intentional device, according to FCC 47 CFR Section 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.1. Result

The antenna used for this product is PCB antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is -7.76 dBi.