

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Client Information

Client Information

Applicant: Wuhu Youfan E-Commerce Co.,Ltd.
Address of applicant: No. 369 industrial Road, Anhui Xinwu Economic Development Zone (In Fulong E-commerce Industrial Park), Wuhu County

Manufacturer: Wuhu Youfan E-Commerce Co.,Ltd.
Address of manufacturer: No. 369 industrial Road, Anhui Xinwu Economic Development Zone (In Fulong E-commerce Industrial Park), Wuhu County

General Description of EUT

Product Name: Bluetooth Battery Kill Switch
Trade Name: /
Model No.: BBKS-2023-250A
Adding Model(s): BBKS-2023-200A, BBKS-2023-120A
Rated Voltage: DC 12V
Power Adapter Model: /
Serial number: /
FCC ID: 2BBQ9-BBKS

Technical Characteristics of EUT	
Bluetooth Version:	V5.0 BLE
Frequency Range:	2402-2480MHz
RF Output Power:	-4.15dBm
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	PCB
Antenna Gain:	1.9dBi

1.2 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Maximum peak output power: -4.15(dBm)

Tune-Up output power: -4(dBm), 0.3981(mW)

Prediction distance: >20(cm)

Prediction frequency: 2440 (MHz)

Antenna gain: 1.9 (dBi)

Directional gain: 1.48 (numeric)

The worst case is power density at prediction frequency at 20cm: 0.00012(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

$0.00012(\text{mw}/\text{cm}^2) < 1 (\text{mw}/\text{cm}^2)$

So the transmitter complies with the RF exposure requirements and the SAR is not required.