RADIO TEST REPORT
FCC ID: 2BBT5-L9X1

Product: MACHENIKE

Trade Mark: MACHENIKE

Model No.: L9 X1

Family Model: N/A

Report No.: S25041006106002

Issue Date: May 10, 2025

Prepared for

Qingdao Machenike Technology Co., Ltd.

Room 1005, Building 1, No. 169 Binhai Road, Jimo District, Qingdao City, Shandong Province, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China

Tel. 0755-23200050 Website: http://www.ntek.org.cn

TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION 3

2 SUMMARY OF TEST RESULTS 4

3 FACILITIES AND ACCREDITATIONS 5

3.1 FACILITIES 5
3.2 LABORATORY ACCREDITATIONS AND LISTINGS 5
3.3 MEASUREMENT UNCERTAINTY 5

4 GENERAL DESCRIPTION OF EUT 6

5 DESCRIPTION OF TEST MODES 8

6 SETUP OF EQUIPMENT UNDER TEST 9

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM 9
6.2 SUPPORT EQUIPMENT 10
6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS 11

7 TEST REQUIREMENTS 13

7.1 CONDUCTED EMISSIONS TEST 13
7.2 RADIATED SPURIOUS EMISSION 16
7.3 6DB BANDWIDTH 25
7.4 DUTY CYCLE 26
7.5 PEAK OUTPUT POWER 28
7.6 POWER SPECTRAL DENSITY 29
7.7 CONDUCTED BAND EDGE MEASUREMENT 31
7.8 SPURIOUS RF CONDUCTED EMISSIONS 32
7.9 ANTENNA APPLICATION 33

8 TEST RESULTS 34

8.1 1M 34
8.2 2M 56

1 TEST RESULT CERTIFICATION

Applicant's name .....:	Qingdao Machenike Technology Co., Ltd.
Address .....:	Room 1005, Building 1, No. 169 Binhai Road, Jimo District, Qingdao City, Shandong Province, China
Manufacturer's Name .....:	Qingdao Machenike Technology Co., Ltd.
Address .....:	Room 1005, Building 1, No. 169 Binhai Road, Jimo District, Qingdao City, Shandong Province, China
Product description	
Product name .....:	MACHENIKE
Model and/or type reference .....:	L9 X1
Family Model .....:	N/A
TestSampleNumber……..:	S250410061006
Date (s) of performance of tests....	Apr. 11, 2025 ~ May 10, 2025

Measurement Procedure Used:

APPLICABLE STANDARDS	
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02	Complied

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.
The test results of this report relate only to the tested sample identified in this report.

Prepared By:	Reviewed By:	Approved By:
Kieron Luo	Aaron Cheng	Alex Li
(Project Engineer)	(Supervisor)	(Manager)

2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	**Test Item**	**Verdict**	**Remark**
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.247 (d)	Band Edge Emission	PASS	
15.247 (d)	Spurious RF Conducted Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:
1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at
No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab.	:	The Certificate Registration Number is L5516.
IC-Registration		The Certificate Registration Number is 9270A. CAB identifier:CN0074
FCC- Accredited		Test Firm Registration Number: 463705. Designation Number: CN1184
A2LA-Lab.		The Certificate Registration Number is 4298.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).
Name of Firm	:	Shenzhen NTEK Testing Technology Co., Ltd.
Site Location	:	No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±2.80dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(30MHz~1GHz)	±2.64dB
5	All emissions, radiated(1GHz~6GHz)	±2.40dB
6	All emissions, radiated(＞6GHz)	±2.52dB
7	Temperature	±0.5°C
8	Humidity	±2%
9	All emissions, radiated(9KHz~30MHz)	±6dB
10	Occupied bandwidth	±3.7dB

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	MACHENIKE
Trade Mark	MACHENIKE
FCC ID	2BBT5-L9X1
Model No.	L9 X1
Family Model	N/A
Model Difference	N/A
Operating Frequency	2402~2480 MHz
Modulation	GFSK
Number of Channels	16Channels
Antenna Type	PCB Antenna
Antenna Gain	-1.66 dBi
Power supply	DC 3.7V from battery or DC 5V from Type-C port
Battery	DC 3.7V, 500mAh, 1.85Wh
Adapter	N/A
Hardware version:	N/A
Firmware version:	N/A
Software version:	N/A

Note 1: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Note 2: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

Revision History

Report No.	Version	Description	Issued Date
S25041006106002	Rev.01	Initial issue of report	May 10, 2025

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency (MHz
1	2402
2	2407
3	2414
4	2419
5	2422
6	2426
7	2436
8	2439
9	2441
10	2445
11	2453
12	2459
13	2463
14	2466
15	2473
16	2480

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Test Cases	
Test Item	Data Rate/ Modulation
AC Conducted Emission	Mode 1: normal link mode
Radiated Test Cases	Mode 1: normal link mode
	Mode 2: GFSK Tx Ch1_2402MHz_1Mbps/2Mbps
	Mode 3: GFSK Tx Ch9_2441MHz_1Mbps/2Mbps
	Mode 4: GFSK Tx Ch16_2480MHz_1Mbps/2Mbps
Conducted Test Cases	Mode 2: GFSK Tx Ch1_2402MHz_1Mbps/2Mbps
	Mode 3: GFSK Tx Ch9_2441MHz_1Mbps/2Mbps
	Mode 4: GFSK Tx Ch16_2480MHz_1Mbps/2Mbps

Note:
1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode(duty cycle =100% during the test)
2. AC power line Conducted Emission was tested under maximum output power.
3. EUT is set to continuous transmission mode. Duty cycle greater than 98%.

6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM

For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
AE-1	Adapter	N/A	N/A	N/A	Peripherals
AE-2	Notebook	N/A	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	YES	YES	1.6 m
C-2	USB Cable	NO	YES	0.8 m
C-3	RF Cable	YES	NO	0.1m

Notes:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.
(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2024.04.26 2025.04.24	2025.04.25 2026.04.23	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024.04.25 2025.04.17	2025.04.24 2026.04.16	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2024.04.25 2025.04.17	2025.04.24 2026.04.16	1 year
4	Test Receiver	R&S	ESPI7	101318	2024.04.26 2025.04.17	2025.04.25 2026.04.16	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2024.05.12	2025.05.11	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
9	Amplifier	EMC	EMC051835SE	980246	2024.04.25 2025.04.17	2025.04.24 2026.04.16	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519 B	055	2024.05.17	2027.05.16	3 year
11	Power Meter	DARE	RPR3006W	15I00041SNO84	2024.04.25 2025.04.17	2025.04.24 2026.04.16	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2023.05.06	2026.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2023.05.06	2026.05.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2022.06.17	2025.06.16	3 year
15	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:
We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2024.04.26 2025.04.17	2025.04.25 2026.04.16	1 year
2	LISN	R&S	ENV216	101313	2024.04.25 2025.04.16	2025.04.24 2026.04.15	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2024.04.25 2025.04.16	2025.04.24 2026.04.15	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC Part 15.207(a)

7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration



7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.6 Test Results

EUT:	MACHENIKE	Model Name :	L9 X1
Temperature:	26.0℃	Relative Humidity:	45.7%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 5V powered by Notebook AC 120V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	45.27	10.02	55.29	65.57	-10.28	QP
0.1580	30.90	10.02	40.92	55.57	-14.65	AVG
0.1900	41.08	10.07	51.15	64.04	-12.89	QP
0.1900	25.69	10.07	35.76	54.04	-18.28	AVG
0.4820	28.79	10.64	39.43	56.30	-16.87	QP
0.4820	13.41	10.64	24.05	46.30	-22.25	AVG
2.2940	24.61	9.83	34.44	56.00	-21.56	QP
2.2940	14.00	9.83	23.83	46.00	-22.17	AVG
6.8940	27.43	10.38	37.81	60.00	-22.19	QP
6.8940	16.00	10.38	26.38	50.00	-23.62	AVG
16.0740	27.34	12.04	39.38	60.00	-20.62	QP
16.0740	18.69	12.04	30.73	50.00	-19.27	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

EUT：	MACHENIKE	Model Name ：	L9 X1
Temperature：	26.0℃	Relative Humidity：	45.7%
Pressure：	1010hPa	Phase :	N
Test Voltage ：	DC 5V powered by Notebook AC 120V/60Hz	Test Mode：	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1685	45.76	9.47	55.23	65.03	-9.80	QP
0.1685	27.37	9.47	36.84	55.03	-18.19	AVG
0.6140	27.56	10.20	37.76	56.00	-18.24	QP
0.6140	15.53	10.20	25.73	46.00	-20.27	AVG
3.0380	25.36	9.14	34.50	56.00	-21.50	QP
3.0380	14.94	9.14	24.08	46.00	-21.92	AVG
6.7580	24.48	9.56	34.04	60.00	-25.96	QP
6.7580	14.74	9.56	24.30	50.00	-25.70	AVG
18.5660	23.99	11.69	35.68	60.00	-24.32	QP
18.5660	13.30	11.69	24.99	50.00	-25.01	AVG
27.5100	23.21	12.72	35.93	60.00	-24.07	QP
27.5100	11.81	12.72	24.53	50.00	-25.47	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. For Frequency 9kHz~30MHz: Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.
For Frequency above 30MHz: Distance extrapolation factor =20log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.

7.2.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration

(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.
This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.
Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
g. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1 MHz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	MACHENIKE	Model No.:	L9 X1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3/ Mode4	Test By:	Kieron Luo

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

■ Spurious Emission below 1GHz (30MHz to 1GHz)
All the modulation modes have been tested, and the worst result was report as below:

EUT：	MACHENIKE	Model Name ：	L9 X1
Temperature：	24.1℃	Relative Humidity：	52%
Pressure：	1010hPa	Test Mode：	Mode 2 2Mbps
Test Voltage ：	DC 3.7V		

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
V	55.8050	2.00	19.71	21.71	40.00	-18.29	QP
V	125.4460	12.22	15.59	27.81	43.50	-15.69	QP
V	243.3770	16.45	18.98	35.43	46.00	-10.57	QP
V	377.2590	5.75	22.11	27.86	46.00	-18.14	QP
V	477.1690	9.15	24.10	33.25	46.00	-12.75	QP
V	948.7610	5.97	30.90	36.87	46.00	-9.13	QP

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
H	117.7730	6.09	17.01	23.10	43.50	-20.40	QP
H	227.6910	13.32	18.79	32.11	46.00	-13.89	QP
H	246.8150	19.88	18.96	38.84	46.00	-7.16	QP
H	374.6230	7.80	22.17	29.97	46.00	-16.03	QP
H	483.9090	6.80	24.10	30.90	46.00	-15.10	QP
H	948.7610	3.15	30.90	34.05	46.00	-11.95	QP

Remark:
Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	MACHENIKE	Model No.:	L9 X1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Kieron Luo

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)(GFSK)--Above 1G									
4804	53.84	5.21	35.59	44.30	50.34	74.00	-23.66	Pk	Vertical
4804	42.58	5.21	35.59	44.30	39.08	54.00	-14.92	AV	Vertical
7206	46.37	6.48	36.27	44.60	44.52	74.00	-29.48	Pk	Vertical
7206	34.90	6.48	36.27	44.60	33.05	54.00	-20.95	AV	Vertical
4804	53.33	5.21	35.55	44.30	49.79	74.00	-24.21	Pk	Horizontal
4804	42.11	5.21	35.55	44.30	38.57	54.00	-15.43	AV	Horizontal
7206	44.95	6.48	36.27	44.52	43.18	74.00	-30.82	Pk	Horizontal
7206	34.00	6.48	36.27	44.52	32.23	54.00	-21.77	AV	Horizontal
Mid Channel (2441 MHz)(GFSK)--Above 1G									
4882	55.29	5.21	35.66	44.20	51.96	74.00	-22.04	Pk	Vertical
4882	44.40	5.21	35.66	44.20	41.07	54.00	-12.93	AV	Vertical
7323	46.29	7.10	36.50	44.43	45.46	74.00	-28.54	Pk	Vertical
7323	32.93	7.10	36.50	44.43	32.10	54.00	-21.90	AV	Vertical
4882	53.75	5.21	35.66	44.20	50.42	74.00	-23.58	Pk	Horizontal
4882	41.82	5.21	35.66	44.20	38.49	54.00	-15.51	AV	Horizontal
7323	44.85	7.10	36.50	44.43	44.02	74.00	-29.98	Pk	Horizontal
7323	32.81	7.10	36.50	44.43	31.98	54.00	-22.02	AV	Horizontal
High Channel (2480 MHz) (GFSK)--Above 1G									
4960	53.65	5.21	35.52	44.21	50.17	74.00	-23.83	Pk	Vertical
4960	43.33	5.21	35.52	44.21	39.85	54.00	-14.15	AV	Vertical
7440	47.19	7.10	36.53	44.60	46.22	74.00	-27.78	Pk	Vertical
7440	34.39	7.10	36.53	44.60	33.42	54.00	-20.58	AV	Vertical
4960	57.28	5.21	35.52	44.21	53.80	74.00	-20.20	Pk	Horizontal
4960	45.92	5.21	35.52	44.21	42.44	54.00	-11.56	AV	Horizontal
7440	47.80	7.10	36.53	44.60	46.83	74.00	-27.17	Pk	Horizontal
7440	36.15	7.10	36.53	44.60	35.18	54.00	-18.82	AV	Horizontal

Note:

(1) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
(2)All other emissions more than 20dB below the limit.
(3)Only the worst data is recorded in the report, the data rates (1Mbps for GFSK modulation) test result is the worst

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

EUT:	MACHENIKE	Model No.:	L9 X1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Kieron Luo

Frequency (MHz)	Meter Reading (dBμV)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
2Mbps(GFSK)									
2310.00	51.69	2.97	27.80	43.80	38.66	74	-35.34	Pk	Horizontal
2310.00	41.14	2.97	27.80	43.80	28.11	54	-25.89	AV	Horizontal
2310.00	50.48	2.97	27.80	43.80	37.45	74	-36.55	Pk	Vertical
2310.00	41.14	2.97	27.80	43.80	28.11	54	-25.89	AV	Vertical
2390.00	53.83	3.14	27.21	43.80	40.38	74	-33.62	Pk	Vertical
2390.00	42.80	3.14	27.21	43.80	29.35	54	-24.65	AV	Vertical
2390.00	54.81	3.14	27.21	43.80	41.36	74	-32.64	Pk	Horizontal
2390.00	43.70	3.14	27.21	43.80	30.25	54	-23.75	AV	Horizontal
2483.50	55.43	3.58	27.70	44.00	42.71	74	-31.29	Pk	Vertical
2483.50	43.31	3.58	27.70	44.00	30.59	54	-23.41	AV	Vertical
2483.50	54.62	3.58	27.70	44.00	41.90	74	-32.10	Pk	Horizontal
2483.50	43.47	3.58	27.70	44.00	30.75	54	-23.25	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.
(2)Only the worst data is recorded in the report, the data rates (1Mbps for GFSK modulation) test result is the worst

■ Spurious Emission in Restricted Band 3260MHz-18000MHz

EUT:	MACHENIKE	Model No.:	L9 X1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Kieron Luo

Frequency	Reading Level	Cable Loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3260	52.81	4.04	29.57	44.70	41.72	74	-32.28	Pk	Vertical
3260	40.57	4.04	29.57	44.70	29.48	54	-24.52	AV	Vertical
3260	53.48	4.04	29.57	44.70	42.39	74	-31.61	Pk	Horizontal
3260	40.51	4.04	29.57	44.70	29.42	54	-24.58	AV	Horizontal
3332	53.38	4.26	29.87	44.40	43.11	74	-30.89	Pk	Vertical
3332	41.14	4.26	29.87	44.40	30.87	54	-23.13	AV	Vertical
3332	53.25	4.26	29.87	44.40	42.98	74	-31.02	Pk	Horizontal
3332	40.51	4.26	29.87	44.40	30.24	54	-23.76	AV	Horizontal
17797	42.23	10.99	43.95	43.50	53.67	74	-20.33	Pk	Vertical
17797	30.99	10.99	43.95	43.50	42.43	54	-11.57	AV	Vertical
17788	42.02	11.81	43.69	44.60	52.92	74	-21.08	Pk	Horizontal
17788	31.00	11.81	43.69	44.60	41.90	54	-12.10	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.
(2)Only the worst data is recorded in the report, the data rates (1Mbps for GFSK modulation) test result is the worst

7.3 6DB BANDWIDTH

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.2.

7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows Subclause 11.8 of ANSI C63.10
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:

a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) ≥ 3*RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3.6 Test Results

EUT:	MACHENIKE	Model No.:	L9 X1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Kieron Luo

Test data reference attachment.

7.4 DUTY CYCLE

7.4.1 Applicable Standard

According to KDB 558074 D01 15.247 Meas Guidance v05r02s Section 6.

7.4.2 Conformance Limit

No limit requirement.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set VBW ≥ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested accroding to the zero-span measurement method, 6.0)b) in KDB 558074

The largest availble value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if T ≤ 6.25 microseconds. (50/6.25 = 8)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are > 50/T.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = Zero Span
RBW = 8MHz(the largest available value)
VBW = 8MHz (≥ RBW)
Number of points in Sweep >100
Detector function = peak
Trace = Clear write
Measure T_{total} and T_{on}
Calculate Duty Cycle = T_{on} / T_{total}

7.4.6 Test Results

EUT:	MACHENIKE	Model No.:	L9 X1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Kieron Luo

Test data reference attachment.

7.5 PEAK OUTPUT POWER

7.5.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.3.1.

7.5.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

The testing follows Subclause 11.9.1.1 of ANSI C63.10
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Set the RBW ≧DTS bandwidth.
Set VBW =3*RBW.
Set the span ≧3*RBW
Set Sweep time = auto couple.
Set Detector = peak.
Set Trace mode = max hold.
Allow trace to fully stabilize.
Use peak marker function to determine the peak amplitude level.

7.5.6 Test Results

EUT:	MACHENIKE	Model No.:	L9 X1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Kieron Luo

Test data reference attachment.

7.6 POWER SPECTRAL DENSITY

7.6.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.4.

7.6.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows Measurement Procedure Subclause 11.10.2 of ANSI C63.10
This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
a) Set analyzer center frequency to DTS channel center frequency.
b) Set the span to 1.5*DTS bandwidth.
c) Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
d) Set the VBW ≥ 3 RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.
j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.6.6 Test Results

EUT:	MACHENIKE	Model No.:	L9 X1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Kieron Luo

Test data reference attachment.

7.7 CONDUCTED BAND EDGE MEASUREMENT

7.7.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.

7.7.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows FCC KDB 558074 D01 15.247 Meas Guidance v05r02 Section 8.7.
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
Repeat above procedures until all measured frequencies were complete.

7.7.6 Test Results

EUT:	MACHENIKE	Model No.:	L9 X1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode4	Test By:	Kieron Luo

Test data reference attachment.

7.8 SPURIOUS RF CONDUCTED EMISSIONS

7.8.1 Conformance Limit

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

7.8.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.3 Test Setup

Please refer to Section 6.1 of this test report.

7.8.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength , and measure frequency range from 30MHz to 26.5GHz.

7.8.5 Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

Test data reference attachment.

7.9 ANTENNA APPLICATION

7.9.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.9.2 Result

The EUT antenna is permanent attached PCB Antenna (Gain: -1.66 dBi). It comply with the standard requirement.

8 TEST RESULTS

8.1 1M

8.1.1 Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	GFSK 1M	2402	Ant1	38.55	4.14	4.55
NVNT	GFSK 1M	2441	Ant1	38.64	4.13	4.35
NVNT	GFSK 1M	2480	Ant1	38.56	4.14	4.55

Test Graphs

Duty Cycle NVNT GFSK 1M 2402MHz Ant1



Duty Cycle NVNT GFSK 1M 2441MHz Ant1



Duty Cycle NVNT GFSK 1M 2480MHz Ant1



8.1.2 Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	GFSK 1M	2402	Ant1	4.84	30	Pass
NVNT	GFSK 1M	2441	Ant1	4.81	30	Pass
NVNT	GFSK 1M	2480	Ant1	4.57	30	Pass

Test Graphs

Power NVNT GFSK 1M 2402MHz Ant1



Power NVNT GFSK 1M 2441MHz Ant1



Power NVNT GFSK 1M 2480MHz Ant1



8.1.3 **-6dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	GFSK 1M	2402	Ant1	0.717	0.5	Pass
NVNT	GFSK 1M	2441	Ant1	0.665	0.5	Pass
NVNT	GFSK 1M	2480	Ant1	0.712	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT GFSK 1M 2402MHz Ant1



-6dB Bandwidth NVNT GFSK 1M 2441MHz Ant1



-6dB Bandwidth NVNT GFSK 1M 2480MHz Ant1



8.1.4 Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	GFSK 1M	2402	Ant1	1.053
NVNT	GFSK 1M	2441	Ant1	1.052
NVNT	GFSK 1M	2480	Ant1	1.054

Test Graphs

OBW NVNT GFSK 1M 2402MHz Ant1



OBW NVNT GFSK 1M 2441MHz Ant1



OBW NVNT GFSK 1M 2480MHz Ant1



8.1.5 Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm)	Limit (dBm)	Verdict
NVNT	GFSK 1M	2402	Ant1	-9.62	8	Pass
NVNT	GFSK 1M	2441	Ant1	-9.82	8	Pass
NVNT	GFSK 1M	2480	Ant1	-9.63	8	Pass

Test Graphs

PSD NVNT GFSK 1M 2402MHz Ant1



PSD NVNT GFSK 1M 2441MHz Ant1



PSD NVNT GFSK 1M 2480MHz Ant1



8.1.6 Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	GFSK 1M	2402	Ant1	-63.32	-20	Pass
NVNT	GFSK 1M	2480	Ant1	-58.25	-20	Pass

Test Graphs

Band Edge NVNT GFSK 1M 2402MHz Ant1 Ref



Band Edge NVNT GFSK 1M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40195 GHz	3.38 dBm		
M2		1	2.4 GHz	-45.71 dBm		
M3		1	2.39 GHz	-63.62 dBm		
M4		1	2.349 GHz	-59.71 dBm		

Band Edge NVNT GFSK 1M 2480MHz Ant1 Ref

Band Edge NVNT GFSK 1M 2480MHz Ant1 Emission



8.1.7 Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	GFSK 1M	2402	Ant1	-53.11	-20	Pass
NVNT	GFSK 1M	2441	Ant1	-53.16	-20	Pass
NVNT	GFSK 1M	2480	Ant1	-53.57	-20	Pass

Test Graphs

Tx. Spurious NVNT GFSK 1M 2402MHz Ant1 Ref



Tx. Spurious NVNT GFSK 1M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.397 GHz	3.95 dBm		
M2		1	4.7946 GHz	-49.46 dBm		
M3		1	4.7946 GHz	-49.46 dBm		
M4		1	7.3357 GHz	-53.05 dBm		
M5		1	9.5327 GHz	-54.69 dBm		

Tx. Spurious NVNT GFSK 1M 2441MHz Ant1 Ref



Tx. Spurious NVNT GFSK 1M 2441MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.44001 GHz	3.18 dBm		
M2		1	15.568772 GHz	-50.07 dBm		
M3		1	4.879304 GHz	-51.46 dBm		
M4		1	7.292486 GHz	-52.74 dBm		
M5		1	9.920074 GHz	-53.74 dBm		

Tx. Spurious NVNT GFSK 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT GFSK 1M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47972 GHz	2.98 dBm		
M2		1	6.996904 GHz	-50.55 dBm		
M3		1	4.959596 GHz	-53.10 dBm		
M4		1	7.253663 GHz	-54.78 dBm		
M5		1	9.75596 GHz	-54.67 dBm		

8.2 2M

8.2.1 Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	GFSK 2M	2402	Ant1	21.73	6.63	8.33
NVNT	GFSK 2M	2441	Ant1	21.69	6.64	8.33
NVNT	GFSK 2M	2480	Ant1	21.77	6.62	8.33

Test Graphs

Duty Cycle NVNT GFSK 2M 2402MHz Ant1



Duty Cycle NVNT GFSK 2M 2441MHz Ant1



Duty Cycle NVNT GFSK 2M 2480MHz Ant1



8.2.2 Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	GFSK 2M	2402	Ant1	4.91	30	Pass
NVNT	GFSK 2M	2441	Ant1	4.77	30	Pass
NVNT	GFSK 2M	2480	Ant1	4.62	30	Pass

Test Graphs

Power NVNT GFSK 2M 2402MHz Ant1



Power NVNT GFSK 2M 2441MHz Ant1



Power NVNT GFSK 2M 2480MHz Ant1



8.2.3 **-6dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	GFSK 2M	2402	Ant1	1.143	0.5	Pass
NVNT	GFSK 2M	2441	Ant1	1.104	0.5	Pass
NVNT	GFSK 2M	2480	Ant1	1.218	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT GFSK 2M 2402MHz Ant1



-6dB Bandwidth NVNT GFSK 2M 2441MHz Ant1



-6dB Bandwidth NVNT GFSK 2M 2480MHz Ant1



8.2.4 Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	GFSK 2M	2402	Ant1	2.049
NVNT	GFSK 2M	2441	Ant1	2.045
NVNT	GFSK 2M	2480	Ant1	2.053

Test Graphs

OBW NVNT GFSK 2M 2402MHz Ant1



OBW NVNT GFSK 2M 2441MHz Ant1



OBW NVNT GFSK 2M 2480MHz Ant1



8.2.5 Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm)	Limit (dBm)	Verdict
NVNT	GFSK 2M	2402	Ant1	-13.06	8	Pass
NVNT	GFSK 2M	2441	Ant1	-13.58	8	Pass
NVNT	GFSK 2M	2480	Ant1	-14.02	8	Pass

Test Graphs

PSD NVNT GFSK 2M 2402MHz Ant1



PSD NVNT GFSK 2M 2441MHz Ant1



PSD NVNT GFSK 2M 2480MHz Ant1



8.2.6 Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	GFSK 2M	2402	Ant1	-63.03	-20	Pass
NVNT	GFSK 2M	2480	Ant1	-55.89	-20	Pass

Test Graphs

Band Edge NVNT GFSK 2M 2402MHz Ant1 Ref

Band Edge NVNT GFSK 2M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40205 GHz	0.16 dBm		
M2		1	2.4 GHz	-37.04 dBm		
M3		1	2.39 GHz	-65.73 dBm		
M4		1	2.3451 GHz	-59.62 dBm		

Band Edge NVNT GFSK 2M 2480MHz Ant1 Ref

Band Edge NVNT GFSK 2M 2480MHz Ant1 Emission



8.2.7 Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	GFSK 2M	2402	Ant1	-54.16	-20	Pass
NVNT	GFSK 2M	2441	Ant1	-54.4	-20	Pass
NVNT	GFSK 2M	2480	Ant1	-52.15	-20	Pass

Test Graphs

Tx. Spurious NVNT GFSK 2M 2402MHz Ant1 Ref



Tx. Spurious NVNT GFSK 2M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.397 GHz	-0.55 dBm		
M2		1	15.9385 GHz	-50.56 dBm		
M3		1	4.7946 GHz	-52.47 dBm		
M4		1	7.3622 GHz	-53.71 dBm		
M5		1	9.4268 GHz	-54.56 dBm		

Tx. Spurious NVNT GFSK 2M 2441MHz Ant1 Ref



Tx. Spurious NVNT GFSK 2M 2441MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.45 GHz	3.60 dBm		
M2		1	14.9856 GHz	-50.89 dBm		
M3		1	5.0064 GHz	-54.94 dBm		
M4		1	7.3887 GHz	-54.28 dBm		
M5		1	9.718 GHz	-54.86 dBm		

Tx. Spurious NVNT GFSK 2M 2480MHz Ant1 Ref



Tx. Spurious NVNT GFSK 2M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.476 GHz	2.89 dBm		
M2		1	2.5976 GHz	-48.75 dBm		
M3		1	4.9534 GHz	-53.47 dBm		
M4		1	7.2828 GHz	-54.62 dBm		
M5		1	9.9298 GHz	-54.34 dBm		

END OF REPORT