

****FCC Variant Difference Cover Letter****

Date: 2025-11-25

To: FCC TCB (Telecommunication Certification Body)

From: Aurodi Corporation

Address: Suite 1100, 7887 E Belleview Ave, Denver, CO 80111, United States.

Contact: [Name, Email, Phone] George Zhang, george@v-mark.com, (877)529-1123

FCC ID: 2BBTA-VTS17W0X

Subject: Declaration of Differences Between Model Variants

We hereby declare that the following models are variants under the same

FCC ID: 2BBTA-VTS17W0X:

- Parent Model: VTS17W01

- Variant Models: VTS17W02, VTS17W03, VTS17W04, VTS17W05, VTS17W06, VTS17P01

****Differences Summary:****

1. VTS17W02 uses an External digital temperature probe, measurement range -40°C ~105°C.

2. VTS17W03 uses an PT1000 platinum resistance temperature probe, measurement range -200°C ~200°C.

3. VTS17W04 uses an Built-in temperature and humidity probe, measurement range -30°C ~70°C, 0~100%RH.

4. VTS17W05 uses an High precision External digital temperature probe, measurement range -40°C ~105°C.

5. VTS17W06 uses an High precision External temperature and humidity probe, measurement range -40°C ~105°C, 0~100%RH.

6. VTS17P01 Support multiple temperature/humidity probes, It includes the following types, and only one can be connected at a time:

Ordinary External Digital Temperature Probe;

PT1000 Platinum Resistance Temperature Probe;

High Precision External Digital Temperature Probe;

High Precision External Temperature and Humidity Probe;

****Compliance Statement:****

All variants comply with FCC Part 15C (for intentional radiators) and do not exceed the permitted RF exposure limits. No additional testing is required for these changes.

Sincerely,

Aurodi Corporation

