

MPE Evaluation

Applicant: Aurodi Corporation
FCC ID: 2BBTA-VTS17W0X
Contain FCC ID: 2AQ7V-KR840T01
Model: VTS17W01

MPE Evaluation

RF Exposure Compliance Requirement

Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06 and FCC 1.1310 Radio frequency radiation exposure limits for General Population/Uncontrolled Exposure.

Limit For Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	< 6
3.0-30	1824/f	4.89/f	*(900/f ²)	< 6
30-300	61.4	0.163	1.0	< 6
300-1500	/	/	f/300	< 6
1500-100,000	/	/	5	< 6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	< 30
1.34-30	824/f	2.19/f	*(180/f ²)	< 30
30-300	27.5	0.073	0.2	< 30
300-1500	/	/	f/1500	< 30
1500-100,000	/	/	1.0	< 30
Note: f = frequency in MHz. * = Plane-wave equivalent power density.				

EUT RF Exposure

$$P_d = PG / 4\pi R^2$$

P_d = power density in mW/cm^2

P = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.14$

R = distance between observation point and center of the radiator in cm

2405-2480GHz mode

According to FCC ID: 2AQ7V-KR840T01 report

The Max Output Power is 7.38 dBm in 2480 MHz;

Antenna gain: 1.06 dBi, gain of antenna in linear scale: 1.276

$R = 20\text{cm}$

$$P_d = PG / (4\pi R^2) = 0.001389 \text{ mW}/\text{cm}^2 < 1 (\text{limits}) \text{ mW}/\text{cm}^2$$

NFC mode

Maximum Electric field strength: 58.57 dBuV/m @ 13.56MHz

The Maximum EIRP = 56.27 dBuV/m - 95.2 = -38.93 dBm = 217.27nW = 0.000217mW < 1mW

Antenna gain: 0 dBi, gain of antenna in linear scale: 1

$R = 20\text{cm}$

$$P_d = PG / (4\pi R^2) = 0.0000000414 \text{ mW}/\text{cm}^2 < 1 (\text{limits}) \text{ mW}/\text{cm}^2$$

So the transmitter complies with the RF exposure requirements and the SAR is not required.

Simultaneous Transmission Calculation (Worst-case mode)

No.	Transmitter Combination	MPE Ratio	Limit	Result
1	905-925MHz Lora + NFC	0.001480414	≤ 1.0	Pass

Note: MPE Ratio = 0.001389 + 0.0000000414 = 0.001480414

--END--