

FCC Test Report

**Test Report
On Behalf of
SPINTSO AB
For**

**Spintso S2 Pro wireless charger
Model No.: S2 Pro, S2 Pro Lite, S2 Pro X, S3 Pro, G6**

FCC ID: 2BBUES2PRO

**Prepared For: SPINTSO AB
Ovre Slottsgatan 6, 753 10 Uppsala, Sweden**

**Prepared By: Shenzhen HUAKE Testing Technology Co., Ltd.
1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping,
Fuhai Street, Bao'an District, Shenzhen, Guangdong, China**

**Date of Test: Sep. 28, 2025 ~ Jan. 08, 2026
Date of Report: Jan. 08, 2026
Report Number: HK2509285464-1E**

Test Result Certification

Applicant's Name..... : SPINTSO AB

Address..... : Ovre Slottsgatan 6, 753 10 Uppsala, Sweden

Manufacturer's Name : Shenzhen Smart Care Technology Limited

Address..... : Workshop 2101, 2401, 2601, Anda Electronic Industrial Park,
Heping Community, Fuhai Sub-district, Bao'an District,
Shenzhen, China

Product Description

Trade Mark : Spintso

Product Name : Spintso S2 Pro wireless charger

Model and/or Type Reference : S2 Pro, S2 Pro Lite, S2 Pro X, S3 Pro, G6

Standards : FCC CFR 47 PART 18

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.


Date of Test..... :

Date (s) of Performance of Tests : Sep. 28, 2025 ~ Jan. 08, 2026

Date of Issue..... : Jan. 08, 2026

Test Result..... : Pass

Testing Engineer



Len Liao

Technical Manager



Sliver Wan

Authorized Signatory



Jason Zhou

Table of Contents

Page

1 . Summary	5
1.1 Test Procedures and Results	5
1.2 Information of the Test Laboratory	5
1.3 Measurement Uncertainty	5
2. General Information	6
2.1 General Description of EUT	6
2.2 Carrier Frequency of Channels	7
2.3 Operation of EUT during Testing	7
2.4 Description of Test Setup	8
2.5 Description of Support Units	9
2.6 Measurement Instruments List	10
3. AC Conducted Emission Test	11
3.1 Block Diagram of Test Setup	11
3.2 Conducted Power Line Emission Limit	11
3.3 Test Procedure	11
3.4 Test Result	12
4. Radiated Emissions	14
4.1 Block Diagram of Test Setup	14
4.2 Rules and Specifications	15
4.3 Test Procedure	15
4.4 Test Result	16
5. Antenna Requirement	19
6. Test Setup Photos of the EUT	20
7. Photos of the EUT	22

**** Issued history ****

Revision	Description	Issued Date	Remark
Revision 1.0	Initial Test Report Release	Jan. 08, 2026	Jason Zhou

1. Summary

1.1 Test Procedures and Results

Description of Test	Section Number	Result
AC Conducted Emissions Test	18.307	PASS
Radiated Emission Test	18.305	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

1.2 Information of the Test Laboratory

Shenzhen HUAKE Testing Technology Co., Ltd.

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

1.3 Measurement Uncertainty

Measurement Uncertainty

Conducted Emission Expanded Uncertainty	= 2.71dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	= 3.90dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	= 3.90dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	= 4.28dB, k=2

2. General Information

2.1 General Description of EUT

Equipment:	Spintso S2 Pro wireless charger
Model Name:	S2 Pro
Series Model(s):	S2 Pro Lite, S2 Pro X, S3 Pro, G6
Model Difference:	All model's the function, software and electric circuit are the same, only with product model named different. Test sample model: S2 Pro.
Trade Mark:	Spintso
FCC ID:	2BBUES2PRO
Antenna Type:	Coil Antenna
Test Frequency:	478KHz
Number of Channels:	1
Modulation Type:	ASK
Power Source:	Input: DC 5V From USB Wireless Output: 2W
Power Rating:	Input: DC 5V From USB Wireless Output: 2W

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2. Antenna gain values are provided by the customer.
3. The cable loss data is obtained from the supplier.
4. The test results in the report only apply to the tested sample.

2.2 Carrier Frequency of Channels


Operation Frequency each of channel	
Channel	Frequency
Middle CH	478KHz

2.3 Operation of EUT during Testing

Test Item	Test mode	Description
Radiated & AC Conducted Test Cases	Mode 1	AC/DC Adapter+ EUT + Watch (Battery Status: <1%)
	Mode 2	AC/DC Adapter+ EUT + Watch (Battery Status: <50%)
	Mode 3	AC/DC Adapter+ EUT + Watch (Battery Status: >95%)
Note: 1. All modes and configurations above have been tested, Only the result of the worst case was recorded in the report. 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode. 3. The watch is provided by the customer. 4. According to the manufacturer's design principle, the wireless charging power will reach its maximum when the client device's battery level is between 1% and 10%.		

2.4 Description of Test Setup

Operation of EUT during Testing:



The sample was placed (0.8m (30MHz~1GHz), 0.8m (9KHz~30MHz)) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. The worst case is X position.

2.5 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Trade Mark	Model/Type No.	Specification	Note
1	Spintso S2 Pro wireless charger	Spintso	S2 Pro	N/A	EUT
2	Watch	Spintso	S2 Pro	N/A	
3	Adapter	N/A	MDY-10-EH	Input: AC100-240V, 50/60Hz, 0.7A Output: DC5V/3A, 9V/3A, 12V/2.25A, 20V/1.35A	
4	Adapter	N/A	N/A	Input: AC100-240V, 50/60Hz, 0.75A Output: DC5V/2A, 9V/2A, 10V/2.25A MAX	

Note:


1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. Wireless load (Load 1) is a device containing rechargeable batteries or capacity loads, connected via charging control circuit that receives power from a source via a coupling antenna.

2.6 Measurement Instruments List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N.	R&S	ENV216	HKE-002	Feb. 19, 2025	1 Year
2.	L.I.S.N.	R&S	ENV216	HKE-059	Feb. 19, 2025	1 Year
3.	EMI Test Receiver	R&S	ESR	HKE-005	Feb. 19, 2025	1 Year
4.	Spectrum analyzer	Agilent	N9020A	HKE-048	Feb. 19, 2025	1 Year
5.	Spectrum analyzer	R&S	FSV3044	HKE-126	Feb. 19, 2025	1 Year
6.	Preamplifier	EMCI	EMC051845S	HKE-006	Feb. 19, 2025	1 Year
7.	Preamplifier	Schwarzbeck	BBV 9743	HKE-016	Feb. 19, 2025	1 Year
8.	Preamplifier	A.H. Systems	SAS-574	HKE-182	Feb. 19, 2025	1 Year
9.	6dB Attenuator	Pasternack	6dB	HKE-184	Feb. 19, 2025	1 Year
10.	EMI Test Receiver	Rohde & Schwarz	ESR-7	HKE-010	Feb. 19, 2025	1 Year
11.	Broadband Antenna	Schwarzbeck	VULB9168	HKE-167	Feb. 21, 2024	2 Year
12.	Loop Antenna	COM-POWER	AL-130R	HKE-014	Feb. 21, 2024	2 Year
13.	Horn Antenna	Schwarzbeck	9120D	HKE-013	Feb. 21, 2024	2 Year
14.	EMI Test Software	Tonscend	JS32-CE 2.5.0.6	HKE-081	/	/
15.	EMI Test Software	Tonscend	JS32-RE 5.0.0	HKE-082	/	/
16.	10dB Attenuator	Schwarzbeck	VTSD9561F	HKE-153	Feb. 19, 2025	1 Year

3. AC Conducted Emission Test

3.1 Block Diagram of Test Setup



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedance Stabilization Network
Test table height=0.8m

3.2 Conducted Power Line Emission Limit

According to FCC Part 18.307(b)

Frequency (MHz)	Maximum RF Line Voltage (dB μ V)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §18.307 Line Conducted Emission Limit is same as above table.

3.3 Test Procedure


1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.

3.4 Test Result

PASS

All the test modes completed for test. Only the worst result was reported as below:

Test Specification: Line



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.4740	51.34	19.84	56.44	5.10	31.50	PK	L
2	0.5685	41.25	19.79	56.00	14.75	21.46	PK	L
3	0.9465	49.84	19.74	56.00	6.16	30.10	PK	L
4	1.8960	41.01	20.11	56.00	14.99	20.90	PK	L
5	2.8455	38.33	20.25	56.00	17.67	18.08	PK	L
6	3.3180	35.93	20.30	56.00	20.07	15.63	PK	L

Final Data List

NO.	Freq. [MHz]	Correction factor[dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	QP Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	AV Reading [dBμV]	Type
1	0.4740	19.84	46.78	56.44	9.66	26.94	41.50	46.44	4.94	21.66	L
2	0.9465	19.74	45.38	56.00	10.62	25.64	41.91	46.00	4.09	22.17	L

Remark: Margin = Limit – Level


Correction factor = Cable loss + LISN insertion loss

Level=Test receiver reading + correction factor

The results shown in this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 15 days only. The document is issued by Shenzhen HUAKE Testing Technology Co., Ltd., this document cannot be reproduced except in full with our prior written permission.

Shenzhen HUAKE Testing Technology Co., Ltd. Tel.: +86-0755-2302 9901 E-mail: info@huak.com Web.: www.huak.com
Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1725	38.43	19.64	64.84	26.41	18.79	PK	N
2	0.4740	50.72	19.73	56.44	5.72	30.99	PK	N
3	0.5685	41.50	19.75	56.00	14.50	21.75	PK	N
4	0.9510	48.09	19.76	56.00	7.91	28.33	PK	N
5	1.9005	35.74	19.93	56.00	20.26	15.81	PK	N
6	2.8455	35.29	20.05	56.00	20.71	15.24	PK	N

Final Data List

NO.	Freq. [MHz]	Correction factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	QP Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	AV Reading [dBμV]	Type
1	0.4739	19.73	43.81	56.45	12.64	24.08	38.39	46.45	8.06	18.66	N
2	0.9480	19.76	42.75	56.00	13.25	22.99	37.77	46.00	8.23	18.01	N



Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor

4. Radiated Emissions

4.1 Block Diagram of Test Setup



4.2 Rules and Specifications

Except as provided elsewhere in this Subpart 18.305 (b), the field strength levels of emissions which lie outside the bands specified in §18.301, unless otherwise indicated, shall not exceed the following table:

Equipment	Operating frequency	RF Power generated by equipment (watts)	Field strength limit (uV/m)	Distance (meters)
(miscellaneous)				
	Any non-ISM frequency	Below 500 500 or more	15 15 × SQRT(power/500)	300 1300

Remark:

- (1) Emission level dBuV/m for 0.009~30MHz = 20log (15) + 40log (300/3) dBuV/m;
- (2) Calculated according FCC 18.305.
- (3) The smaller limit shall apply at the cross point between two frequency bands.
- (4) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.3 Test Procedure

Measurement distance 3m

For the measurement range up to 30MHz in the following plots the field strength result from 3m Distance measurements are extrapolated to 300m and 30m distance respectively, by 40dB/decade, Per antenna factor scaling.


Measurements below 1000MHz are performed with a peak detector and compared to average limits; Measurements with an average detector are not required.

4.4 Test Result

PASS

Note: All the test modes completed for test. Only the worst result was reported as below:

For 9KHz - 30MHz




Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]
1	0.0116	20.32	48.67	68.99	103.50	34.51
2	0.0174	20.32	45.61	65.93	103.50	37.57
3	0.4785	20.22	69.95	90.17	103.50	13.33
4	1.3745	20.49	26.18	46.67	103.50	56.83
5	4.0324	20.15	16.45	36.60	103.50	66.90
6	12.8127	20.05	10.81	30.86	103.50	72.64

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

For 30MHz-1GHz

Antenna polarity: Horizontal




Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	55.2452	-14.00	26.53	12.53	63.50	50.97	100	211	Horizontal
2	139.7197	-18.07	33.74	15.67	63.50	47.83	100	3	Horizontal
3	218.3684	-14.63	29.95	15.32	63.50	48.18	100	42	Horizontal
4	363.0430	-9.68	33.98	24.30	63.50	39.20	100	262	Horizontal
5	440.7207	-8.67	33.19	24.52	63.50	38.98	100	320	Horizontal
6	741.7217	-3.40	29.16	25.76	63.50	37.74	100	309	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical



Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	41.6517	-13.41	33.51	20.10	63.50	43.40	100	278	Vertical
2	64.9550	-15.33	36.94	21.61	63.50	41.89	100	122	Vertical
3	99.9099	-14.70	34.18	19.48	63.50	44.02	100	263	Vertical
4	130.0100	-17.24	34.63	17.39	63.50	46.11	100	289	Vertical
5	372.7528	-9.90	33.05	23.15	63.50	40.35	100	96	Vertical
6	721.3313	-4.21	28.46	24.25	63.50	39.25	100	322	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

5. Antenna Requirement


Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction



The antenna used in this product is a Coil Antenna, which permanently attached. It conforms to the standard requirements.

Antenna



6. Test Setup Photos of the EUT

Radiated Emission



AC Conducted Emission



7. Photos of the EUT

Reference to the report: ANNEX A of external photos and ANNEX B of internal photos.

-----End of test report-----

