

RF Exposure Evaluation according to KDB 447498 D01 v06

Report identification number: 1-5707/23-01-08-A_MPE_FCC

Certification numbers and labeling requirements	
FCC ID	2BBWS-418536


This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



cn=Alexander Hnatovskiy, o=cetecom
advanced GmbH, ou=HNA-230601,
email=alexander.hnatovskiy@cetecomadvan
ced.com, c=DE
2023.09.12 09:49:01 +02'00'

Alexander Hnatovskiy
Lab Manager
Radio Labs



cn=Marco Scigliano, o=cetecom
advanced GmbH, ou=SCI-230601,
email=Marco.Scigliano@cetecomadvanc
ed.com, c=DE
2023.09.12 09:27:54 +02'00'

Marco Scigliano
Testing Manager
Radio Labs

1. MPE at given distance (KDB 447498 D01 General RF Exposure Guidance v06)

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
P = Power input to the antenna
G = Antenna gain
R = Distance to the center of radiation of the antenna
PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

2. EUT technologies

Declared minimum safety distance: **20 cm**

SRD Technology	Frequency [MHz]		Reference	Output Power [dBm]			Power Density [mW/cm ²]		Share of Limit
	f _{Min}	f _{Max}	#	P _{ERP}	P _{EIRP}	P _{RF Exp}	S _{Result}	S _{Limit}	%
57-64 GHz	57000	64000	A	N/A	1.6	1.6	0.0003	1.0000	0.03%

Referenced Documents:

#	Results from:
A	Test Report 1-5707_23-01-03, p. 31

3. Conclusion

This prediction demonstrates the following:

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

Conclusion: RF exposure evaluation is not required.