

PART NUMBER APPLICATION TABLE			
ITEM	PART No.	SPECIFICATION	REMARK
	YB020300491	GEN 3.0 A48N指示灯标签	

-  #73AA33
-  #0BEBFE
-  #DB0B16
-  #FFBF00

NOTE:

1.印刷如上图
Printing as the drawing

2.尺寸:具体见上图所示 (公差: +0/-0.2mm),R=1mm
Dimension:as the above drawing(Tolerance:+0/-0.2mm),R=1mm

3.材质: 50#PET带不干背胶(材质需经过UL认证). 导入有底雾膜
Material:100#PET with glue on the backside (material must be certified by UL laboratory)

4.底色: 银色; 字体颜色: 黑色
Background color:Black, Fonts color:silver

5.贴附位置: 贴于后壳ID 槽上
Paste position: all plastic surface、all metal parts,

6.粘着力: 在钢板上测试, 单位:Kg f/25mm(铜版纸自带永久胶≥1. 2Kg f/25mm, PET/PC自带永久胶≥1. 2Kg f/25mm)
粘着力测试方法:将label切成25mm宽, 长度200mm, 一端粘贴于钢板上, 以180°方向的力拉label另一端, 所得拉力即为粘着力 (粘着力为所得拉力的平均值)。用拉力测试仪进行测试。
Adhesion: test on the steel plate, unit: KGF /25mm(coated paper with permanent adhesive≥1.2KGF /25mm, PET with permanent adhesive≥1.2KGF /25mm)
Adhesive force test method: cut the Label into 25mm width and 200mm length, paste one end on the steel plate, pull the other end of the Label with a force in the direction of 180°, and the tensile force obtained is the adhesive force (the adhesive force is the average value of the tensile force obtained).Test with a tension tester.

7.耐高温测试: 在钢板上耐温范围为-20~100°C, 100°C保持8小时后不翘角,不分层,不脱落,不起泡等。
在所有塑胶贴附面/所有金属贴附面/所有纸箱贴附面上耐温范围为-20~65° C, 在65°C保持8小时后不翘角,不分层,不脱落,不起泡等。
若特殊要求是可移胶, 则撕下时背胶不能遗留在被贴物上, 且背胶不能破坏被贴物表面。
High temperature test: the temperature range on the steel plate is -20~100°C, 100°C is maintained for 8 hours after no warp Angle, no layering, no falling off, no foaming etc.
On all plastic surfaces /all metal surfaces /all Carton surfaces on the temperature range of -20 ~ 65°C, at 65°C for 8 hours after keeping no warp, no lamination, no falling off, no foaming etc.If the special requirement is removeable glue, when it is removed the adhesive cannot be left on the paste object , and the adhesive cannot damage the surface of the paste.

8.温湿度循环测试: 循环条件: 在所有塑胶贴附面/所有金属贴附面/所有纸箱贴附面上, 温度-20~65°C, 湿度30~90%, 时间 96小时。每分钟温度变化不低于5°C, 时间96小时时后不翘角不分层不脱落不起泡及无油墨脱、褪色、变色等现象。若特殊要求是可移胶, 则撕下时背胶不能遗留在被贴物上, 且背胶不能破坏被贴物表面。
Temperature and humidity cycle test : Cycle conditions: all plastic surfaces /all metal surfaces /all Carton surfaces , In temperature of -20~65°C and humidity of 30~90% to maintain 96 hours ,temperature changes every minute not less than 5°C, after 96 hours, there will be no warping, no delamination, no shedding, no blistering, no ink detachment,no ink fading,no ink discoloration etc. If the special requirement is removeable glue, when it is removed the adhesive cannot be left on the paste object , and the adhesive cannot damage the surface of the paste.

9.裁切需均匀且印刷不可有溢墨及颜色不均等不良现象。
Printing ink can not have overflow and printing color can not be uneven etc.

10.包装方式: 卷状, 连接处打齿孔。
Packing style: coil and there should be a toothed hole between the link of two pieces

11.两张连接处距离3mm, 左右边离型纸3mm(公差: +/-0.5mm).
3mm should be left between the link of two pieces.Around the edge of paper distance is 3mm(Tolerance:+/-0.5mm)

12.内容由厂内打印, 具体内容有PM/业务提供。
The content printed by the factory barcode group and the specific content provided by PM/SS.

13.其它测试要求详见 (FQ-背胶类产品测试检验规格)。

Length:5.12” (130 mm)

CHARGING STATUS INDICATOR:

PLEASE PLUG IN	PLUGGED IN	CHARGING	CHARGING FINISHED	FAULT	WARNING

SIGNAL STATUS INDICATOR:

CONNECTED		CONFIGURATION MODE		CONNECTING TO THE INTERNET		NO CONNECTION	
-----------	--	--------------------	--	----------------------------	--	---------------	--

EV IQO

ELECTRIC VEHICLE AC SMART CHARGING STATION

MODEL: EVIPOWER250N

Power Frequency: 50-60 Hz
Rated Current: 50 A
Protection Level: Type 4
Conforms to: UL Std. 2594
For Use with Electric Vehicles
Operating Temperature: -22 °F (-30 °C) to 131 °F (55 °C)

Rated Power: 12 kW
Rated Voltage: 200-240 VAC
Production Date: 24-09
Conforms to: CSA Std. C22.2#280
Ventilation Not Required
SN: EVI14525520001
Bluetooth Name: EVI QO-A00A

IOS APP Android APP APP Guide

R=1

Width:1.38” (35 mm)

技术要求			
材质	销银龙	印刷颜色	1C
规格（厚度）	75*40*5C	胶型要求	永久胶粘剂
使用膜类	覆光膜	认证要求	ROSH/REACH
不干胶长期耐温性	零下40°高温80 摄氏度	产品特征要求	防水防晒,耐高低温
被贴物	PC材料带皮纹+喷漆+平贴		
标准要求	符合GB/T22771-2008的标准 和 GB/18724-2008的标准，		
印刷要求	印刷清晰，表面干净整洁，无变形，无划伤，扫码等级达到B级以上		
备注：	1. GB/T22771-2008的标准, 耐光等级需达到7级以上（不含7级） 2. GB/18724-2008的标准，（印刷品与印刷油墨耐各种试剂性的测定）		

mm<size(A)<=mm	DRW. No.			福州远近传能科技有限公司											
-	NAME	指示灯标签													
0<A<=30															
30<A<=50	DESIGNED	王羽晨	2026.06.05	UNIT	mm	MATERIAL									
50<A<=100	STANDARD			SCALE	1:1	50#PET									
100<A<=200	CHECKED			SIZE	A4	PROJECT	EVQ								
200<A	APPROVED			SHEET No.	1/1	REV	P	1.0							