



FCC Part 18 Test Report

FCC ID: 2BBZE-G3

Applicant: DONGGUAN JINCHI ELECTRONIC TECHNOLOGY CO., LTD
Address: 2-3/F, A Bk, NO.2 LONGTONG RD, XINHE CONMMUNITY, WANJIANG DISTRICT,
DONGGUAN, China
Manufacturer: DONGGUAN JINCHI ELECTRONIC TECHNOLOGY CO., LTD
Address: 2-3/F, A Bk, NO.2 LONGTONG RD, XINHE CONMMUNITY, WANJIANG DISTRICT,
DONGGUAN, China
Product Name: Wireless Cradle Charger
Trade Mark: N/A
Model Number: BMS-ChargerWirelessCradleG3
Date of Receipt: May 21, 2026
Test Date: May 21, 2026 ~ May 28, 2026
Date of Report: Jun. 05, 2026
Prepared By: Shenzhen DL Testing Technology Co., Ltd.
Address: 101-201, Comprehensive Building, Tongzhou Electronics Longgang Factory Area, No.1
Baolong Fifth Road, Baolong Community, Baolong Street, Longgang District,
Shenzhen, China
Applicable Standards: FCC CFR 47 PART 18
Test Result: Pass
Report Number: DLE-260605002R

Prepared by(Engineer): Ken Tan
Reviewer(Supervisor): Jack Bu
Approved(Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



Table of Contents

Page

1. Summary	4
1.1 Test Procedures and Results	4
1.2 Measurement Uncertainty	4
2. General Information	5
2.1 General Description of EUT	5
2.2 Carrier Frequency of Channels	6
2.3 Operation of EUT during Testing	6
2.4 Description of Test Setup	7
2.5 Description of Support Units	8
2.6 Measurement Instruments List	9
3. AC Conducted Emission Test	10
3.1 Block Diagram of Test Setup	10
3.2 Conducted Power Line Emission Limit	10
3.3 Test Procedure	10
3.4 Test Result	11
4. Radiated Emissions	13
4.1 Block Diagram of Test Setup	13
4.2 Rules and Specifications	14
4.3 Test Procedure	14
4.4 Test Result	15
5. Antenna Requirement	18
6. Test Setup Photos of the EUT	19
7. Photos of the EUT	21

**** Issued History ****

Revision	Description	Issued Date	Remark
Revision 1.0	Initial Test Report Release	Jun. 05, 2026	



1. Summary

1.1 Test Procedures and Results

Description of Test	Section Number	Result
AC Conducted Emissions Test	18.307	PASS
Radiated Emission Test	18.305	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

1.2 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Uncertainty(150KHz-30MHz)	$\pm 2.56\text{dB}$
2	Radiated Emission Uncertainty(9KHz-1GHz)	$\pm 3.24\text{dB}$



2. General Information

2.1 General Description of EUT

Equipment:	Wireless Cradle Charger
Model Name:	BMS-ChargerWirelessCradleG3
Series Model(s):	N/A
Model Difference:	N/A
Antenna Type:	Coil Antenna
Operation Frequency:	112kHz~205kHz
Test Frequency:	120kHz
Modulation Type:	ASK
Power Source:	Input: 5V/2A, 9V/2A, 12V/2A Wireless Output: 5W/7.5W/10W/15W
Power Rating:	Input: 5V/2A, 9V/2A, 12V/2A Wireless Output: 5W/7.5W/10W/15W
Note: - For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. - Antenna gain values are provided by the customer. - The cable loss data is obtained from the supplier. - The test results in the report only apply to the tested sample.	



2.2 Carrier Frequency of Channels

Operation Frequency each of channel	
Channel	Frequency
Middle CH	120kHz

2.3 Operation of EUT during Testing

Test Item	Test mode	Description
Radiated & AC Conducted Test Cases	Mode 1	AC/DC Adapter+ EUT + Mobile Phone (Battery Status: <1%)
	Mode 2	AC/DC Adapter+ EUT + Mobile Phone (Battery Status: <50%)
	Mode 3	AC/DC Adapter+ EUT + Mobile Phone (Battery Status: >95%)

Note:

1. All modes and configurations above have been tested, Only the result of the worst case was recorded in the report.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. The Mobile Phone provided by Lab.
4. According to the manufacturer's design principle, the wireless charging power will reach its maximum when the client device's battery level is between 1% and 10%.



2.4 Description of Test Setup

Operation of EUT during Testing:



The sample was placed (0.8m (30MHz~1GHz), 0.8m (9KHz~30MHz)) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The report only reflects the worst emission test results. The worst case is X position.



2.5 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Trade Mark	Model Name	Specification	Remark
1	Wireless Cradle Charger	N/A	BMS-ChargerWirelessCradleG3	N/A	EUT
2	USB Cable	N/A	N/A	Length: 100cm	
3	Adapter	N/A	CD289	Input: AC100-240V, 50/60Hz, 2A Max USB-C1 Output: DC5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A, 28V/5A 140W MAX USB-C2 Output: DC5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A 100W MAX USB-A Output: DC5V/4.5A, 4.5V/5A, 5V/3A, 9V/2A, 12V/1.5A 22.5W MAX Total Output: 140W Max	
4	Mobile phone	OPPO	Find X8	N/A	

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. Wireless load (Load 1) is a device containing rechargeable batteries or capacity loads, connected via charging control circuit that receives power from a source via a coupling antenna.

**2.6 Measurement Instruments List****For Conducted Emission Test (843 Shielded Room)**

Equipment	Manufacturer	Model	Serial	Last Cal.	Next Cal.
843 Shielded Room	YIHENG	843 Room	843	Nov. 05, 2023	Nov. 04, 2026
EMI Receiver	R&S	ESR	101421	Oct. 25, 2025	Oct. 24, 2026
LISN	R&S	ENV216	102417	Oct. 25, 2025	Oct. 24, 2026
Clamp	COM-POWER	CLA-050	431071	Oct. 27, 2025	Oct. 26, 2026
3-Loop Antenna	DAZE	ZN30401	13021	Oct. 27, 2025	Oct. 26, 2026
ISN T8	Schwarzbeck	NTFM 8158	101135	Oct. 25, 2025	Oct. 24, 2026
ISN T5	Schwarzbeck	NTFM 8158	101136	Oct. 25, 2025	Oct. 24, 2026
843 Cable 1#	ChengYu	CE Cable	001	Oct. 25, 2025	Oct. 24, 2026
843 Cable 1#	ChengYu	CE Cable	002	Oct. 25, 2025	Oct. 24, 2026


For Radiated Emission Test (966 chamber)

Equipment	Manufacturer	Model	Serial	Last Cal.	Next Cal.
966 Chamber	YIHENG	966 Room	966	Nov. 06, 2023	Nov. 05, 2026
Spectrum Analyzer	Agilent	E4408B	MY50140780	Oct. 25, 2025	Oct. 24, 2026
EMI Receiver	R&S	ESRP7	101393	Oct. 25, 2025	Oct. 24, 2026
Amplifier	Schwarzbeck	BBV9743B	00153	Oct. 25, 2025	Oct. 24, 2026
Amplifier	EMEC	EM01G8GA	00270	Oct. 25, 2025	Oct. 24, 2026
Broadband Trilog Antenna	Schwarzbeck	VULB9162	00306	Oct. 26, 2025	Oct. 25, 2026
Horn Antenna	Schwarzbeck	BBHA9120D	02139	Oct. 26, 2025	Oct. 25, 2026
Loop Antenna	ZHINAN	ZN30900A	/	Oct. 26, 2025	Oct. 25, 2026
966 Cable 1#	ChengYu	966	004	Oct. 25, 2025	Oct. 24, 2026
966 Cable 2#	ChengYu	966	003	Oct. 25, 2025	Oct. 24, 2026



3. AC Conducted Emission Test

3.1 Block Diagram of Test Setup



Remark:

E.U.T: Equipment Under Test

LISN: Line Impedance Stabilization Network

Test table height=0.8m

3.2 Conducted Power Line Emission Limit

According to FCC Part 18.307(b)

Frequency (MHz)	Maximum RF Line Voltage (dB μ V)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §18.307 Line Conducted Emission Limit is same as above table.

3.3 Test Procedure

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.




3.4 Test Result

PASS

All the test modes completed for test. Only the worst result was reported as below:

Test Specification: Line



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1725	45.34	19.81	64.84	19.50	25.53	PK	L
2	0.2265	41.23	19.76	62.58	21.35	21.47	PK	L
3	0.3615	35.97	19.80	58.69	22.72	16.17	PK	L
4	0.5955	40.43	19.90	56.00	15.57	20.53	PK	L
5	2.5170	35.86	20.10	56.00	20.14	15.76	PK	L
6	10.0580	37.10	21.24	60.00	22.90	15.86	PK	L


Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor



Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1860	43.91	19.81	64.21	20.30	24.10	PK	N
2	0.2985	37.92	19.82	60.28	22.36	18.10	PK	N
3	0.6000	41.36	19.95	56.00	14.64	21.41	PK	N
4	2.2740	36.34	20.17	56.00	19.66	16.17	PK	N
5	8.1410	36.35	20.83	60.00	23.65	15.52	PK	N
6	13.8875	36.65	21.75	60.00	23.35	14.90	PK	N

Remark: Margin = Limit – Level



Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor



4. Radiated Emissions

4.1 Block Diagram of Test Setup





4.2 Rules and Specifications

Except as provided elsewhere in this Subpart 18.305 (b), the field strength levels of emissions which lie outside the bands specified in §18.301, unless otherwise indicated, shall not exceed the following table:

Equipment	Operating frequency	RF Power generated by equipment (watts)	Field strength limit (uV/m)	Distance (meters)
(miscellaneous)				
	Any non-ISM frequency	Below 500 500 or more	15 15 × SQRT(power/500)	300 1300

Remark:

- (1) Emission level dBuV/m for 0.009~30MHz = $20\log(15) + 40\log(300/3)$ dBuV/m;
- (2) Calculated according FCC 18.305.
- (3) The smaller limit shall apply at the cross point between two frequency bands.
- (4) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

4.3 Test Procedure

Measurement distance 3m

For the measurement range up to 30MHz in the following plots the field strength result from 3m Distance measurements are extrapolated to 300m and 30m distance respectively, by 40dB/decade, Per antenna factor scaling.

Measurements below 1000MHz are performed with a peak detector and compared to average limits; Measurements with an average detector are not required.




4.4 Test Result

PASS

Note: All the test modes completed for test. Only the worst result was reported as below:

For 9KHz - 30MHz



Suspected List


NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]
1	0.120	13.67	80.67	94.34	103.50	9.16
2	0.359	13.64	56.71	70.35	103.50	33.15
3	0.598	13.72	46.75	60.47	103.50	43.03
4	0.837	13.97	39.81	53.78	103.50	49.72
5	1.076	14.40	34.29	48.69	103.50	54.81
6	1.897	14.46	22.41	36.87	103.50	66.63

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level



For 30MHz-1GHz

Antenna polarity: Horizontal




Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	87.287	-17.12	35.60	18.48	63.50	45.02	100	348	Horizontal
2	143.604	-18.41	42.53	24.12	63.50	39.38	100	129	Horizontal
3	192.152	-15.24	43.20	27.96	63.50	35.54	100	112	Horizontal
4	287.307	-12.41	42.81	30.40	63.50	33.10	100	191	Horizontal
5	384.404	-10.15	38.07	27.92	63.50	35.58	100	228	Horizontal
6	501.892	-7.71	32.73	25.02	63.50	38.48	100	17	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level



Antenna polarity: Vertical



Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	37.768	-14.27	43.00	28.73	63.50	34.77	100	297	Vertical
2	84.374	-17.95	48.83	30.88	63.50	32.62	100	309	Vertical
3	143.604	-18.41	46.74	28.33	63.50	35.17	100	45	Vertical
4	192.152	-15.24	41.73	26.49	63.50	37.01	100	28	Vertical
5	287.307	-12.41	38.09	25.68	63.50	37.82	100	65	Vertical
6	513.544	-7.46	36.18	28.72	63.50	34.78	100	251	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level



5. Antenna Requirement


Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The antenna used in this product is a Coil Antenna, which permanently attached. It conforms to the standard requirements.



Antenna





6. Test Setup Photos of the EUT

Radiated Emission





AC Conducted Emission





7. Photos of the EUT

Reference to the report: ANNEX A of external photos and ANNEX B of internal photos.

-----End of test report-----