RF TEST REPORT

Report Reference No.....	**: MAX260209113P01-R01RF**
FCC ID.....	**: 2BC5F-HH-9011Y**
Compiled by (position+printed name+signature)..	: Engineer/ Cindy Zheng
Supervised by (position+printed name+signature)..	: Manager/Haley Wen
Approved by (position+printed name+signature)..	: RF Manager/ Vivian Jiang
Date of issue.....	: February 12, 2026

Cindy zheng
Haley wen
Vivian Jiang

Testing Laboratory Name.....	**: MAXLAB Testing Co.,Ltd.**
Address.....	: 1/F, Building B, Xinshidai GR Park,Shiyan Street, Bao'an District, Shenzhen,Guangdong, 518052, People's Republic of China
Applicant's name.....	**: Henan Honghui Electronic Technology Co., Ltd**
Address.....	: NO.20, 4/F ,Building 1, NO36, Hong song road, High-techzone, zhengzhou, China
Test specification.....	**:**
Standard.....	: KDB 447498 D01 General RF Exposure Guidance v06

MAXLAB Testing Co.,Ltd.All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAXLAB Testing Co.,Ltd. is acknowledged as copyright owner and source of the material. MAXLAB Testing Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Equipment description.....	**: Remote Control**
Trade Mark.....	: 鸿珲电子
Manufacturer.....	: Henan Honghui Electronic Technology Co., Ltd
Model/Type reference.....	: HH-9011Y
Listed Models	: HH-9012Y, HH9013Y, HH9016Y, HH-9018Y, HH-9022Y, HH-9023Y, HH9026Y, HH-9028Y
Modulation	: GFSK
Frequency.....	From 2419MHz to 2474MHz
Ratings.....	: DC 3.0V
Result.....	: **PASS**

RF EXPOSURE EVALUATION METHOD

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

According to KDB 447498 D01 General RF Exposure Guidance v06, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

EUT Specification

Frequency band (Operating)	☐ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.150GHz ~ 5.250GHz ☐ WLAN: 5.725GHz ~ 5.850GHz ☒ Others 2.4G:2419-2474MHz
Device category	☒ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm^2) ☒ General Population/Uncontrolled exposure (S=1mW/cm^2)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	2.35 dBm
Antenna gain (Max)	0 dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

RF EXPOSURE EVALUATION METHOD

SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,where f(GHz) is the RF channel transmit frequency in GHz
Power and distance are rounded to the nearest mW and mm before calculation
The result is rounded to one decimal place for comparison
The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

For 2.4G Measurement Data

Operating Mode	Frequency	Field strength	EIRP	Max tune-up	Antenna Gain	min. test separation distance	Result	Limit
	(MHz)	(dBuV/m @3)	(dBm)	(mW)	(dBi)	(mm)		
GFSK	2445	97.51	2.35	2	0	5	0.6255	3

$EIRP=E_{Meas}+20\log(d_{Meas})-104.7$

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBuV/m

d_{Meas} is the measurement distance, in m

Conclusion: No SAR is required.