

SPECIFICATIONS

PRODUCT NAME : Bluetooth Low Energy Antenna

MODEL NAME : ETWBCLUL04 Ant.

The information contained herein is the exclusive property of LG Innotek and shall not be distributed, reproduced or disclosed in whole or no in part without prior written permission of LG Innotek.

Designed	Checked	Approved	LG Innotek Co., Ltd.	
Y.U.Jeong				
			DOCUMENT No.	2021RF-LG019
2021.09.16	-	-	PAGE	7



REG. DATE : 2021.09.16

SPECIFICATION

REV.NO : 1.0

REV. DATE : 2021.09.16

MODEL NAME : ETWBCLUL04

PAGE : 1 / 7

Change History of Revision

Revision	Date	Contents of Revision Change	Remark
1.0	2021.09.16	BLE ANT Spec	Y.U.Jeong



REG. DATE : 2021.09.16

SPECIFICATION

REV.NO : 1.0

REV. DATE : 2021.09.16

MODEL NAME : ETWBCLUL04

PAGE : 2 / 7

Table of Contents

No	Description	Page
1	ANT Features	3
2	Antenna Characteristics	3
	2.1 Network Data	4
	2.2 Efficiency	5
	2.3 Radiation Pattern	6
3	ANT Test Condition	6
4	ANT Dimension	7

REG. DATE : 2021.09.16

SPECIFICATION

REV.NO : 1.0

REV. DATE : 2021.09.16

MODEL NAME : ETWBCLUL04

PAGE : 3 / 7

1. ANT Features

- BLE ANT
- Main Frequency: 2.45GHz
- Frequency range
: From 2.412~2.485GHz
- Operating temperature range
: -35 to +95°C (typ.)
- ANT Material : PCB pattern

2. Antenna Characteristics

- Dual Band ANT1

Antenna Performance				
Parameter	Min	Typ	Max	Unit
Frequency Range	2412	2450	2485	MHz
Directivity	-	Omni	-	-
Full Bands Average Gain	-	-7.24	-	dBi
Full Bands Peak Gain		-	-1.39	
V.S.W.R	3:1	-	-	Under
Impedance		50		Ohm
Radiation Material		PCB pattern		



REG. DATE : 2021.09.16


SPECIFICATION

REV.NO : 1.0

REV. DATE : 2021.09.16

MODEL NAME : ETWBCLUL04

PAGE : 4 / 7

2.1 Network Data**VSWR**

REG. DATE : 2021.09.16

SPECIFICATION

REV.NO : 1.0

REV. DATE : 2021.09.16

MODEL NAME : ETWBCLUL04

PAGE : 5 / 7

2.2. Efficiency

	1	2	3	4	5	6	7	8	9	10
Frequency(MHz)	2402	2412	2430	2440	2445	2450	2460	2470	2480	2485
Efficiency(dB)	-7.05	-7.06	-7.08	-7.05	-6.99	-7.08	-7.25	-7.39	-7.64	-7.87
Efficiency(%)	19.70	19.67	19.61	19.70	20.02	19.57	18.83	18.24	17.23	16.34
TRG(dB)	-7.05	-7.06	-7.08	-7.05	-6.99	-7.08	-7.25	-7.39	-7.64	-7.87
TRG _{Theta} (dB)	-8.80	-8.89	-9.15	-9.24	-9.23	-9.38	-9.57	-9.78	-10.01	-10.22
TRG _{Phi} (dB)	-11.85	-11.70	-11.28	-11.08	-10.93	-10.94	-11.08	-11.13	-11.40	-11.66
UHRG(dB)	-10.87	-10.83	-10.82	-10.82	-10.75	-10.88	-11.12	-11.29	-11.55	-11.78
UHRG/TRG(%)	41.55	42.01	42.23	41.97	41.98	41.70	41.03	40.78	40.62	40.59
H-Plane	-9.20	-9.22	-9.26	-9.25	-9.18	-9.35	-9.61	-9.91	-10.14	-10.33
E1-Plane, AVG(dB)	-9.10	-9.33	-9.81	-10.01	-10.11	-10.24	-10.44	-10.66	-10.92	-11.12
E2-Plane, AVG(dB)	-8.73	-8.80	-9.04	-9.13	-9.08	-9.24	-9.41	-9.60	-9.82	-10.04
Peak Gain(dB)	-1.39	-1.58	-1.93	-2.10	-2.25	-2.30	-2.41	-2.53	-2.76	-2.93
Directivity(dB)	5.67	5.48	5.14	4.95	4.73	4.79	4.84	4.86	4.88	4.94
Minimum Gain(dB)	-15.65	-16.23	-17.03	-17.34	-17.36	-17.56	-17.82	-17.68	-17.52	-17.55
Test Condition	FS									
Antenna Type										
Average Efficiency	-7.24 dB, 18.89 %									

REG. DATE : 2021.09.16


SPECIFICATION

REV.NO : 1.0


REV. DATE : 2021.09.16

MODEL NAME : ETWBCLUL04

PAGE : 6 / 7

2.3. Radiation Pattern

<2.45GHz>

3. ANT Test Condition**CTIA-OTA Test Chamber : 3x6x3m**

REG. DATE : 2021.09.16

SPECIFICATION

REV.NO : 1.0

REV. DATE : 2021.09.16

MODEL NAME : ETWBCLUL04

PAGE : 7 / 7

4. Dimensions