



TEST REPORT



Report No. : KES-RF-23T0159
Page 1 / 86

KES Co., Ltd.
3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
Tel : +82-31-425-6200, Fax : +82-31-425-6200

■ FCC TEST REPORT

1. Client

- Name : TCL Co.,Ltd
- Address : 29-1 Wago-Kitakagaya, Togo-Cho, Aichi-Gun, Aichi-Ken, 470-0153 Japan

2. Sample Description

- Product item : Smart Reco
- Model name : WHSR-S100
- Manufacturer etc. : MISO E&T CO., LTD.

3. Date of test : 2023.11.03 ~ 2023.11.24

4. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing

- Address : 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, Korea

5. Test method used : Part 15 Subpart C 15.247

6. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This laboratory is not accredited for the test results marked *.

This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager
	Name : Gu-Bong, Kang (Signature)	Name : Young-Jin Lee (Signature)

2023 . 12. 07.

KES Co., Ltd.

Accredited by KOLAS, Republic of KOREA

KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr



REPORT REVISION HISTORY

Date	Test Report No.	Revision History
2023.12.07	KES-RF-23T0159	Initial

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

Use of uncertainty of measurement for decisions on conformity (decision rule):

■ No decision rule is specified by the standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty("simple acceptance" decision rule, previously known as "accuracy method").

☐ Other (to be specified, for example when required by the standard or client)





TABLE OF CONTENTS

1.	General information	4
1.1.	EUT description	4
1.2.	Test configuration.....	4
1.3.	Information about derivative model	5
1.4.	Accessory information	5
1.5.	Device modifications.....	5
1.6.	Worst case data rate.....	5
1.7.	Sample calculation	6
1.8.	Measurement Uncertainty	6
1.9.	Frequency/channel operations	6
2.	Summary of tests	7
3.	Test results	8
3.1.	6 dB bandwidth	8
3.2.	Output power	15
3.3.	Power spectral density	17
3.4.	Radiated restricted band and emissions	24
3.5.	Conducted spurious emissions & band edge	72
3.6.	Antenna Requirement.....	85
Appendix A.	Measurement equipment.....	86



Report No. : KES-RF-23T0159

Page 4 / 86

1. General information

Applicant: TCL Co.,Ltd
 Applicant address: 29-1 Wago-Kitakagaya, Togo-Cho, Aichi-Gun, Aichi-Ken, 470-0153 Japan
 Test site: KES Co., Ltd.
 Test site address: ☐ 3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
☒ 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
 Test Facility: FCC Accreditation Designation No.: KR0100, Registration No.: 444148
 FCC rule part(s): 15.247
 FCC ID: 2BC9S-WHSR-S100
 Test device serial No.: ☒ Production ☐ Pre-production ☐ Engineering

1.1. EUT description

Equipment under test: Smart Reco
 Frequency range: 2 412 MHz ~ 2 462 MHz (802.11b/g/n_HT20)
 Model: WHSR-S100
 Modulation technique: DSSS, OFDM
 Number of channels: 2 412 MHz ~ 2 462 MHz (802.11b/g/n_HT20) : 11 ch
 Antenna specification: Chip Antenna // Peak gain: 1.46 dBi
 Power source: DC 12 V, 24 V
 H/W version: E0.2
 S/W version: 0.04

1.2. Test configuration



The **TCL Co.,Ltd // Smart Reco // WHSR-S100 // FCC ID: 2BC9S-WHSR-S100** was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247
 KDB 558074 D01 v05 r02
 ANSI C63.10-2013

KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr



1.3. Information about derivative model
N/A

1.4. Accessory information


Equipment	Manufacturer	Model	Serial No.	Power source
Main Body	MISO E&T CO., LTD.	WHSR-S100	-	DC 12 V, DC 24 V
Left Camera	MISO E&T CO., LTD.	-	-	-
Right Camera	MISO E&T CO., LTD.	-	-	-
Power cable	-	-	-	-
Ext. Cable(2ea)	-	-	-	-
Double-sided Tape	-	-	-	-
Micro SD Card	-	-	-	-

1.5. Device modifications
N/A

1.6. Worst case data rate

1. Worst-case data rates were:

802.11b : 1 Mbps, 802.11g : 6 Mbps, 802.11n_HT20 : MCS0



1.7. Sample calculation

Where relevant, the following sample calculation is provided

For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 0.71 + 10 = 10.71 \text{ (dB)}\end{aligned}$$

For Radiation test :


$$\text{Field strength level (dB}\mu\text{V/m)} = \text{Measured level (dB}\mu\text{V)} + \text{Antenna factor (dB)} + \text{Cable loss (dB)} - \text{Amplifier gain (dB)}$$

1.8. Measurement Uncertainty

Test Item		Uncertainty
Uncertainty for Conduction emission test		2.22 dB (SHIELD ROOM #6)
Uncertainty for Radiation emission test (include Fundamental emission)	Below 1 GHz	4.04 dB (SAC #6)
	Above 1 GHz	5.32 dB (SAC #5)
Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.		

1.9. Frequency/channel operations

Ch.	Frequency (MHz)	Mode
1	2 412	802.11b/g/n_HT20
.	.	.
6	2 437	802.11b/g/n_HT20
.	.	.
11	2 462	802.11b/g/n_HT20





2. Summary of tests

Section in FCC Part 15	Test description	Test results
15.247(a)(2)	6 dB bandwidth	Pass
15.247(b)(3)	Output power	Pass
15.247(e)	Power spectral density	Pass
15.205, 15.209	Radiated restricted band and emission	Pass
15.247(d)	Conducted spurious emission and band edge	Pass
15.207(a)	AC Conducted emissions	N/A ^{note1.}
15.203	Antenna Requirement	Pass

Note.

1. This device is powered by DC 12 V, DC 24 V.
2. By the request of the applicant, test was performed with condition below:

Mode	Frequency (MHz)	Power Setting value
802.11b	2 412 MHz ~ 2 462 MHz	55
802.11g	2 412 MHz ~ 2 462 MHz	55
802.11n_HT20	2 412 MHz ~ 2 462 MHz	65




3. Test results

3.1. 6 dB bandwidth

Test procedure

ANSI C63.10-2013 - Section 11.8.2

Test setup



ANSI C63.10-2013 - Section 11.8.2

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq 3 \times$ RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

Limit


According to §15.247(a)(2), systems using digital modulation techniques may operate 902 ~ 928 MHz, 2 400 ~ 2 483.5 MHz, and 5 725 ~ 5 850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.



Test results




Mode : 802.11b (1 Mbps)_DC 12 V

Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 412	10.00	≥ 0.500
2 437	9.96	
2 462	10.03	



Mode : 802.11b (1 Mbps)_DC 24 V



Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 412	10.03	≥ 0.500
2 437	10.04	
2 462	9.49	



Report No. : KES-RF-23T0159

Mode : 802.11g (6 Mbps)_DC 12 V



Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 412	16.07	≥ 0.500
2 437	16.13	
2 462	15.99	



Report No. : KES-RF-23T0159

Mode : 802.11g (6 Mbps)_DC 24 V

Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 412	15.97	≥ 0.500
2 437	16.10	
2 462	16.13	




Report No. : KES-RF-23T0159

Page 13 / 86

Mode : 802.11n_HT20 (MCS0)_DC 12 V

Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 412	17.28	≥ 0.500
2 437	17.27	
2 462	17.21	



MultiView Spectrum 3

Ref Level: 17.00 dBm
Att: 25 dB
SWT: 30.1 ms
RBW: 100 kHz
VBW: 300 kHz
Mode: Auto Sweep
100% 26.5G 100%

1 Frequency Sweep

CF 2.462 GHz 30001 pts 5.0 MHz/ Span 50.0 MHz

2 Marker Table

Type	Ref	Trc	Value	Unit	Function	Function Result
M1	1		2.4572623 GHz	-3.52 dBm		
M2	1		2.4570135 GHz	-2.08 dBm		
D3	M1	1	17.2111 MHz	0.04 dB		

Blank




Report No. : KES-RF-23T0159

Page 14 / 86

Mode : 802.11n_HT20 (MCS0)_DC 24 V

Frequency(MHz)	6 dB bandwidth(MHz)	Limit(MHz)
2 412	16.42	≥ 0.500
2 437	17.22	
2 462	17.07	




3.2. Output power

Test procedure

ANSI C63.10-2013 - Section 11.9.1.3 and 11.9.2.3.2

Test setup



ANSI C63.10-2013 - Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

ANSI C63.10-2013 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.


Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 MHz, 2 400~2 483.5 MHz, and 5 725~5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.




Test results

Mode	2 412 MHz		2 437 MHz		2 462 MHz		Power Limit (dBm)
	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	Average (dBm)	Peak (dBm)	
802.11b DC 12 V	12.63	14.44	12.39	14.25	11.83	13.80	30.00
802.11b DC 24 V	12.69	14.48	12.39	14.24	11.85	13.80	30.00
802.11g DC 12 V	12.26	16.53	11.92	16.41	11.46	16.42	30.00
802.11g DC 24 V	12.23	16.53	12.05	16.57	11.47	16.22	30.00
802.11n_HT20 DC 12 V	12.20	16.47	12.04	16.43	11.69	16.39	30.00
802.11n_HT20 DC 24 V	12.17	16.43	12.04	16.46	11.64	16.37	30.00



3.3. Power spectral density**Test procedure**

ANSI C63.10-2013 - Section 11.10.2

Test setup**Section 10.2 & ANSI C63.10-2013 - Section 11.10.2**

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- d. Set the VBW $\geq [3 \times \text{RBW}]$.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.
- j. If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

Limit



According to §15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.



Results




Mode : 802.11b (1 Mbps)_DC 12 V

Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 412	-10.53	≤ 8
2 437	-10.85	
2 462	-11.29	





Mode : 802.11b (1 Mbps)_DC 24 V

Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 412	-10.68	≤ 8
2 437	-10.99	
2 462	-11.18	





Mode : 802.11g (6 Mbps)_DC 12 V

Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 412	-14.19	≤ 8
2 437	-14.42	
2 462	-14.83	





Mode : 802.11g (6 Mbps)_DC 24 V

Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 412	-14.22	≤ 8
2 437	-14.44	
2 462	-14.87	




Mode : 802.11n_HT20 (MCS0)_DC 12 V

Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 412	-13.84	≤ 8
2 437	-13.81	
2 462	-14.40	



Mode : 802.11n_HT20 (MCS0)_DC 24 V


Frequency(MHz)	PSD (dBm/3kHz)	Limit(dBm/3kHz)
2 412	-13.77	≤ 8
2 437	-13.90	
2 462	-14.34	




3.4. Radiated restricted band and emissions

Test setup


The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



Test procedure



Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that parallel was worst-case orientation; therefore, all final radiated testing was performed with the EUT in parallel.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 MHz

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna ,and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
5. Spectrum analyzer settings for $f < 1$ GHz:
 - ① Span = wide enough to fully capture the emission being measured
 - ② RBW = 100 kHz
 - ③ VBW $\geq$ RBW
 - ④ Detector = quasi peak
 - ⑤ Sweep time = auto
 - ⑥ Trace = max hold



6. Spectrum analyzer settings for $f \geq 1$ GHz: Peak

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW ≥ 3 MHz
- ④ Detector = peak
- ⑤ Sweep time = auto
- ⑥ Trace = max hold
- ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for $f \geq 1$ GHz: Average

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW $\geq 3 \times$ RBW
- ④ Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ⑤ Averaging type = power(i.e., RMS)
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- ⑥ Sweep = auto
- ⑦ Trace = max hold
- ⑧ Perform a trace average of at least 100 traces.
- ⑨ A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.



Note.

1. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40\log(D_m/D_s)$
 $f \geq 30$ MHz, extrapolation factor of 20 dB/decade of distance. $F_d = 20\log(D_m/D_s)$
 Where:
 F_d = Distance factor in dB
 D_m = Measurement distance in meters
 D_s = Specification distance in meters
2. Field strength(dB μ V/m) = Level(dB μ V) + CF (dB) + or DCF(dB)
3. Margin(dB) = Limit(dB μ V/m) - Field strength(dB μ V/m)
4. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that **X orientation** was worst-case orientation; therefore, all final radiated testing was performed with the EUT in **X orientation**.
6. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (Meters)	Radiated (μ V/m)
0.009 ~ 0.490	300	2400/F(kHz)
0.490 ~ 1.705	30	24000/F(kHz)
1.705 ~ 30.0	30	30
30 ~ 88	3	100**
88 ~ 216	3	150**
216 ~ 960	3	200**
Above 960	3	500

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

