RF TEST REPORT

Product Name: ATS25

Model Name: ATS25 max-Decoder, ATS25 max

FCC ID: 2BCA4-ATS25

Issued For : Shenzhen Borun International Trade Co., Ltd

403, Building 2, Youpin Cultural Creative Park, Meilong Road, Minzhi Street, Longhua District, Shenzhen City, Guangdong Province, China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China

Report Number:	LGT23G112RF03
Sample Received Date:	Jul. 29, 2023
Date of Test:	Jul. 29, 2023 – Aug. 11, 2023
Date of Issue:	Aug. 11, 2023

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.

TEST REPORT CERTIFICATION

Applicant:	Shenzhen Borun International Trade Co., Ltd
Address:	403, Building 2, Youpin Cultural Creative Park, Meilong Road, Minzhi Street, Longhua District, Shenzhen City, Guangdong Province, China
Manufacturer:	Shenzhen Borun International Trade Co., Ltd
Address:	403, Building 2, Youpin Cultural Creative Park, Meilong Road, Minzhi Street, Longhua District, Shenzhen City, Guangdong Province, China
Product Name:	ATS25
Trademark:	N/A
Model Name:	ATS25 max-Decoder, ATS25 max
Sample Status:	Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.247, Subpart C ANSI C63.10-2013	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li
Technical Director

Table of Contents

Page

1. SUMMARY OF TEST RESULTS **6**

1.1 TEST FACTORY 7

1.2 MEASUREMENT UNCERTAINTY 7

2. GENERAL INFORMATION **8**

2.1 GENERAL DESCRIPTION OF THE EUT 8

2.2 DESCRIPTION OF THE TEST MODES 10

2.3 TEST SOFTWARE AND POWER LEVEL 11

2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS 11

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS 12

3. EMC EMISSION TEST **13**

3.1 CONDUCTED EMISSION MEASUREMENT 13

3.2 RADIATED EMISSION MEASUREMENT 17

4. CONDUCTED SPURIOUS & BAND EDGE EMISSION **29**

4.1 LIMIT 29

4.2 TEST PROCEDURE 29

4.3 DEVIATION FROM STANDARD 29

4.4 TEST SETUP 29

4.5 EUT OPERATION CONDITIONS 29

4.6 TEST RESULTS 29

5. POWER SPECTRAL DENSITY TEST **30**

5.1 LIMIT 30

5.2 TEST PROCEDURE 30

5.3 DEVIATION FROM STANDARD 30

5.4 TEST SETUP 30

5.5 EUT OPERATION CONDITIONS 30

5.6 TEST RESULTS 30

6. BANDWIDTH TEST **31**

6.1 LIMIT 31

6.2 TEST PROCEDURE 31

6.3 DEVIATION FROM STANDARD 31

6.4 TEST SETUP 31

6.5 EUT OPERATION CONDITIONS 31

6.6 TEST RESULTS 31

Table of Contents **Page**

7. PEAK OUTPUT POWER TEST **32**

7.1 LIMIT 32

7.2 TEST PROCEDURE 32

7.3 DEVIATION FROM STANDARD 32

7.4 TEST SETUP 32

7.5 EUT OPERATION CONDITIONS 32

7.6 TEST RESULTS 32

8. ANTENNA REQUIREMENT **33**

8.1 STANDARD REQUIREMENT 33

8.2 EUT ANTENNA 33

APPENDIX I:TEST RESULTS **34**

DUTY CYCLE 34

MAXIMUM PEAK CONDUCTED OUTPUT POWER 39

-6DB BANDWIDTH 40

OCCUPIED CHANNEL BANDWIDTH 45

MAXIMUM POWER SPECTRAL DENSITY LEVEL 50

BAND EDGE 55

CONDUCTED RF SPURIOUS EMISSION 62

Revision History

Rev.	Issue Date	Contents
00	Aug. 11, 2023	Initial Issue

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247,Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted Band Edge Emission	PASS	--
Part 15.247(d)/ Part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1) 'N/A' denotes test is not applicable in this Test Report.

(2) All tests are according to ANSI C63.10-2013.

1.1 TEST FACTORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y ± U**, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95** %.

No.	Item	Uncertainty
1	RF Output Power, Conducted	±0.71dB
2	Power Spectral Density, Conducted	±1.57 dB
3	Unwanted Emission, Conducted	±0.63dB
4	Conducted emission	±2.80dB
5	All Emissions, Radiated (0.009-30MHz)	±2.16dB
6	All Emissions, Radiated (30MHz-1GHz)	±4.40dB
7	All Emissions, Radiated (1GHz-18GHz)	±5.49dB

Note: The measurement uncertainty is not included in the test result.

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

<table>
<tr><td>Product Name:</td><td>ATS25</td></tr>
<tr><td>Trademark:</td><td>N/A</td></tr>
<tr><td>Model Name:</td><td>ATS25 max-Decoder</td></tr>
<tr><td>Series Model:</td><td>ATS25 max</td></tr>
<tr><td>Model Difference:</td><td>They are different only for the model name.</td></tr>
<tr><td>Product Description:</td><td>
<table>
<tr><td>Operation Frequency:</td><td>802.11b/g/n(20MHz): 2412~2462 MHz
802.11n (40MHz):2422~2452MHz</td></tr>
<tr><td>Modulation Type:</td><td>802.11b(DSSS):CCK,DQPSK,DBPSK
802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM
802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM</td></tr>
<tr><td>Number of Channel:</td><td>802.11b/g/n(HT20): 11CH
802.11n(HT40): 7CH</td></tr>
<tr><td>Antenna Designation:</td><td>Dipole Antenna.</td></tr>
<tr><td>Antenna Gain(dBi):</td><td>2.5dBi</td></tr>
</table>
</td></tr>
<tr><td>Channel List:</td><td>Please refer to the Note 2.</td></tr>
<tr><td>Rating:</td><td>Input: DC 5V, 1.2A</td></tr>
<tr><td>Battery:</td><td>Capacity: 3000mAh
Rated Voltage: 3.7V</td></tr>
<tr><td>Hardware Version:</td><td>1.0</td></tr>
<tr><td>Software Version:</td><td>V4.16</td></tr>
<tr><td>Connecting I/O Port(s):</td><td>Please refer to the Note 1.</td></tr>
</table>

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refers to the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.

2.

Operation Frequency of channel			
802.11b/g/n(20MHz)		Channel List for 802.11n(40MHz)	
Channel	Frequency	Channel	Frequency
01	2412	03	2422
02	2417	04	2427
03	2422	05	2432
04	2427	06	2437
05	2432	07	2442
06	2437	08	2447
07	2442	09	2452
08	2447		
09	2452		
10	2457		
11	2462		

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, themiddle frequency, and the highest frequency of channel were selected to perform the test, and the selectedchannel see below:
Carrier Frequency Channel

2.4GHz Test Frequency:

For 802.11b/g/n (HT20)		For 802.11n (HT40)	
Channel	Freq.(MHz)	Channel	Freq.(MHz)
01	2412	03	2422
06	2437	06	2437
11	2462	09	2452

2.2 DESCRIPTION OF THE TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11b CH1	1 Mbps
Mode 2	TX IEEE 802.11b CH6	1 Mbps
Mode 3	TX IEEE 802.11 b CH11	1 Mbps
Mode 4	TX IEEE 802.11g CH1	6 Mbps
Mode 5	TX IEEE 802.11g CH6	6 Mbps
Mode 6	TX IEEE 802.11g CH11	6 Mbps
Mode 7	TX IEEE 802.11n HT20 CH1	MCS 0
Mode 8	TX IEEE 802.11n HT20 CH6	MCS 0
Mode 9	TX IEEE 802.11n HT20 CH11	MCS 0
Mode 10	TX IEEE 802.11n HT40 CH3	MCS 0
Mode 11	TX IEEE 802.11n HT40 CH6	MCS 0
Mode 12	TX IEEE 802.11n HT40 CH9	MCS 0

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode13: Keeping TX + WLAN Link

2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test software Version	Test program: 2.4G WIFI	
EspRFTestTool_v2.8	Mode Or Modulation type	Power setting
	b	Default
	g	Default
	n20	Default
	n40	Default

2.4 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	HUAWEI	HKF-16	N/A	N/A

Note:

(1) For detachable type I/O cable should be specified the length in cm in『Length』column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conducted Emission					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Cal. Date**	**Cal. Until**
EMI Test Receiver	R&S	ESU8	100372	2023.04.13	2024.04.12
LISN	COM-POWER	LI-115	02032	2023.04.07	2024.04.06
LISN	SCHWARZBECK	NNLK 8121	00847	2023.04.07	2024.04.06
LISN	SCHWARZBECK	NNLK 8122	00160	2023.04.07	2024.04.06
Transient Limiter	CYBERTEK	EM5010A	E2250100049	2023.04.07	2024.04.06
Temperature & Humidity	KTJ	TA218B	N.A	2023.04.24	2024.04.23
Testing Software	EMC-I_V1.4.0.3_SKET				

Radiated Test equipment					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Cal. Date**	**Cal. Until**
EMI Test Receiver	R&S	ESU8	100372	2023.04.13	2024.04.12
Active loop Antenna	ETS	6502	00049544	2022.06.02	2025.06.01
Spectrum Analyzer	Keysight	N9010B	MY60242508	2023.04.10	2024.04.09
Bilog Antenna(30M-1G)	SCHWARZBECK	VULB 9168	01447	2022.06.05	2025.06.04
Horn Antenna(1-18G)	SCHWARZBECK	3115	10SL0060	2022.06.02	2025.06.01
Horn Antenna(18-40G)	A-INFO	LB-180400-KF	J211060273	2022.06.08	2025.06.07
Pre-amplifier(30M-1G)	EMtrace	RP01A	02019	2023.04.07	2024.04.06
Pre-amplifier(1-26.5G)	Agilent	8449B	3008A4722	2023.04.07	2024.04.06
Pre-amplifier(18-40G)	com-mw	LNPA_18-40-01	18050003	2023.04.07	2024.04.06
Wireless Communications Test Set	R&S	CMW 500	137737	2023.04.13	2024.04.12
Temperature & Humidity	KTJ	TA218B	N.A	2023.04.24	2024.04.23
Testing Software	EMC-I_V1.4.0.3_SKET				

Conducted Test equipment					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Cal. Date**	**Cal. Until**
Signal Analyzer	Keysight	N9010B	MY60242508	2023.04.10	2024.04.09
Wireless Communications Test Set	R&S	CMW 500	137737	2023.04.13	2024.04.12
MXG Vector Signal Generator	Keysight	N5182B	MY59100717	2023.04.07	2024.04.06
Power Senor	MW	MW100-RFCB	MW220324LG-33	2023.04.13	2024.04.12
Temperature & Humidity	KTJ	TA218B	N.A	2023.04.24	2024.04.23
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2023.05.10	2024.05.09
Attenuator	eastsheep	90db	N.A	2023.04.10	2024.04.09
Testing Software	MTS8200_ V2.0.0.0_MW				

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	**Setting**
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

a. The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN is at least 80 cm from the nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.5 TEST RESULT

Project: LGT23G112	Test Engineer: LiuH
EUT: ATS-25 max-Decoder	Temperature: 27.5℃
M/N: ATS-25 max-Decoder	Humidity: 49%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-07-31
Test Mode: 2.4GHz Wi-Fi TX	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.154	41.59	10.57	52.16	65.78	-13.62	QP	L1
2*	0.174	39.60	10.58	50.18	64.77	-14.59	QP	L1
3*	0.546	32.09	10.58	42.67	56.00	-13.33	QP	L1
4*	1.454	26.95	10.66	37.61	56.00	-18.39	QP	L1
5*	10.930	37.45	10.88	48.33	60.00	-11.67	QP	L1
6*	16.982	36.04	11.18	47.22	60.00	-12.78	QP	L1
7*	0.150	24.84	10.56	35.40	56.00	-20.60	AV	L1
8*	0.182	23.59	10.59	34.18	54.39	-20.22	AV	L1
9*	0.546	21.13	10.58	31.71	46.00	-14.29	AV	L1
10*	0.778	19.05	10.58	29.63	46.00	-16.37	AV	L1
11*	1.698	13.66	10.70	24.36	46.00	-21.64	AV	L1
12*	10.914	23.69	10.88	34.57	50.00	-15.43	AV	L1

Project: LGT23G112	Test Engineer: LiuH
EUT: ATS-25 max-Decoder	Temperature: 27.5℃
M/N: ATS-25 max-Decoder	Humidity: 49%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-07-31
Test Mode: 2.4GHz Wi-Fi TX	
Note:	



No.	Frequency MHz	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	0.150	42.66	10.56	53.22	66.00	-12.78	QP	N
2*	0.542	33.40	10.58	43.98	56.00	-12.02	QP	N
3*	1.518	26.56	10.67	37.23	56.00	-18.77	QP	N
4*	3.378	23.75	10.73	34.48	56.00	-21.52	QP	N
5*	10.590	33.10	10.89	43.99	60.00	-16.01	QP	N
6*	16.958	31.44	11.24	42.68	60.00	-17.32	QP	N
7*	0.154	25.89	10.56	36.45	55.78	-19.33	AV	N
8*	0.546	23.92	10.58	34.50	46.00	-11.50	AV	N
9*	1.310	16.62	10.64	27.26	46.00	-18.74	AV	N
10*	1.998	14.29	10.75	25.04	46.00	-20.96	AV	N
11*	4.746	10.25	10.71	20.96	46.00	-25.04	AV	N
12*	13.110	20.00	11.02	31.02	50.00	-18.98	AV	N

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2310 to 2430 MHz Upper Band Edge: 2445 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

a. The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
b. The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
e. If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.3 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

Please refer to section 3.1.4 of this report.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting theAmplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

Factor=AF+CL-AG

3.2.6 TEST RESULT

Results of Radiated Emissions (9 KHz~30MHz)

No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Remark
1*	-	-	-	-	-	-	-	See Note

Note:

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
Limit line = specific limits (dBuV) + distance extrapolation factor.

Results of Radiated Emissions (30MHz~1000MHz):

Project: LGT23G112	Test Engineer: LiuH
EUT: ATS-25 max-Decoder	Temperature: 27.6℃
M/N: ATS-25 max-Decoder	Humidity: 44%RH
Test Voltage: Battery	Test Data: 2023-08-09
Test Mode: 2.4GHz Wi-Fi TX	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	44.550MHz	2.15	19.23	21.38	40.00	-18.62	PK	Hor
2*	64.556MHz	2.92	18.36	21.28	40.00	-18.72	PK	Hor
3*	149.310MHz	4.79	19.93	24.72	43.50	-18.78	PK	Hor
4*	315.665MHz	4.08	20.41	24.49	46.00	-21.51	PK	Hor
5*	777.506MHz	4.55	30.88	35.43	46.00	-10.57	PK	Hor
6*	971.264MHz	4.12	34.37	38.49	54.00	-15.51	PK	Hor



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	92.444MHz	12.00	15.20	27.20	43.50	-16.30	PK	Ver
2*	120.089MHz	10.77	17.65	28.42	43.50	-15.08	PK	Ver
3*	136.943MHz	11.69	18.88	30.57	43.50	-12.93	PK	Ver
4*	145.551MHz	11.09	19.57	30.66	43.50	-12.84	PK	Ver
5*	312.149MHz	6.06	20.30	26.36	46.00	-19.64	PK	Ver
6*	990.906MHz	4.56	34.53	39.09	54.00	-14.91	PK	Ver

Results of Radiated Emissions (Above 1000MHz):

Note: All the modes have been tested, found worst case at IEEE 802.11g, recorded the worst case results in this report.

Project: LGT23G112	Test Engineer: LiuH
EUT: ATS-25 max-Decoder	Temperature: 27.6℃
M/N: ATS-25 max-Decoder	Humidity: 44%RH
Test Voltage: Battery	Test Data: 2023-08-09
Test Mode: 802.11g 2412	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.3272GHz	62.61	-21.96	40.65	74.00	-33.35	PK	Hor
2*	2.4089GHz	66.43	-11.94	54.49	74.00	-19.51	PK	Hor
3*	3.1399GHz	54.66	-8.39	46.27	74.00	-27.73	PK	Hor
4*	4.6040GHz	54.55	-5.84	48.71	74.00	-25.29	PK	Hor
5*	5.8131GHz	57.33	-7.61	49.72	74.00	-24.28	PK	Hor
6*	11.2786GHz	53.64	1.79	55.43	74.00	-18.57	PK	Hor
7*	17.6175GHz	50.36	8.25	58.61	74.00	-15.39	PK	Hor
8*	11.2786GHz	44.21	1.79	46.00	54.00	-8.00	AV	Hor
9*	17.6175GHz	39.45	8.25	47.70	54.00	-6.30	AV	Hor



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.4484GHz	63.78	-21.12	42.66	74.00	-31.34	PK	Ver
2*	2.4067GHz	65.03	-11.96	53.07	74.00	-20.93	PK	Ver
3*	3.1399GHz	54.41	-8.39	46.02	74.00	-27.98	PK	Ver
4*	4.8207GHz	55.38	-6.00	49.38	74.00	-24.62	PK	Ver
5*	8.4609GHz	54.43	-2.70	51.73	74.00	-22.27	PK	Ver
6*	13.8329GHz	50.13	5.30	55.43	74.00	-18.57	PK	Ver
7*	17.9405GHz	50.27	8.48	58.75	74.00	-15.25	PK	Ver
8*	13.8329GHz	39.10	5.30	44.40	54.00	-9.60	AV	Ver
9*	17.9405GHz	40.92	8.48	49.40	54.00	-4.60	AV	Ver

Project: LGT23G112	Test Engineer: LiuH
EUT: ATS-25 max-Decoder	Temperature: 27.6℃
M/N: ATS-25 max-Decoder	Humidity: 44%RH
Test Voltage: Battery	Test Data: 2023-08-09
Test Mode: 802.11g 2437	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.3272GHz	62.94	-21.96	40.98	74.00	-33.02	PK	Hor
2*	2.4429GHz	67.34	-11.58	55.76	74.00	-18.24	PK	Hor
3*	4.7867GHz	55.36	-5.98	49.38	74.00	-24.62	PK	Hor
4*	8.2526GHz	57.04	-3.29	53.75	74.00	-20.25	PK	Hor
5*	11.3891GHz	53.90	1.86	55.76	74.00	-18.24	PK	Hor
6*	16.3701GHz	52.95	6.84	59.79	74.00	-14.21	PK	Hor
7*	11.3891GHz	44.44	1.86	46.30	54.00	-7.70	AV	Hor
8*	16.3701GHz	40.86	6.84	47.70	54.00	-6.30	AV	Hor



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.5100GHz	62.09	-20.77	41.32	74.00	-32.68	PK	Ver
2*	2.4344GHz	65.75	-11.67	54.08	74.00	-19.92	PK	Ver
3*	4.8016GHz	54.70	-5.99	48.71	74.00	-25.29	PK	Ver
4*	7.5684GHz	55.98	-4.25	51.73	74.00	-22.27	PK	Ver
5*	11.3849GHz	53.23	1.86	55.09	74.00	-18.91	PK	Ver
6*	16.3722GHz	51.27	6.84	58.11	74.00	-15.89	PK	Ver
7*	11.3849GHz	43.54	1.86	45.40	54.00	-8.60	AV	Ver
8*	16.3722GHz	41.86	6.84	48.70	54.00	-5.30	AV	Ver

Project: LGT23G112	Test Engineer: LiuH
EUT: ATS-25 max-Decoder	Temperature: 27.6℃
M/N: ATS-25 max-Decoder	Humidity: 44%RH
Test Voltage: Battery	Test Data: 2023-08-09
Test Mode: 802.11g 2462	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.3272GHz	63.61	-21.96	41.65	74.00	-32.35	PK	Hor
2*	2.4577GHz	67.53	-11.43	56.10	74.00	-17.90	PK	Hor
3*	4.3214GHz	54.74	-6.51	48.23	74.00	-25.77	PK	Hor
4*	5.4434GHz	56.60	-7.56	49.04	74.00	-24.96	PK	Hor
5*	7.5896GHz	56.64	-4.24	52.40	74.00	-21.60	PK	Hor
6*	11.4996GHz	53.17	1.92	55.09	74.00	-18.91	PK	Hor
7*	17.9405GHz	51.31	8.48	59.79	74.00	-14.21	PK	Hor
8*	11.4996GHz	43.78	1.92	45.70	54.00	-8.30	AV	Hor
9*	17.9405GHz	41.92	8.48	50.40	54.00	-3.60	AV	Hor



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.3294GHz	62.25	-21.94	40.31	74.00	-33.69	PK	Ver
2*	2.0476GHz	58.06	-15.73	42.33	74.00	-31.67	PK	Ver
3*	2.4577GHz	65.85	-11.43	54.42	74.00	-19.58	PK	Ver
4*	4.8399GHz	54.39	-6.02	48.37	74.00	-25.63	PK	Ver
5*	6.6695GHz	55.65	-6.27	49.38	74.00	-24.62	PK	Ver
6*	11.2722GHz	52.96	1.79	54.75	74.00	-19.25	PK	Ver
7*	17.9447GHz	49.87	8.48	58.35	74.00	-15.65	PK	Ver
8*	11.2722GHz	43.91	1.79	45.70	54.00	-8.30	AV	Ver
9*	17.9447GHz	41.22	8.48	49.70	54.00	-4.30	AV	Ver

Remark:
In frequency ranges 18~25GHz no any other harmonic emissions detected which are tested to compliance with the limit. No recording in the test report. No any other emissions level which are attenuated less than 20dB below the limit. No recording in the test report.

3.2.7 TEST RESULTS(Band edge Requirements)

Project: LGT23G112	Test Engineer: LiuH
EUT: ATS-25 max-Decoder	Temperature: 27.6℃
M/N: ATS-25 max-Decoder	Humidity: 44%RH
Test Voltage: Battery	Test Data: 2023-08-09
Test Mode: 802.11g 2412	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2.3462GHz	17.23	34.06	51.29	74.00	-22.71	PK	Hor
2*	2.3900GHz	13.25	33.95	47.20	74.00	-26.80	PK	Hor



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2.3141GHz	18.06	34.13	52.19	74.00	-21.81	PK	Ver
2*	2.3900GHz	13.45	33.95	47.40	74.00	-26.60	PK	Ver

Project: LGT23G112	Test Engineer: LiuH
EUT: ATS-25 max-Decoder	Temperature: 27.6℃
M/N: ATS-25 max-Decoder	Humidity: 44%RH
Test Voltage: Battery	Test Data: 2023-08-09
Test Mode: 802.11g 2462	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2.4835GHz	14.87	34.13	49.00	74.00	-25.00	PK	Hor
2*	2.4964GHz	17.10	34.16	51.26	74.00	-22.74	PK	Hor



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2.4835GHz	12.97	34.13	47.10	74.00	-26.90	PK	Ver
2*	2.4948GHz	17.27	34.15	51.42	74.00	-22.58	PK	Ver

4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2432 MHz Upper Band Edge: 2442 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.
Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

4.6 TEST RESULTS

For the measurement records, refer to the appendix I.

5. POWER SPECTRAL DENSITY TEST

5.1 LIMIT

FCC Part15.247 , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤8 dBm (RBW ≥3KHz)	2400-2483.5	PASS

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the 100 kHz ≥ RBW ≥3 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

5.6 TEST RESULTS

For the measurement records, refer to the appendix I.

6. BANDWIDTH TEST

6.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	≥500KHz (6dB bandwidth)	2400-2483.5	PASS

6.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW≥3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be≥6 dB.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP

6.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

6.6 TEST RESULTS

For the measurement records, refer to the appendix I.

7. PEAK OUTPUT POWER TEST

7.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2 TEST PROCEDURE

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

RBW ≥ DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

a) Set the RBW ≥ DTS bandwidth.
b) Set VBW ≥ [3 × RBW].
c) Set span ≥ [3 × RBW].
d) Sweep time = auto couple.
e) Detector = peak.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use peak marker function to determine the peak amplitude level.

Integrated band power method:

The following procedure can be used when the maximum available RBW of the instrument is less than the

DTS bandwidth:

a) Set the RBW = 1 MHz.
b) Set the VBW ≥ [3 × RBW].
c) Set the span ≥ [1.5 × DTS bandwidth].
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel bandwidth.

PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

7.6 TEST RESULTS

For the measurement records, refer to the appendix I.

8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible partyshall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is Dipole Antenna. It comply with the standard requirement.

APPENDIX I:TEST RESULTS

Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	Ant1	100	0	0
NVNT	b	2437	Ant1	100	0	0
NVNT	b	2462	Ant1	100	0	0
NVNT	g	2412	Ant1	100	0	0
NVNT	g	2437	Ant1	100	0	0
NVNT	g	2462	Ant1	100	0	0
NVNT	n20	2412	Ant1	100	0	0
NVNT	n20	2437	Ant1	100	0	0
NVNT	n20	2462	Ant1	100	0	0
NVNT	n40	2422	Ant1	100	0	0
NVNT	n40	2437	Ant1	100	0	0
NVNT	n40	2452	Ant1	100	0	0

Test Graphs
Duty Cycle NVNT b 2412MHz Ant1



Duty Cycle NVNT b 2437MHz Ant1



Duty Cycle NVNT b 2462MHz Ant1

Duty Cycle NVNT g 2412MHz Ant1



Duty Cycle NVNT g 2437MHz Ant1

Duty Cycle NVNT g 2462MHz Ant1



Duty Cycle NVNT n20 2412MHz Ant1

Duty Cycle NVNT n20 2437MHz Ant1

Duty Cycle NVNT n20 2462MHz Ant1

Duty Cycle NVNT n40 2422MHz Ant1



Duty Cycle NVNT n40 2437MHz Ant1

Duty Cycle NVNT n40 2452MHz Ant1

Maximum Peak Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	15.86	30	Pass
NVNT	b	2437	Ant1	15.56	30	Pass
NVNT	b	2462	Ant1	14.84	30	Pass
NVNT	g	2412	Ant1	17.25	30	Pass
NVNT	g	2437	Ant1	17.16	30	Pass
NVNT	g	2462	Ant1	16.88	30	Pass
NVNT	n20	2412	Ant1	17.13	30	Pass
NVNT	n20	2437	Ant1	17.14	30	Pass
NVNT	n20	2462	Ant1	16.68	30	Pass
NVNT	n40	2422	Ant1	16.66	30	Pass
NVNT	n40	2437	Ant1	16.44	30	Pass
NVNT	n40	2452	Ant1	16.59	30	Pass

-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	9.079	0.5	Pass
NVNT	b	2437	Ant1	9.084	0.5	Pass
NVNT	b	2462	Ant1	9.101	0.5	Pass
NVNT	g	2412	Ant1	16.403	0.5	Pass
NVNT	g	2437	Ant1	16.407	0.5	Pass
NVNT	g	2462	Ant1	16.393	0.5	Pass
NVNT	n20	2412	Ant1	17.322	0.5	Pass
NVNT	n20	2437	Ant1	17.34	0.5	Pass
NVNT	n20	2462	Ant1	17.352	0.5	Pass
NVNT	n40	2422	Ant1	33.581	0.5	Pass
NVNT	n40	2437	Ant1	33.302	0.5	Pass
NVNT	n40	2452	Ant1	33.144	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1

-6dB Bandwidth NVNT b 2437MHz Ant1

-6dB Bandwidth NVNT b 2462MHz Ant1

-6dB Bandwidth NVNT g 2412MHz Ant1



-6dB Bandwidth NVNT g 2437MHz Ant1

-6dB Bandwidth NVNT g 2462MHz Ant1

-6dB Bandwidth NVNT n20 2412MHz Ant1

-6dB Bandwidth NVNT n20 2437MHz Ant1

-6dB Bandwidth NVNT n20 2462MHz Ant1

-6dB Bandwidth NVNT n40 2422MHz Ant1

-6dB Bandwidth NVNT n40 2437MHz Ant1

-6dB Bandwidth NVNT n40 2452MHz Ant1

Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	b	2412	Ant1	13.076
NVNT	b	2437	Ant1	13.066
NVNT	b	2462	Ant1	13.075
NVNT	g	2412	Ant1	16.489
NVNT	g	2437	Ant1	16.506
NVNT	g	2462	Ant1	16.521
NVNT	n20	2412	Ant1	17.38
NVNT	n20	2437	Ant1	17.385
NVNT	n20	2462	Ant1	17.389
NVNT	n40	2422	Ant1	34.735
NVNT	n40	2437	Ant1	34.676
NVNT	n40	2452	Ant1	34.736

Test Graphs

OBW NVNT b 2412MHz Ant1

OBW NVNT b 2437MHz Ant1

OBW NVNT b 2462MHz Ant1

OBW NVNT g 2412MHz Ant1



OBW NVNT g 2437MHz Ant1

OBW NVNT g 2462MHz Ant1

OBW NVNT n20 2412MHz Ant1



OBW NVNT n20 2437MHz Ant1

OBW NVNT n20 2462MHz Ant1

OBW NVNT n40 2422MHz Ant1



OBW NVNT n40 2437MHz Ant1

OBW NVNT n40 2452MHz Ant1

Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	Ant1	-10.1	8	Pass
NVNT	b	2437	Ant1	-10.2	8	Pass
NVNT	b	2462	Ant1	-10.94	8	Pass
NVNT	g	2412	Ant1	-15.18	8	Pass
NVNT	g	2437	Ant1	-15.25	8	Pass
NVNT	g	2462	Ant1	-15.74	8	Pass
NVNT	n20	2412	Ant1	-15.2	8	Pass
NVNT	n20	2437	Ant1	-15.34	8	Pass
NVNT	n20	2462	Ant1	-15.59	8	Pass
NVNT	n40	2422	Ant1	-16.27	8	Pass
NVNT	n40	2437	Ant1	-16.7	8	Pass
NVNT	n40	2452	Ant1	-16.58	8	Pass

Test Graphs
PSD NVNT b 2412MHz Ant1

PSD NVNT b 2437MHz Ant1

PSD NVNT b 2462MHz Ant1

PSD NVNT g 2412MHz Ant1

PSD NVNT g 2437MHz Ant1



PSD NVNT g 2462MHz Ant1



PSD NVNT n20 2412MHz Ant1

PSD NVNT n20 2437MHz Ant1



PSD NVNT n20 2462MHz Ant1



PSD NVNT n40 2422MHz Ant1



PSD NVNT n40 2437MHz Ant1



PSD NVNT n40 2452MHz Ant1

Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-57.62	-20	Pass
NVNT	b	2462	Ant1	-55.2	-20	Pass
NVNT	g	2412	Ant1	-39.32	-20	Pass
NVNT	g	2462	Ant1	-50.1	-20	Pass
NVNT	n20	2412	Ant1	-39.82	-20	Pass
NVNT	n20	2462	Ant1	-49.78	-20	Pass
NVNT	n40	2422	Ant1	-36.42	-20	Pass
NVNT	n40	2452	Ant1	-43.99	-20	Pass

Test Graphs

Band Edge NVNT b 2412MHz Ant1 Ref



Band Edge NVNT b 2412MHz Ant1 Emission

Band Edge NVNT b 2462MHz Ant1 Ref

Band Edge NVNT b 2462MHz Ant1 Emission



Band Edge NVNT g 2412MHz Ant1 Ref

Band Edge NVNT g 2412MHz Ant1 Emission

Band Edge NVNT g 2462MHz Ant1 Ref

Band Edge NVNT g 2462MHz Ant1 Emission

Band Edge NVNT n20 2412MHz Ant1 Ref

Band Edge NVNT n20 2412MHz Ant1 Emission



Band Edge NVNT n20 2462MHz Ant1 Ref

Band Edge NVNT n20 2462MHz Ant1 Emission

Band Edge NVNT n40 2422MHz Ant1 Ref

Band Edge NVNT n40 2422MHz Ant1 Emission

Band Edge NVNT n40 2452MHz Ant1 Ref



Band Edge NVNT n40 2452MHz Ant1 Emission



Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-50.93	-20	Pass
NVNT	b	2437	Ant1	-51.6	-20	Pass
NVNT	b	2462	Ant1	-51.66	-20	Pass
NVNT	g	2412	Ant1	-43.87	-20	Pass
NVNT	g	2437	Ant1	-43.85	-20	Pass
NVNT	g	2462	Ant1	-44.84	-20	Pass
NVNT	n20	2412	Ant1	-43.41	-20	Pass
NVNT	n20	2437	Ant1	-45.02	-20	Pass
NVNT	n20	2462	Ant1	-45.33	-20	Pass
NVNT	n40	2422	Ant1	-40.5	-20	Pass
NVNT	n40	2437	Ant1	-40.48	-20	Pass
NVNT	n40	2452	Ant1	-41	-20	Pass

Test Graphs

Tx. Spurious NVNT b 2412MHz Ant1 Ref



Tx. Spurious NVNT b 2412MHz Ant1 Emission



Tx. Spurious NVNT b 2437MHz Ant1 Ref



Tx. Spurious NVNT b 2437MHz Ant1 Emission



Tx. Spurious NVNT b 2462MHz Ant1 Ref

Tx. Spurious NVNT b 2462MHz Ant1 Emission

Tx. Spurious NVNT g 2412MHz Ant1 Ref

Tx. Spurious NVNT g 2412MHz Ant1 Emission



Tx. Spurious NVNT g 2437MHz Ant1 Ref



Tx. Spurious NVNT g 2437MHz Ant1 Emission



Tx. Spurious NVNT g 2462MHz Ant1 Ref

Tx. Spurious NVNT g 2462MHz Ant1 Emission



Tx. Spurious NVNT n20 2412MHz Ant1 Ref



Tx. Spurious NVNT n20 2412MHz Ant1 Emission



Tx. Spurious NVNT n20 2437MHz Ant1 Ref

Tx. Spurious NVNT n20 2437MHz Ant1 Emission



Tx. Spurious NVNT n20 2462MHz Ant1 Ref

Tx. Spurious NVNT n20 2462MHz Ant1 Emission

Tx. Spurious NVNT n40 2422MHz Ant1 Ref



Tx. Spurious NVNT n40 2422MHz Ant1 Emission



Tx. Spurious NVNT n40 2437MHz Ant1 Ref

Tx. Spurious NVNT n40 2437MHz Ant1 Emission



Tx. Spurious NVNT n40 2452MHz Ant1 Ref

Tx. Spurious NVNT n40 2452MHz Ant1 Emission

※※※※※END OF THE REPORT※※※※※