Test Report

Product: smart speaker

Trade Mark: N/A

Model Number: N73

FCC ID: 2BCC6-N73

Prepared for

Shenzhen Nuohao Technology Co., Ltd

2nd Floor, Building B, Jiaye Industrial Park, No.11Jiaye Road, Pinghu Town, Longgang District, Shenzhen, China

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd

Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China

Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110

Website: http://www.sz-hongbiao.com

Table of Contents

1 GENERAL DESCRIPTION 6

1.1 DESCRIPTION OF EUT 6
1.2 TEST MODE 6
1.3 OPERATION CHANNEL LIST 7
1.4 TEST SETUP 7
1.5 POWER SETTING CONFIGURATION PARAMETERS 7
1.6 ANCILLARY EQUIPMENT 7

2 SUMMARY OF TEST RESULT 8

3 TEST FACILITIES AND ACCREDITATIONS 9

3.1 TEST LABORATORY 9
3.2 ENVIRONMENTAL CONDITIONS 9
3.3 MEASUREMENT UNCERTAINTY 9
3.4 TEST SOFTWARE 10

4 LIST OF TEST EQUIPMENT 11

5 TEST ITEM AND RESULTS 13

5.1 ANTENNA REQUIREMENT 13
5.1.1 Standard Requirement *13*
5.1.2 Test Result *13*
5.2 CONDUCTED EMISSION 14
5.2.1 Limits *14*
5.2.2 Test Procedures *14*
5.2.3 Test Setup *15*
5.2.4 Test Result *15*
5.3 RADIATED EMISSION 18
5.3.1 Limits *18*
5.3.2 Test Procedures *18*
5.3.3 Test Setup *18*
5.3.4 Test Result *19*
5.3.5 Band Edge - Radiated *23*
5.3.6 Spurious emission in restricted band 1000MHz-25000MHz *24*
5.4 PEAK OUTPUT POWER 25
5.4.1 Limit *25*
5.4.2 Test Procedure *25*
5.4.3 Test Setup *25*
5.4.4 Test Results *25*
5.5 POWER SPECTRAL DENSITY 28
5.5.1 Limit *28*
5.5.2 Test Procedure *28*
5.5.3 Test Setup *28*
5.5.4 Test Results *28*
5.6 6DB BANDWIDTH 31
5.6.1 Limit *31*
5.6.2 Test Procedure *31*
5.6.3 Test Setup *31*
5.6.4 Test Results *31*
5.7 DUTY CYCLE 34
5.7.1 Limit *34*
5.7.2 Test Procedure *34*
5.7.3 Test Setup *34*
5.7.4 Test Results *34*
5.8 CONDUCTED BAND EDGE 39

5.8.1 Limit *39*
5.8.2 Test Procedure *39*
5.8.3 Test Setup *39*
5.8.4 Test Results *39*
5.9 SPURIOUS RF CONDUCTED EMISSIONS 42
5.9.1 Limit *42*
5.9.2 Measuring Instruments *42*
5.9.3 Test Procedure *42*
5.9.4 Test Setup *42*
5.9.5 Test Results *42*
6 PHOTOGRAPHS OF THE TEST SETUP 45
7 PHOTOGRAPHS OF THE EUT 47

TEST RESULT CERTIFICATION

Applicant's Name	:	Shenzhen Nuohao Technology Co., Ltd
Address	:	2nd Floor, Building B, Jiaye Industrial Park, No.11Jiaye Road, Pinghu Town, Longgang District, Shenzhen, China
Manufacturer's Name	:	Shenzhen Nuohao Technology Co., Ltd
Address	:	2nd Floor, Building B, Jiaye Industrial Park, No.11Jiaye Road, Pinghu Town, Longgang District, Shenzhen, China

Product description

Product name	:	smart speaker
Model Number	:	N73
Standards	:	FCC Part 15.247
Test procedure	:	IEEE/ANSI C63.10-2020 KDB 558074 D01 15.247 Meas Guidance v05r02

This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test

Date (s) of performance of tests	:	Oct. 21, 2025~Nov. 27, 2025
Test Result	:	**Pass**

Testing Engineer : Zoe Su

(Z o e S u)

Technical Manager : Gary Lu

(G a r y L u)

Authorized Signatory : Leo Su

(L e o S u)

Revision History

Revised No.	Date of Issue	Description
01	Nov. 27, 2025	Original

1 General Description

1.1 Description of EUT

Product name:	smart speaker
Model name:	N73
Series Model:	N73-1, N73-2, N73-3, N73-4, N73-5, N73-6, N76, NH-73, X82, X132, 965
Different of series model:	Except for the model and appearance color, the circuits and modules of all models are the same.
Operation frequency:	2402-2480MHz
Modulation type:	GFSK
Bit Rate of transmitter:	1 Mbps, 2 Mbps
Antenna type:	PCB Antenna
Antenna gain:	-0.68dBi
Max. output power:	-0.91dBm
Hardware version:	V1.0
Software version:	V1.0
Battery:	DC 3.7V, 2600mAh, 9.62Wh
Power supply:	Input voltage: 5V⎓2A, 9V⎓2A Speaker power: 10W Wireless Output: 15W
Adapter information:	N/A

1.2 Test Mode

Test Mode	Channel	Frequency (MHz)
BLE 1M	00	2402
BLE 1M	19	2440
BLE 1M	39	2480
BLE 2M	00	2402
BLE 2M	19	2440
BLE 2M	39	2480

1.3 Operation Channel list

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

1.4 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.5 Power setting configuration parameters

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters.

Test software Version		FCC_assist_1.0.2.2	
Frequency	2402 MHz	2440 MHz	2480 MHz
Parameters	Default	Default	Default
RF cable			
Description	Connector	Length	Supplied by
Antenna Cable	SMA	10cm	Applicant

Note: Disclaimer: the loss of RF cable is too small and can be ignored.

1.6 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
Adapter	CD289	35810	Ugreen Group Limited
Laptop	BDR-WDH	A3RQPM242 0002411	Honor Terminal Co., Ltd.

Note: The laptop is used to assist the RF test. In order to prevent the laptop from causing unnecessary impact on the test, the laptop will be removed from the test environment after the EUT successfully transmits at a fixed frequency using the laptop.

2 Summary of Test Result

No.	Standard Section	Test Item	Result	Remark
1	15.203	Antenna Requirement	Pass	
2	15.247 (b)	Peak Output Power	Pass	
3	15.207	Conducted Emission	Pass	
4	15.247 (d) & 15.209	Radiated Spurious Emission	Pass	
5	15.247 (e)	Power Spectral Density	Pass	
6	15.247 (a)(2)	6dB Bandwidth	Pass	
7	558074 D01 15.247 Meas Guidance v05r02 Chapter 6	Duty Cycle	Pass	
8	15.205	Band Edge Emission	Pass	
9	15.247(d)	Spurious RF Conducted Emissions	Pass	

3 Test Facilities and Accreditations

3.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

3.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15ºC~35ºC
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

3.3 Measurement Uncertainty

The reported uncertainty of measurement y ± U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.
The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.
In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2x 10^{-5}	
RF power, conducted	± 0.57 dB	
Conducted emission(150kHz~30MHz)	± 2.5 dB	
Radiated emission(9kHz-30MHz)	± 2.5 dB	
Radiated emission(30MHz~1GHz)	± 4.2 dB	
Radiated emission (above 1GHz)	± 4.7 dB	
Occupied Bandwidth	±3%	
Temperature	±1 degree	
Humidity	± 5 %	

3.4 Test Software

Software name	Manufacturer	Model	Version
Conducted Emission test Software	Farad	EZ-EMC	EMC-CON 3A1.1+
Radiated Emission test Software	Farad	EZ-EMC	FA-03A2
RF Test System	MWRF	MTS 8310	2.0.0.0

4 List of Test Equipment

Radiation emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E001	Horn Antenna	Schwarzbeck	BBHA 9120D	02592	2024-05-18	2026-05-17
2	HB-E002	Biconical log-periodic composite antenna	Schwarzbeck	VULB 9168	01340	2024-05-18	2026-05-17
3	HB-E003	SHF-EHF Horn	Schwarzbeck	BBHA 9170	01193	2024-05-18	2026-05-17
4	HB-E005	Preamplifier	Noyetec	LAN-0118	NYCM1420102	2025-05-07	2026-05-06
5	HB-E006	Preamplifier	Noyetec	LAN-1840	NYCM1420103	2025-05-07	2026-05-06
6	HB-E007	EMI TEST RECEIVER	R&S	ESR7	102520	2025-05-07	2026-05-06
7	HB-E009	POSITINAL COTROLLER	Noyetec	N/A	N/A	/	/
8	HB-E013	RF switch	Noyetec	NY-RF4	NY0CM1420204	/	/
9	HB-E066	Illuminance Tester	TASI	TA8121	N/A	2025-05-13	2026-05-12
10	HB-E075	Active loop antenna	Schwarzbeck	FMZB 1519B	1519B-245	2024-05-18	2026-05-17
11	HB-E076	Preamplifier	Hewlett Packard	8447D	1937A02278	2025-05-07	2026-05-06
Conduction emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E014	4 Path V-LISN	Schwarzbeck	NNLK 8121	00770	2025-05-07	2026-05-06
2	HB-E015	Pulse Limiter	Schwarzbeck	VTSD 9561-F	00949	2025-05-07	2026-05-06
3	HB-E016	Absorb clamp	ZHINAN	ZN23201	N/A	2025-05-10	2026-05-09
4	HB-E059	Attenuator	Xianghua	TS2-6-1	220215166	2025-05-10	2026-05-09
5	HB-E069	EMI TEST RECEIVER	R&S	ESCI	N/A	2025-05-07	2026-05-06

RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG Anaiog Signal Generator	Agilent	N5181A	MY47070421	2025-05-07	2026-05-06
2	HB-E042	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW500	132108	2025-05-08	2026-05-07

3	HB-E043	MXG Anaiog Signal Generator	Agilent	N5182A	US46240335	2025-05-08	2026-05-07
4	HB-E044	Signal& spectrum Analyzer	R&S	FSV3044	101264	2025-05-07	2026-05-06
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	2025-05-08	2026-05-07
6	HB-E058	Thermometer Clock Humidity Monitor	N/A	HTC-1S	N/A	2025-05-09	2026-05-08

Note: the calibration interval of the above test instruments is 12&24 months and the calibrations are traceable to international system unit (SI).

5 Test Item And Results

5.1 Antenna Requirement

5.1.1 Standard Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 Test Result

The EUT antenna is PCB Antenna. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

5.2 Conducted Emission

5.2.1 Limits

Limits – Class B		
Frequency (MHz)	Limit (dBμV)	
	Quasi-Peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

Note:
1. the tighter limit applies at the band edges.
2. the limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

5.2.2 Test Procedures

a) EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item – photographs of the test setup.

5.2.3 Test Setup



5.2.4 Test Result

EUT:	smart speaker	Model Name:	N73
Test Mode:	Charging + TX	Phase:	L
Test Voltage:	DC 9V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.335	27.93	10.09	38.02	59.33	-21.31	QP
2	0.335	25.79	10.09	35.88	49.33	-13.45	AVG
3	1.005	30.71	10.13	40.84	56.00	-15.16	QP
4 *	1.005	26.60	10.13	36.73	46.00	-9.27	AVG
5	1.675	30.67	10.28	40.95	56.00	-15.05	QP
6	1.675	24.69	10.28	34.97	46.00	-11.03	AVG
7	2.346	29.97	10.45	40.42	56.00	-15.58	QP
8	2.346	21.43	10.45	31.88	46.00	-14.12	AVG
9	3.692	28.69	10.84	39.53	56.00	-16.47	QP
10	3.692	20.53	10.84	31.37	46.00	-14.63	AVG
11	21.116	23.00	14.80	37.80	60.00	-22.20	QP
12	21.116	20.14	14.80	34.94	50.00	-15.06	AVG

EUT:	smart speaker	Model Name:	N73
Test Mode:	Charging + TX	Phase:	N
Test Voltage:	DC 9V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.335	28.59	10.13	38.72	59.33	-20.61	QP
2	0.335	25.84	10.13	35.97	49.33	-13.36	AVG
3	0.897	21.82	10.12	31.94	56.00	-24.06	QP
4	0.897	20.65	10.12	30.77	46.00	-15.23	AVG
5	1.005	27.21	10.13	37.34	56.00	-18.66	peak
6 *	1.005	25.35	10.13	35.48	46.00	-10.52	AVG
7	1.675	29.05	10.28	39.33	56.00	-16.67	QP
8	1.675	21.11	10.28	31.39	46.00	-14.61	AVG
9	3.683	28.93	10.83	39.76	56.00	-16.24	QP
10	3.683	20.31	10.83	31.14	46.00	-14.86	AVG
11	4.357	29.27	11.10	40.37	56.00	-15.63	QP
12	4.357	20.10	11.10	31.20	46.00	-14.80	AVG

5.3 Radiated Emission

5.3.1 Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.3.2 Test Procedures

a) The radiated emission tests were performed in the 3 meters.
b) The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
c) The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d) If the peak mode measured value compliance with and lower than quasi peak mode limit, the EUT shall be deemed to meet QP limits and then no additional QP mode measurement performed.
e) If the peak mode measured value compliance with and lower than average mode limit, the EUT shall be deemed to meet average limits and then no additional average mode measurement performed.
f) For the actual test configuration, please refer to the related item – EUT test photos.

5.3.3 Test Setup

Radiated Emission Test-Up Frequency Below 30MHz



Radiated Emission Test-Up Frequency 30MHz~1GHz



Radiated emission test-up frequency above 1GHz



5.3.4 Test Result

Below 30MHz

EUT:	smart speaker	Model Name:	N73
Pressure:	1010 hPa	Test Voltage:	DC 3.7V from battery
Test Mode:	TX	Polarization:	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass

Note:

1. For 9kHz-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor =40 log (specific distance/test distance)(dB);
3. Limit line = specific limits (dBuV) + distance extrapolation factor.

Frequency range (30MHz – 1GHz)

EUT:	smart speaker	Model Name:	N73
Test Mode:	TX	Phase:	Vertical
Test Voltage:	DC 9V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	47.8260	47.31	-14.02	33.29	40.00	-6.71	QP
2 *	56.7916	48.22	-14.43	33.79	40.00	-6.21	QP
3	139.3608	46.81	-14.16	32.65	43.50	-10.85	QP
4	159.7844	45.99	-13.27	32.72	43.50	-10.78	QP
5	319.9368	45.88	-12.01	33.87	46.00	-12.13	QP
6	545.1825	40.74	-6.23	34.51	46.00	-11.49	QP

EUT:	smart speaker	Model Name:	N73
Test Mode:	TX	Phase:	Horizontal
Test Voltage:	DC 9V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	56.3947	37.74	-14.40	23.34	40.00	-16.66	QP
2	73.1025	37.59	-16.50	21.09	40.00	-18.91	QP
3	141.3296	40.00	-14.06	25.94	43.50	-17.56	QP
4	189.7384	41.56	-16.06	25.50	43.50	-18.00	QP
5 *	319.9368	48.42	-12.01	36.41	46.00	-9.59	QP
6	547.0976	35.51	-6.18	29.33	46.00	-16.67	QP

5.3.5 Band Edge - Radiated

Frequency (MHz)	Meter Reading (dBμV)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
GFSK(2M)									
2310.00	45.97	3.40	27.80	32.41	44.76	74	-29.24	Pk	Horizontal
2310.00	33.38	3.40	27.80	32.41	32.17	54	-21.83	AV	Horizontal
2310.00	44.93	3.40	27.80	32.41	43.72	74	-30.28	Pk	Vertical
2310.00	33.55	3.40	27.80	32.41	32.34	54	-21.66	AV	Vertical
2390.00	45.65	3.45	27.70	32.49	44.31	74	-29.69	Pk	Vertical
2390.00	34.54	3.45	27.70	32.49	33.20	54	-20.80	AV	Vertical
2390.00	46.16	3.45	27.70	32.49	44.82	74	-29.18	Pk	Horizontal
2390.00	34.47	3.45	27.70	32.49	33.13	54	-20.87	AV	Horizontal
2400.00	46.72	3.46	27.80	32.54	45.44	74	-28.56	Pk	Vertical
2400.00	34.61	3.46	27.80	32.54	33.33	54	-20.67	AV	Vertical
2400.00	45.95	3.46	27.80	32.54	44.67	74	-29.33	Pk	Horizontal
2400.00	34.46	3.46	27.80	32.54	33.18	54	-20.82	AV	Horizontal
2483.50	47.27	3.48	28.53	32.55	46.73	74	-27.27	Pk	Vertical
2483.50	33.98	3.48	28.53	32.55	33.44	54	-20.56	AV	Vertical
2483.50	46.37	3.48	28.53	32.55	45.83	74	-28.17	Pk	Horizontal
2483.50	33.81	3.48	28.53	32.55	33.27	54	-20.73	AV	Horizontal
2500.00	45.27	3.49	29.20	32.66	45.30	74	-28.70	Pk	Vertical
2500.00	33.75	3.49	29.20	32.66	33.78	54	-20.22	AV	Vertical
2500.00	45.22	3.49	29.20	32.66	45.25	74	-28.75	Pk	Horizontal
2500.00	33.70	3.49	29.20	32.66	33.73	54	-20.27	AV	Horizontal

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level – Limit
2. All the modulation modes have been tested, and only the worst results are reflected in the report.

5.3.6 Spurious emission in restricted band 1000MHz-25000MHz

Frequency (MHz)	Reading Level (dBμV)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
Low Channel (2402 MHz)(GFSK 2M)--Above 1G									
4804.338	42.78	4.83	33.5	30.80	50.31	74.00	-23.69	Pk	Vertical
4804.338	31.66	4.83	33.5	30.80	39.19	54.00	-14.81	AV	Vertical
7206.107	42.91	5.83	37.79	31.40	55.13	74.00	-18.87	Pk	Horizontal
7206.107	32.02	5.83	37.79	31.40	44.24	54.00	-9.76	AV	Horizontal
4804.169	42.84	4.83	33.5	30.80	50.37	74.00	-23.63	Pk	Vertical
4804.169	31.89	4.83	33.5	30.80	39.42	54.00	-14.58	AV	Vertical
7206.214	42.79	5.83	37.79	31.40	55.01	74.00	-18.99	Pk	Horizontal
7206.214	32.08	5.83	37.79	31.40	44.30	54.00	-9.70	AV	Horizontal
Mid Channel (2440 MHz)(GFSK 2M)--Above 1G									
4880.473	44.12	4.89	33.76	30.80	51.97	74.00	-22.03	Pk	Vertical
4880.473	31.91	4.89	33.76	30.80	39.76	54.00	-14.24	AV	Vertical
7320.265	44.52	5.95	38.25	31.70	57.02	74.00	-16.98	Pk	Horizontal
7320.265	32.99	5.95	38.25	31.70	45.49	54.00	-8.51	AV	Horizontal
4880.366	43.79	4.89	33.76	30.80	51.64	74.00	-22.36	Pk	Vertical
4880.366	31.90	4.89	33.76	30.80	39.75	54.00	-14.25	AV	Vertical
7320.234	43.99	5.95	38.25	31.70	56.49	74.00	-17.51	Pk	Horizontal
7320.234	32.80	5.95	38.25	31.70	45.30	54.00	-8.70	AV	Horizontal
High Channel (2480 MHz)(GFSK 2M)-- Above 1G									
4960.482	42.78	4.95	34.33	30.80	51.26	74.00	-22.74	Pk	Vertical
4960.482	32.11	4.95	34.33	30.80	40.59	54.00	-13.41	AV	Vertical
7440.131	43.38	6.11	37.60	31.74	55.35	74.00	-18.65	Pk	Horizontal
7440.131	32.16	6.11	37.60	31.74	44.13	54.00	-9.87	AV	Horizontal
4960.326	42.75	4.95	34.33	30.80	51.23	74.00	-22.77	Pk	Vertical
4960.326	32.04	4.95	34.33	30.80	40.52	54.00	-13.48	AV	Vertical
7440.199	43.19	6.11	37.60	31.74	55.16	74.00	-18.84	Pk	Horizontal
7440.199	32.44	6.11	37.60	31.74	44.41	54.00	-9.59	AV	Horizontal

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. All the modulation modes have been tested, and only the worst results are reflected in the report.

5.4 Peak Output Power

5.4.1 Limit

FCC Part15 Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(3)	Peak output power	1 watt or 30dBm	2400-2483.5

5.4.2 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting:

RBW=2MHz, VBW=10MHz, Detector=Peak

(3) The EUT was set to continuously transmitting in the max power during the test.

5.4.3 Test Setup



5.4.4 Test Results

EUT:	smart speaker	Model Name:	N73
Test Mode:	TX Mode	Test Voltage:	DC 3.7V from battery

BLE 1M			
Test Channel	Frequency (MHz)	Maximum Peak Output Power(dBm)	Limit (dBm)
CH00	2402	-1.18	30
CH19	2440	-1.03	30
CH39	2480	-1.33	30

BLE 2M			
Test Channel	Frequency (MHz)	Maximum Peak Output Power(dBm)	Limit (dBm)
CH00	2402	-1.1	30
CH19	2440	-0.91	30
CH39	2480	-1.21	30

BLE 1M	
GFSK on Channel 00	GFSK on Channel 19
	
GFSK on Channel 39	/
	/

BLE 2M	
GFSK on Channel 00	GFSK on Channel 19
	
GFSK on Channel 39	/
	/

5.5 Power Spectral Density

5.5.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247	Power Spectral Density	8 dBm (in any 3kHz)	2400-2483.5

5.5.2 Test Procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.5.3 Test Setup



5.5.4 Test Results

EUT:	smart speaker	Model Name:	N73
Pressure:	1015 hPa	Test Voltage:	DC 3.7V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		

BLE 1M			
Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2402 MHz	-17.68	8	Pass
2440 MHz	-17.4	8	Pass
2480 MHz	-17.93	8	Pass

GFSK on Channel 00	GFSK on Channel 19
	
GFSK on Channel 39	/
	/

BLE 2M			
Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2402 MHz	-20.81	8	Pass
2440 MHz	-20.53	8	Pass
2480 MHz	-20.94	8	Pass

GFSK on Channel 00	GFSK on Channel 19
	
GFSK on Channel 39	/
	/

5.6 6dB Bandwidth

5.6.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	>= 500kHz (6dB bandwidth)	2400-2483.5

5.6.2 Test Procedure

1. Set RBW= shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = No faster than coupled (auto) time.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.6.3 Test Setup



5.6.4 Test Results

EUT:	smart speaker	Model Name:	N73
Pressure:	1012 hPa	Test Voltage:	DC 3.7V from battery
Test Mode:	GFSK/ CH00, CH19, CH39		

BLE 1M				
Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	659	500	Pass
Middle	2440	664	500	Pass
High	2480	662	500	Pass

Test plots

GFSK on Channel 00	GFSK on Channel 19
	
GFSK on Channel 39	/
	/

BLE 2M				
Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	1165	500	Pass
Middle	2440	1216	500	Pass
High	2480	1163	500	Pass

Test plots

GFSK on Channel 00	GFSK on Channel 19
	
GFSK on Channel 39	/
	/

5.7 Duty Cycle

5.7.1 Limit

No limit requirement.

5.7.2 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set VBW ≥ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0(b) in KDB 558074 D01 DTS Meas Guidance v05r02.

The largest availble value of RBW is 10 MHz and VBW is 10 MHz. The zero-span method of measuring duty cycle shall not be used if T ≤ 6.25 microseconds. (50/6.25 = 8)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are > 50/T.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT was operating in controlled its channel.
Use the following spectrum analyzer settings:
Span = Zero Span
RBW = 10MHz (the largest available value)
VBW = 10MHz (≥ RBW)
Number of points in Sweep >100
Detector function = peak
Trace = Clear write
Measure Total and Ton
Calculate Duty Cycle = Ton / Total

5.7.3 Test Setup



5.7.4 Test Results

EUT:	smart speaker	Model Name:	N73
Pressure:	1012 hPa	Test Voltage:	DC 3.7V from battery
Test Mode:	TX Mode /CH00, CH19, CH39		

Mode	Data rate	Frequency (MHz)	T_{on} (ms)	T_{total} (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
BLE 1M	1Mbps	2402	2.129	2.501	85.14	0.7	0.47
BLE 1M	1Mbps	2440	2.129	2.500	85.14	0.7	0.47
BLE 1M	1Mbps	2480	2.129	2.500	85.14	0.7	0.47
BLE 2M	2Mbps	2402	1.077	2.501	43.07	3.66	0.93
BLE 2M	2Mbps	2440	1.077	2.501	43.07	3.66	0.93
BLE 2M	2Mbps	2480	1.077	2.501	43.07	3.66	0.93

Note:
1. Duty Cycle = T_{on} / T_{total}
2. Correction Factor = 10 log (1 / Duty Cycle)
3. 1 / T = 1 / T_{on}

Test plots

BLE 1M
TX CH 00



TX CH 19



TX CH 39


BLE 2M
TX CH 00


TX CH 19



TX CH 39



5.8 Conducted Band Edge

5.8.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.8.2 Test Procedure

a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
e) Repeat above procedures until all measured frequencies were complete.

5.8.3 Test Setup



5.8.4 Test Results

EUT:	smart speaker	Model Name:	N73
Pressure:	1012 hPa	Test Voltage:	DC 3.7V from battery
Test Mode:	TX Mode /CH00, CH39		

BLE 1M: Band Edge, Left Side





BLE 1M: Band Edge, Right Side





BLE 2M: Band Edge, Left Side





BLE 2M: Band Edge, Right Side





5.9 Spurious RF Conducted Emissions

5.9.1 Limit

Below -20dB of the highest emission level in operating band.

5.9.2 Measuring Instruments

The Measuring equipment is listed in the section 4 of this test report.

5.9.3 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2020 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300kHz to measure the peak field strength, and measure frequency range from 9kHz to 26.5GHz.

5.9.4 Test Setup



5.9.5 Test Results

Note:

1: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.

BLE 1M	
GFSK on Channel 00	GFSK on Channel 00
	
GFSK on Channel 19	GFSK on Channel 19
	
GFSK on Channel 39	GFSK on Channel 39
	

BLE 2M	
GFSK on Channel 00	GFSK on Channel 00
	
GFSK on Channel 19	GFSK on Channel 19
	
GFSK on Channel 39	GFSK on Channel 39
	

6 Photographs of the Test Setup

Radiated Emission Below 1GHz
Radiated Emission Above 1GHz

Conducted Emission


7 Photographs of the EUT

Please refer to report HB20251021053E-01 for product photos.

******** END OF REPORT ********