

Prüfbericht-Nr.: Test report no.:	CN26FBZZ 002	Auftrags-Nr.: Order no.:	27243298	Page 1 of 16 Seite 1 von 16
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2026-06-23	
Auftraggeber: Client:	SHOKZ (SINGAPORE) PTE. LTD. 11 NORTH BUONA VISTA DRIVE #16-09 THE METROPOLIS, SINGAPORE 138589, Singapore			
Prüfgegenstand: Test item:	OPENFIT 2 AI			
Bezeichnung / Typ-Nr.: Identification / Type no.:	SHOKZ T922 (Trademark: SHOKZ)			
Auftrags-Inhalt: Order content:	Type test			
Prüfgrundlage: Test specification:	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.209		RSS-247 Issue 4 July 24, 2025 RSS-Gen Issue 5 February 2021	
Wareneingangsdatum: Date of sample receipt:	2026-06-24	Refer to photos document		
Prüfmuster-Nr.: Test sample no.:	A004314451			
Prüfzeitraum: Testing period:	2026-06-24 – 2026-07-20			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:			genehmigt von: authorized by:	
Datum: Date:	2026-08-03 Signed by: Harry W. C. Wu		Ausstellungsdatum: Issue date:	2026-08-03 Signed by: Alex Lan
Stellung / Position:	Project Manager		Stellung / Position:	Authorizer
Sonstiges / Other:	FCC ID: 2BCD6-T922			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN26FBZZ 002
Test report no.:

Page 2 of 16
Seite 2 von 16

Remarks
Anmerkungen

1	The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request. <i>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</i> <i>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</i>
2	As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. <i>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</i>
3	Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report. <i>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</i>
4	The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019. <i>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</i>

Prüfbericht-Nr.: CN26FBZZ 002
Test report no.:

Seite 3 von 21
Page 3 of 21

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

RESULT: Pass

5.1.3 CONDUCTED POWER SPECTRAL DENSITY

RESULT: Pass

5.1.4 99%dB BANDWIDTH

RESULT: Pass

5.1.5 6dB BANDWIDTH

RESULT: Pass

5.1.6 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH

RESULT: Pass

5.1.7 RADIATED SPURIOUS EMISSION

RESULT: Pass

Prüfbericht-Nr.: CN26FBZZ 002
Test report no.:

Seite 4 von 21
Page 4 of 21

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	10
3.5	SUBMITTED DOCUMENTS.....	10
4	TEST SET-UP AND OPERATION MODES	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE.....	11
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	11
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	11
4.5	TEST SETUP DIAGRAM	12
5	TEST RESULTS	14
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	14
5.1.1	<i>Antenna Requirement</i>	<i>14</i>
5.1.2	<i>Maximum Peak Conducted Output Power.....</i>	<i>15</i>
5.1.3	<i>Conducted Power Spectral Density</i>	<i>16</i>
5.1.4	<i>99%dB Bandwidth</i>	<i>17</i>
5.1.5	<i>6dB Bandwidth</i>	<i>18</i>
5.1.6	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>19</i>
5.1.7	<i>Radiated Spurious Emission</i>	<i>20</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	21
7	LIST OF TABLES.....	21

Prüfbericht-Nr.: CN26FBZZ 002
*Test report no.:*Seite 5 von 21
Page 5 of 21

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results of Bluetooth Low Energy (left earbud)..

Appendix C: Test Results of Bluetooth Low Energy (right earbud).

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China

FCC Registration No.: CN1260

IC Registration No.: 25069 and the CAB identifier is CN0078.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	22.09.2026
MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	22.09.2026
EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	22.09.2026
DC Power Supply	Keysight	E3642A	MY61276100	22.09.2026
Wireless Connectivity Tester	R&S	CMW270	102505	22.09.2026
Power Control Unit	Tonscend	JS0806-4ADC	N/A	22.09.2026
Automation Control Unit	Tonscend	JS0806-2	21C8060396	22.09.2026
Test Software	Tonscend	JS1120-3	N/A	N/A
Control PC	Lenovo	TianYi510S-071MB	YLX23JMF	N/A
Humid & Temp Programmable Tester	BOST	NTH090-60	19040801	01.02.2027
Unwanted Emission Testing				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	21.09.2026
Signal Analyzer	R&S	FSV 40	101439	21.09.2026
System Controller Interface	R&S	SCI-100	S10010038	N/A
Filterbank	R&S	Wlan	100759	21.09.2026
OSP	R&S	OSP 120	102040	N/A
Pre-amplifier	R&S	SCU08F1	08320031	21.09.2026
Amplifier	R&S	SCU-18F	180070	21.09.2026
Amplifier	R&S	SCU40A	100475	21.09.2026
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	27.09.2026
Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	27.09.2026
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	27.09.2026
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	27.09.2026
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	13.09.2027

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Parameter	Uncertainty (k=2)
Occupied Channel Bandwidth	± 2.08 %
RF output power, conducted	± 0.99 dB
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	± 4.17 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, People's Republic of China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUTs are True Wireless Stereo Earbuds, which consist of a left earbud, a right earbud and a charging box, the left & right earbuds support Bluetooth dual mode wireless technology.

Note: The left and right earbuds share the same Schematics, the PCB layout is different Full test performed on right earbud and left earbud.
This report is for earbuds with Bluetooth function.

For details refer to the User Manual and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	OPENFIT 2 AI
Type Designation	SHOKZ T922
Trademark	SHOKZ
FCC ID	2BCD6-T922
Extreme Temperature Range	0°C to +40°C
Operating Voltage (for earbuds):	Internal battery operated (3.85Vdc)
Technical Specification of Classical Bluetooth	
Operating Frequency band	2402 ~ 2480 MHz
Channel Number	79 channels
Channel separation	1MHz
Modulation	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type	Integral Antenna
Antenna Gain	-3.67 dBi (Provided by the Client)
Technical Specification of Bluetooth Low Energy	
Operating Frequency band	2402 – 2480 MHz for data rate 1Mbps 2404 - 2478 MHz for data rate 2Mbps
Channel Number	40 channels for data rate 1Mbps 38 channels for data rate 2Mbps
Channel separation	2MHz
Data rate	1Mbps, 2Mbps
Modulation	GFSK
Antenna Type	Integral Antenna
Antenna Gain	-3.67 dBi (Provided by the Client)

Table 3: RF Channel and Frequency of Classic Bluetooth

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	2402.00	20	2422.00	40	2442.00	60	2462.00
01	2403.00	21	2423.00	41	2443.00	61	2463.00
02	2404.00	22	2424.00	42	2444.00	62	2464.00
03	2405.00	23	2425.00	43	2445.00	63	2465.00
04	2406.00	24	2426.00	44	2446.00	64	2466.00
05	2407.00	25	2427.00	45	2447.00	65	2467.00
06	2408.00	26	2428.00	46	2448.00	66	2468.00
07	2409.00	27	2429.00	47	2449.00	67	2469.00
08	2410.00	28	2430.00	48	2450.00	68	2470.00
09	2411.00	29	2431.00	49	2451.00	69	2471.00
10	2412.00	30	2432.00	50	2452.00	70	2472.00
11	2413.00	31	2433.00	51	2453.00	71	2473.00
12	2414.00	32	2434.00	52	2454.00	72	2474.00
13	2415.00	33	2435.00	53	2455.00	73	2475.00
14	2416.00	34	2436.00	54	2456.00	74	2476.00
15	2417.00	35	2437.00	55	2457.00	75	2477.00
16	2418.00	36	2438.00	56	2458.00	76	2478.00
17	2419.00	37	2439.00	57	2459.00	77	2479.00
18	2420.00	38	2440.00	58	2460.00	78	2480.00
19	2421.00	39	2441.00	59	2461.00	--	--

Table 4: RF Channel and Frequency of Bluetooth Low Energy

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	2402.00	10	2422.00	20	2442.00	30	2462.00
01	2404.00	11	2424.00	21	2444.00	31	2464.00
02	2406.00	12	2426.00	22	2446.00	32	2466.00
03	2408.00	13	2428.00	23	2448.00	33	2468.00
04	2410.00	14	2430.00	24	2450.00	34	2470.00
05	2412.00	15	2432.00	25	2452.00	35	2472.00
06	2414.00	16	2434.00	26	2454.00	36	2474.00
07	2416.00	17	2436.00	27	2456.00	37	2476.00
08	2418.00	18	2438.00	28	2458.00	38	2478.00
09	2420.00	19	2440.00	29	2460.00	39	2480.00

3.3 Independent Operation Modes

The basic operation modes are:

A. On, Bluetooth LE transmitting mode

1. Low channel
2. Middle channel
3. High channel

B. On, Bluetooth connecting mode

C. Off

Note: Bluetooth function will be disabled when product is in charging.

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|----------------------------------|------------------|
| - Application Form | - Photo Document |
| - Block Diagram | - Schematics |
| - FCC/IC Label and Location Info | - User Manual |
| - Operation Description | |

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10-2020, ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024.

4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N or Rating
Laptop	Lenovo	T480	PF-16A6N8

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 30MHz)




Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard	:	FCC Part 15.247(b)(4) and Part 15.203
	:	RSS-Gen Clause 6.8
Limit	:	the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declared, the EUT has one integral antenna, the directional gain of antennas is -3.67 dBi for left and right earbud, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

Prüfbericht-Nr.: CN26FBZZ 002
Test report no.:

Seite 15 von 21
Page 15 of 21

5.1.2 Maximum Peak Conducted Output Power

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(b)(3)
RSS-247 Clause 6.3.2
Basic standard : ANSI C63.10-2020, ANSI C63.10-2020+Cor. 1-
2023+C63.10a-2024
Limits : < 1 Watt (Maximum Conducted Peak Power)
e.i.r.p. <4W
Kind of test site : Shielded Room

Test Setup

Date of testing : 2026-06-23 to 2026-07-20
Input voltage : DC 3.85V
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 24.8 °C
Relative humidity : 55 %
Atmospheric pressure : 101 kPa

For details refer to following test result.

Table 6: Test Result of Maximum Peak Conducted Output Power, left earbud

Data Rate	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
1 Mbps	2402	8.45	0.00700	< 1.0
	2440	8.09	0.00644	
	2480	7.93	0.00621	
2 Mbps	2404	8.42	0.00695	
	2440	8.07	0.00641	
	2478	7.94	0.00622	
Maximum Measured Value		8.45	0.00700	

Note: The cable loss is taken into account in results and the maximum e.i.r.p. is 4.78dBm less than 4W (36 dBm).

Table 7: Test Result of Maximum Peak Conducted Output Power, right earbud

Data Rate	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
1 Mbps	2402	8.34	0.00682	< 1.0
	2440	8.12	0.00649	
	2480	7.52	0.00565	
2 Mbps	2404	8.14	0.00652	
	2440	7.75	0.00596	
	2478	7.62	0.00578	
Maximum Measured Value		8.34	0.00682	

Note: The cable loss is taken into account in results and the maximum e.i.r.p. is 4.67dBm less than 4W (36 dBm).

Prüfbericht-Nr.: CN26FBZZ 002
Test report no.:

Seite 16 von 21
Page 16 of 21

5.1.3 Conducted Power Spectral Density

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(e)
RSS-247 Clause 6.3.1
Basic standard : ANSI C63.10-2020, ANSI C63.10-2020+Cor. 1-
2023+C63.10a-2024
Limits : 8 dBm / 3kHz
Kind of test site : Shielded Room

Test Setup

Date of testing : 2026-06-23 to 2026-07-20
Input voltage : DC 3.85V
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 24.8 °C
Relative humidity : 55 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B & C.

Table 8: Test Result of Conducted Power Spectral Density, left earbud

Data Rate	Channel Frequency (MHz)	Measured Conducted Power Spectral Density	Limit
		(dBm / 3kHz)	
1 Mbps	2402	-6.85	8 dBm / 3kHz
	2440	-7.34	
	2480	-7.36	
2 Mbps	2404	-10.22	8 dBm / 3kHz
	2440	-10.48	
	2478	-10.62	

Table 9: Test Result of Conducted Power Spectral Density, right earbud

Data Rate	Channel Frequency (MHz)	Measured Conducted Power Spectral Density	Limit
		(dBm / 3kHz)	
1 Mbps	2402	-6.96	8 dBm / 3kHz
	2440	-7.32	
	2480	-7.81	
2 Mbps	2404	-10.47	8 dBm / 3kHz
	2440	-10.73	
	2478	-11.01	

Prüfbericht-Nr.: CN26FBZZ 002
Test report no.:

Seite 17 von 21
Page 17 of 21

5.1.4 99%dB Bandwidth

RESULT:
Pass
Test Specification

Test standard : RSS-Gen Clause 6.7
Basic standard : ANSI C63.10-2020, ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024
Kind of test site : Shielded Room

Test Setup

Date of testing : 2026-06-23 to 2026-07-20
Input voltage : DC 3.85V
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 24.8 °C
Relative humidity : 55 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B & C.

Table 10: Test Result of 99% Bandwidth, left earbud

Data Rate	Channel Frequency (MHz)	Measured 99% Bandwidth	Limit
		(MHz)	
1 Mbps	2402	1.0296	/
	2440	1.0255	
	2480	1.0301	
2 Mbps	2404	2.0471	/
	2440	2.0319	
	2478	2.0427	

Table 11: Test Result of 99% Bandwidth, right earbud

Data Rate	Channel Frequency (MHz)	Measured 99% Bandwidth	Limit
		(MHz)	
1 Mbps	2402	1.0309	/
	2440	1.0324	
	2480	1.0227	
2 Mbps	2404	2.0346	/
	2440	2.0387	
	2478	2.0388	

Note: The fundamental emissions stay within the allocated band 2400-2483.5MHz.

Prüfbericht-Nr.: CN26FBZZ 002
Test report no.:

Seite 18 von 21
Page 18 of 21

5.1.5 6dB Bandwidth

RESULT:
Pass
Test Specification

Test standard : FCC Part 15.247(a)(2)
RSS-247 Clause 6.3.1
Basic standard : ANSI C63.10-2020, ANSI C63.10-2020+Cor. 1-
2023+C63.10a-2024
Kind of test site : Shielded Room

Test Setup

Date of testing : 2026-06-23 to 2026-07-20
Input voltage : DC 3.85V
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 24.8 °C
Relative humidity : 55 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B & C.

Table 12: Test Result of 6dB Bandwidth, Left earbud

Data Rate	Channel Frequency (MHz)	Measured 6dB Bandwidth	Limit
		(MHz)	
1 Mbps	2402	0.668	>500kHz
	2440	0.668	
	2480	0.676	
2 Mbps	2404	1.144	>500kHz
	2440	1.136	
	2478	1.144	

Table 13: Test Result of 6dB Bandwidth, Left earbud, right earbud

Data Rate	Channel Frequency (MHz)	Measured 6dB Bandwidth	Limit
		(MHz)	
1 Mbps	2402	0.684	>500kHz
	2440	0.680	
	2480	0.660	
2 Mbps	2404	1.136	>500kHz
	2440	1.152	
	2478	1.128	

Prüfbericht-Nr.: **CN26FBZZ 002**
Test report no.:Seite 19 von 21
Page 19 of 21**5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth****RESULT:****Pass****Test Specification**

Test standard	: FCC Part 15.247(d) RSS-247 Clause 6.6
Basic standard	: ANSI C63.10-2020, ANSI C63.10-2020+Cor. 1- 2023+C63.10a-2024
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-06-23 to 2026-07-20
Input voltage	: DC 3.85V
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 24.8 °C
Relative humidity	: 55 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix B & C .

Prüfbericht-Nr.: **CN26FBZZ 002**
Test report no.:

Seite 20 von 21
Page 20 of 21

5.1.7 Radiated Spurious Emission

RESULT:

Pass

Test Specification

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 2.4
Basic standard	:	ANSI C63.10-2020, ANSI C63.10-2020+Cor. 1- 2023+C63.10a-2024
Limits	:	Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Table 5~7
Kind of test site	:	3m Semi-anechoic Chamber

Test Setup

Date of testing	:	2026-06-23 to 2026-07-20
Input voltage	:	DC 3.85V
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	Refer to test result
Relative humidity	:	Refer to test result
Atmospheric pressure	:	101 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix B & CAA.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Technical Specification of EUT	8
Table 3: RF Channel and Frequency of Classic Bluetooth.....	9
Table 4: RF Channel and Frequency of Bluetooth Low Energy	9
Table 5: List of Accessories and Auxiliary Equipment.....	11
Table 6: Test Result of Maximum Peak Conducted Output Power, left earbud	15
Table 7: Test Result of Maximum Peak Conducted Output Power, right earbud	15
Table 8: Test Result of Conducted Power Spectral Density, left earbud	16
Table 9: Test Result of Conducted Power Spectral Density, right earbud	16
Table 10: Test Result of 99% Bandwidth, left earbud	17
Table 11: Test Result of 99% Bandwidth, right earbud	17
Table 12: Test Result of 6dB Bandwidth, Left earbud	18
Table 13: Test Result of 6dB Bandwidth, Left earbud, right earbud	18

Appendix B: Test Results of Bluetooth Low Energy (Left earbud)

APPENDIX B: TEST RESULTS OF BLUETOOTH LOW ENERGY (LEFT EARBUD)	1
APPENDIX B.1: TEST RESULTS OF CONDUCTED POWER SPECTRAL DENSITY	2
APPENDIX B.2: TEST RESULTS OF 6dB BANDWIDTH	5
APPENDIX B.3: TEST RESULTS OF 99% BANDWIDTH	8
APPENDIX B.4: TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 kHz BANDWIDTH	11
<i>Conducted measurements</i>	11
<i>Band edge measurements</i>	18
APPENDIX B.5: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS	20
30MHz - 1GHz	20
1GHz - 18GHz	22
APPENDIX B.6: TEST RESULTS OF RADIATED EMISSIONS IN RESTRICTED BANDS	34

Appendix B.1: Test Results of Conducted Power Spectral Density

TestMode	Antenna	Channel	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-6.85	≤8.00	PASS
		2440	-7.34	≤8.00	PASS
		2480	-7.36	≤8.00	PASS
BLE_2M	Ant1	2404	-10.22	≤8.00	PASS
		2440	-10.48	≤8.00	PASS
		2478	-10.62	≤8.00	PASS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



Appendix B CN26FBZZ 002



Prüfbericht - Produkte
Test Report - Products

Page 3 of 41


BLE 1M Ant1 2480



BLE 2M Ant1 2404



BLE 2M Ant1 2440





Appendix B.2: Test Results of 6dB Bandwidth

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.668	2401.660	2402.328	0.5	PASS
		2440	0.668	2439.660	2440.328	0.5	PASS
		2480	0.676	2479.664	2480.340	0.5	PASS
BLE_2M	Ant1	2404	1.144	2403.432	2404.576	0.5	PASS
		2440	1.136	2439.424	2440.560	0.5	PASS
		2478	1.144	2477.424	2478.568	0.5	PASS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



Appendix B CN26FBZZ 002



Prüfbericht - Produkte
Test Report - Products

Page 6 of 41

BLE 1M Ant1 2480



BLE 2M Ant1 2404



BLE 2M Ant1 2440





Appendix B.3: Test Results of 99% Bandwidth

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0296	2401.4942	2402.5238	---	---
		2440	1.0255	2439.4969	2440.5224	---	---
		2480	1.0301	2479.4914	2480.5215	---	---
BLE_2M	Ant1	2404	2.0471	2402.9961	2405.0432	---	---
		2440	2.0319	2439.0087	2441.0406	---	---
		2478	2.0427	2476.9972	2479.0399	---	---

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



Appendix B
CN26FBZZ 002

Prüfbericht - Produkte
Test Report - Products

Page 9 of 41

BLE 1M Ant1 2480



BLE 2M Ant1 2404



BLE 2M Ant1 2440





Appendix B.4: Test Results of Conducted Spurious Emissions Measured in 100 kHz Bandwidth

Conducted measurements

TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	7.34	7.34	---	PASS
			30~1000	7.34	-40.98	≤-12.66	PASS
			1000~26500	7.34	-43.25	≤-12.66	PASS
		2440	Reference	7.23	7.23	---	PASS
			30~1000	7.23	-41.36	≤-12.77	PASS
			1000~26500	7.23	-42.34	≤-12.77	PASS
		2480	Reference	7.08	7.08	---	PASS
			30~1000	7.08	-41.43	≤-12.92	PASS
			1000~26500	7.08	-43.44	≤-12.92	PASS
BLE_2M	Ant1	2404	Reference	7.65	7.65	---	PASS
			30~1000	7.65	-40.28	≤-12.35	PASS
			1000~26500	7.65	-42.63	≤-12.35	PASS
		2440	Reference	7.27	7.27	---	PASS
			30~1000	7.27	-41.54	≤-12.73	PASS
			1000~26500	7.27	-42.59	≤-12.73	PASS
		2478	Reference	6.99	6.99	---	PASS
			30~1000	6.99	-41.3	≤-13.01	PASS
			1000~26500	6.99	-43.14	≤-13.01	PASS



BLE 1M Ant1 2402 30~1000




BLE 1M Ant1 2402 1000~26500



BLE 1M Ant1 2440 0~Reference





BLE 1M Ant1 2480 30~1000



BLE 1M Ant1 2480 1000~26500



BLE 2M Ant1 2404 0~Reference



BLE 2M Ant1 2404 30~1000



BLE 2M Ant1 2404 1000~26500



BLE 2M Ant1 2440 0~Reference



BLE 2M Ant1 2440 30~1000



BLE 2M Ant1 2440 1000~26500



BLE 2M Ant1 2478 0~Reference





Band edge measurements

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	7.39	-41.17	≤-12.61	PASS
		High	2480	7.14	-41.64	≤-12.86	PASS
BLE_2M	Ant1	Low	2404	6.86	-42.09	≤-13.14	PASS
		High	2478	6.54	-41.69	≤-13.46	PASS

BLE_1M_Ant1_Low_2402



BLE_1M_Ant1_High_2480



BLE 2M Ant1 Low 2404



BLE 2M Ant1 High 2478




Appendix B.5: Test Results of Radiated Spurious Emissions

Note: 1. Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 26.5GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported. 2. This testing was carried out on different modulations, but only the worst case (GFSK) was presented in this report.

30MHz - 1GHz

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.166667	14.49	40.00	25.51	100.0	H	48.0	-18.7
108.785556	17.70	43.50	25.80	100.0	H	166.0	-19.1
140.418333	11.49	43.50	32.01	100.0	H	120.0	-22.4
250.028333	13.84	46.00	32.16	100.0	H	22.0	-17.4
514.083889	18.56	46.00	27.44	100.0	H	111.0	-11.6
890.982778	28.68	46.00	17.32	100.0	H	231.0	-4.9
938.405000	28.33	46.00	17.67	100.0	H	120.0	-4.4

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Mid channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.112778	14.59	40.00	25.41	100.0	V	24.0	-18.8
108.785556	18.16	43.50	25.34	100.0	V	134.0	-19.1
269.374444	12.88	46.00	33.12	100.0	V	0.0	-17.0
436.915000	16.55	46.00	29.45	100.0	V	216.0	-13.0
742.465000	23.95	46.00	22.05	100.0	V	358.0	-7.2
890.982778	32.56	46.00	13.44	100.0	V	241.0	-4.9
936.950000	28.12	46.00	17.88	100.0	V	345.0	-4.4

1GHz - 18GHz

Note: The highest waveform in the figure is Bluetooth Fundamental.

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4801.000000	50.79	---	74.00	23.21	150.0	H	343.0	13.3
4802.500000	---	40.60	54.00	13.40	150.0	H	260.0	13.3

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Low channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4805.500000	---	40.90	54.00	13.10	150.0	V	269.0	13.3
4805.500000	51.31	---	74.00	22.69	150.0	V	269.0	13.3

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Mid channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4880.500000	---	39.89	54.00	14.11	150.0	H	300.0	13.3
4880.500000	50.32	---	74.00	23.68	150.0	H	300.0	13.3

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Mid channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4880.000000	---	39.72	54.00	14.28	150.0	V	294.0	13.3
4880.000000	49.99	---	74.00	24.01	150.0	V	294.0	13.3

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4961.000000	50.82	---	74.00	23.18	150.0	H	281.0	13.3
4961.500000	---	40.45	54.00	13.55	150.0	H	354.0	13.3

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4960.000000	---	40.61	54.00	13.39	150.0	V	175.0	13.3
4962.500000	51.03	---	74.00	22.97	150.0	V	347.0	13.3

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Low channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7205.458333	---	36.38	54.00	17.62	150.0	H	157.0	8.8
7205.950000	43.79	---	74.00	30.21	150.0	H	169.0	8.8
12147.200000	---	42.73	54.00	11.27	150.0	H	259.0	16.7
12152.116667	51.13	---	74.00	22.87	150.0	H	69.0	16.6

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Low channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7205.458333	42.67	---	74.00	31.33	150.0	V	133.0	8.8
7206.441667	---	34.96	54.00	19.04	150.0	V	354.0	8.8
11786.808333	50.71	---	74.00	23.29	150.0	V	255.0	15.0
11798.116667	---	40.80	54.00	13.20	150.0	V	200.0	14.9

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7319.525000	41.87	---	74.00	32.13	150.0	H	309.0	8.2
7320.508333	---	34.92	54.00	19.08	150.0	H	0.0	8.2
12141.300000	51.18	---	74.00	22.82	150.0	H	309.0	16.5
12150.150000	---	42.58	54.00	11.42	150.0	H	124.0	16.7

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Mid channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7321.983333	---	34.35	54.00	19.65	150.0	V	4.0	8.2
7322.966667	43.01	---	74.00	30.99	150.0	V	190.0	8.2
12143.266667	---	43.04	54.00	10.96	150.0	V	0.0	16.6
12150.641667	51.16	---	74.00	22.84	150.0	V	37.0	16.7

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7439.491667	42.79	---	74.00	31.21	150.0	H	9.0	8.4
7439.983333	---	36.26	54.00	17.74	150.0	H	0.0	8.4
12149.166667	---	43.41	54.00	10.59	150.0	H	0.0	16.7
12150.150000	51.07	---	74.00	22.93	150.0	H	179.0	16.7

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_High channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7438.016667	42.60	---	74.00	31.40	150.0	V	240.0	8.4
7444.408333	---	35.58	54.00	18.42	150.0	V	358.0	8.5
12141.791667	50.63	---	74.00	23.37	150.0	V	218.0	16.5
12145.725000	---	42.96	54.00	11.04	150.0	V	0.0	16.6

Appendix B.6: Test Results of Radiated Emissions in Restricted Bands

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2366.176471	---	40.43	54.00	13.57	150.0	H	282.0	8.5
2366.764706	51.68	---	74.00	22.32	150.0	H	127.0	8.5

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Low channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2336.764706	50.71	---	74.00	23.29	150.0	V	175.0	8.4
2355.588235	---	40.41	54.00	13.59	150.0	V	317.0	8.5

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2485.294118	---	41.96	54.00	12.04	150.0	H	115.0	9.0
2492.352941	51.89	---	74.00	22.11	150.0	H	248.0	9.0

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_High channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2489.411765	51.78	---	74.00	22.22	150.0	V	299.0	9.0
2497.058824	---	41.43	54.00	12.57	150.0	V	45.0	9.0

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 2M_Low channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2353.529412	---	40.39	54.00	13.61	150.0	H	226.0	8.5
2356.176471	50.96	---	74.00	23.04	150.0	H	324.0	8.5

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 2M_Low channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2363.529412	---	40.64	54.00	13.36	150.0	V	0.0	8.5
2390.000000	50.62	---	74.00	23.38	150.0	V	106.0	8.5

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 2M_High channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2491.176471	52.18	---	74.00	21.82	150.0	H	249.0	9.0
2492.647059	---	41.41	54.00	12.59	150.0	H	244.0	9.0

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 2M_High channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2493.235294	52.36	---	74.00	21.64	150.0	V	113.0	9.0
2493.529412	---	41.49	54.00	12.51	150.0	V	120.0	9.0

Appendix C: Test Results of Bluetooth Low Energy (Right earbud)

APPENDIX C: TEST RESULTS OF BLUETOOTH LOW ENERGY (RIGHT EARBUD)	1
APPENDIX C.1: TEST RESULTS OF CONDUCTED POWER SPECTRAL DENSITY	2
APPENDIX C.2: TEST RESULTS OF 6dB BANDWIDTH	3
APPENDIX C.3: TEST RESULTS OF 99% BANDWIDTH	4
APPENDIX C.4: TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 kHz BANDWIDTH	5
<i>Conducted measurements</i>	5
<i>Band edge measurements</i>	6
APPENDIX C.5: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS	7
30MHz - 1GHz	7
1GHz - 18GHz	8
APPENDIX C.6: TEST RESULTS OF RADIATED EMISSIONS IN RESTRICTED BANDS	9

Appendix C.1: Test Results of Conducted Power Spectral Density

TestMode	Antenna	Channel	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-6.96	≤8.00	PASS
		2440	-7.32	≤8.00	PASS
		2480	-7.81	≤8.00	PASS
BLE_2M	Ant1	2404	-10.47	≤8.00	PASS
		2440	-10.73	≤8.00	PASS
		2478	-11.01	≤8.00	PASS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440





Appendix C.2: Test Results of 6dB Bandwidth

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.684	2401.640	2402.324	0.5	PASS
		2440	0.680	2439.656	2440.336	0.5	PASS
		2480	0.660	2479.672	2480.332	0.5	PASS
BLE_2M	Ant1	2404	1.136	2403.448	2404.584	0.5	PASS
		2440	1.152	2439.428	2440.580	0.5	PASS
		2478	1.128	2477.424	2478.552	0.5	PASS

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



Appendix C CN26FBZZ 002



Prüfbericht - Produkte
Test Report - Products

Page 6 of 41

BLE 1M Ant1 2480



BLE 2M Ant1 2404



BLE 2M Ant1 2440





Appendix C.3: Test Results of 99% Bandwidth

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0309	2401.4950	2402.5259	---	---
		2440	1.0324	2439.4942	2440.5266	---	---
		2480	1.0227	2479.4993	2480.5220	---	---
BLE_2M	Ant1	2404	2.0346	2403.0052	2405.0398	---	---
		2440	2.0387	2438.9987	2441.0374	---	---
		2478	2.0388	2477.0019	2479.0407	---	---

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



Appendix C
CN26FBZZ 002

Prüfbericht - Produkte
Test Report - Products

Page 9 of 41

BLE 1M Ant1 2480



BLE 2M Ant1 2404



BLE 2M Ant1 2440





Appendix C.4: Test Results of Conducted Spurious Emissions Measured in 100 kHz Bandwidth

Conducted measurements

TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	7.32	7.32	---	PASS
			30~1000	7.32	-41.73	≤-12.68	PASS
			1000~26500	7.32	-43.48	≤-12.68	PASS
		2440	Reference	7.06	7.06	---	PASS
			30~1000	7.06	-41.39	≤-12.94	PASS
			1000~26500	7.06	-43.78	≤-12.94	PASS
		2480	Reference	6.70	6.70	---	PASS
			30~1000	6.70	-42.15	≤-13.3	PASS
			1000~26500	6.70	-43.73	≤-13.3	PASS
BLE_2M	Ant1	2404	Reference	7.18	7.18	---	PASS
			30~1000	7.18	-40.59	≤-12.82	PASS
			1000~26500	7.18	-43.46	≤-12.82	PASS
		2440	Reference	6.87	6.87	---	PASS
			30~1000	6.87	-41.47	≤-13.13	PASS
			1000~26500	6.87	-43.36	≤-13.13	PASS
		2478	Reference	6.72	6.72	---	PASS
			30~1000	6.72	-41.89	≤-13.28	PASS
			1000~26500	6.72	-43.35	≤-13.28	PASS



BLE 1M Ant1 2402 30~1000



BLE 1M Ant1 2402 1000~26500



BLE 1M Ant1 2440 0~Reference



BLE 1M Ant1 2440 30~1000



BLE 1M Ant1 2440 1000~26500



BLE 1M Ant1 2480 0~Reference



BLE 1M Ant1 2480 30~1000




BLE 1M Ant1 2480 1000~26500



BLE 2M Ant1 2404 0~Reference





BLE 2M Ant1 2440 30~1000



BLE 2M Ant1 2440 1000~26500



BLE 2M Ant1 2478 0~Reference





Band edge measurements

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	7.09	-39.73	≤-12.91	PASS
		High	2480	6.84	-40.72	≤-13.16	PASS
BLE_2M	Ant1	Low	2404	6.94	-42.84	≤-13.06	PASS
		High	2478	6.09	-42.46	≤-13.91	PASS

BLE_1M Ant1 Low 2402



BLE_1M Ant1 High 2480



Appendix C CN26FBZZ 002



Prüfbericht - Produkte
Test Report - Products

Page 19 of 41

BLE 2M Ant1 Low 2404



BLE 2M Ant1 High 2478




Appendix C.5: Test Results of Radiated Spurious Emissions

Note: 1. Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 26.5GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported. 2. This testing was carried out on different modulations, but only the worst case (GFSK) was presented in this report.

30MHz - 1GHz

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.760000	14.69	40.00	25.31	100.0	H	305.0	-20.9
104.797778	17.90	43.50	25.60	100.0	H	246.0	-18.9
238.118889	23.51	46.00	22.49	100.0	H	118.0	-17.8
309.952778	24.78	46.00	21.22	100.0	H	141.0	-16.0
600.360000	24.51	46.00	21.49	100.0	H	109.0	-9.7
890.982778	30.59	46.00	15.41	100.0	H	343.0	-4.9
936.950000	28.44	46.00	17.56	100.0	H	118.0	-4.4

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Mid channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
34.526667	15.73	40.00	24.27	100.0	V	72.0	-22.1
104.582222	16.70	43.50	26.80	100.0	V	138.0	-18.9
236.610000	15.57	46.00	30.43	100.0	V	59.0	-17.9
305.210556	16.22	46.00	29.78	100.0	V	109.0	-16.1
890.982778	29.89	46.00	16.11	100.0	V	271.0	-4.9
936.950000	28.34	46.00	17.66	100.0	V	0.0	-4.4

1GHz - 18GHz

Note: The highest waveform in the figure is Bluetooth Fundamental.

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4809.000000	---	40.99	54.00	13.01	150.0	H	176.0	13.3
4850.500000	52.70	---	74.00	21.30	150.0	H	22.0	13.3

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Low channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4813.000000	---	41.72	54.00	12.28	150.0	V	227.0	13.3
4826.000000	52.58	---	74.00	21.42	150.0	V	259.0	13.3

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_Mid channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4880.000000	---	40.64	54.00	13.36	150.0	H	78.0	13.3
4880.500000	51.04	---	74.00	22.96	150.0	H	101.0	13.3

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Mid channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4880.000000	---	40.10	54.00	13.90	150.0	V	308.0	13.3
4880.000000	50.34	---	74.00	23.66	150.0	V	308.0	13.3

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_High channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4956.500000	---	41.01	54.00	12.99	150.0	H	9.0	13.3
4970.000000	51.58	---	74.00	22.42	150.0	H	244.0	13.3

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_High channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4955.500000	52.03	---	74.00	21.97	150.0	V	119.0	13.3
4969.000000	---	41.09	54.00	12.91	150.0	V	132.0	13.3

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7205.458333	44.26	---	74.00	29.74	150.0	H	232.0	8.8
7240.858333	---	36.46	54.00	17.54	150.0	H	165.0	8.6
12140.808333	---	43.54	54.00	10.46	150.0	H	142.0	16.5
12140.808333	51.08	---	74.00	22.92	150.0	H	142.0	16.5

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7218.241667	---	36.14	54.00	17.86	150.0	V	0.0	8.7
7238.891667	43.53	---	74.00	30.47	150.0	V	168.0	8.6
12147.691667	50.73	---	74.00	23.27	150.0	V	37.0	16.7
12167.358333	---	42.75	54.00	11.25	150.0	V	236.0	15.8

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Mid channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7324.441667	---	34.91	54.00	19.09	150.0	H	290.0	8.2
7327.391667	43.18	---	74.00	30.82	150.0	H	224.0	8.1
12147.200000	51.70	---	74.00	22.30	150.0	H	0.0	16.7
12149.658333	---	42.78	54.00	11.22	150.0	H	0.0	16.7

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Mid channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7315.591667	43.84	---	74.00	30.16	150.0	V	212.0	8.2
7321.491667	---	34.83	54.00	19.17	150.0	V	138.0	8.2
12148.183333	---	42.37	54.00	11.63	150.0	V	268.0	16.7
12151.133333	50.55	---	74.00	23.45	150.0	V	6.0	16.7

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_High channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7410.483333	---	36.03	54.00	17.97	150.0	H	218.0	8.3
7438.508333	44.83	---	74.00	29.17	150.0	H	58.0	8.4
12147.200000	---	42.57	54.00	11.43	150.0	H	207.0	16.7
12161.458333	51.17	---	74.00	22.83	150.0	H	118.0	16.1

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_High channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
7403.108333	---	35.67	54.00	18.33	150.0	V	0.0	8.3
7416.875000	43.96	---	74.00	30.04	150.0	V	139.0	8.3
12146.708333	50.56	---	74.00	23.44	150.0	V	51.0	16.6
12147.691667	---	42.40	54.00	11.60	150.0	V	251.0	16.7

Appendix C.6: Test Results of Radiated Emissions in Restricted Bands

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_Low channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2352.058824	51.23	---	74.00	22.77	150.0	H	30.0	8.5
2362.058824	---	40.76	54.00	13.24	150.0	H	281.0	8.5

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_Low channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2327.058824	51.08	---	74.00	22.92	150.0	V	167.0	8.3
2362.058824	---	40.47	54.00	13.53	150.0	V	206.0	8.5

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 1M_High channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2486.764706	---	41.26	54.00	12.74	150.0	H	38.0	9.0
2487.058824	52.04	---	74.00	21.96	150.0	H	93.0	9.0

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 1M_High channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2485.000000	---	41.84	54.00	12.16	150.0	V	326.0	9.0
2485.000000	51.98	---	74.00	22.02	150.0	V	326.0	9.0

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 2M_Low channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2346.176471	51.41	---	74.00	22.59	150.0	H	357.0	8.5
2371.470588	---	40.52	54.00	13.48	150.0	H	225.0	8.5

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 2M_Low channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2319.411765	51.19	---	74.00	22.81	150.0	V	332.0	8.2
2362.352941	---	40.40	54.00	13.60	150.0	V	298.0	8.5

EUT Information

EUT Name:	OPENFIT 2 AI
Model:	SHOKZ T922
Test Mode:	BLE 2M_High channel
Order No/Sample No:	A004314451-011
Test Voltage:	Battery
Remark:	Temp 23.2°C Humi:51%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2487.352941	---	41.68	54.00	12.32	150.0	H	204.0	9.0
2498.529412	52.59	---	74.00	21.41	150.0	H	100.0	9.0

EUT Information

EUT Name: OPENFIT 2 AI
Model: SHOKZ T922
Test Mode: BLE 2M_High channel
Order No/Sample No: A004314451-011
Test Voltage: Battery
Remark: Temp 23.2°C Humi:51%
Test Standard: FCC 15.247
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2492.058824	52.36	---	74.00	21.64	150.0	V	358.0	9.0
2497.058824	---	41.40	54.00	12.60	150.0	V	293.0	9.0