TEST REPORT

FCC Rules Part 15.247

Report Reference No..... :	**MTEB23070313-R**	
FCC ID.. ..... :	**2BCEH-CMK323**	
Compiled by (position+printed name+signature):	File administrators Alisa Luo	Alisa Luo
Supervised by (position+printed name+signature):	Test Engineer Sunny Deng	Sunny Deng
Approved by (position+printed name+signature):	Manager Yvette Zhou	Yvette Zhou
Date of issue..... :	**Jul.28,2023**	
Representative Laboratory Name ..... :	**Shenzhen Most Technology Service Co., Ltd.**	
Address ..... :	No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.	
Applicant' s name ..... :	**Zhangzhou Easepal Electronics Co.,Ltd.**	
Address ..... :	2nd Floor,No. 6 building,Easepal Factoty. No.228 Jiaosong Road, Jiaomei Town, Zhangzhou.Taiwanese Investment Zone.Zhangzhou City,Fujian Province, 363107, P.R.China	
Test specification/ Standard ..... :	**FCC Rules Part 15.247**	
TRF Originator..... :	Shenzhen Most Technology Service Co., Ltd.	

Shenzhen Most Technology Service Co., Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description..... :	MASSAGE DEVICE
Trade Mark .....:	CASADA
Model/Type reference.....:	CMK-323
Listed Models .....:	Quattromed V Braintronics,Y60760
Modulation Type .....:	GFSK
Operation Frequency.....:	From 2402MHz to 2480MHz
Hardware Version.....	BT4.2 BLE
Software Version	V1.0
Rating .....:	DC 24V (by Adapter)
Result .....:	PASS

T E S T R E P O R T

Equipment under Test	:	MASSAGE DEVICE
Model /Type	:	CMK-323
Listed Models		Quattromed V Braintronics,Y60760
Remark		Only the model name is different, and the input voltage, product structure, emission module, PCB board, PCB layout, circuit principle and appearance are consistent.
Applicant	:	**Zhangzhou Easepal Electronics Co.,Ltd.**
Address	:	2nd Floor,No. 6 building,Easepal Factoty. No.228 Jiaosong Road, Jiaomei Town, Zhangzhou.Taiwanese Investment Zone.Zhangzhou City,Fujian Province, 363107, P.R.China
Manufacturer	:	**Zhangzhou Easepal Electronics Co.,Ltd.**
Address	:	2nd Floor,No. 6 building,Easepal Factoty. No.228 Jiaosong Road, Jiaomei Town, Zhangzhou.Taiwanese Investment Zone.Zhangzhou City,Fujian Province, 363107, P.R.China

Test Result:	**PASS**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. REVISION HISTORY 4

2. TEST STANDARDS 5

3. SUMMARY 6

3.1. General Remarks 6
3.2. Product Description 6
3.3. Equipment Under Test 6
3.4. Short description of the Equipment under Test (EUT) 6
3.5. EUT operation mode 7
3.6. Block Diagram of Test Setup 7
3.7. Test Item (Equipment Under Test) Description* 7
3.8. Auxiliary Equipment (AE) Description 7
3.9. Antenna Information* 8
3.10. EUT configuration 8
3.11. Modifications 8

4. TEST ENVIRONMENT 9

4.1. Address of the test laboratory 9
4.2. Environmental conditions 9
4.3. Test Description 10
4.4. Statement of the measurement uncertainty 10
4.5. Equipments Used during the Test 11

5. TEST CONDITIONS AND RESULTS 12

5.1. AC Power Conducted Emission 12
5.2. Radiated Emission 15
5.3. Maximum Peak Output Power 22
5.4. Power Spectral Density 23
5.5. 6dB Bandwidth and 99% Bandwidth 24
5.6. Band Edge Compliance of RF Emission 25
5.7. Spurious RF Conducted Emission 30
5.8. Antenna Requirement 31

6. TEST SETUP PHOTOS OF THE EUT 32

7. EXTERNAL AND INTERNAL PHOTOS OF THE EUT 33

APPENDIX I.Conducted Peak Output Power 34
APPENDIX II.99% Bandwidth 35
APPENDIX III.6dB Bandwidth 36
APPENDIX IV.Conducted Out Of Band Emission 37
APPENDIX V.Duty Cycle 39
APPENDIX VI.Power Spectral Density 41

1. Revision History

Revision	Issue Date	Revisions	Revised By
00	2023.07.28	Initial Issue	Alisa Luo

2. TEST STANDARDS

The tests were performed according to following standards:

The tests were performed according to following standards:
FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

ANSI C63.10:2013 : American National Standard for Testing Unlicensed Wireless Devices

3. SUMMARY

3.1. General Remarks

Date of receipt of test sample	:	2023.07.23
Testing commenced on	:	2023.07.24
Testing concluded on	:	2023.07.28

3.2. Product Description

Product Name:	MASSAGE DEVICE
Model/Type reference:	CMK-323
Power Supply：	DC 24V (by Adapter)
Testing sample ID：	MTYP02232
Bluetooth :	
Supported Type:	BLE
Modulation:	GFSK
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	PCB antenna
Antenna gain:	0dBi

3.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	○	230V / 50 Hz	○	120V / 60Hz
		○	12 V DC	○	24 V DC
		●	Other (specified in blank below)		

DC 24V (by Adapter)

3.4. Short description of the Equipment under Test (EUT)

This is a Treadmill For more details, refer to the user's manual of the EUT.

3.5. EUT operation mode

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 40 channels provided to the EUT. Channel 00/19/39 was selected to test.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
0	**2402**	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	**2440**	**39**	**2480**

3.6. Block Diagram of Test Setup



3.7. Test Item (Equipment Under Test) Description*

Short designation	EUT Name	EUT Description	Serial number	Hardware status	Software status
EUT A	Adapter		MP60M-240250-E2	/	/
EUT B	/	/	/	/	/

*: declared by the applicant. According to customers information EUTs A and B are the same devices.

3.8. Auxiliary Equipment (AE) Description

AE short designation	EUT Name (if available)	EUT Description	Serial number (if available)	Software (if used)
AE 1	/	/	/	/
AE 2	/	/	/	/

3.9. Antenna Information*

Short designation	Antenna Name	Antenna Type	Frequency Range	Serial number	Antenna Peak Gain
Antenna 1	---	PCB antenna	2.4 – 2.5 GHz	---	0dBi
Antenna 2	/	/	/	/	/

*: declared by the applicant.

3.10. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - Supplied by the lab

●	ADAPTER	M/N:	MP60M-240250-E2
		Manufacturer:	Mitra Power Solutions Co.,Ltd

3.11. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Shenzhen Most Technology Service Co., Ltd.
No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.
The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 0031192610

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 6343.01

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

4.2. Environmental conditions

Radiated Emission:

Temperature:	21.6 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

Conducted testing：

Temperature:	21.6 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

4.3. Test Description

FCC and IC Requirements		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247 (a)(2)	6dB Bandwidth & 99% Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Conducted Output Power	PASS
FCC Part 15.247 (e)	Power Spectral Density	PASS
FCC Part 15.205/15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge	PASS

Remark:
1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Most Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Most Technology Service Co., Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approxiGF6101ly the 95% confidence level using a coverage factor of k=2.

4.5. Equipments Used during the Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware versions	Last Cal.
1.	L.I.S.N.	R&S	ENV216	100093	/	2023/03/17
2	Three-phase artificial power network	Schwarzback Mess	NNLK8129	8129178	/	2023/03/17
3.	Receiver	R&S	ESCI	100492	V3.0-10-2	2023/03/17
4	Receiver	R&S	ESPI	101202	V3.0-10-2	2023/03/17
5	Spectrum analyzer	Agilent	9020A	MT-E306	A14.16	2023/03/17
6	Bilong Antenna	Sunol Sciences	JB3	A121206	/	2023/03/17
7	Horn antenna	HF Antenna	HF Antenna	MT-E158	/	2023/03/17
8	Loop antenna	Beijing Daze	ZN30900B	/	/	2023/03/17
9	Horn antenna	R&S	OBH100400	26999002	/	2023/03/17
10	Wireless Communication Test Set	R&S	CMW500	/	CMW-BASE-3.7.21	2023/03/17
11	Spectrum analyzer	R&S	FSP	100019	V4.40 SP2	2023/03/17
12	High gain antenna	Schwarzbeck	LB-180400KF	MT-E389	/	2023/03/17
13	Preamplifier	Schwarzbeck	BBV 9743	MT-E390	/	2023/03/17
14	Pre-amplifier	EMCI	EMC051845SE	MT-E391	/	2023/03/17
15	Pre-amplifier	Agilent	83051A	MT-E392	/	2023/03/17
16	High pass filter unit	Tonscend	JS0806-F	MT-E393	/	2023/03/17
17	RF Cable(below1GHz)	Times	9kHz-1GHz	MT-E394	/	2023/03/17
18	RF Cable(above 1GHz)	Times	1-40G	MT-E395	/	2023/03/17
19	RF Cable (9KHz-40GHz)	Tonscend	170660	N/A	/	2023/03/17

Note: 1. The Cal.Interval was one year.

5. TEST CONDITIONS AND RESULTS

5.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
2 Support equipment, if needed, was placed as per ANSI C63.10-2013
3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
4 The EUT received DC5V power, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5 All support equipments received AC power from a second LISN, if any.
6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For unintentional device, according to RSS Gen 8.8 and § 15.207(a) Line Conducted Emission Limits is as following:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

TEST RESULTS

Remark:

1. GFSK modes were test at Low, Middle, and High channel; only the worst result of GFSK Middle Channel was reported as below:

Power supply:	DC 24V (by Adapter)	Polarization	L



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.2100	27.95	9.60	37.55	53.21	-15.66	AVG	
2		0.2220	38.94	9.60	48.54	62.74	-14.20	QP	
3		0.4060	34.19	9.59	43.78	57.73	-13.95	QP	
4	*	0.4500	25.92	9.59	35.51	46.88	-11.37	AVG	
5		0.7980	28.57	9.60	38.17	56.00	-17.83	QP	
6		0.8060	18.19	9.60	27.79	46.00	-18.21	AVG	
7		1.6660	25.80	9.60	35.40	56.00	-20.60	QP	
8		1.6660	15.99	9.60	25.59	46.00	-20.41	AVG	
9		3.5180	14.81	9.62	24.43	56.00	-31.57	QP	
10		3.5940	4.22	9.62	13.84	46.00	-32.16	AVG	
11		15.1980	10.05	9.70	19.75	50.00	-30.25	AVG	
12		15.2940	19.91	9.70	29.61	60.00	-30.39	QP	

*:Maximum data x:Over limit !:over margin

Power supply:	DC 24V (by Adapter)	Polarization	N



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.2740	28.40	9.60	38.00	51.00	-13.00	AVG	
2		0.2780	38.40	9.59	47.99	60.88	-12.89	QP	
3	*	0.5500	24.94	9.59	34.53	46.00	-11.47	AVG	
4		0.5540	33.61	9.59	43.20	56.00	-12.80	QP	
5		1.0620	26.69	9.60	36.29	56.00	-19.71	QP	
6		1.0620	17.09	9.60	26.69	46.00	-19.31	AVG	
7		3.2860	20.24	9.61	29.85	56.00	-26.15	QP	
8		3.3180	9.41	9.61	19.02	46.00	-26.98	AVG	
9		9.6860	7.34	9.69	17.03	50.00	-32.97	AVG	
10		10.3860	16.98	9.69	26.67	60.00	-33.33	QP	
11		28.4220	10.39	9.76	20.15	50.00	-29.85	AVG	
12		28.7500	17.20	9.77	26.97	60.00	-33.03	QP	

*:Maximum data x:Over limit !:over margin

5.2. Radiated Emission

TEST CONFIGURATION

Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 32.768KHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Anternna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Transd=AF +CL-AG

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in table below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission

Unwanted emissions that fall into restricted bands shall comply with the limits specified in RSS-Gen; and Unwanted emissions that do not fall within the restricted frequency bands shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

1. We measured Radiated Emission at GFSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
2. For below 1GHz testing recorded worst at GFSK DH5 middle channel.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		66.0342	18.25	9.02	27.27	40.00	-12.73	QP	200	10	
2		111.7380	16.31	14.89	31.20	43.50	-12.30	QP	200	40	
3		221.3921	7.76	14.60	22.36	46.00	-23.64	QP	200	70	
4		259.2338	13.37	14.11	27.48	46.00	-18.52	QP	200	120	
5		531.9635	8.47	23.05	31.52	46.00	-14.48	QP	200	250	
6	*	821.7103	5.63	28.14	33.77	46.00	-12.23	QP	200	330	

*:Maximum data x:Over limit !:over margin

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	43.9658	21.68	11.18	32.86	40.00	-7.14	QP	100	50	
2		80.0806	19.83	10.10	29.93	40.00	-10.07	QP	100	120	
3		145.3506	10.44	17.10	27.54	43.50	-15.96	QP	100	170	
4		213.7634	6.38	14.81	21.19	43.50	-22.31	QP	100	200	
5		494.1984	3.98	22.39	26.37	46.00	-19.63	QP	100	270	
6		887.6099	5.96	28.86	34.82	46.00	-11.18	QP	100	310	

*:Maximum data x:Over limit !:over margin

For 1GHz to 25GHz

GFSK (above 1GHz)

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804.00	55.47	PK	74	18.53	53.57	31.42	6.98	36.5	1.9
4804.00	43.39	AV	54	10.61	41.49	31.42	6.98	36.5	1.9
7206.00	50.94	PK	74	23.06	40.34	37.03	8.87	35.3	10.6
7206.00	43.45	AV	54	10.55	32.85	37.03	8.87	35.3	10.6

Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804.00	56.09	PK	74	17.91	54.19	31.42	6.98	36.5	1.9
4804.00	42.84	AV	54	11.16	40.94	31.42	6.98	36.5	1.9
7206.00	53.56	PK	74	20.44	42.96	37.03	8.87	35.3	10.6
7206.00	42.61	AV	54	11.39	32.01	37.03	8.87	35.3	10.6

Frequency(MHz):			2440		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4880.00	55.26	PK	74	18.74	53.2	30.98	7.58	36.5	2.06
4880.00	46.65	AV	54	7.35	44.59	30.98	7.58	36.5	2.06
7320.00	51.8	PK	74	22.2	40.88	37.66	8.56	35.3	10.92
7320.00	43.25	AV	54	10.75	32.33	37.66	8.56	35.3	10.92

Frequency(MHz):			2440		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4880.00	53.17	PK	74	20.83	51.11	30.98	7.58	36.5	2.06
4880.00	42.51	AV	54	11.49	40.45	30.98	7.58	36.5	2.06
7320.00	51.39	PK	74	22.61	40.47	37.66	8.56	35.3	10.92
7320.00	42.82	AV	54	11.18	31.9	37.66	8.56	35.3	10.92

Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960.00	53.9	PK	74	20.1	50.83	31.47	7.8	36.2	3.07
4960.00	47.63	AV	54	6.37	44.56	31.47	7.8	36.2	3.07
7440.00	55.51	PK	74	18.49	43.77	38.32	8.72	35.3	11.74
7440.00	43.26	PK	54	10.74	31.52	38.32	8.72	35.3	11.74

Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960.00	58.76	PK	74	15.24	55.69	31.47	7.8	36.2	3.07
4960.00	47.22	AV	54	6.78	44.15	31.47	7.8	36.2	3.07
7440.00	56.49	PK	74	17.51	44.75	38.32	8.72	35.3	11.74
7440.00	42.32	PK	54	11.68	30.58	38.32	8.72	35.3	11.74

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)- Pre-amplifier
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

5.3. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power,9.1.2.
The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

LIMIT

The Maximum Peak Output Power Measurement is 30dBm.

TEST RESULTS

See Appendix I

5.4. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

1.Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2.Set the RBW =3 kHz.
3.Set the VBW =10 KHz.
4.Set the span to 1.5 times the DTS channel bandwidth.
5.Detector = peak.
6.Sweep time = auto couple.
7.Trace mode = max hold.
8.Allow trace to fully stabilize.
9.Use the peak marker function to determine the maximum power level.
10.If measured value exceeds limit,reduce RBW(no less than 3 kHz)and repeat.
11.The resulting peak PSD level must be 8 dBm.

LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST RESULTS

See APPENDIX VI

5.5. 6dB Bandwidth and 99% Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz.
The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.
According to KDB558074 D01 V03 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.
1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 43 KHz RBW and 150 KHz VBW record the 99% bandwidth.

LIMIT

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

TEST RESULTS

See Appendix II&Appendix III

5.6. Band Edge Compliance of RF Emission

TEST REQUIREMENT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was placed on a turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed..
5. The distance between test antenna and EUT was 3 meter:
6. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

LIMIT

Below -20dB of the highest emission level in operating band.
Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)

TEST RESULTS

Results of Band Edges Test (Radiated)

Polarity:HORIZONTAL(GFSK-2480MHz)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	52.38	-8.29	44.09	74.00	-29.91	peak			
2	*	2483.500	42.10	-8.29	33.81	54.00	-20.19	AVG			

*:Maximum data x:Over limit !:over margin

Polarity:VERTICAL(GFSK-2480MHz)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	56.64	-8.29	48.35	74.00	-25.65	peak			
2	*	2483.500	45.23	-8.29	36.94	54.00	-17.06	AVG			

*:Maximum data x:Over limit !:over margin

Polarity:HORIZONTAL(GFSK-2402MHz)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.000	46.60	-8.43	38.17	74.00	-35.83	peak			
2	*	2390.000	35.20	-8.43	26.77	54.00	-27.23	AVG			

*:Maximum data x:Over limit !:over margin

Polarity:VERTICAL(GFSK-2402MHz)



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.000	46.24	-8.43	37.81	74.00	-36.19	peak			
2	*	2390.000	35.82	-8.43	27.39	54.00	-26.61	AVG			

*:Maximum data x:Over limit !:over margin

5.7. Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength , and mwasure frequeny range from 9KHz to 25GHz.

LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

TEST RESULTS

See Appendix IV

5.8. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The directional gains of antenna used for transmitting is 0dBi, and the antenna is an PCB antenna to PCB board and no consideration of replacement. Please see EUT photo for details.

Results: Compliance.

6. Test Setup Photos of the EUT





7. External and Internal Photos of the EUT

See related photo report.

APPENDIX I.Conducted Peak Output Power

Test Result

Mode	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Max. Avg. Power (dBm)	Limit (dBm)	Result
LE	0	3.112	2.05	None	30	PASS
	19	2.970	1.98	None	30	PASS
	39	2.511	1.78	None	30	PASS

APPENDIX II.99% Bandwidth

Test Result

Mode	Channel	99% BW (MHz)
LE	0	1.0188
LE	19	1.0264
LE	39	1.0225

Test Graphs

LE_Channel 0



LE_Channel 19



LE_Channel 39

Void

APPENDIX III.6dB Bandwidth

Test Result

Mode	Channel	Center Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
LE	0	2402	0.6603	0.5	PASS
	19	2440	0.6755		PASS
	39	2480	0.6573		PASS

Test Graphs



LE_Channel 0



LE_Channel 19



LE_Channel 39

Void

APPENDIX IV.Conducted Out Of Band Emission

Test Result

Mode	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
LE	0	2400.00	-41.318	-17.3	-24	PASS
		4803.76	-34.917	-17.3	-17.617	PASS
		7205.31	-55.595	-17.3	-38.295	PASS
		9608.11	-59.555	-17.3	-42.255	PASS
		24915.7	-51.339	-17.3	-34.039	PASS
	19	4879.30	-34.699	-17.49	-17.209	PASS
		7319.55	-54.542	-17.49	-37.052	PASS
		9759.80	-61.555	-17.49	-44.065	PASS
		24981.9	-51.389	-17.49	-33.899	PASS
	39	2483.50	-47.795	-17.94	-30	PASS
		4959.20	-36.858	-17.94	-18.918	PASS
		7439.41	-57.675	-17.94	-39.735	PASS
		9920.24	-61.639	-17.94	-43.699	PASS
		24948.2	-51.893	-17.94	-33.953	PASS

Test Graphs

In-Band Reference Level
LE_Channel 0

Out Of Band Emission
LE_Channel 0



Spurious Emission
LE_Channel 0

In-Band Reference Level
LE_Channel 19



Spurious Emissions
LE_Channel 19

In-Band Reference Level
LE_Channel 39



Out Of Band Emission
LE_Channel 39



Spurious Emission
LE_Channel 39

APPENDIX V.Duty Cycle

Test Result

Mode	Channel	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle (linear)	Duty Cycle Factor (dB)
LE	0	2.819	2.946	95.69	0.9569	0.1913
	19	2.822	2.952	95.59	0.9559	0.1959
	39	2.822	2.952	95.59	0.9559	0.1959

Test Graphs



LE


Agilent Spectrum Analyzer - Swept SA
05:12:04 PM Jul 24, 2023
Center Freq 2.440000000 GHz
Avg Type: RMS
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 26 dB
Ref Offset 12.2 dB
10 dB/div
Ref 20.00 dBm
ΔMkr3 2.952 ms
-39.50 dB
Center 2.440000000 GHz
Res BW 8 MHz
#VBW 8.0 MHz*
Span 0 Hz
Sweep 11.33 ms (2000 pts)
1 N 1 t 5.236 ms -3.35 dBm
2 Δ1 1 t (Δ) 2.822 ms (Δ) 0.39 dB
3 Δ1 1 t (Δ) 2.952 ms (Δ) -39.50 dB

LE


Agilent Spectrum Analyzer - Swept SA
05:12:40 PM Jul 24, 2023
Center Freq 2.480000000 GHz
Avg Type: RMS
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 26 dB
Ref Offset 12.25 dB
10 dB/div
Ref 20.00 dBm
ΔMkr3 2.952 ms
-39.24 dB
Center 2.480000000 GHz
Res BW 8 MHz
#VBW 8.0 MHz*
Span 0 Hz
Sweep 11.33 ms (2000 pts)
1 N 1 t 4.669 ms -3.59 dBm
2 Δ1 1 t (Δ) 2.822 ms (Δ) 0.38 dB
3 Δ1 1 t (Δ) 2.952 ms (Δ) -39.24 dB

LE

APPENDIX VI.Power Spectral Density

Test Result

Mode	Channel	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
LE	0	2.627	8	PASS
LE	19	2.484	8	PASS
LE	39	1.967	8	PASS

Test Graphs



LE_Channel 0



LE_Channel 19

LE_Channel 39

Void

.....End of Report.....