

1	2	3	4	5	6			
					Remark	Description	Editor	Date
A	封底 封面 正面 反面 折痕线, 无需印刷				Remark Description Editor Date			
B								
C								
D	NOTES(技术要求) : 1.Dimension after folding(折叠后尺寸): 150*150mm 2.Print colour(印刷颜色):4Colour printing (四色印刷). 3.Material(材质): 128g copperplate paper(128g 铜版纸). 4.Coating(表面处理): Varnishing(双面过光油) 5.Binding process(装订工艺): Paper folding(折页)——对折 6.Output Ipi(输出网线): 200 Ipi. 7.Tolerance(公差): L(长)*W(宽):±1mm. 8.Raw materials and the corresponding post processing should meet requirements defined in the T&W Environmental Protection Technical Standards. (原材料及后处理工艺均能满足我司《环保技术标准》要求).				1 2 3 4 5 6			

正面

反面

折痕线, 无需印刷

TOL± DIM							CUSTOMER: Heights		T&W 同维 SHENZHEN GONGJIN ELECTRONICS CO., LTD.			
RANGE		C1	C2	C3	C4							
0~6		0.1	0.1	0.15	0.2	TITLE: QUICK INSTALLATION GUIDE	MODEL: HT-360AXE V2				PART NO: 614000005387	
6~30		0.2	0.3	0.4	0.5							
30~80		0.25	0.5	0.9	1.2		UNIT'S	mm	VER:	V01	DRAW	郭海涛
80~180		0.3	0.8	1.2	1.5		MAT'L	/	SCALE	N/A	CHECK	赵 柳
180~315		0.5	1.3	1.8	3		FINISH	/	SHEET	1/1	PDE	DATE: 20231011
315~500		0.7	1.5	2.5	4							
500~800		0.9	1.8	3	5							
ANG.TOL±		0°~30°/0.1°	30°~60°/0.3°	60°~90°/0.5°								