

A	1	2	3	4	5	6				A
	封面 封底 正面 反面 折痕线, 无需印刷				Remark	Description		Editor	Date	
B									B	
C										C
D	NOTES(技术要求): 1.Dimension after folding(折叠后尺寸): 150*150mm 2.Print colour(印刷颜色):4Colour printing (四色印刷). 3.Material(材质): 128g copperplate paper(128g 铜版纸). 4.Coating(表面处理): Matte lamination (双面耐刮花哑膜) 5.Binding process(装订工艺): Paper folding(折页)——对折 6.Output lpi(输出网线): 200 lpi. 7.Tolerance(公差): L(长)*W(宽):±1mm. 8.Raw materials and the corresponding post processing should meet requirements defined in the Environmental Protection Technical Standards. (原材料及后处理工艺均能满足我司《环保技术标准》要求).									
1	2	3	4	5	6					

NOTES(技术要求):

1.Dimension after folding(折叠后尺寸): 150*150mm

2.Print colour(印刷颜色): 4Colour printing (四色印刷).

3.Material(材质): 128g copperplate paper(128g 铜版纸).

4.Coating(表面处理): Matte lamination (双面耐刮花哑膜)

5.Binding process(装订工艺): Paper folding(折页)——对折

6.Output lpi(输出网线): 200 lpi.

7.Tolerance(公差): L(长)*W(宽): ±1mm.

8.Raw materials and the corresponding post processing should meet requirements defined in the Environmental Protection Technical Standards.

(原材料及后处理工艺均能满足我司《环保技术标准》要求).

DIM	TOL±							CUSTOMER: Heights					
	RANGE	C1	C2	C3	C4								
	0~6	0.1	0.1	0.15	0.2			MODEL: HT-6766BE			PART NO:		
	6~30	0.2	0.3	0.4	0.5								
	30~80	0.25	0.5	0.9	1.2								
	80~180	0.3	0.8	1.2	1.5								
	180~315	0.5	1.3	1.8	3								
	315~500	0.7	1.5	2.5	4	UNIT'S mm		VER:	V01	DRAW	郭海涛		
	500~800	0.9	1.8	3	5	MAT'L /		SCALE	N/A	CHECK	赵 柳		
	ANG.TOL±	0°~30°/0.1°	30°~60°/0.3°	60°~90°/0.5°		FINISH /		SHEET	1/1	PDE	N/A		