

TEST REPORT

Product Name : Upgraded square wireless charger
Model Number : SW169, 1128280, 1128281
FCC ID : 2BCGV0051

Prepared for : NINGBO CSTAR IMPRINT E-COMMERCE CO., LTD.
Address : B46, BUILDING B, INDUSTRIAL BLOCK, QIAOTOUHU STREET, NINGHAI COUNTY, NINGBO CITY, ZHEJIANG PROVINCE

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : 1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology Research and Development Base, No.9, Xincheng Avenue, Songshanhu High-technology Industrial Development Zone, Dongguan, Guangdong, China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2608180296E00601R
Date of sample receipt : August 18, 2026
Date(s) of Tests : August 18, 2026 to September 12, 2026
Date of issue : September 12, 2026

TABLE OF CONTENT

Test Report Description	Page
1. TEST REPORT DESCRIPTION	3
2. GENERAL INFORMATION	5
2.1. Description of Device (EUT)	5
2.2. Input / Output Ports	5
2.3. Independent Operation Modes	5
2.4. Test Manner	6
2.5. Description of Test Facility	6
2.6. Description of Support Device	6
2.7. Measurement Uncertainty	7
3. SUMMARY OF TEST RESULTS	8
4. MEASURING DEVICE AND TEST EQUIPMENT	9
4.1. Conducted Emission Test Equipment	9
4.2. For 3m Radiated Emission Measurement	9
4.3. For other test items:	10
5. 20DB BANDWIDTH	11
5.1. Test Procedure	11
5.2. Test Results	11
6. POWER LINE CONDUCTED EMISSION MEASUREMENT	12
6.1. Block Diagram of Test Setup	12
6.2. Limits	12
6.3. Test Procedure	12
6.4. Measuring Results	13
7. RADIATED EMISSION TEST	16
7.1. Measurement Procedure	16
7.2. Test SET-UP (Block Diagram of Configuration)	16
7.3. Radiated Emission Limit	17
7.4. Measurement Result	18
8. ANTENNA REQUIREMENT	23

1. TEST REPORT DESCRIPTION

Applicant : NINGBO CSTAR IMPRINT E-COMMERCE CO., LTD.
Address : B46, BUILDING B, INDUSTRIAL BLOCK, QIAOTOUHU STREET, NINGHAI COUNTY, NINGBO CITY, ZHEJIANG PROVINCE
Manufacturer : NINGBO CSTAR IMPRINT E-COMMERCE CO., LTD.
Address : B46, BUILDING B, INDUSTRIAL BLOCK, QIAOTOUHU STREET, NINGHAI COUNTY, NINGBO CITY, ZHEJIANG PROVINCE
EUT : Upgraded square wireless charger
Model Name : SW169, 1128280, 1128281
Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by EMTEK (DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2020) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15C

The test results of this report relate only to the tested sample identified in this report.

Date of Test : August 18, 2026 to September 12, 2026

Prepared by : 
Jessica Zhang /Editor

Reviewer : 
Warren Deng /Supervisor

Approve & Authorized Signer : 
Sam Lv / Manager

Modified History

Version	Report No.	Revision Date	Summary
	EDG2608180296E00601R	/	Original Report



2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Characteristics	Description
Product Name	Upgraded square wireless charger
Model number	SW169, 1128280, 1128281 (Note: These models are the same, except for the model number; SW169 was selected for full test.)
Power Supply	DC 5V/2A, DC 9V 2A from USB
Operating Frequency Range	111-205KHz
Wireless Output Power	5W/7.5W/10W/15W
Modulation Technique	FSK
Antenna Type	Induction Coil antenna
Temperature Range	-10°C ~ +45°C

2.2. Input / Output Ports

Port #	Name	Type*	Cable Max. >3m	Cable Shielded	Comments
1	Enclosure	N/E	--	--	None
2	DC IN port	I/O	No	Unshielded	1 port
* Note: For the purposes of the present document, the following symbols apply: AC AC Power Port DC DC Power Port N/E Non-Electrical I/O Signal Input or Output Port (Not Involved in Process Control) TP Telecommunication Ports					

2.3. Independent Operation Modes

- A ON
1. Wireless 15W(100% load)
 2. Wireless 15W(50% load)
 3. Wireless 15W(10% load)
- Note: The mode A1 is the worst mode

2.4. Test Manner

Test Items	Test Voltage	Operation Modes
Conducted Emission	AC 120V/60Hz Battery	Mode A1
Radiated Emission	AC 120V/60Hz Battery	Mode A1

2.5. Description of Test Facility

Site Description

EMC Lab.

: Accredited by CNAS, 2026.08.12
The certificate is valid until 2030.07.05
The Laboratory has been assessed and proved to be in compliance with
CNAS-CL01:2018
The Certificate Registration Number is L3150

Accredited by FCC
Designation Number: CN1451
Test Firm Registration Number: 846861

Accredited by A2LA, April 05, 2021
The Certificate Registration Number is 4321.02

Accredited by Industry Canada
The Certificate Registration Number is CN0113

Name of Firm

: EMTEK (DONGGUAN) CO., LTD.

Site Location

: 1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology Research and
Development Base, No.9, Xincheng Avenue, Songshanhu
High-technology Industrial Development Zone, Dongguan, Guangdong,
China

2.6. Description of Support Device

No.	Equipment	Trade name	Model	S/N	Power Cord
1.	Wireless Load	N/A	15W	N/A	N/A
2.	Load	N/A	N/A	N/A	N/A

2.7. Measurement Uncertainty

Test Item	Uncertainty
Conducted Emission Uncertainty	: 2.08dB(9K-150KHz) 2.42dB(150K-30MHz)
Radiated Emission Uncertainty (3m Chamber)	: 3.32dB (30M~1GHz Polarize: H) 3.34dB (30M~1GHz Polarize: V) 4.98dB (1~6GHz) 5.20dB (6~18GHz)



3. SUMMARY OF TEST RESULTS

EMISSION		
Description of Test Item	Standard & Limits	Results
20DB BANDWIDTH	FCC Part 15, Subpart C- Section 15.217-257 ANSI C63.10-2020	Pass
Conducted Emission	FCC Part 15, Subpart C- Section 15.207 ANSI C63.10-2020	Pass
Radiated Emission	FCC Part 15, Subpart C- Section 15.209 ANSI C63.10-2020	Pass
Antenna requirement	FCC Part 15, Subpart C- Section 15.203 ANSI C63.10-2020	Pass
Note: N/A is an abbreviation for Not Applicable.		

4. MEASURING DEVICE AND TEST EQUIPMENT

4.1. Conducted Emission Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCI	100137	2026/4/23	1Year
AMN	Rohde&Schwarz	ENV216	101209	2026/4/23	1Year
AMN	Rohde&Schwarz	ENV216	100017	2026/4/23	1Year
RF Switching Unit	CDS	RSU-M2	38401	2026/4/23	1Year
AMN	Schwarzbeck	NNLK8121	8121-641	2026/4/23	1Year
AMN	Rohde&Schwarz	ESH3-Z6	101101	2026/4/23	1Year
AMN	Rohde&Schwarz	ESH3-Z6	101102	2026/4/23	1Year
Power Splitters & Dividers	Weinschel Associates	WA1506A	A1066	2026/4/23	1Year
Current Probe	FCC	F-52	8377	2026/4/23	1Year
Passive voltage probe	Rohde&Schwarz	ESH2-Z3	100122	2026/4/23	1Year
Cable	Rosenberger	RG 223/U	525178	2026/4/23	1Year
Cable	Rosenberger	RG223/U	525179	2026/4/23	1Year
Test Software	Farad	Ver.CON-03A1	--	N/A	N/A

4.2. For 3m Radiated Emission Measurement

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCI	101415	2026/4/23	1Year
Bi-log Hybrid Antenna	Schwarzbeck	VULB9163	141	2026/4/25	1Year
Pre-Amplifie	HP	8447F	OPTH64	2026/4/23	1 Year
Signal Analyzer	R&S	FSV30	103039	2026/4/23	1 Year
Horn Antenna	Schwarzbeck	BBHA9120D	1272	2026/4/25	1Year
Horn Antenna	Schwarzbeck	BBHA9170	9170-567	2026/4/25	1Year
Pre-Amplifie	LUNAR EM	PM1-18-40	J1010000008 1	2026/4/23	1Year
Loop antenna	Schwarzbeck	FMZB1519	1519-012	2026/4/25	1Year
Cable	Rosenberger	CIL02	A0783566	2026/4/23	1Year
Cable	HTS	CBL-26	D1245	2026/4/23	1Year
Cable	HTS	CBL-26	D8503	2026/4/23	1Year
Cable	HTS	CBL-26	/	2026/4/23	1Year
6 db attenuator	AR-WORLDWIDE	6dB/50FH-006-100	324011	2026/4/23	1Year
Test Software	Farad	Ver.RA-03A1	--	N/A	N/A

4.3. For other test items:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Wireless Connectivity Tester	R&S	CMW270	102543	2026/4/23	1Year
Automatic Control Unit	Tonscend	JS0806-2	2118060480	2026/4/23	1Year
Signal Analyzer	KEYSIGHT	N9010B	MY60242456	2026/4/23	1Year
Analog Signal Generator	KEYSIGHT	N5173B	MY61252625	2026/4/23	1Year
UP/DOWN-Converter	R&S	CMW-Z800A	100274	2026/4/23	1Year
Vector Signal Generator	KEYSIGHT	N5182B	MY61252674	2026/4/23	1Year
Frequency Extender	KEYSIGHT	N5182BX07	MY59362541	2026/4/23	1Year
Temperature&Humidity test chamber	ESPEC	EL-02KA	12107166	2026/4/23	1 Year
Radio frequency test system	Tonscend	JS1120-3	--	N/A	N/A

5. 20DB BANDWIDTH

5.1. Test Procedure


Set to the maximum power setting and enable the EUT transmit continuously
 Set RBW = 3 Hz.
 Set the video bandwidth (VBW) =10 Hz
 Set Span= 100 Hz
 Set Detector = Peak.
 Set Trace mode = max hold.
 Set Sweep = auto couple.
 Measure and record the results in the test report.

5.2. Test Results

Temperature: 25.1℃
 Humidity: 55.4%

Test Date: 2026.09.12
 Test By: Calvin


20dB Band=20.41 Hz



Date: 12.SEP.2026 11:02:43

6. POWER LINE CONDUCTED EMISSION MEASUREMENT

6.1. Block Diagram of Test Setup



LISN: Line Impedance Stabilization Network
AE: Associated equipment
EUT: Equipment under test

6.2. Limits

FCC Part 15.207

Frequency (MHz)			Limit (dBμV)	
			Quasi-peak Level	Average Level
0.15	~	0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50	~	5.00	56.0	46.0
5.00	~	30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.
NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

6.3. Test Procedure

The EUT was placed on a desk 0.8 m height from the metal ground plane and 0.4 m from the conducting wall of the shielding room and it was kept at least 0.8 m from any other grounded conducting surface. The size of the table will nominally be 1.5 m x1.0 m.

The rear of the arrangement shall be flush with the back of the supporting tabletop unless that would not be possible or typical of normal use.

All units of equipment forming the system under test (includes the EUT as well as connected peripherals and associated equipment or devices) shall be arranged such that a nominal 0.1 m separation is achieved between the neighboring units.

Connect EUT to the power mains through a line impedance stabilization network (LISN). Where the mains cable supplied by the manufacturer is longer than 1 m, the excess should be folded at the centre into a bundle no longer than 0.4 m, so that its length is shortened to 1 m.

All the support units are connecting to the other LISN.

The LISN provides 50 ohm coupling impedance for the measuring instrument.

Both sides of AC line were checked for maximum conducted interference.

The frequency range from 150 kHz to 30 MHz was sweep.

Set the test-receiver system to quasi peak detect function and average detect function, and to measure the conducted emissions values.

Test results were obtained from the following equation:


Emission Level (dB μ V) = LISN Factor (dB) + Cable Loss (dB) + Reading (dB μ V)

Margin (dB) = Emission Level (dB μ V) - Limit (dB μ V)

6.4. Measuring Results

PASS






Site site #1 Phase: L1 Temperature: 24.6

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		1.0260	24.56	17.57	42.13	56.00	-13.87	QP	
2		1.0260	18.70	17.57	36.27	46.00	-9.73	AVG	
3		2.3100	26.41	17.63	44.04	56.00	-11.96	QP	
4		2.3100	22.11	17.63	39.74	46.00	-6.26	AVG	
5		3.8500	27.42	17.70	45.12	56.00	-10.88	QP	
6	*	3.8500	24.38	17.70	42.08	46.00	-3.92	AVG	
7		5.1340	27.89	17.75	45.64	60.00	-14.36	QP	
8		5.1340	24.88	17.75	42.63	50.00	-7.37	AVG	
9		15.9180	29.58	17.79	47.37	60.00	-12.63	QP	
10		15.9180	25.60	17.79	43.39	50.00	-6.61	AVG	
11		19.2540	29.42	17.81	47.23	60.00	-12.77	QP	
12		19.2540	25.58	17.81	43.39	50.00	-6.61	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Weishanqin



Site site #1 Phase: **N** Temperature: 24.6

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.7700	26.47	17.56	44.03	56.00	-11.97	QP	
2	0.7700	19.56	17.56	37.12	46.00	-8.88	AVG	
3	2.3100	28.42	17.63	46.05	56.00	-9.95	QP	
4	2.3100	22.35	17.63	39.98	46.00	-6.02	AVG	
5	3.5900	29.75	17.69	47.44	56.00	-8.56	QP	
6 *	3.5900	23.66	17.69	41.35	46.00	-4.65	AVG	
7	5.1340	30.96	17.75	48.71	60.00	-11.29	QP	
8	5.1340	26.26	17.75	44.01	50.00	-5.99	AVG	
9	6.4180	29.84	17.76	47.60	60.00	-12.40	QP	
10	6.4180	24.23	17.76	41.99	50.00	-8.01	AVG	
11	16.6780	31.82	17.80	49.62	60.00	-10.38	QP	
12	16.6780	27.11	17.80	44.91	50.00	-5.09	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Weishanqin


7. RADIATED EMISSION TEST

7.1.Measurement Procedure


1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.
5. Use the following receiver/spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW=200Hz for 9KHz to 150KHz,
RBW=9kHz for 150KHz to 30MHz,
RBW=120KHz for 30MHz to 1GHz
VBW $\geq 3 \times$ RBW
Sweep = auto
Detector function = QP
Trace = max hold

7.2.Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



7.3.Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

FCC Part 15.209				
Frequency (MHz)	Field Strength Limitation		Field Strength Limitation Frequency tion at 3m Measurement Dist	
	(uV/m)	Dist	(uV/m)	(dBuV/m)
0.009 – 0.490	2400 / F(KHz)	300m	10000 * 2400/F(KHz)	20log 2400/F(KHz) + 80
0.490 – 1.705	24000 / F(KHz)	30m	100 * 24000/F(KHz)	20log 24000/F(KHz) + 40
1.705 – 30.00	30	30m	100* 30	20log 30 + 40
30.0 – 88.0	100	3m	100	20log 100
88.0 – 216.0	150	3m	150	20log 150
216.0 – 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

- Remark:
1. Emission level in dBuV/m=20 log (uV/m)
 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

7.4.Measurement Result

Operation Mode:	Low frequency	Test Date :	2026.08.31
Frequency Range:	9KHz~30MHz	Temperature :	24.3℃
Test Result:	PASS	Humidity :	56.0 %
Measured Distance:	3m	Test By:	Hu

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)	Note
0.1515	H	35.06	103.99	-68.93	PK
0.3976	H	42.12	95.61	-53.49	PK
0.6578	H	31.88	71.25	-39.37	PK
0.9282	H	25.13	68.27	-43.14	PK
1.8483	H	17.61	69.54	-51.93	PK
3.2240	H	14.20	69.54	-55.34	PK
0.0240	V	48.53	119.99	-71.46	PK
0.0400	V	53.89	115.55	-61.66	PK
0.0560	V	55.49	112.63	-57.14	PK
0.0720	V	56.55	110.45	-53.90	PK
0.0948	V	56.02	108.06	-52.04	PK
0.1333	V	81.55	105.10	-23.55	PK



Note: (1) All Readings are Peak Value.



(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) The average measurement was not performed when the peak measured data under the limit of average detection.


(4) EUT lying on the table position is the worst case result in the report.

9KHz-30MHz:






30MHz-1GHz:



No.	Mk.	Freq.	Reading	Ant.	Pre Amp	Cable	Measure-	Limit	Over	HI	Degree
		MHz	dBuV	Factor	Gain	loss	ment				
							dBuV/m	dBuV/m	dB	Detector	cm
1		54.4516	39.93	13.35	29	0.93	25.21	40.00	-14.79	QP	
2		80.6442	42.84	9.02	29.14	1.14	23.86	40.00	-16.14	QP	
3	*	112.5244	54.95	11.7	28.81	1.32	39.16	43.50	-4.34	QP	
4		173.8135	44.16	9.46	28.64	1.62	26.60	43.50	-16.90	QP	
5		239.9874	45.60	11.6	28.45	1.79	30.54	46.00	-15.46	QP	
6		373.3112	42.86	15.24	28.75	2.48	31.83	46.00	-14.17	QP	

*:Maximum data x:Over limit !:over margin

Operator: HU



No.	Mk.	Freq. MHz	Reading Level dBuV	Ant. Factor dB/m	Pre Amp Gain dB	Cable loss dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	HI	Degree	Comment
1		35.6240	50.16	11.52	29.08	0.92	33.52	40.00	-6.48	QP		
2	*	41.4215	49.87	12.53	29.04	0.94	34.30	40.00	-5.70	QP		
3		51.6616	48.54	13.06	28.98	0.96	33.58	40.00	-6.42	QP		
4		109.4116	51.33	12.06	28.82	1.3	35.87	43.50	-7.63	QP		
5		132.6850	52.75	8.64	28.76	1.43	34.06	43.50	-9.44	QP		
6		368.1116	41.85	15.35	28.71	2.46	30.95	46.00	-15.05	QP		

*:Maximum data x:Over limit !:over margin

Operator: HU

Remark:

1. Measurement (dBuV/m) = Antenna Factor(dB) -Amp Factor(dB) +Cable Loss(dB) + Reading(dBuV/m)
2. Over (dB) = Measurement (dBuV/m) - Limit (dBuV/m)

8. ANTENNA REQUIREMENT

The EUT's antenna, permanent attached antenna, used an Induction coil, The antenna's gain meets the requirement.



*** End of Report ***

声明 Statement

1. 本报告无授权批准人签字及“检验检测专用章”无效；

This report will be void without authorized signature or special seal for testing report.

2. 未经许可本报告不得部分复制；

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责；

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用；

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外；

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检测报告若有异议，请于收到报告之日起 20 日内提出；

Objections shall be raised within 20 days from the date receiving the report.