

## **FCC RF EXPOSURE REPORT**

*For*

**AX1800 Wi-Fi 6 Range Extender**

**MODEL NUMBER: RE600X**

**REPORT NUMBER: 4791046401-1-RF-3**

**ISSUE DATE: January 9, 2024**

**FCC ID: 2BCGWRE600XV2**

*Prepared for*

**TP-LINK CORPORATION PTE. LTD.**

**7 Temasek Boulevard #29-03 Suntec Tower One, Singapore 038987**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch**

**Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**

## Revision History

| Rev. | Issue Date      | Revisions     | Revised By |
|------|-----------------|---------------|------------|
| V0   | January 9, 2024 | Initial Issue |            |

## TABLE OF CONTENTS

|                                       |   |
|---------------------------------------|---|
| 1. ATTESTATION OF TEST RESULTS .....  | 4 |
| 2. TEST METHODOLOGY .....             | 5 |
| 3. FACILITIES AND ACCREDITATION ..... | 5 |
| 4. DESCRIPTION OF EUT .....           | 6 |
| 5. REQUIREMENT .....                  | 7 |

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: TP-LINK CORPORATION PTE. LTD.  
Address: 7 Temasek Boulevard #29-03 Suntec Tower One, Singapore  
038987

### Manufacturer Information


Company Name: TP-LINK CORPORATION PTE. LTD.  
Address: 7 Temasek Boulevard #29-03 Suntec Tower One, Singapore  
038987

### EUT Information

EUT Name: AX1800 Wi-Fi 6 Range Extender  
Model: RE600X  
Brand: tp-link  
Sample Received Date: October 17, 2023  
Sample Status: Normal  
Sample ID: 6552093  
Date of Tested: November 17, 2023 to January 8, 2024

| APPLICABLE STANDARDS |              |
|----------------------|--------------|
| STANDARD             | TEST RESULTS |
| FCC 47CFR§2.1091     | PASS         |
| KDB 447498 D04       | PASS         |


Prepared By:



Denny Huang

Senior Project Engineer

Checked By:



Kebo Zhang

Senior Project Engineer

Approved By:



Stephen Guo

Operations Manager

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 1 Subpart I, section 1.1307 and KDB 447498 D04 Interim General RF Exposure Guidance v01.

## 3. FACILITIES AND ACCREDITATION

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Accreditation Certificate | <p><b>A2LA (Certificate No.: 4102.01)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>ISED (Company No.: 21320)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p><b>VCCI (Registration No.: G-20192, R-20202, C-20153 and T-20155)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.<br/>Facility Name:<br/>Chamber D, the VCCI registration No. is G-20192 and C-20153<br/>Shielding Room B, the VCCI registration No. is C-20153 and T-20155</p> |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.

#### 4. DESCRIPTION OF EUT

|                                    |                     |                                                                                                                                                                                                                           |
|------------------------------------|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EUT Name/PMN:                      |                     | AX1800 Wi-Fi 6 Range Extender                                                                                                                                                                                             |
| HVIN:                              |                     | RE600XV2                                                                                                                                                                                                                  |
| FVIN:                              |                     | V2.20                                                                                                                                                                                                                     |
| Product Description<br>(2.4G WLAN) | Frequency Range:    | 2412 MHz to 2462 MHz                                                                                                                                                                                                      |
|                                    | Type of Modulation: | IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK)<br>IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)<br>IEEE 802.11ax: OFDMA(1024-QAM, 64-QAM, 16-QAM, QPSK, BPSK)                                                                   |
|                                    | Radio Technology:   | IEEE802.11b/g/n HT20/n HT40/ax HE20/ax HE40                                                                                                                                                                               |
| Product Description<br>(5G RLAN)   | Frequency Range:    | 5180 MHz to 5240 MHz(U-NII-1)<br>5260 MHz to 5320 MHz(U-NII-2A)<br>5500 MHz to 5720 MHz(U-NII-2C)<br>5745 MHz to 5825 MHz(U-NII-3)                                                                                        |
|                                    | Type of Modulation: | IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)<br>IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK) |
|                                    | Radio Technology:   | IEEE802.11a/n HT20/n HT40/<br>ac VHT20/ac VHT40/ac VHT80/<br>ax HE20/ax HE40/ax HE80/                                                                                                                                     |
| Normal Test Voltage:               |                     | AC 120 V, 60 Hz                                                                                                                                                                                                           |

## 5. REQUIREMENT

### LIMIT AND CALCULATION METHOD

According to 447498 D04 Interim General RF Exposure Guidance v01,

#### 2.1.4 MPE-Based Exemption

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.<sup>10</sup> For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

#### B.4 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of  $\lambda/4$ .

As for devices with antennas of length greater than  $\lambda/4$  where the gain is not well defined, but always less than that of a half-wave dipole (length  $\lambda/2$ ), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula (B.2).

### **MPE-based Exemption**

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20 \text{ cm}}$  is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

| Frequency (MHz) | Distance (mm) |    |    |    |     |     |     |     |     |     |     |
|-----------------|---------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|
|                 |               | 5  | 10 | 15 | 20  | 25  | 30  | 35  | 40  | 45  | 50  |
|                 | 300           | 39 | 65 | 88 | 110 | 129 | 148 | 166 | 184 | 201 | 217 |
|                 | 450           | 22 | 44 | 67 | 89  | 112 | 135 | 158 | 180 | 203 | 226 |
|                 | 835           | 9  | 25 | 44 | 66  | 90  | 116 | 145 | 175 | 207 | 240 |
|                 | 1900          | 3  | 12 | 26 | 44  | 66  | 92  | 122 | 157 | 195 | 236 |
|                 | 2450          | 3  | 10 | 22 | 38  | 59  | 83  | 111 | 143 | 179 | 219 |
|                 | 3600          | 2  | 8  | 18 | 32  | 49  | 71  | 96  | 125 | 158 | 195 |
|                 | 5800          | 1  | 6  | 14 | 25  | 40  | 58  | 80  | 106 | 136 | 169 |

### **Fixed RF sources operating in the same time-averaging period- § 1.1307(b)(3)(ii)(B)**

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated $_k$  term) shall be used to determine exemption for simultaneous transmission according to Formula (C.1) [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1 \quad (\text{C.1})$$

**CALCULATED RESULTS****For Single RF Source**

| Operating Mode | Max. Tune up Power | Antenna Gain | EIRP  | ERP   | ERP     | Distance | Limit Threshold |
|----------------|--------------------|--------------|-------|-------|---------|----------|-----------------|
|                | (dBm)              | (dBi)        | (dBm) | (dBm) | (mW)    | (cm)     | (mW)            |
| WIFI 2.4GHz    | 27                 | 2            | 29    | 26.85 | 484.172 | 20       | 3060            |
| WIFI 5GHz      | 28                 | 3            | 31    | 28.85 | 767.361 | 20       | 3060            |

**For Simultaneous Transmissions**

| Operating Mode | ERP    | Limit Threshold | Ratio | Sum of Ratios | Limit of Ratios |
|----------------|--------|-----------------|-------|---------------|-----------------|
|                | (mW)   | (mW)            |       |               |                 |
| WIFI 2.4GHz    | 147.23 | 3060            | 0.158 | 0.401         | 1               |
| WIFI 5GHz      | 108.89 | 3060            | 0.251 |               |                 |

Note:

1. The calculated distance is 20 cm.
2. The power comes from operation description.
3. All modes had been evaluated, but only the worst data was recorded in the report.

---

**END OF REPORT**