

CFR 47 FCC PART 15 SUBPART C

TEST REPORT

For

SPECTA Mini

MODEL NUMBER: TQFDUB1

REPORT NUMBER: 4791156651.2-1-RF-1

ISSUE DATE: February 7, 2024

FCC ID: 2BCHV-TQFDUB1

Prepared for

**COGITO TECH COMPANY LIMITED
21/F Tai Yau Building, 181 Johnston Road, Wanchai Hong Kong**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	February 7, 2024	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	/	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.2.3.1	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.5	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.12 & Clause 11.13	FCC Part 15.247 (d) FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C > when <Simple Acceptance> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	6
2. TEST METHODOLOGY.....	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY.....	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT	9
5.2. MAXIMUM OUTPUT POWER.....	9
5.3. CHANNEL LIST	9
5.4. TEST CHANNEL CONFIGURATION	11
5.5. THE WORSE CASE POWER SETTING PARAMETER	12
5.6. DESCRIPTION OF AVAILABLE ANTENNAS	12
5.7. THE WORSE CASE CONFIGURATIONS.....	13
5.8. DESCRIPTION OF TEST SETUP.....	14
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	15
7. ANTENNA PORT TEST RESULTS	17
7.1. CONDUCTED OUTPUT POWER	17
7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....	18
7.3. POWER SPECTRAL DENSITY	20
7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	21
7.5. DUTY CYCLE	23
8. RADIATED TEST RESULTS.....	24
8.1. RESTRICTED BANDEDGE	32
8.2. SPURIOUS EMISSIONS (1 GHZ ~ 3 GHZ)	56
8.3. SPURIOUS EMISSIONS (3 GHZ ~ 18 GHZ)	62
8.4. SPURIOUS EMISSIONS (9 KHZ ~ 30 MHZ).....	100
8.5. SPURIOUS EMISSIONS (18 GHZ ~ 26 GHZ)	103
8.6. SPURIOUS EMISSIONS (30 MHZ ~ 1 GHZ)	105
9. ANTENNA REQUIREMENT	107
10. AC POWER LINE CONDUCTED EMISSION	108
11. TEST DATA.....	111
11.1. APPENDIX A: DTS BANDWIDTH.....	111

11.1.1.	Test Result.....	111
11.1.2.	Test Graphs	113
11.2.	<i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH.....</i>	<i>128</i>
11.2.1.	Test Result.....	128
11.2.2.	Test Graphs	130
11.3.	<i>APPENDIX C: MAXIMUM CONDUCTED AVERAGE OUTPUT POWER.....</i>	<i>145</i>
11.3.1.	Test Result.....	145
11.4.	<i>APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY</i>	<i>147</i>
11.4.1.	Test Result.....	147
11.4.2.	Test Graphs	149
11.5.	<i>APPENDIX E: BAND EDGE MEASUREMENTS.....</i>	<i>164</i>
11.5.1.	Test Result.....	164
11.5.2.	Test Graphs	166
11.6.	<i>APPENDIX F: CONDUCTED SPURIOUS EMISSION</i>	<i>178</i>
11.6.1.	Test Result.....	178
11.6.2.	Test Graphs	181
11.7.	<i>APPENDIX G: DUTY CYCLE.....</i>	<i>224</i>
11.7.1.	Test Result.....	224
11.7.2.	Test Graphs	225

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: COGITO TECH COMPANY LIMITED
Address: 21/F Tai Yau Building, 181 Johnston Road, Wanchai Hong Kong

Manufacturer Information


Company Name: COGITO TECH COMPANY LIMITED
Address: 21/F Tai Yau Building, 181 Johnston Road, Wanchai Hong Kong

EUT Information

EUT Name: SPECTA Mini
Model: TQFDUB1
Brand: SPECTA
Sample Received Date: January 15, 2024
Sample Status: Normal
Sample ID: 6847974
Date of Tested: January 29, 2024 to February 5, 2024


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	Pass

Prepared By:



Denny Huang
Senior Project Engineer

Checked By:



Kebo Zhang
Senior Project Engineer

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C, KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, KDB 662911 D01 Multiple Transmitter Output v02r01, CFR 47 FCC Part 2, ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: G-20192, C-20153, T-20155 and R-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20192 and R-20202 Shielding Room B, the VCCI registration No. is C-20153 and T-20155
----------------------------------	--

Note 1:

All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	SPECTA Mini
Model	TQFDUB1
Ratings	Input: DC 5 V, 2 A Battery: DC 7.7 V, 17.32 Wh

Radio Technology	SRD 2.4G
Operation Frequency	2.4GHz 1.4 MHz Bandwidth (2407.5 MHz ~ 2465.5 MHz) 2.4GHz 1.4 MHz Bandwidth (CA Mode) (2409.12 MHz ~ 2467.12 MHz) 2.4GHz 3 MHz Bandwidth (2417.5 MHz ~ 2456.5 MHz) 2.4GHz 10 MHz Bandwidth (2405.5 MHz ~ 2476.5 MHz) 2.4GHz 20 MHz Bandwidth (2410.5 MHz ~ 2472.5 MHz)
Modulation	OFDM (QPSK, 16QAM, 64QAM)

5.2. MAXIMUM OUTPUT POWER

SRD 2.4GHz	Frequency (MHz)	Channel Number	Maximum Conducted Average Output Power (dBm)
1.4 MHz Mode	2407.5 MHz ~ 2465.5 MHz	1-30[30]	13.35
1.4 MHz CA Mode	2409.12 MHz ~ 2467.12 MHz	1-30[30]	13.21
3 MHz Mode	2417.5 MHz ~ 2456.5 MHz	1-14[14]	13.28
10 MHz Mode	2405.5 MHz ~ 2476.5 MHz	1-72[72]	23.14
20 MHz Mode	2410.5 MHz ~ 2472.5 MHz	1-63[63]	22.64

5.3. CHANNEL LIST

2.4GHz 1.4 MHz Bandwidth (2407.5 MHz ~ 2465.5 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2407.5	9	2423.5	17	2439.5	25	2455.5
2	2409.5	10	2425.5	18	2441.5	26	2457.5
3	2411.5	11	2427.5	19	2443.5	27	2459.5
4	2413.5	12	2429.5	20	2445.5	28	2461.5
5	2415.5	13	2431.5	21	2447.5	29	2463.5
6	2417.5	14	2433.5	22	2449.5	30	2465.5
7	2419.5	15	2435.5	23	2451.5	/	/
8	2421.5	16	2437.5	24	2453.5	/	/

2.4GHz 1.4 MHz Bandwidth CA Mode (2409.12 MHz ~ 2467.12 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2409.12	9	2425.12	17	2441.12	25	2457.12
2	2411.12	10	2427.12	18	2443.12	26	2459.12
3	2413.12	11	2429.12	19	2445.12	27	2461.12
4	2415.12	12	2431.12	20	2447.12	28	2463.12
5	2417.12	13	2433.12	21	2449.12	29	2465.12
6	2419.12	14	2435.12	22	2451.12	30	2467.12
7	2421.12	15	2437.12	23	2453.12	/	/
8	2423.12	16	2439.12	24	2455.12	/	/

2.4GHz 3 MHz Bandwidth Mode (2417.5 MHz ~ 2456.5 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2417.5	5	2432.5	9	2441.5	13	2453.5
2	2420.5	6	2429.5	10	2444.5	14	2456.5
3	2423.5	7	2435.5	11	2447.5	/	/
4	2426.5	8	2438.5	12	2450.5	/	/

2.4GHz 10 MHz Bandwidth (2405.5 MHz ~ 2476.5 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405.5	18	2424.5	37	2443.5	56	2462.5
2	2406.5	19	2425.5	38	2444.5	57	2463.5
3	2407.5	20	2426.5	39	2445.5	58	2464.5
4	2408.5	21	2427.5	40	2446.5	59	2465.5
5	2409.5	22	2428.5	41	2447.5	60	2466.5
6	2410.5	23	2429.5	42	2448.5	61	2467.5
7	2411.5	24	2430.5	43	2449.5	62	2466.5
8	2412.5	25	2431.5	44	2450.5	63	2467.5
9	2413.5	26	2432.5	45	2451.5	64	2468.5
10	2414.5	27	2433.5	46	2452.5	65	2469.5
11	2415.5	28	2434.5	47	2453.5	66	2470.5
12	2416.5	29	2435.5	48	2454.5	67	2471.5
13	2417.5	30	2436.5	49	2455.5	68	2472.5
14	2418.5	31	2437.5	50	2456.5	69	2473.5
15	2419.5	32	2438.5	51	2457.5	70	2474.5
16	2420.5	33	2439.5	52	2458.5	71	2475.5
17	2421.5	34	2440.5	53	2459.5	72	2476.5
18	2422.5	35	2441.5	54	2460.5	/	/
17	2423.5	36	2442.5	55	2461.5	/	/

2.4GHz 20 MHz Bandwidth (2410.5 MHz ~ 2472.5 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2410.5	17	2426.5	33	2442.5	49	2458.5
2	2411.5	18	2427.5	34	2443.5	50	2459.5
3	2412.5	19	2428.5	35	2444.5	51	2460.5
4	2413.5	20	2429.5	36	2445.5	52	2461.5
5	2414.5	21	2430.5	37	2446.5	53	2462.5
6	2415.5	22	2431.5	38	2447.5	54	2463.5
7	2416.5	23	2432.5	39	2448.5	55	2464.5
8	2417.5	24	2433.5	40	2449.5	56	2465.5
9	2418.5	25	2434.5	41	2450.5	57	2466.5
10	2419.5	26	2435.5	42	2451.5	58	2467.5
11	2420.5	27	2436.5	43	2452.5	59	2468.5
12	2421.5	28	2437.5	44	2453.5	60	2469.5
13	2422.5	29	2438.5	45	2454.5	61	2470.5
14	2423.5	30	2439.5	46	2455.5	62	2471.5
15	2424.5	31	2440.5	47	2456.5	63	2472.5
16	2425.5	32	2441.5	48	2457.5	/	/

5.4. TEST CHANNEL CONFIGURATION

SRD 2.4GHz	Test Channel Number	Frequency
1.4 MHz Mode	CH 1(Low Channel), CH 16(MID Channel), CH 30(High Channel)	2407.5 MHz, 2437.5 MHz, 2465.5 MHz
1.4 MHz CA Mode	CH 1(Low Channel), CH 15(MID Channel), CH 34(High Channel)	2409.12 MHz, 2437.12 MHz, 2467.12 MHz
3 MHz Mode	CH 1(Low Channel), CH 8(MID Channel), CH 14(High Channel)	2417.5 MHz, 2438.5 MHz, 2456.5 MHz
10 MHz Mode	CH 1(Low Channel), CH 2, CH 3, CH 34(MID Channel), CH 71, CH 72(High Channel)	2405.5 MHz, 2406.5 MHz, 2407.5 MHz, 2440.5 MHz, 2475.5 MHz, 2476.5 MHz
20 MHz Mode	CH 1(Low Channel), CH 2, CH 3, CH 4, CH 5, CH 32(MID Channel), CH 60, CH 61, CH 62, CH 63(High Channel)	2410.5 MHz, 2411.5 MHz, 2412.5 MHz, 2413.5 MHz, 2414.5 MHz, 2441.5 MHz, 2469.5 MHz, 2470.5 MHz, 2471.5 MHz, 2472.5 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5 MHz Band				
Test Software		SdrConsole		
Mode	Transmit Antenna Number	Test Software setting value		
		NCB: 1.4 MHz/1.4 MHz CA/3 MHz/10 MHz/20 MHz		
		Low Channel	MID Channel	High Channel
1.4 MHz Mode	1	-2	-2	0
	2	-2	-2	0
1.4 MHz Mode CA	1	0	0	0
	2	0	0	0
3 MHz Mode	1	2	2	2
	2	2	2	2
10 MHz Mode	1	16	6	38
	2	16	6	38
20 MHz Mode	1	28	4	50
	2	28	4	50

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	Maximum Antenna Gain (dBi)
1	2400 ~ 2483.5	Dipole Antenna	2.5
2	2400 ~ 2483.5	Dipole Antenna	2.5

Test Mode	Transmit and Receive Mode	Description
1.4 MHz Mode	☒ 1TX, 2RX (Note 3)	ANT 1 & 2 can be used as transmitting antenna. ANT 1 & 2 can be used as receiving antenna.
1.4 MHz CA Mode	☒ 1TX, 2RX (Note 3)	ANT 1 & 2 can be used as transmitting antenna. ANT 1 & 2 can be used as receiving antenna.
3 MHz Mode	☒ 1TX, 2RX (Note 3)	ANT 1 & 2 can be used as transmitting antenna. ANT 1 & 2 can be used as receiving antenna.
10 MHz Mode	☒ 1TX, 2RX (Note 3)	ANT 1 & 2 can be used as transmitting antenna. ANT 1 & 2 can be used as receiving antenna.
20 MHz Mode	☒ 1TX, 2RX (Note 3)	ANT 1 & 2 can be used as transmitting antenna. ANT 1 & 2 can be used as receiving antenna.

Note: 1. The value of the antenna gain was declared by customer.

2. 2.4GHz and 5.8GHz radio doesn't support simultaneous transmission.

3. The EUT has two antennas, but only one antenna was used as transmit antenna during used.

5.7. THE WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst case Data Rates declared by the customer:

- SRD 2.4G-1.4 MHz Mode/QPSK
- SRD 2.4G-1.4 MHz CA Mode/QPSK
- SRD 2.4G-3 MHz Mode/QPSK
- SRD 2.4G-10 MHz Mode/QPSK
- SRD 2.4G-20 MHz Mode/QPSK

The EUT has 2 separate antennas which correspond to 2 separate antenna ports. Core 1 and Core 2 correspond to antenna 1 and antenna 2 respectively.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

The EUT has two antennas, but only one antenna was enabled during used.

Radiated emissions tests were performed with both two antennas, but only the worst data (ANT2) was recorded in the report.

5.8. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	Lenovo	E42-80	/
2	Adapter Power	/	QC18-US	Input: AC 100 ~ 240 V, 50/60 Hz, 0.3 A Output: DC 5 V, 3 A

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	Type C	Unshielded	1.0	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a laptop.

SETUP DIAGRAM FOR TESTS



6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Mar.31,2023	Mar.30,2024
Vector Signal Generator	R&S	SMBV100A	261637	Oct.12, 2023	Oct.11, 2024
Signal Generator	R&S	SMB100A	178553	Oct.12, 2023	Oct.11, 2024
Signal Analyzer	R&S	FSV40	101118	Oct.12, 2023	Oct.11, 2024
Software					
Description	Manufacturer		Name	Version	
For R&S TS 8997 Test System	Rohde & Schwarz		EMC 32	10.60.10	
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.12, 2023	Oct.11, 2024
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.25, 2023	Sep.24, 2024
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.12, 2023	Oct.11, 2024
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.12, 2023	Oct.11, 2024
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.12, 2023	Oct.11, 2024
DC power supply	Keysight	E3642A	MY55159130	Oct.12, 2023	Oct.11, 2024
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Oct.12, 2023	Oct.11, 2024
Attenuator	Aglient	8495B	2814a12853	Oct.12, 2023	Oct.11, 2024
RF Control Unit	Tonscend	JS0806-2	23B80620666	April 18, 2023	April 17, 2024
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Oct.13, 2023	Oct.12, 2024
Two-Line V-Network	R&S	ENV216	101983	Oct.13, 2023	Oct.12, 2024
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Oct.13, 2023	Oct.12, 2024
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.12, 2023	Oct.11, 2024
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.12, 2023	Oct.11, 2024
EMI Measurement Receiver	R&S	ESR26	101377	Oct.12, 2023	Oct.11, 2024
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.12, 2023	Oct.11, 2024
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.12, 2023	Oct.11, 2024
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.12, 2023	Oct.11, 2024
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.12, 2023	Oct.11, 2024
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Oct.12, 2023	Oct.11, 2024
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Oct.12, 2023	Oct.11, 2024
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	AVG Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4 °C	Relative Humidity	64.5%
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4 °C	Relative Humidity	64.5%
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.5.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms)
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{OBW bandwidth}$
Trace	Employ trace averaging(rms)mode over a minimum of 100 traces
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4 °C	Relative Humidity	64.5%
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4 °C	Relative Humidity	64.5%
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

TEST RESULTS

Please refer to section "Test Data" - Appendix E&F

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	23.4 °C	Relative Humidity	64.5%
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

TEST RESULTS

Please refer to section "Test Data" - Appendix G

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz




TEST ENVIRONMENT

Temperature	24.7 °C	Relative Humidity	55%
Atmosphere Pressure	101 kPa	Test Voltage	DC 5 V

TEST RESULTS


8.1. RESTRICTED BANDEDGE

Test Mode:	SRD 1.4MHz PK	Frequency(MHz):	2407.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2371.425	17.92	32.11	50.03	74.00	-23.97	peak
2	2390.000	14.85	32.16	47.01	74.00	-26.99	peak

Test Mode:	SRD 1.4MHz PK	Frequency(MHz):	2465.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.76	32.44	47.20	74.00	-26.80	peak
2	2486.040	16.58	32.44	49.02	74.00	-24.98	peak

Test Mode:	SRD 1.4MHz CA PK	Frequency(MHz):	2409.12
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2371.110	17.36	32.10	49.46	74.00	-24.54	peak
2	2390.000	15.29	32.16	47.45	74.00	-26.55	peak

Test Mode:	SRD 1.4MHz CA PK	Frequency(MHz):	2467.12
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.70	32.44	47.14	74.00	-26.86	peak
2	2486.095	16.36	32.44	48.80	74.00	-25.20	peak

Test Mode:	SRD 3MHz PK	Frequency(MHz):	2417.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2371.200	20.17	32.11	52.28	74.00	-21.72	peak
2	2390.000	19.67	32.16	51.83	74.00	-22.17	peak

Test Mode:	SRD 3MHz AV	Frequency(MHz):	2417.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2371.200	8.51	32.11	40.62	54.00	-13.38	AVG
2	2390.000	5.83	32.16	37.99	54.00	-16.01	AVG

Test Mode:	SRD 3MHz PK	Frequency(MHz):	2456.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	19.38	32.44	51.82	74.00	-22.18	peak
2	2486.700	20.58	32.45	53.03	74.00	-20.97	peak

Test Mode:	SRD 3MHz AV	Frequency(MHz):	2456.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	6.76	32.44	39.20	54.00	-14.80	AVG
2	2486.700	6.85	32.45	39.30	54.00	-14.70	AVG

Test Mode:	SRD 10MHz PK	Frequency(MHz):	2405.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2371.200	21.30	32.11	53.41	74.00	-20.59	peak
2	2390.000	20.77	32.16	52.93	74.00	-21.07	peak

Test Mode:	SRD 10MHz AV	Frequency(MHz):	2405.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2371.200	8.42	32.11	40.53	54.00	-13.47	AVG
2	2390.000	7.13	32.16	39.29	54.00	-14.71	AVG

Test Mode:	SRD 10MHz PK	Frequency(MHz):	2475.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	35.04	32.44	67.48	74.00	-6.52	peak
2	2483.600	36.16	32.44	68.60	74.00	-5.40	peak

Test Mode:	SRD 10MHz AV	Frequency(MHz):	2475.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.28	32.44	52.72	54.00	-1.28	AVG
2	2483.600	20.26	32.44	52.70	54.00	-1.30	AVG

Test Mode:	SRD 10MHz PK	Frequency(MHz):	2476.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	37.80	32.44	70.24	74.00	-3.76	peak

Test Mode:	SRD 10MHz AV	Frequency(MHz):	2476.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	19.71	32.44	52.15	54.00	-1.85	AVG

Test Mode:	SRD 20MHz PK	Frequency(MHz):	2410.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.600	29.61	32.16	61.77	74.00	-12.23	peak
2	2390.000	27.76	32.16	59.92	74.00	-14.08	peak

Test Mode:	SRD 20MHz AV	Frequency(MHz):	2410.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.600	13.17	32.16	45.33	54.00	-8.67	AVG
2	2390.000	13.94	32.16	46.10	54.00	-7.90	AVG

Test Mode:	SRD 20MHz PK	Frequency(MHz):	2469.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	33.31	32.44	65.75	74.00	-8.25	peak
2	2484.200	34.63	32.44	67.07	74.00	-6.93	peak

Test Mode:	SRD 20MHz AV	Frequency(MHz):	2469.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.28	32.44	52.72	54.00	-1.28	AVG
2	2484.200	20.01	32.44	52.45	54.00	-1.55	AVG

Test Mode:	SRD 20MHz PK	Frequency(MHz):	2470.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	38.38	32.44	70.82	74.00	-3.18	peak
2	2484.850	38.76	32.44	71.20	74.00	-2.80	peak

Test Mode:	SRD 20MHz AV	Frequency(MHz):	2470.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.14	32.44	52.58	54.00	-1.42	AVG
2	2484.850	20.09	32.44	52.53	54.00	-1.47	AVG

Test Mode:	SRD 20MHz PK	Frequency(MHz):	2471.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	34.40	32.44	66.84	74.00	-7.16	peak
2	2485.150	36.38	32.44	68.82	74.00	-5.18	peak

Test Mode:	SRD 20MHz AV	Frequency(MHz):	2471.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.27	32.44	52.71	54.00	-1.29	AVG
2	2485.150	19.76	32.44	52.20	54.00	-1.80	AVG

Test Mode:	SRD 20MHz PK	Frequency(MHz):	2472.5
Polarity:	Vertical	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.03	32.44	71.47	74.00	-2.53	peak
2	2483.600	40.56	32.44	73.00	74.00	-1.00	peak


Test Mode:	SRD 20MHz AV	Frequency(MHz):	2472.5
Polarity:	Vertical	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	15.22	32.44	47.66	54.00	-6.34	AVG
2	2483.600	15.20	32.44	47.64	54.00	-6.36	AVG


8.2. SPURIOUS EMISSIONS (1 GHZ ~ 3 GHZ)

Test Mode:	SRD 10MHz	Frequency(MHz):	2405.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1174.000	46.33	-14.22	32.11	74.00	-41.89	peak
2	1770.000	45.35	-11.82	33.53	74.00	-40.47	peak
3	2182.000	45.31	-10.13	35.18	74.00	-38.82	peak
4	2405.500	46.75	-8.96	37.79	/	/	Fundamental
5	2586.000	44.02	-8.06	35.96	74.00	-38.04	peak
6	2828.000	43.48	-6.84	36.64	74.00	-37.36	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2405.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1464.000	46.13	-12.87	33.26	74.00	-40.74	peak
2	2122.000	46.53	-10.43	36.10	74.00	-37.90	peak
3	2342.000	47.02	-9.30	37.72	74.00	-36.28	peak
4	2405.500	47.43	-8.96	38.47	/	/	Fundamental
5	2578.000	47.36	-8.10	39.26	74.00	-34.74	peak
6	2622.000	47.96	-7.87	40.09	74.00	-33.91	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2440.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1414.000	46.47	-13.11	33.36	74.00	-40.64	peak
2	1950.000	47.02	-11.22	35.80	74.00	-38.20	peak
3	2122.000	46.46	-10.43	36.03	74.00	-37.97	peak
4	2440.500	45.07	-8.80	36.27	/	/	Fundamental
5	2590.000	44.57	-8.04	36.53	74.00	-37.47	peak
6	2904.000	43.97	-6.46	37.51	74.00	-36.49	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2440.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1298.000	46.98	-13.65	33.33	74.00	-40.67	peak
2	2122.000	48.41	-10.43	37.98	74.00	-36.02	peak
3	2342.000	48.97	-9.30	39.67	74.00	-34.33	peak
4	2440.500	55.06	-8.80	46.26	/	/	Fundamental
5	2622.000	48.07	-7.87	40.20	74.00	-33.80	peak
6	2906.000	45.01	-6.46	38.55	74.00	-35.45	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2476.5
Polarity:	Horizontal	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1744.000	48.37	-11.90	36.47	74.00	-37.53	peak
2	1966.000	51.26	-11.17	40.09	74.00	-33.91	peak
3	2194.000	48.15	-10.06	38.09	74.00	-35.91	peak
4	2340.000	47.94	-9.31	38.63	74.00	-35.37	peak
5	2476.500	47.41	-8.66	38.75	/	/	Fundamental
6	2644.000	49.67	-7.77	41.90	74.00	-32.10	peak


Test Mode:	SRD 10MHz	Frequency(MHz):	2476.5
Polarity:	Vertical	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1464.000	46.30	-12.87	33.43	74.00	-40.57	peak
2	1728.000	45.56	-11.95	33.61	74.00	-40.39	peak
3	2122.000	48.60	-10.43	38.17	74.00	-35.83	peak
4	2344.000	47.92	-9.30	38.62	74.00	-35.38	peak
5	2476.500	55.68	-8.66	47.02	/	/	Fundamental
6	2622.000	47.39	-7.87	39.52	74.00	-34.48	peak


8.3. SPURIOUS EMISSIONS (3 GHZ ~ 18 GHZ)

Test Mode:	SRD 1.4MHz	Frequency(MHz):	2407.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6570.000	40.99	4.57	45.56	74.00	-28.44	peak
2	9240.000	37.38	10.58	47.96	74.00	-26.04	peak
3	10425.000	36.58	12.84	49.42	74.00	-24.58	peak
4	11775.000	33.07	17.35	50.42	74.00	-23.58	peak
5	13635.000	28.66	21.19	49.85	74.00	-24.15	peak
6	17955.000	24.29	25.42	49.71	74.00	-24.29	peak

Test Mode:	SRD 1.4MHz	Frequency(MHz):	2407.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6420.000	44.42	3.91	48.33	74.00	-25.67	peak
2	6570.000	42.70	4.57	47.27	74.00	-26.73	peak
3	11070.000	34.46	15.03	49.49	74.00	-24.51	peak
4	11880.000	32.49	17.63	50.12	74.00	-23.88	peak
5	13620.000	28.60	21.15	49.75	74.00	-24.25	peak
6	17925.000	24.34	25.25	49.59	74.00	-24.41	peak

Test Mode:	SRD 1.4MHz	Frequency(MHz):	2437.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6495.000	39.43	4.20	43.63	74.00	-30.37	peak
2	9360.000	36.77	10.64	47.41	74.00	-26.59	peak
3	10365.000	35.95	12.72	48.67	74.00	-25.33	peak
4	11475.000	33.39	16.51	49.90	74.00	-24.10	peak
5	13920.000	28.04	21.79	49.83	74.00	-24.17	peak
6	17955.000	23.67	25.42	49.09	74.00	-24.91	peak

Test Mode:	SRD 1.4MHz	Frequency(MHz):	2437.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3855.000	48.46	-4.14	44.32	74.00	-29.68	peak
2	7005.000	37.33	6.69	44.02	74.00	-29.98	peak
3	10290.000	36.44	12.59	49.03	74.00	-24.97	peak
4	12675.000	31.80	17.99	49.79	74.00	-24.21	peak
5	13875.000	28.28	21.70	49.98	74.00	-24.02	peak
6	17940.000	24.22	25.34	49.56	74.00	-24.44	peak

Test Mode:	SRD 1.4MHz	Frequency(MHz):	2465.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3900.000	46.02	-4.03	41.99	74.00	-32.01	peak
2	6570.000	42.51	4.57	47.08	74.00	-26.92	peak
3	9090.000	37.34	10.51	47.85	74.00	-26.15	peak
4	11280.000	33.82	15.80	49.62	74.00	-24.38	peak
5	13110.000	30.37	19.20	49.57	74.00	-24.43	peak
6	17925.000	24.29	25.25	49.54	74.00	-24.46	peak

Test Mode:	SRD 1.4MHz	Frequency(MHz):	2465.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6570.000	41.84	4.57	46.41	74.00	-27.59	peak
2	9150.000	36.62	10.54	47.16	74.00	-26.84	peak
3	11655.000	32.11	17.01	49.12	74.00	-24.88	peak
4	12615.000	31.31	17.86	49.17	74.00	-24.83	peak
5	13995.000	27.36	21.95	49.31	74.00	-24.69	peak
6	18000.000	22.92	25.69	48.61	74.00	-25.39	peak

Test Mode:	SRD 1.4MHz CA	Frequency(MHz):	2409.12
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6420.000	42.21	3.91	46.12	74.00	-27.88	peak
2	8925.000	36.89	9.94	46.83	74.00	-27.17	peak
3	11055.000	34.45	14.96	49.41	74.00	-24.59	peak
4	11940.000	32.41	17.80	50.21	74.00	-23.79	peak
5	13155.000	30.45	19.40	49.85	74.00	-24.15	peak
6	18000.000	23.72	25.69	49.41	74.00	-24.59	peak

Test Mode:	SRD 1.4MHz CA	Frequency(MHz):	2409.12
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6420.000	43.27	3.91	47.18	74.00	-26.82	peak
2	10185.000	36.39	12.38	48.77	74.00	-25.23	peak
3	11055.000	35.08	14.96	50.04	74.00	-23.96	peak
4	11670.000	32.88	17.07	49.95	74.00	-24.05	peak
5	13995.000	27.96	21.95	49.91	74.00	-24.09	peak
6	17955.000	24.56	25.42	49.98	74.00	-24.02	peak

Test Mode:	SRD 1.4MHz CA	Frequency(MHz):	2437.12
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6870.000	37.74	6.05	43.79	74.00	-30.21	peak
2	9090.000	37.02	10.51	47.53	74.00	-26.47	peak
3	10320.000	36.06	12.64	48.70	74.00	-25.30	peak
4	11370.000	34.34	16.12	50.46	74.00	-23.54	peak
5	12690.000	32.59	18.02	50.61	74.00	-23.39	peak
6	17985.000	24.11	25.60	49.71	74.00	-24.29	peak

Test Mode:	SRD 1.4MHz CA	Frequency(MHz):	2437.12
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5760.000	41.36	1.58	42.94	74.00	-31.06	peak
2	6840.000	38.07	5.89	43.96	74.00	-30.04	peak
3	9225.000	36.55	10.58	47.13	74.00	-26.87	peak
4	11085.000	33.93	15.08	49.01	74.00	-24.99	peak
5	13530.000	28.95	20.96	49.91	74.00	-24.09	peak
6	17925.000	24.09	25.25	49.34	74.00	-24.66	peak

Test Mode:	SRD 1.4MHz CA	Frequency(MHz):	2467.12
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6570.000	42.32	4.57	46.89	74.00	-27.11	peak
2	9390.000	37.59	10.64	48.23	74.00	-25.77	peak
3	11430.000	32.89	16.34	49.23	74.00	-24.77	peak
4	12285.000	32.21	17.75	49.96	74.00	-24.04	peak
5	13560.000	28.82	21.04	49.86	74.00	-24.14	peak
6	18000.000	24.17	25.69	49.86	74.00	-24.14	peak

Test Mode:	SRD 1.4MHz CA	Frequency(MHz):	2467.12
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6570.000	41.41	4.57	45.98	74.00	-28.02	peak
2	9360.000	36.96	10.64	47.60	74.00	-26.40	peak
3	11055.000	34.49	14.96	49.45	74.00	-24.55	peak
4	12240.000	32.85	17.79	50.64	74.00	-23.36	peak
5	13410.000	29.45	20.50	49.95	74.00	-24.05	peak
6	17700.000	25.59	23.91	49.50	74.00	-24.50	peak

Test Mode:	SRD 3MHz	Frequency(MHz):	2417.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6450.000	41.20	4.02	45.22	74.00	-28.78	peak
2	9240.000	36.69	10.58	47.27	74.00	-26.73	peak
3	10290.000	35.70	12.59	48.29	74.00	-25.71	peak
4	12150.000	31.51	17.86	49.37	74.00	-24.63	peak
5	13920.000	28.41	21.79	50.20	74.00	-23.80	peak
6	17940.000	24.61	25.34	49.95	74.00	-24.05	peak

Test Mode:	SRD 3MHz	Frequency(MHz):	2417.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6450.000	40.72	4.02	44.74	74.00	-29.26	peak
2	9240.000	37.08	10.58	47.66	74.00	-26.34	peak
3	11340.000	33.94	16.01	49.95	74.00	-24.05	peak
4	12240.000	32.38	17.79	50.17	74.00	-23.83	peak
5	13110.000	31.16	19.20	50.36	74.00	-23.64	peak
6	17370.000	26.69	22.25	48.94	74.00	-25.06	peak

Test Mode:	SRD 3MHz	Frequency(MHz):	2438.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6870.000	37.04	6.05	43.09	74.00	-30.91	peak
2	9105.000	37.10	10.53	47.63	74.00	-26.37	peak
3	9720.000	36.66	11.27	47.93	74.00	-26.07	peak
4	11760.000	32.60	17.31	49.91	74.00	-24.09	peak
5	13920.000	28.17	21.79	49.96	74.00	-24.04	peak
6	17910.000	23.52	25.16	48.68	74.00	-25.32	peak

Test Mode:	SRD 3MHz	Frequency(MHz):	2438.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6495.000	39.77	4.20	43.97	74.00	-30.03	peak
2	9300.000	37.89	10.61	48.50	74.00	-25.50	peak
3	11055.000	34.39	14.96	49.35	74.00	-24.65	peak
4	12630.000	31.91	17.89	49.80	74.00	-24.20	peak
5	13920.000	28.02	21.79	49.81	74.00	-24.19	peak
6	17700.000	25.55	23.91	49.46	74.00	-24.54	peak

Test Mode:	SRD 3MHz	Frequency(MHz):	2456.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6540.000	40.85	4.41	45.26	74.00	-28.74	peak
2	9255.000	37.48	10.59	48.07	74.00	-25.93	peak
3	10365.000	36.74	12.72	49.46	74.00	-24.54	peak
4	11130.000	34.45	15.25	49.70	74.00	-24.30	peak
5	13410.000	29.56	20.50	50.06	74.00	-23.94	peak
6	17985.000	24.62	25.60	50.22	74.00	-23.78	peak

Test Mode:	SRD 3MHz	Frequency(MHz):	2456.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6540.000	40.03	4.41	44.44	74.00	-29.56	peak
2	7050.000	38.03	6.66	44.69	74.00	-29.31	peak
3	10365.000	35.28	12.72	48.00	74.00	-26.00	peak
4	11910.000	32.50	17.72	50.22	74.00	-23.78	peak
5	13575.000	29.50	21.06	50.56	74.00	-23.44	peak
6	17985.000	24.36	25.60	49.96	74.00	-24.04	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2405.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6405.000	43.68	3.84	47.52	74.00	-26.48	peak
2	9060.000	37.03	10.51	47.54	74.00	-26.46	peak
3	10335.000	35.63	12.67	48.30	74.00	-25.70	peak
4	11880.000	32.82	17.63	50.45	74.00	-23.55	peak
5	13545.000	28.90	20.99	49.89	74.00	-24.11	peak
6	17805.000	24.60	24.54	49.14	74.00	-24.86	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2405.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6405.000	44.55	3.84	48.39	74.00	-25.61	peak
2	10215.000	37.13	12.43	49.56	74.00	-24.44	peak
3	11055.000	35.49	14.96	50.45	74.00	-23.55	peak
4	11820.000	32.86	17.47	50.33	74.00	-23.67	peak
5	13110.000	31.66	19.20	50.86	74.00	-23.14	peak
6	18000.000	24.02	25.69	49.71	74.00	-24.29	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2440.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6510.000	42.05	4.28	46.33	74.00	-27.67	peak
2	9390.000	37.47	10.64	48.11	74.00	-25.89	peak
3	10230.000	36.35	12.46	48.81	74.00	-25.19	peak
4	11055.000	34.12	14.96	49.08	74.00	-24.92	peak
5	12645.000	31.89	17.92	49.81	74.00	-24.19	peak
6	17700.000	25.17	23.91	49.08	74.00	-24.92	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2440.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6510.000	41.98	4.28	46.26	74.00	-27.74	peak
2	9330.000	37.18	10.62	47.80	74.00	-26.20	peak
3	10305.000	36.21	12.61	48.82	74.00	-25.18	peak
4	11805.000	32.02	17.43	49.45	74.00	-24.55	peak
5	13020.000	31.14	18.80	49.94	74.00	-24.06	peak
6	17775.000	24.95	24.36	49.31	74.00	-24.69	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2475.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6600.000	41.00	4.71	45.71	74.00	-28.29	peak
2	9255.000	36.47	10.59	47.06	74.00	-26.94	peak
3	10305.000	35.92	12.61	48.53	74.00	-25.47	peak
4	11595.000	33.29	16.86	50.15	74.00	-23.85	peak
5	12675.000	32.42	17.99	50.41	74.00	-23.59	peak
6	17970.000	24.25	25.51	49.76	74.00	-24.24	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2475.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6600.000	41.64	4.71	46.35	74.00	-27.65	peak
2	9255.000	36.85	10.59	47.44	74.00	-26.56	peak
3	9900.000	36.56	11.75	48.31	74.00	-25.69	peak
4	11670.000	32.86	17.07	49.93	74.00	-24.07	peak
5	13665.000	28.40	21.25	49.65	74.00	-24.35	peak
6	17910.000	24.70	25.16	49.86	74.00	-24.14	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2476.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6600.000	40.38	4.71	45.09	74.00	-28.91	peak
2	9195.000	36.80	10.56	47.36	74.00	-26.64	peak
3	11070.000	33.62	15.03	48.65	74.00	-25.35	peak
4	11820.000	31.94	17.47	49.41	74.00	-24.59	peak
5	13080.000	30.28	19.07	49.35	74.00	-24.65	peak
6	18000.000	23.48	25.69	49.17	74.00	-24.83	peak

Test Mode:	SRD 10MHz	Frequency(MHz):	2476.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6600.000	42.80	4.71	47.51	74.00	-26.49	peak
2	9390.000	36.91	10.64	47.55	74.00	-26.45	peak
3	11835.000	32.07	17.51	49.58	74.00	-24.42	peak
4	12210.000	31.92	17.81	49.73	74.00	-24.27	peak
5	13875.000	27.84	21.70	49.54	74.00	-24.46	peak
6	18000.000	23.56	25.69	49.25	74.00	-24.75	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2410.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6810.000	37.31	5.76	43.07	74.00	-30.93	peak
2	8940.000	37.66	10.04	47.70	74.00	-26.30	peak
3	10230.000	36.94	12.46	49.40	74.00	-24.60	peak
4	11505.000	33.57	16.61	50.18	74.00	-23.82	peak
5	13920.000	28.50	21.79	50.29	74.00	-23.71	peak
6	18000.000	24.58	25.69	50.27	74.00	-23.73	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2410.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6420.000	40.33	3.91	44.24	74.00	-29.76	peak
2	10230.000	36.34	12.46	48.80	74.00	-25.20	peak
3	11055.000	34.73	14.96	49.69	74.00	-24.31	peak
4	12630.000	32.74	17.89	50.63	74.00	-23.37	peak
5	13080.000	31.12	19.07	50.19	74.00	-23.81	peak
6	18000.000	24.62	25.69	50.31	74.00	-23.69	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2441.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6510.000	39.37	4.28	43.65	74.00	-30.35	peak
2	8985.000	36.65	10.37	47.02	74.00	-26.98	peak
3	10215.000	35.51	12.43	47.94	74.00	-26.06	peak
4	11850.000	32.21	17.56	49.77	74.00	-24.23	peak
5	13875.000	28.66	21.70	50.36	74.00	-23.64	peak
6	18000.000	23.84	25.69	49.53	74.00	-24.47	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2441.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3900.000	44.44	-4.03	40.41	74.00	-33.59	peak
2	6510.000	42.10	4.28	46.38	74.00	-27.62	peak
3	9270.000	36.44	10.59	47.03	74.00	-26.97	peak
4	11025.000	34.34	14.85	49.19	74.00	-24.81	peak
5	13005.000	31.50	18.74	50.24	74.00	-23.76	peak
6	17940.000	24.41	25.34	49.75	74.00	-24.25	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2469.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6585.000	38.93	4.64	43.57	74.00	-30.43	peak
2	9225.000	37.13	10.58	47.71	74.00	-26.29	peak
3	10305.000	36.03	12.61	48.64	74.00	-25.36	peak
4	11835.000	32.40	17.51	49.91	74.00	-24.09	peak
5	13545.000	29.65	20.99	50.64	74.00	-23.36	peak
6	18000.000	24.69	25.69	50.38	74.00	-23.62	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2469.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6585.000	40.32	4.64	44.96	74.00	-29.04	peak
2	8850.000	37.34	9.39	46.73	74.00	-27.27	peak
3	9810.000	36.51	11.51	48.02	74.00	-25.98	peak
4	11790.000	31.57	17.38	48.95	74.00	-25.05	peak
5	13920.000	28.72	21.79	50.51	74.00	-23.49	peak
6	18000.000	24.22	25.69	49.91	74.00	-24.09	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2470.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6585.000	38.71	4.64	43.35	74.00	-30.65	peak
2	9300.000	36.29	10.61	46.90	74.00	-27.10	peak
3	11055.000	34.96	14.96	49.92	74.00	-24.08	peak
4	11505.000	33.43	16.61	50.04	74.00	-23.96	peak
5	13995.000	28.99	21.95	50.94	74.00	-23.06	peak
6	17985.000	25.09	25.60	50.69	74.00	-23.31	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2470.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6585.000	40.61	4.64	45.25	74.00	-28.75	peak
2	9195.000	36.28	10.56	46.84	74.00	-27.16	peak
3	11055.000	34.39	14.96	49.35	74.00	-24.65	peak
4	12675.000	31.96	17.99	49.95	74.00	-24.05	peak
5	13860.000	28.24	21.67	49.91	74.00	-24.09	peak
6	17940.000	24.36	25.34	49.70	74.00	-24.30	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2471.5
Polarity:	Horizontal	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6585.000	40.89	4.64	45.53	74.00	-28.47	peak
2	9255.000	37.19	10.59	47.78	74.00	-26.22	peak
3	11055.000	34.82	14.96	49.78	74.00	-24.22	peak
4	11820.000	33.33	17.47	50.80	74.00	-23.20	peak
5	12660.000	32.63	17.95	50.58	74.00	-23.42	peak
6	17985.000	24.41	25.60	50.01	74.00	-23.99	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2471.5
Polarity:	Vertical	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6585.000	40.56	4.64	45.20	74.00	-28.80	peak
2	9210.000	36.53	10.57	47.10	74.00	-26.90	peak
3	11280.000	33.26	15.80	49.06	74.00	-24.94	peak
4	11820.000	32.31	17.47	49.78	74.00	-24.22	peak
5	13860.000	28.55	21.67	50.22	74.00	-23.78	peak
6	18000.000	24.09	25.69	49.78	74.00	-24.22	peak

Test Mode:	SRD 20MHz	Frequency(MHz):	2472.5
Polarity:	Horizontal	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6585.000	42.85	4.64	47.49	74.00	-26.51	peak
2	9825.000	35.96	11.56	47.52	74.00	-26.48	peak
3	11055.000	34.51	14.96	49.47	74.00	-24.53	peak
4	12225.000	31.95	17.79	49.74	74.00	-24.26	peak
5	13935.000	28.60	21.82	50.42	74.00	-23.58	peak
6	17985.000	24.01	25.60	49.61	74.00	-24.39	peak


Test Mode:	SRD 20MHz	Frequency(MHz):	2472.5
Polarity:	Vertical	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6585.000	40.96	4.64	45.60	74.00	-28.40	peak
2	9780.000	35.27	11.43	46.70	74.00	-27.30	peak
3	11070.000	34.11	15.03	49.14	74.00	-24.86	peak
4	11865.000	32.81	17.59	50.40	74.00	-23.60	peak
5	13605.000	29.21	21.12	50.33	74.00	-23.67	peak
6	17700.000	25.94	23.91	49.85	74.00	-24.15	peak


8.4. SPURIOUS EMISSIONS (9 KHZ ~ 30 MHZ)

Test Mode:	SRD 10 MHz	Channel:	2440.5 MHz
Polarity:	Loop Antenna Face On To The EUT	Test Voltage:	DC 5 V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Result (dBuA/m)	Limit (dBuV/m)	Limit (dBuA/m)	Margin (dB)	Remark
1	0.01	81.72	-101.4	-19.68	-71.18	47.6	-3.9	-67.28	peak
2	0.016	77.47	-101.37	-23.9	-75.40	43.52	-7.98	-67.42	peak
3	0.0273	72.99	-101.38	-28.39	-79.89	38.88	-12.62	-67.27	peak
4	0.0349	70.03	-101.41	-31.38	-82.88	36.75	-14.75	-68.13	peak
5	0.0675	65.14	-101.56	-36.42	-87.92	31.02	-20.48	-67.44	peak
6	0.0981	61.77	-101.78	-40.01	-91.51	27.77	-23.73	-67.78	peak

Test Mode:	SRD 10 MHz	Channel:	2440.5 MHz
Polarity:	Loop Antenna Face On To The EUT	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Result (dBuA/m)	Limit (dBuV/m)	Limit (dBuA/m)	Margin (dB)	Remark
1	0.1595	79.86	-101.65	-21.79	-73.29	23.55	-27.95	-45.34	peak
2	0.172	77.69	-101.67	-23.98	-75.48	22.9	-28.6	-46.88	peak
3	0.1925	74.96	-101.7	-26.74	-78.24	21.92	-29.58	-48.66	peak
4	0.2442	69.03	-101.79	-32.76	-84.26	19.85	-31.65	-52.61	peak
5	0.3163	66.2	-101.87	-35.67	-87.17	17.6	-33.9	-53.27	peak
6	0.3573	62.58	-101.91	-39.33	-90.83	16.54	-34.96	-55.87	peak


Test Mode:	SRD 10 MHz	Channel:	2440.5 MHz
Polarity:	Loop Antenna Face On To The EUT	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Result (dBuA/m)	Limit (dBuV/m)	Limit (dBuA/m)	Margin (dB)	Remark
1	0.5342	64.98	-62.08	2.9	-48.60	33.05	-18.45	-30.15	peak
2	0.7641	64.42	-62.12	2.3	-49.20	29.94	-21.56	-27.64	peak
3	1.387	61.32	-62.09	-0.77	-52.27	24.76	-26.74	-25.53	peak
4	2.1463	58.77	-61.79	-3.02	-54.52	29.54	-21.96	-32.56	peak
5	3.71	54.7	-61.41	-6.71	-58.21	29.54	-21.96	-36.25	peak
6	6.2445	53.63	-61.32	-7.69	-59.19	29.54	-21.96	-37.23	peak


8.5. SPURIOUS EMISSIONS (18 GHZ ~ 26 GHZ)

Test Mode:	SRD 10 MHz	Channel:	2440.5 MHz
Polarity:	Horizontal	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18200.000	49.79	-5.52	44.27	74.00	-29.73	peak
2	19560.000	49.36	-5.48	43.88	74.00	-30.12	peak
3	21600.000	48.52	-4.54	43.98	74.00	-30.02	peak
4	23744.000	47.15	-3.20	43.95	74.00	-30.05	peak
5	24272.000	46.25	-2.79	43.46	74.00	-30.54	peak
6	25616.000	45.18	-1.24	43.94	74.00	-30.06	peak


Test Mode:	SRD 10 MHz	Channel:	2440.5 MHz
Polarity:	Vertical	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18616.000	48.89	-5.34	43.55	74.00	-30.45	peak
2	20240.000	49.32	-5.61	43.71	74.00	-30.29	peak
3	21544.000	47.76	-4.63	43.13	74.00	-30.87	peak
4	23088.000	46.52	-3.41	43.11	74.00	-30.89	peak
5	24568.000	45.60	-2.33	43.27	74.00	-30.73	peak
6	25728.000	44.61	-0.72	43.89	74.00	-30.11	peak


8.6. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)

Test Mode:	SRD 10 MHz	Channel:	2440.5 MHz
Polarity:	Horizontal	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.9100	44.71	-18.17	26.54	40.00	-13.46	QP
2	117.3000	48.89	-19.55	29.34	43.50	-14.16	QP
3	132.8200	52.65	-18.75	33.90	43.50	-9.60	QP
4	147.3700	49.84	-18.04	31.80	43.50	-11.70	QP
5	297.7200	42.59	-14.97	27.62	46.00	-18.38	QP
6	324.8800	42.72	-13.66	29.06	46.00	-16.94	QP

Test Mode:	SRD 10 MHz	Channel:	2440.5 MHz
Polarity:	Vertical	Test Voltage:	DC 5 V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	33.8800	44.62	-18.37	26.25	40.00	-13.75	QP
2	68.8000	52.64	-20.22	32.42	40.00	-7.58	QP
3	95.9600	49.59	-21.22	28.37	43.50	-15.13	QP
4	129.9100	52.55	-18.88	33.67	43.50	-9.83	QP
5	137.6700	53.94	-18.50	35.44	43.50	-8.06	QP
6	157.0700	46.45	-17.26	29.19	43.50	-14.31	QP

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a)


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP




TEST ENVIRONMENT

Temperature	22.4 °C	Relative Humidity	53%
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Test Mode:	SRD 10 MHz	Channel:	2440.5 MHz
Line	L		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1503	33.34	9.59	42.93	65.98	-23.05	QP
2	0.1503	15.57	9.59	25.16	55.98	-30.82	AVG
3	0.3033	25.12	9.59	34.71	60.15	-25.44	QP
4	0.3033	13.10	9.59	22.69	50.15	-27.46	AVG
5	0.5277	29.48	9.60	39.08	56.00	-16.92	QP
6	0.5277	15.38	9.60	24.98	46.00	-21.02	AVG
7	0.9438	21.82	9.61	31.43	56.00	-24.57	QP
8	0.9438	8.40	9.61	18.01	46.00	-27.99	AVG
9	2.7336	26.23	9.66	35.89	56.00	-20.11	QP
10	2.7336	16.22	9.66	25.88	46.00	-20.12	AVG
11	9.1832	24.54	9.72	34.26	60.00	-25.74	QP
12	9.1832	16.40	9.72	26.12	50.00	-23.88	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Test Mode:	SRD 10 MHz	Channel:	2440.5 MHz
Line	N		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1741	29.83	9.54	39.37	64.76	-25.39	QP
2	0.1741	10.47	9.54	20.01	54.76	-34.75	AVG
3	0.4454	33.02	9.52	42.54	56.96	-14.42	QP
4	0.4454	21.55	9.52	31.07	46.96	-15.89	AVG
5	0.5233	29.29	9.50	38.79	56.00	-17.21	QP
6	0.5233	20.23	9.50	29.73	46.00	-16.27	AVG
7	1.1081	28.78	9.52	38.30	56.00	-17.70	QP
8	1.1081	18.34	9.52	27.86	46.00	-18.14	AVG
9	2.7988	31.21	9.62	40.83	56.00	-15.17	QP
10	2.7988	21.27	9.62	30.89	46.00	-15.11	AVG
11	7.1338	22.21	9.63	31.84	60.00	-28.16	QP
12	7.1338	14.23	9.63	23.86	50.00	-26.14	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

11. TEST DATA


11.1. APPENDIX A: DTS BANDWIDTH


11.1.1. Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
SRD 1.4MHZ	Ant1	2407.5	1.10	2406.95	2408.05	≥0.5	PASS
	Ant2	2407.5	1.10	2406.95	2408.05	≥0.5	PASS
	Ant1	2437.5	1.10	2436.95	2438.05	≥0.5	PASS
	Ant2	2437.5	1.10	2436.95	2438.05	≥0.5	PASS
	Ant1	2465.5	1.10	2464.95	2466.05	≥0.5	PASS
	Ant2	2465.5	1.10	2464.95	2466.05	≥0.5	PASS
SRD 1.4MHZ CA	Ant1	2409.12	1.10	2408.57	2409.67	≥0.5	PASS
	Ant2	2409.12	1.10	2408.57	2409.67	≥0.5	PASS
	Ant1	2437.12	1.10	2436.57	2437.67	≥0.5	PASS
	Ant2	2437.12	1.10	2436.57	2437.67	≥0.5	PASS
	Ant1	2467.12	1.10	2466.57	2467.67	≥0.5	PASS
	Ant2	2467.12	1.10	2466.57	2467.67	≥0.5	PASS
SRD 3MHZ	Ant1	2417.5	2.21	2416.41	2418.62	≥0.5	PASS
	Ant2	2417.5	2.21	2416.41	2418.62	≥0.5	PASS
	Ant1	2438.5	2.20	2437.41	2439.62	≥0.5	PASS
	Ant2	2438.5	2.20	2437.41	2439.62	≥0.5	PASS
	Ant1	2456.5	2.21	2455.41	2457.62	≥0.5	PASS
	Ant2	2456.5	2.20	2455.41	2457.62	≥0.5	PASS


Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
SRD 10MHZ	Ant1	2405.5	8.98	2401.00	2409.98	≥0.5	PASS
	Ant2	2405.5	8.98	2401.00	2409.98	≥0.5	PASS
	Ant1	2406.5	8.98	2402.00	2410.98	≥0.5	PASS
	Ant2	2406.5	9.00	2402.00	2411.00	≥0.5	PASS
	Ant1	2407.5	8.96	2403.02	2411.98	≥0.5	PASS
	Ant2	2407.5	8.90	2403.02	2411.92	≥0.5	PASS
	Ant1	2440.5	8.92	2436.02	2444.94	≥0.5	PASS
	Ant2	2440.5	8.88	2436.00	2444.88	≥0.5	PASS
	Ant1	2475.5	8.92	2471.04	2479.96	≥0.5	PASS
	Ant2	2475.5	8.84	2471.10	2479.94	≥0.5	PASS
	Ant1	2476.5	8.96	2472.02	2480.98	≥0.5	PASS
	Ant2	2476.5	8.86	2472.02	2480.88	≥0.5	PASS
SRD 20MHZ	Ant1	2410.5	18.00	2401.50	2419.50	≥0.5	PASS
	Ant2	2410.5	17.96	2401.50	2419.46	≥0.5	PASS
	Ant1	2411.5	18.00	2402.50	2420.50	≥0.5	PASS
	Ant2	2411.5	17.96	2402.54	2420.50	≥0.5	PASS
	Ant1	2412.5	17.96	2403.54	2421.50	≥0.5	PASS
	Ant2	2412.5	17.92	2403.54	2421.46	≥0.5	PASS
	Ant1	2413.5	18.00	2404.50	2422.50	≥0.5	PASS
	Ant2	2413.5	17.96	2404.50	2422.46	≥0.5	PASS
	Ant1	2414.5	17.96	2405.50	2423.46	≥0.5	PASS
	Ant2	2414.5	17.96	2405.50	2423.46	≥0.5	PASS
	Ant1	2441.5	17.92	2432.54	2450.46	≥0.5	PASS
	Ant2	2441.5	17.96	2432.50	2450.46	≥0.5	PASS
	Ant1	2469.5	17.96	2460.54	2478.50	≥0.5	PASS
	Ant2	2469.5	17.88	2460.50	2478.38	≥0.5	PASS
	Ant1	2470.5	18.00	2461.50	2479.50	≥0.5	PASS
	Ant2	2470.5	17.92	2461.50	2479.42	≥0.5	PASS
	Ant1	2471.5	18.00	2462.50	2480.50	≥0.5	PASS
	Ant2	2471.5	17.96	2462.50	2480.46	≥0.5	PASS
	Ant1	2472.5	17.92	2463.54	2481.46	≥0.5	PASS
	Ant2	2472.5	17.96	2463.50	2481.46	≥0.5	PASS

11.1.2. Test Graphs







SRD 1.4MHz Ant2 2437.5




SRD 1.4MHz Ant1 2465.5



SRD 1.4MHz Ant2 2465.5




SRD 1.4MHZ CA_Ant1_2409.12




Date: 30.JAN.2024 10:55:07

SRD 1.4MHZ CA_Ant2_2409.12




Date: 30.JAN.2024 10:11:15

SRD 1.4MHZ CA_Ant1_2437.12




Date: 30.JAN.2024 10:57:04


SRD 1.4MHZ CA_Ant2_2437.12




SRD 1.4MHz CA Ant1_2467.12




SRD 1.4MHz CA Ant2_2467.12



SRD 3MHz Ant1_2417.5




SRD 3MHZ_Ant2_2417.5




Date: 30.JAN.2024 10:37:13

SRD 3MHZ_Ant1_2438.5






Date: 30.JAN.2024 11:04:05


SRD 3MHZ_Ant2_2438.5




Date: 30.JAN.2024 10:39:10

SRD 3MHZ_Ant1_2456.5







SRD 10MHz_Ant1_2406.5




SRD 10MHz_Ant2_2406.5



SRD 10MHz_Ant1_2407.5




SRD 10MHZ_Ant2_2407.5




Date: 1.FEB.2024 08:21:10

SRD 10MHZ_Ant1_2440.5



Date: 1.FEB.2024 10:48:48

SRD 10MHZ_Ant2_2440.5



Date: 4.FEB.2024 07:48:33

SRD 10MHZ_Ant1_2475.5